

Zero-inflated models: Poisson, Binomial, negative Binomial and BetaBinomial

Parametrisation

There is support two types of zero-inflated models, which we name type 0 and type 1. These are defined for both the Binomial, the Poisson, the negative Binomial and BetaBinomial likelihood. For simplicity we will describe only the Poisson as the other cases are similar.

Type 0

The (type 0) likelihood is defined as

$$\text{Prob}(y \mid \dots) = p \times 1_{[y=0]} + (1 - p) \times \text{Poisson}(y \mid y > 0)$$

where p is a hyperparameter where

$$p = \frac{\exp(\theta)}{1 + \exp(\theta)}$$

and θ is the internal representation of p ; meaning that the initial value and prior is given for θ . This model is called `zeroinflatedpoisson0` (and `zeroinflatedbinomial0`).

Type 1

The (type 1) likelihood is defined as

$$\text{Prob}(y \mid \dots) = p \times 1_{[y=0]} + (1 - p) \times \text{Poisson}(y)$$

where p is a hyperparameter where

$$p = \frac{\exp(\theta)}{1 + \exp(\theta)}$$

and θ is the internal representation of p ; meaning that the initial value and prior is given for θ . This model is called `zeroinflatedpoisson1` (and `zeroinflatedbinomial1`).

Link-function

As for the Poisson, the Binomial the negative Binomial and the BetaBinomial.

Hyperparameters

For Poisson and the Binomial, there is one hyperparameter; where

$$p = \frac{\exp(\theta)}{1 + \exp(\theta)}$$

and the prior and initial value is given for θ .

For the negative Binomial and BetaBinomial, there are two hyperparameters. The overdispersion parameter n for the negative Binomial is represented as

$$\theta_1 = \log(n)$$

and the prior is defined on θ_1 . The zero-inflation parameter p , is represented as

$$p = \frac{\exp(\theta_2)}{1 + \exp(\theta_2)}$$

and the prior and initial value is given for θ_2 . For the BetaBinomial it is similar.

Specification

- family = zeroinflatedbinomial0
- family = zeroinflatedbinomial1
- family = zeroinflatednbinomial0
- family = zeroinflatednbinomial1
- family = zeroinflatedpoisson0
- family = zeroinflatedpoisson1
- family = zeroinflatedbetabinomial0
- family = zeroinflatedbetabinomial1
- Required arguments: As for the Binomial, the negative Binomial, BetaBinomial and Poisson likelihood.

Hyperparameter specification and default values

Zeroinflated Binomial Type 0

hyper

theta

hyperid 90001
name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default logit cauchit probit cloglog loglog

pdf zeroinflated

Zeroinflated Binomial Type 1

hyper

theta

hyperid 91001
name logit probability
short.name prob
initial -1

```

    fixed FALSE
    prior gaussian
    param -1 0.2
    to.theta function(x) log(x/(1-x))
    from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default logit cauchit probit cloglog loglog

pdf zeroinflated

```

Zeroinflated NegBinomial Type 0

```

hyper
  theta1
    hyperid 95001
    name log size
    short.name size
    initial 2.30258509299405
    fixed FALSE
    prior loggamma
    param 1 1
    to.theta function(x) log(x)
    from.theta function(x) exp(x)

  theta2
    hyperid 95002
    name logit probability
    short.name prob
    initial -1
    fixed FALSE
    prior gaussian
    param -1 0.2
    to.theta function(x) log(x/(1-x))
    from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default log

pdf zeroinflated

```

Zeroinflated NegBinomial Type 1

hyper

theta1

hyperid 96001
name log size
short.name size
initial 2.30258509299405
fixed FALSE
prior loggamma
param 1 1
to.theta function(x) log(x)
from.theta function(x) exp(x)

theta2

hyperid 96002
name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default log

pdf zeroinflated

Zeroinflated BetaBinomial Type 0

hyper

theta1

hyperid 88001
name overdispersion
short.name rho
initial 0
fixed FALSE
prior gaussian
param 0 0.4
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

theta2

hyperid 88002

name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete TRUE

link default logit cauchit probit cloglog loglog

pdf zeroinflated

Zeroinflated BetaBinomial Type 1

hyper

theta1

hyperid 89001
name overdispersion
short.name rho
initial 0
fixed FALSE
prior gaussian
param 0 0.4
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

theta2

hyperid 89002
name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete TRUE

link default logit cauchit probit cloglog loglog

pdf zeroinflated

Zeroinflated Poisson Type 0

hyper

theta

hyperid 85001
name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default log

pdf zeroinflated

Zeroinflated Poisson Type 1

hyper

theta

hyperid 86001
name logit probability
short.name prob
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x/(1-x))
from.theta function(x) exp(x)/(1+exp(x))

survival FALSE

discrete FALSE

link default log

pdf zeroinflated

Example

In the following example we estimate the parameters in a simulated example for both type 0 and type 1.

Poisson

```
## type 0
n=100
a = 1
b = 1
z = rnorm(n)
eta = a + b*z
p = 0.2
E = sample(c(1,5,10,15), size=n, replace=TRUE)
lambda = E*exp(eta)

## first sample y|y>0
y = rpois(n, lambda = lambda)
is.zero = (y == 0)
while(sum(is.zero) > 0)
{
  y[is.zero] = rpois(sum(is.zero), lambda[is.zero])
  is.zero = (y == 0)
}
## then set some of these to zero
y[ rbinom(n, size=1, prob=p) == 1 ] = 0

data = list(y=y,z=z)
formula = y ~ 1+z
result0 = inla(formula, family = "zeroinflatedpoisson0", data = data, E=E)
summary(result0)

## type 1
y = rpois(n, lambda = lambda)
y[ rbinom(n, size=1, prob=p) == 1 ] = 0
data = list(y=y,z=z)
formula = y ~ 1+z
result1 = inla(formula, family = "zeroinflatedpoisson1", data = data, E=E)
summary(result1)
```

Binomial

```
## type 0
n=100
a = 1
b = 1
z = rnorm(n)
eta = a + b*z
p = 0.2
Ntrials = sample(c(1,5,10,15), size=n, replace=TRUE)
prob = exp(eta)/(1 + exp(eta))

y = rbinom(n, size = Ntrials, prob = prob)
is.zero = (y == 0)
while(sum(is.zero) > 0)
{
```

```

    y[is.zero] = rbinom(sum(is.zero), size = Ntrials[is.zero], prob = prob[is.zero])
    is.zero = (y == 0)
}
y[ rbinom(n, size=1, prob=p) == 1 ] = 0
data = list(y=y,z=z)
formula = y ~ 1+z
result0 = inla(formula, family = "zeroinflatedbinomial0", data = data, Ntrials = Ntrials)
summary(result0)

## type 1
y = rbinom(n, size = Ntrials, prob = prob)
y[ rbinom(n, size=1, prob=p) == 1 ] = 0
data = list(y=y,z=z)
formula = y ~ 1+z
result1 = inla(formula, family = "zeroinflatedbinomial1", data = data, Ntrials=Ntrials)
summary(result1)

```


Advanced example

In the following example we estimate the parameters in a simulated example for a type0 likelihood, where one linear predictor enters the zero-probability and one other linear predictor enters the non-zero Poisson for example. The same trick can be used for other models of type0. The trick is that the likelihood

$$p^* 1_{[y=0]} + (1 - p^*) P(y|y > 0)$$

can be reformulated as a Bernoulli likelihood for the “class”-variable

$$z = \begin{cases} 1, & \text{if } y = 0 \\ 0, & \text{if } y > 0. \end{cases}$$

where p^* is the probability for success, and zero-inflated type0 likelihood (with fixed $p = 0$) for those $y > 0$. Since p^* and the linear predictor in P is separated into two likelihoods, we can apply one linear predictor to each one, hence extend the basic model to cases where p^* also depends on a linear predictor. Here is a small simulated example doing this.

```
require(INLA)

n = 100
a = 0.5
b = 1.5
x1 = rnorm(n, sd = 0.5)

eta.z = -a - b*x1
z = rbinom(n, 1, inla.link.logit(eta.z, inverse=TRUE))
n.y = sum(z)

x2 = rnorm(n.y, sd = 0.5)
eta.y = a + b*x2
lambda = exp(eta.y)
y = rpois(n.y, lambda)

is.zero = (y == 0)
while(sum(is.zero) > 0)
{
  y[is.zero] = rpois(sum(is.zero), lambda[is.zero])
  is.zero = (y == 0)
}

Y = matrix(NA, n + n.y, 2)
Y[1:n, 1] = z
Y[n + 1:n.y, 2] = y

form = Y ~ 0 + mu.z + mu.y + cov.z + cov.y
ldat = list(
  Y=Y,
  mu.z=rep(1:0, c(n, n.y)),
  mu.y=rep(0:1, c(n, n.y)),
  cov.z=c(x1, rep(NA,n.y)),
  cov.y=c(rep(NA, n), x2))
```

```
res <- inla(form, data=ldat,
            family=c('binomial', 'zeroinflatedpoisson0'),
            control.family=list(
              list(),
              list(hyper = list(
                prob = list(
                  initial = -20,
                  fixed = TRUE))))))
round(res$summary.fix, 4)
```

Notes

None.

Extentions

There are some extentions available which currently is only implemented for the cases where its needed/requested.

Type 2 Is like Type 1 but where (for the Poisson)

$$p = 1 - \left(\frac{E \exp(x)}{1 + E \exp(x)} \right)^\alpha$$

where $\alpha > 0$ is the hyperparameter instead of p (and $E \exp(x)$ is the mean). Available for Poisson as **zeroinflatedpoisson2**, for binomial as **zeroinflatedbinomial2** and for the negative binomial as **zeroinflatednbinomial2**.

The internal representation is $\theta = \log(\alpha)$ and prior is defined on $\log(\alpha)$.

Zeroinflated Poisson Type 2

hyper

theta

```
hyperid 87001
name log alpha
short.name a
initial 0.693147180559945
fixed FALSE
prior gaussian
param 0.693147180559945 1
to.theta function(x) log(x)
from.theta function(x) exp(x)
```

survival FALSE

discrete FALSE

link default log

pdf zeroinflated

Zeroinflated Binomial Type 2

hyper

theta

hyperid 92001
name alpha
short.name alpha
initial -1
fixed FALSE
prior gaussian
param -1 0.2
to.theta function(x) log(x)
from.theta function(x) exp(x)

survival FALSE

discrete FALSE

link default logit cauchit probit cloglog loglog

pdf zeroinflated

Zeroinflated Negative Binomial Type 2

hyper

theta1

hyperid 99001
name log size
short.name size
initial 2.30258509299405
fixed FALSE
prior loggamma
param 1 1
to.theta function(x) log(x)
from.theta function(x) exp(x)

theta2

hyperid 99002
name log alpha
short.name a
initial 0.693147180559945
fixed FALSE
prior gaussian
param 2 1
to.theta function(x) log(x)
from.theta function(x) exp(x)

survival FALSE

discrete FALSE

link default log

pdf zeroinflated