Unloved Full Stack Commands

Desktop launcher and manual startup reference for APF, ShadowCast, Mission Control, and infrastructure. For APF enrichment/Digistore24 detail, see **Unloved Stack Useful Commands** in this folder.

Repo paths

Repo	Path
APF	`~/APF`
ShadowCast	`~/shadowcast-`
Mission Control	`~/mission-control`
SearXNG (Docker)	`~/searxng`
Desktop launchers	`~/.local/bin/unloved-launchers`

Shared secret

`INTERNAL_SERVICE_SECRET` must be **identical** in `~/APF/.env`, `~/shadowcast-/backend/.env`, and `~/mission-control/backend/.env`.

```
~/.local/bin/unloved-launchers/preflight-unloved-stack.sh
```

Service map

Service	URL	Start (summary)
MySQL	per DATABASE_URL	`docker start apf-mysql`
SearXNG	http://localhost:8088	`cd ~/searxng && docker compose up -d`
Ollama	http://localhost:11434	`ollama serve &`
APF	http://localhost:3001	`pnpm local:start` or launcher
ShadowCast	http://localhost:8000	uvicorn or launcher
Mission Control API	http://localhost:8100	uvicorn or launcher
Mission Control UI	http://localhost:3100	`pnpm dev` or launcher

One-shot desktop launchers

```
# Full stack: ShadowCast + APF + Mission Control (4 tabs, opens :3100)
~/.local/bin/unloved-launchers/launch-unloved-stack.sh

# Individual apps
~/.local/bin/unloved-launchers/launch-shadowcast.sh
~/.local/bin/unloved-launchers/launch-apf.sh
~/.local/bin/unloved-launchers/launch-mission-control.sh

# Preflight only
~/.local/bin/unloved-launchers/preflight-unloved-stack.sh
~/.local/bin/unloved-launchers/preflight-apf.sh
~/.local/bin/unloved-launchers/preflight-shadowcast.sh
```

`launch-unloved-stack.sh` order: ShadowCast → APF → MC backend → MC frontend → open http://localhost:3100.

`launch-apf.sh` starts review enrichment daemon ~20s after APF when enabled.

Note: Launchers do not start SearXNG — start it separately below.

Infrastructure startup

```
# MySQL
docker start apf-mysql
# or: sudo systemctl start mysql

# SearXNG
cd ~/searxng
docker compose up -d
docker compose down             # stop
docker restart unloved-searxng  # restart

# Ollama
ollama serve &
ollama pull qwen2.5:14b-instruct-q5_K_M
```

Manual per-service startup

ShadowCast

```
cd ~/shadowcast-/backend
source ../.venv/bin/activate
source .env
python -m uvicorn app:app --host 0.0.0.0 --port 8000 --reload
```

Or: `~/.local/bin/unloved-launchers/run-shadowcast-terminal.sh`

APF

```
cd ~/APF
source .env
export PORT="${PORT:-3001}"
pnpm dev
# or: pnpm local:start
```

Or: `~/.local/bin/unloved-launchers/run-apf-terminal.sh`

Mission Control backend

```
cd ~/mission-control/backend
source venv/bin/activate
source .env
python -m uvicorn main:app --host 0.0.0.0 --port 8100 --reload
```

Mission Control frontend

```
cd ~/mission-control/frontend
pnpm run dev -- --host 0.0.0.0 --port 3100
```

Health matrix

```
docker ps --filter name=apf-mysql --filter name=unloved-searxng
curl -fsS http://localhost:8088/ >/dev/null && echo "SearXNG OK"
curl -fsS http://localhost:11434/api/tags >/dev/null && echo "Ollama OK"
curl -fsS http://localhost:8000/api/health >/dev/null && echo "ShadowCast OK"
curl -fsS http://localhost:3001/api/health >/dev/null && echo "APF OK"
curl -fsS http://localhost:8100/api/health >/dev/null && echo "MC backend OK"
curl -fsS http://localhost:3100 >/dev/null && echo "MC frontend OK"
```

APF video audit helper

```
cd ~/APF
pnpm video-audit:start
```

Auto-starts ShadowCast and APF if not healthy, then runs the style matrix audit.

Recommended full-stack startup order

1. Infrastructure: MySQL → SearXNG → Ollama
2. `launch-unloved-stack.sh` or start each service manually
3. `cd ~/APF && pnpm digistore24:daemon` (if using Digistore24)
4. `pnpm review:status` until complete
5. ShadowCast handoff from APF UI or `pnpm local:smoke-test`

APF enrichment detail: unloved-stack-useful-commands.md. Runbook: LOCAL_SHADOWCAST.md.