

This is a copy of a conversation between ChatGPT & Anonymous.
Report conversation

I have an active codebase with a handful of contributors. I have a husky commit hook that runs on `lint - staged`. I added `csPELL` on `lint - staged` but it seems that it's not running for every contributor. is it because husky only gets set up once when they first clone the codebase?

Husky is a tool used to run scripts during Git events such as `commit` or `push`. It is typically used in Node.js projects to enforce coding standards and run tests before code is committed or pushed. When a contributor clones the repository, they should get the Husky setup as part of the project dependencies.

However, there could be a few reasons why `csPELL` is not running for every contributor on `lint - staged`:

- 1. Husky Not Installed or Initialized:** If a contributor hasn't run `npm install` or `yarn install` after cloning the repository, they wouldn't have installed the project dependencies including Husky, causing the hooks not to run. Also, in some versions of Husky (like Husky 6), you need to run `husky install` to initialize Husky in your project.
- 2. Different Environment:** Husky runs in a Node.js environment. If some contributors are using an environment where Node.js is not available or properly set up, Husky may not run.
- 3. Git Version:** Husky requires Git 2.13.0 or newer. If the contributors are using an older version of Git, Husky hooks may not work properly.
- 4. Inconsistent Husky Version:** If your project is using an older version of Husky, it might have inconsistencies with the newer versions. Husky has made significant changes in its configuration format in recent versions (especially from v4 to v5). If the local setup of the contributors is different from the one specified in the project, it could cause such problems.
- 5. Bypassing Pre-Commit Hooks:** Contributors may be bypassing the Husky hooks intentionally or unintentionally when they commit. Using `git commit --no-verify`

ChatGPT 5.2

properly configured to run with `lint-staged`. Check your `lint-staged` configuration to ensure `cspell` is set to check the files you expect.

- 7. OS-Specific Issues:** There can be issues that are specific to the operating system. For example, Husky might have problems running on Windows. If the contributors experiencing issues are all using the same operating system, you might need to do some OS-specific troubleshooting.

To solve this, ensure all contributors have properly installed all dependencies (including Husky), they have the correct version of Git, and they are not bypassing the hooks. Also, check your configuration of `cspell` and `lint-staged` and ensure it's working as expected. Lastly, look for any possible OS-specific issues that could be causing the problem.

so to clarify that means that if we update the commit hooks, the already existing contributors will have their hooks updated next time they run `yarn install`?

Unfortunately, simply running `yarn install` or `npm install` again after updating the commit hooks might not update the hooks for existing contributors.

In Husky 6, the hooks are stored in the `.husky` directory in the root of your repository. These are not directly linked to your `node_modules` directory, so running `yarn install` or `npm install` won't directly affect them.

When you update the hooks, you should inform your contributors to pull the latest changes from the repository, which will update the scripts in the `.husky` directory. After that, contributors will need to run `npx husky install` (or `yarn husky install`, depending on your setup) to set up the Git hooks on their local repository.

This is because `npx husky install` (or `yarn husky install`) sets up the Git hooks by creating symbolic links to the scripts in your `.husky` directory.

So, in summary, when you update your Husky hooks:

1. Commit the changes and push to the repository.
2. Ask your contributors to pull the latest changes.
3. Have them run `npx husky install` (or `yarn husky install`) to update the Git hooks on their local repository.

This should ensure that all contributors are using the latest versions of your Husky hooks.