

This is a copy of a conversation between ChatGPT & Anonymous.

Report conversation

React ■■■■■ ■■■ ■■

PR Link: <https://github.com/carrot-stick/design-system/pull/12>

Conversation Link: <https://chat.openai.com/share/6165a646-8fce-4c97-9ac6-b348c228c451>

React eslint, prettier

- Axis

<Input

```
placeholder={'Error placeholder'}
```

```
error={true}
```

/>

- Tobe

<Input

placeholder="Error placeholder"

error

/ >

Asis ■■■ Tobe■ ■■■■■ ■■■ ■■■ ■■ ■■.

THE UNITED STATES OF AMERICA, DISTRICT OF COLUMBIA,)
COUNTY OF DISTRICT OF COLUMBIA,)
JOHN J. HARRIS,)
Plaintiff,)
vs.)
THE UNITED STATES OF AMERICA,)
COUNTY OF DISTRICT OF COLUMBIA,)
JOHN J. HARRIS,)
Defendant.)

██████████ ██████████, ██████████ ██████████ ██████████: ██████████

1. ****String Props:**** JSX■■ string ■■ ■■ ■■■ ■■■ ■, ■■■■ ■■ ■■■ ■■■
■ ■■■■ ■■■■.

- Asis: `placeholder={'Error placeholder'}`

- Tobe: `placeholder="Error placeholder"`

2. ****Boolean Props:**** ■ ■■ ■■ Boolean ■■■■ ■■, ■■ ■■■■ ■(true)■ ■■■■ ■■, ■■ ■■■■ ■■■■■■.

- Axis: ``error={true}``

- Tobe: `error`

ESLint Prettier. .

1. ESLint

- **jsx-quotes:** JSX boolean ,
- **react/jsx-boolean-value:** JSX boolean ,

`.eslintrc` ESLint

Code

```
{
  "rules": {
    "jsx-quotes": ["error", "prefer-double"],
    "react/jsx-boolean-value": ["error", "never"]
  }
}
```

2. Prettier

Prettier, ESLint, Prettier ESLint, Prettier JSX

`.prettierrc` Prettier

Code

```
{
  "jsxSingleQuote": false
}
```

ESLint Prettier

ESLint Prettier `eslint-config-prettier` `eslint-plugin-prettier` Prettier ESLint

, ESLint

1. :

Code

```
npm install --save-dev eslint-config-prettier eslint-plugin-prettier
```

2. `.eslintrc` 文件:

Code

```
{
  "extends": [
    "some-other-config-you-use",
    "prettier"
  ],
  "plugins": [
    "prettier"
  ],
  "rules": {
    "prettier/prettier": "error",
    // ...
  }
}
```

在 `.eslintrc` 文件中, ESLint 和 Prettier 的配置文件可以放在同一个文件中,也可以放在不同的文件中,这取决于你的项目结构。