

Report conversation

Reword this (It's for a documentation / technote)

If we use NLP to store the test-data value in a runtime variable `$(runtimeVariable)`, it will try to evaluate the runtime value of `$(runtimeVariable)` and then stores to the evaluated value.

Example :

Store 'title' in `$(runtimeVariable)`

here the 'title' will be stored in the evaluated value of `runtimeVariable`, not in variable name 'runtimeVariable'.

If you just want to store the test-data value into a variable you have to use a plain text value 'runtimeVariable'

Example :

Store 'title' in `runtimeVariable`

Here the 'title' will be stored in the variable name 'runtimeVariable'.

So in next steps you can use the variable in NLP's like
Enter `$(runtimeVariable)` in element

If NLP is utilized to store the test data value in a runtime variable, denoted as `$(runtimeVariable)`, the system will attempt to evaluate the runtime value represented by `$(runtimeVariable)` and then store the result of the evaluation.

Example:

Store 'title' in `$(runtimeVariable)`

In this case, 'title' will be stored in the evaluated value of the `runtimeVariable`, not in a variable named 'runtimeVariable'.

Alternatively, if the goal is to simply store the test data value into a variable without any evaluation, a plain text value 'runtimeVariable' should be used.

Example:

Store 'title' in runtimeVariable

Here, 'title' will be stored in the variable named 'runtimeVariable'. Subsequently, in the following steps, the variable can be employed in NLP commands, such as entering \$|runtimeVariable| in an element.