

Report conversation

My CreatePost component has redundant MUI FAB components. I want to map which marker is pressed that should change the background color and set as the selected marker. Can this be done? Here is the portion of the redundant code below:

```
<Fab
    className=
    {${styles['CreatePost__fab']}} ${marker ===
    'cone' ? styles['CreatePost__active'] :
    ''}}
    size="large"
    aria-label="cone"
    onClick={() => markerClick('cone')}
  >
    <img
      className=
      {styles['CreatePost__images']}
      src={cone}
      alt=""
    />
  </Fab>
<Fab
    className=
    {${styles['CreatePost__fab']}} ${marker ===
    'pothole' ? styles['CreatePost__active'] :
    ''}}
    size="large"
    aria-label="pothole"
    onClick={() => markerClick('pothole')}
  >
    <img
      className=
      {styles['CreatePost__images']}
      src={pothole}
      alt=""
    />
  </Fab>
```

```

<Fab
  className=
    ${styles['CreatePost__fab']} ${marker ===
    'roadDamage' ? styles['CreatePost__active']
    : ''}}
  size="large"
  aria-label="roadDamage"
  onClick={() =>
markerClick('roadDamage')}
>
  <img
    className=
    {styles['CreatePost__images']}
    src={roadDamage}
    alt=""
  />
</Fab>
<Fab
  className=
    ${styles['CreatePost__fab']} ${marker ===
    'carAccident' ?
    styles['CreatePost__active'] : ''}}
  size="large"
  aria-label="carAccident"
  onClick={() => markerClick('carAccident')}
>
  <img
    className=
    {styles['CreatePost__images2']}
    src={carAccident}
    alt=""
  />
</Fab>
<Fab
  className=
    ${styles['CreatePost__fab']} ${marker ===
    'warningSign' ?
    styles['CreatePost__active'] : ''}}
  size="large"
  aria-label="warningSign"

```

```

onClick={() => markerClick('warningSign')}
>
<img
  className=
    {styles['CreatePost__images']}
  src={warning}
  alt=""
/>
</Fab>
<Fab
  className=
    ${styles['CreatePost__fab']} ${marker ===
    'etc' ? styles['CreatePost__active'] : ''}
  size="large"
  aria-label="etc"
  onClick={() => markerClick('etc')}
>
  <MoreHoriz className=
    {styles['CreatePost__images']} />
</Fab>

```

You can avoid redundancy in your code by dynamically rendering the FAB components using an array of markers and mapping through them. Here's how you can do it:

jsx

 Copy code

```

const markers = [
  { name: 'cone', icon: cone },
  { name: 'pothole', icon: pothole },
  { name: 'roadDamage', icon: roadDamage },
  { name: 'carAccident', icon: carAccident },
  { name: 'warningSign', icon: warning },
  { name: 'etc', icon: MoreHoriz },
];

return (
  <>
    {markers.map((marker, index) => (
      <Fab
        key={index}

```

```

      className={` ${styles['CreatePost__fab']} ${selectedMarker :
      size="large"
      aria-label={marker.name}
      onClick={() => markerClick(marker.name)}
    >
      {typeof marker.icon === 'string' ? (
        <img
          className={styles['CreatePost__images']}
          src={marker.icon}
          alt=""
        />
      ) : (
        <marker.icon className={styles['CreatePost__images']} />
      )}
    </Fab>
  )}
</>
);

```

This code dynamically renders the FAB components based on the `markers` array. It maps through each marker and renders a FAB component for each one. The `selectedMarker` state variable is used to determine whether a marker is active, and the `markerClick` function is called when a FAB component is clicked.