

Report conversation

what's the difference between openapi oneOf vs anyOf ?

In OpenAPI, `oneOf` and `anyOf` are JSON Schema keywords used to define the validation rules for request or response payloads. They are used to specify alternative schemas that a given value must conform to.

Here's the difference between `oneOf` and `anyOf` :

1. `oneOf` : It specifies that a value must match exactly one of the provided schemas. In other words, the value must adhere to the constraints of exactly one of the defined schemas. If a value matches multiple schemas, it would be considered invalid. It enforces a mutually exclusive choice.

Example:

yaml

 Copy code

```
oneOf:  
  - type: string  
    maxLength: 5  
  - type: number  
    minimum: 10
```

In the above example, the value must either be a string with a maximum length of 5 or a number greater than or equal to 10.

2. `anyOf` : It specifies that a value must match at least one of the provided schemas. The value can conform to any of the defined schemas, allowing for multiple valid options. If a value matches multiple schemas, it is considered valid.

Example:

yaml

 Copy code

```
anyOf:  
  - type: string  
    maxLength: 5
```

```
- type: number  
  minimum: 10
```

In the above example, the value can be a string with a maximum length of 5 or a number greater than or equal to 10. It can satisfy either condition.

To summarize, `oneOf` enforces a single, exclusive choice among the provided schemas, while `anyOf` allows for multiple valid options by matching any of the provided schemas.