

Report conversation

how do i open a url in windows 10 command-line? (CMD or powershell)

To open a URL from the Windows Command Prompt (CMD) or PowerShell, you can use the following commands:

1. In CMD:

nginx

 Copy code

```
start https://www.example.com
```

2. In PowerShell:

arduino

 Copy code

```
Start-Process "https://www.example.com"
```

Both commands will launch the default web browser and navigate to the specified URL.

```
void open_url( const std::string &url )
{
    static const std::string executable =
#ifdef _WIN32
        "explorer";
#elif defined(_WIN64)
        "start";
#elif defined(__linux__)
        "xdg-open";
#elif defined(__APPLE__)
        "open";
#elif defined(__ANDROID__)
        "am start -a android.intent.action.VIEW -d";
#endif
    const std::string command = executable + "\"" + url +
        "\"";
```

```
const int exitcode = std::system( command.data() );
if( exitcode != 0 ) {
    debugmsg( "Failed to open URL: %s\nAttempted
command was: %s", url, command );
}
}
```

this failed, does std::system in windows use CMD or powershell?

std::system on Windows generally uses `cmd.exe` to execute the given command string. Your code snippet has a few issues that could make it fail on Windows:

1. For `_WIN64`, you're using `"start"`, but you should use `"start \"%\""` to avoid treating the URL as the title of the new Command Prompt window.
2. For `_WIN32`, you're using `"explorer"` which should work, but make sure to compile for the correct architecture (`_WIN32` or `_WIN64`).

Here's a corrected version:

cpp

 Copy code

```
void open_url(const std::string &url) {
    std::string executable;

    #if defined(_WIN32) || defined(_WIN64)
        executable = "start \"%\"";
    #elif defined(__linux__)
        executable = "xdg-open";
    #elif defined(__APPLE__)
        executable = "open";
    #elif defined(__ANDROID__)
        executable = "am start -a android.intent.action.VIEW -d";
    #endif

    const std::string command = executable + " \"%\" + url + "\"";

    const int exitcode = std::system(command.c_str());
    if (exitcode != 0) {
        // debugmsg("Failed to open URL: %s\nAttempted command was: %s", ur
        // Replace debugmsg with your debugging/logging function
```

```
}  
}
```

Make sure you are using the right compile-time definitions (`_WIN32` or `_WIN64`) for your build.

```
will running  
start "cataclysmteam/Cataclysm-BN/issues/r
```

in CMD.exe open correct url?

No, running that command in CMD.exe will not open the correct URL. The reason is that the `start` command in CMD.exe treats the first argument in quotes as the title for the new Command Prompt window that gets opened.

You can get around this by providing an empty title argument like this:

cmd

 Copy code

```
start "" "cataclysmteam/Cataclysm-BN/issues/new?labels=bug&template=bug_
```

However, this command will still fail because the URL is incomplete (it lacks the `https://` prefix and the domain name).

A complete and correct command should look something like this:

cmd

 Copy code

```
start "" "https://github.com/cataclysmteam/Cataclysm-BN/issues/new?label
```

i don't understand why https is omitted, this is the exact code and the only usage:

C++

```
constexpr const char *const bug_
    "https://github.com/cataclyst
    "?labels=bug"
    "&template=bug_report.yml"
    "&versions-and-configuration
```

```
const std::string report = game_
const std::string url = bug_repa
```

```
open_url( url );
```

C++

```
void open_url( const std::string &url )
{
    static const std::string executable =
#ifdef _WIN32
        "explorer";
#elif defined(_WIN64)
        "start";
#elif defined(__linux__)
        "xdg-open";
#elif defined(__APPLE__)
        "open";
#elif defined(__ANDROID__)
        "am start -a android.intent.action.\
#endif
    const std::string command = executable -

    const int exitcode = std::system( commar
    if( exitcode != 0 ) {
        debugmsg( "Failed to open URL: %s\n"
    }
}
```

The issue is likely in the `open_url` function's handling for Windows. The code for `_WIN64` should not be `"start"` but `"start \"\""` to handle the argument correctly.

Here's the modified portion of your `open_url` function:

cpp

 Copy code

```
#if defined(_WIN32) || defined(_WIN64)
    executable = "start \"%\"";
```

This change makes sure that `start` does not mistake your URL for the title of the window.

Additionally, please ensure that the `#if defined(_WIN32) || defined(_WIN64)` is correct based on your build target, as `_WIN32` will also be defined for 64-bit builds. So having separate blocks for `_WIN32` and `_WIN64` may not behave as expected. Just having one block to handle Windows should be enough.