

Report conversation

What is tailwindcss and can you make a simple code snippet that shows its use and what it does?

Tailwind CSS is a utility-first CSS framework that provides low-level utility classes to build custom designs quickly. It allows you to create designs by composing utility classes directly in your HTML markup, rather than writing custom CSS.

Here's a simple code snippet demonstrating the use of Tailwind CSS to create a basic button:

html

 Copy code

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Tailwind CSS Example</title>
  <!-- Include Tailwind CSS -->
  <link href="https://cdn.jsdelivr.net/npm/tailwindcss@2.2.19/dist/tailwind"
</head>
<body>

<!-- Example button using Tailwind CSS -->
<button class="bg-blue-500 hover:bg-blue-700 text-white font-bold py-2 px-4">
  Button
</button>

</body>
</html>
```

In this example:

- The `bg-blue-500` class sets the background color of the button to a shade of blue.

- The `hover:bg-blue-700` class changes the background color to a darker shade of blue when the button is hovered over.
- The `text-white` class sets the text color to white.
- The `font-bold` class makes the text bold.
- The `py-2` and `px-4` classes add padding to the top and bottom (`py`) and left and right (`px`) of the button, respectively.
- The `rounded` class adds rounded corners to the button.

These utility classes allow you to quickly style elements without having to write custom CSS, making it easy to create consistent and responsive designs.

Here is the most recent code:

```
import React from 'react'
import { Linking, SafeAreaView, Text, View } from 'react-native'
```

```
import { Feather, Fontisto, SimpleLineIcons } from
 '@expo/vector-icons'
```

```
import NavBar from '~/components/ui/nav-bar/NavBar'
```

```
const viewStyles = { flexDirection: 'row', alignItems:
 'center', marginTop: 20 }
const textStyles = { fontSize: 18, color: '#CACACA' }
```

```
export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor:
      '#1C1B1B' }}>
      { /* Header */ }
      <NavBar center='Contact Us' />

      <View style={{ flex: 1, paddingHorizontal: 20,
paddingTop: 20 }}>
        { /* Email */ }
        <View style={{ flexDirection: 'row', alignItems:
'center', marginTop: 30 }}>
          <Fontisto name='email' size={24} color='#CACACA'
```

```

style={{ marginRight: 10 }} />
    <Text style={{ fontSize: 18, color: '#CACACA'
}}>barbell_support@gmail.com</Text>
</View>

{/* Phone */}
<View style={{ flexDirection: 'row', alignItems:
'center', marginTop: 30 }}>
    <Feather name='phone' size={24} color='#CACACA'
style={{ marginRight: 10 }} />
    <Text style={{ fontSize: 18, color: '#CACACA' }}>+1
(702) 895-3011</Text>
</View>

{/* Location */}
<View style={{ flexDirection: 'row', alignItems:
'center', marginTop: 30 }}>
    <SimpleLineIcons
    name='location-pin'
    size={24}
    color='#CACACA'
    style={{ marginRight: 10 }}
    />
    <View>
        <Text style={{ fontSize: 18, color: '#CACACA'
}}>University of Nevada, Las Vegas</Text>
        <Text style={{ fontSize: 18, color: '#CACACA'
}}>4505 South Maryland Parkway</Text>
        <Text style={{ fontSize: 18, color: '#CACACA' }}>Las
Vegas, NV 89154</Text>
    </View>
</View>

{/* Response Time */}
<Text style={{ fontSize: 16, marginTop: 40, color:
'#CACACA', textAlign: 'center' }}>
    Our goal is to respond to your inquiries within a 24-
hour time frame on weekdays.
</Text>
</View>

```

```

    </SafeAreaView>
  )
}

```

Create some variables that are set to the more common styling so that I can reference the variable rather than having the entire line

Sure, I can help you refactor the code to use variables for common styling. Here's the modified code:

javascript

 Copy code

```

import React from 'react';
import { Linking, SafeAreaView, Text, View } from 'react-native';

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons';

import NavBar from '~/components/ui/nav-bar/NavBar';

// Common styles
const baseTextStyle = { fontSize: 18, color: '#CACACA' };
const iconStyle = { marginRight: 10 };

export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor: '#1C1B1B' }}>
      { /* Header */ }
      <NavBar center='Contact Us' />

      <View style={{ flex: 1, paddingHorizontal: 20, paddingTop: 20 }}>
        { /* Email */ }
        <View style={[viewStyles, { marginTop: 30 }]}>
          <Fontisto name='email' size={24} color='#CACACA' style={iconStyle}>
            <Text style={baseTextStyle}>barbell_support@gmail.com</Text>
          </View>

          { /* Phone */ }
          <View style={[viewStyles, { marginTop: 30 }]}>
            <Feather name='phone' size={24} color='#CACACA' style={iconStyle}>
              <Text style={baseTextStyle}>+1 (702) 895-3011</Text>
            </Feather>
          </View>
        </View>
      </SafeAreaView>
    </View>
  );
}

```

```

</View>

{/* Location */}
<View style={[viewStyles, { marginTop: 30 }]}>
  <SimpleLineIcons
    name='location-pin'
    size={24}
    color='#CACACA'
    style={iconStyle}
  />
  <View>
    <Text style={baseTextStyle}>University of Nevada, Las Vegas</Text>
    <Text style={baseTextStyle}>4505 South Maryland Parkway</Text>
    <Text style={baseTextStyle}>Las Vegas, NV 89154</Text>
  </View>
</View>

{/* Response Time */}
<Text style={{ ...baseTextStyle, fontSize: 16, marginTop: 40, text/
  Our goal is to respond to your inquiries within a 24-hour time fi
</Text>
</View>
</SafeAreaView>
);
}

```

In this refactored version:

- `baseTextStyle` contains common text styles.
- `iconStyle` contains common styles for icons.
- The `viewStyles` object is kept inline as it's more specific and might not be reused elsewhere.

Here is my latest version of the code:

```

import React from 'react'
import { Linking, SafeAreaView, Text, View } from 'react-
native'

```

```
import { Feather, Fontisto, SimpleLineIcons } from
 '@expo/vector-icons'

import NavBar from '~/components/ui/nav-bar/NavBar'

const viewStyles = { flexDirection: 'row', alignItems:
 'center', marginTop: 30 }
const textStyles = { fontSize: 18, color: '#CACACA' }

export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor:
 '#1C1B1B' }}>
      { /* Header */ }
      <NavBar center='Contact Us' />

      <View style={{ flex: 1, paddingHorizontal: 20,
 paddingTop: 20 }}>
        { /* Email */ }
        <View style={{ flexDirection: 'row', alignItems:
 'center', marginTop: 30 }}>
          <Fontisto name='email' size={24} color='#CACACA'
 style={{ marginRight: 10 }} />
          <Text style=
 {textStyles}>barbell_support@gmail.com</Text>
        </View>

        { /* Phone */ }
        <View style={{ flexDirection: 'row', alignItems:
 'center', marginTop: 30 }}>
          <Feather name='phone' size={24} color='#CACACA'
 style={{ marginRight: 10 }} />
          <Text style={textStyles}>+1 (702) 895-3011</Text>
        </View>

        { /* Location */ }
        <View style={{ flexDirection: 'row', alignItems:
 'center', marginTop: 30 }}>
          <SimpleLineIcons
            name='location-pin'
```

```
        size={24}
        color='#CACACA'
        style={{ marginRight: 10 }}
      />
    <View>
      <Text style={textStyles}>University of Nevada, Las
Vegas</Text>
      <Text style={textStyles}>4505 South Maryland
Parkway</Text>
      <Text style={textStyles}>Las Vegas, NV
89154</Text>
    </View>
  </View>

  { /* Response Time */ }
  <Text style={{ fontSize: 16, marginTop: 40, color:
'#CACACA', textAlign: 'center' }}>
    Our goal is to respond to your inquiries within a 24-
hour time frame on weekdays.
  </Text>
</View>
</SafeAreaView>
)
}
```

I need your help with something?

Of course, I'm here to help. What do you need assistance with?

Do you see the two const variables that I have declared at the top?

Yes, I see the two constants `viewStyles` and `textStyles` that you have declared at the top of your `contactUsPage` component. They contain styles for the views and texts used in your component, respectively. How can I assist you with them?

I need you to take the variable "const viewStyles = { flexDirection: 'row', alignItems: 'center', marginTop: 30 }" and I need you to replace every line that has "<View style={{ flexDirection: 'row', alignItems: 'center', marginTop: 30 }}" with this variable and make sure the code is functioning. Do I need to clarify anything for you?

Got it! You want to replace every occurrence of the inline styles <View style={{ flexDirection: 'row', alignItems: 'center', marginTop: 30 }}> with the viewStyles constant, and ensure the code remains functional. I'll make the necessary modifications. Let me know if you need further clarification or assistance.

No further assistance is needed, go ahead and make the change for me please!

Sure, here's the modified code with the viewStyles constant used instead of inline styles:

javascript

 Copy code

```
import React from 'react';
import { Linking, SafeAreaView, Text, View } from 'react-native';

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons';

import NavBar from '~/components/ui/nav-bar/NavBar';

const viewStyles = { flexDirection: 'row', alignItems: 'center', marginTop
const textStyles = { fontSize: 18, color: '#CACACA' };

export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor: '#1C1B1B' }}>
```



```

    { /* Header */}
    <NavBar center='Contact Us' />

    <View style={{ flex: 1, paddingHorizontal: 20, paddingTop: 20 }}>
      { /* Email */}
      <View style={viewStyles}>
        <Fontisto name='email' size={24} color='#CACACA' style={{ marginR
        <Text style={textStyles}>barbell_support@gmail.com</Text>
      </View>

      { /* Phone */}
      <View style={viewStyles}>
        <Feather name='phone' size={24} color='#CACACA' style={{ marginR:
        <Text style={textStyles}>+1 (702) 895-3011</Text>
      </View>

      { /* Location */}
      <View style={viewStyles}>
        <SimpleLineIcons
          name='location-pin'
          size={24}
          color='#CACACA'
          style={{ marginRight: 10 }}
        />
        <View>
          <Text style={textStyles}>University of Nevada, Las Vegas</Text>
          <Text style={textStyles}>4505 South Maryland Parkway</Text>
          <Text style={textStyles}>Las Vegas, NV 89154</Text>
        </View>
      </View>

      { /* Response Time */}
      <Text style={{ ...textStyles, fontSize: 16, marginTop: 40, textAliq
        Our goal is to respond to your inquiries within a 24-hour time fi
      </Text>
    </View>
  </SafeAreaView>
);
}

```

I replaced every occurrence of `<View style={{ flexDirection: 'row', alignItems: 'center', marginTop: 30 }}>` with `viewStyles`. Let me know if everything looks good!

I get the following error from my compiler when I use the above code:

No overload matches this call.

Overload 1 of 2, '(props: ViewProps): View', gave the following error.

Type '{ flexDirection: string; alignItems: string; marginTop: number; }' is not assignable to type 'StyleProp<ViewStyle>'.

Type '{ flexDirection: string; alignItems: string; marginTop: number; }' is not assignable to type 'ViewStyle'.

Types of property 'alignItems' are incompatible.

Type 'string' is not assignable to type 'FlexAlignType | undefined'.

Overload 2 of 2, '(props: ViewProps, context: any): View', gave the following error.

Type '{ flexDirection: string; alignItems: string; marginTop: number; }' is not assignable to type 'StyleProp<ViewStyle>'.ts(2769)

ViewPropTypes.d.ts(234, 3): The expected type comes from property 'style' which is declared here on type 'IntrinsicAttributes & IntrinsicClassAttributes<View> & Readonly<ViewProps>'

ViewPropTypes.d.ts(234, 3): The expected type comes from property 'style' which is declared here on type 'IntrinsicAttributes & IntrinsicClassAttributes<View> & Readonly<ViewProps>'

(property) style?: StyleProp<ViewStyle>

Why is this happening and does it have something to do with the code you just changed?

The error you're encountering suggests that there's a type incompatibility with the style object passed to the `view` component. This issue might arise due to the difference in the type expected for the `style` prop of the `view` component and the type provided by the `viewStyles` constant.

To resolve this issue, you can explicitly specify the type of the `style` prop using `ViewStyle`. Here's how you can do it:

javascript

 Copy code

```
import React from 'react';
import { Linking, SafeAreaView, Text, View, ViewStyle } from 'react-native';

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons';

import NavBar from '~/components/ui/nav-bar/NavBar';

const viewStyles: ViewStyle = { flexDirection: 'row', alignItems: 'center',
const textStyles = { fontSize: 18, color: '#CACACA' };

export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor: '#1C1B1B' }}>
      { /* Header */ }
      <NavBar center='Contact Us' />

      <View style={{ flex: 1, paddingHorizontal: 20, paddingTop: 20 }}>
        { /* Email */ }
        <View style={viewStyles}>
          <Fontisto name='email' size={24} color='#CACACA' style={{ margin: 0 10 }}>
            <Text style={textStyles}>barbell_support@gmail.com</Text>
          </View>

          { /* Phone */ }
          <View style={viewStyles}>
            <Feather name='phone' size={24} color='#CACACA' style={{ margin: 0 10 }}>
              <Text style={textStyles}>+1 (702) 895-3011</Text>
            </View>

            { /* Location */ }
```

```

<View style={viewStyles}>
  <SimpleLineIcons
    name='location-pin'
    size={24}
    color='#CACACA'
    style={{ marginRight: 10 }}
  />
  <View>
    <Text style={textStyles}>University of Nevada, Las Vegas</Text>
    <Text style={textStyles}>4505 South Maryland Parkway</Text>
    <Text style={textStyles}>Las Vegas, NV 89154</Text>
  </View>
</View>

{/* Response Time */}
<Text style={{ ...textStyles, fontSize: 16, marginTop: 40, textAliq
  Our goal is to respond to your inquiries within a 24-hour time fi
</Text>
</View>
</SafeAreaView>
);
}

```

By explicitly specifying the type of `viewStyles` as `ViewStyle`, you ensure that it matches the expected type for the `style` prop of the `view` component. This should resolve the type incompatibility issue. Let me know if it works for you!

Here is the current version of my code:

```

import React from 'react'
import { Linking, SafeAreaView, Text, View, ViewStyle }
from 'react-native' // Import ViewStyle

```

```

import { Feather, Fontisto, SimpleLineIcons } from
 '@expo/vector-icons'

```

```

import NavBar from '~/components/ui/nav-bar/NavBar'

```

```

{

```

```

    /* these variables are used to simplify common styling */
  }
  const viewStyles: ViewStyle = { flexDirection: 'row',
    alignItems: 'center', marginTop: 30 }
  const textStyles = { fontSize: 18, color: '#CACACA' }

  export default function ContactUsPage() {
    return (
      <SafeAreaView style={{ flex: 1, backgroundColor:
        '#1C1B1B' }}>
        { /* Header */ }
        <NavBar center='Contact Us' />

        <View style={{ flex: 1, paddingHorizontal: 20,
paddingTop: 20 }}>
          { /* Email */ }
          <View style={viewStyles}>
            <Fontisto name='email' size={24} color='#CACACA'
style={{ marginRight: 10 }} />
            <Text style=
{textStyles}>barbell_support@gmail.com</Text>
          </View>

          { /* Phone */ }
          <View style={viewStyles}>
            <Feather name='phone' size={24} color='#CACACA'
style={{ marginRight: 10 }} />
            <Text style={textStyles}>+1 (702) 895-3011</Text>
          </View>

          { /* Location */ }
          <View style={viewStyles}>
            <SimpleLineIcons
              name='location-pin'
              size={24}
              color='#CACACA'
              style={{ marginRight: 10 }}
            />
            <View>
              <Text style={textStyles}>University of Nevada, Las

```

```
Vegas</Text>
  <Text style={textStyles}>4505 South Maryland
Parkway</Text>
  <Text style={textStyles}>Las Vegas, NV
89154</Text>
</View>
</View>

{/* Response Time */}
<Text style={{ ...textStyles, fontSize: 16, marginTop:
40, textAlign: 'center' }}>
  Our goal is to respond to your inquiries within 24
business hours.
</Text>
</View>
</SafeAreaView>
)
}
```

I need help with one more thing

Sure, what do you need help with?

Can you convert the above React Native styling to use tailwindcss instead? Is this possible?

Yes, it's possible to convert the React Native styling to use Tailwind CSS. However, Tailwind CSS is primarily designed for web development, so directly using it in React Native might not work as expected. React Native uses a different styling approach compared to web development.

Instead, you can achieve a similar utility-first approach in React Native by using libraries like `tailwind-rn` or `react-native-tailwindcss`. These libraries provide a similar experience to Tailwind CSS but are tailored for React Native development.

Here's how you can convert your React Native code to use `react-native-tailwindcss`:

First, install the library:

bash

 Copy code

```
npm install react-native-tailwindcss
```

Then, modify your code to use Tailwind CSS utility classes:

javascript

 Copy code

```
import React from 'react';
import { Linking, SafeAreaView, Text, View } from 'react-native';
import tw from 'react-native-tailwindcss'; // Import tailwindcss

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons';

import NavBar from '~/components/ui/nav-bar/NavBar';

export default function ContactUsPage() {
  return (
    <SafeAreaView style={[tw.flex1, tw.bgGray900]}>
      {/* Header */}
      <NavBar center='Contact Us' />

      <View style={[tw.flex1, tw.px8, tw.pt8]}>
        {/* Email */}
        <View style={[tw.flexRow, tw.itemsCenter, tw.mt4]}>
          <Fontisto name='email' size={24} color='#CACACA' style={tw.mr2} />
          <Text style={[tw.textBase, tw.textGray400]}>barbell_support@gmail.com</Text>
        </View>

        {/* Phone */}
        <View style={[tw.flexRow, tw.itemsCenter, tw.mt4]}>
          <Feather name='phone' size={24} color='#CACACA' style={tw.mr2} />
          <Text style={[tw.textBase, tw.textGray400]}>+1 (702) 895-3011</Text>
        </View>

        {/* Location */}
        <View style={[tw.flexRow, tw.itemsCenter, tw.mt4]}>
          <SimpleLineIcons
            name='location-pin'

```

```

        size={24}
        color='#CACACA'
        style={tw.mr2}
      />
    <View>
      <Text style={[tw.textBase, tw.textGray400]}>University of Nevada
      <Text style={[tw.textBase, tw.textGray400]}>4505 South Maryland
      <Text style={[tw.textBase, tw.textGray400]}>Las Vegas, NV 89154
    </View>
  </View>

  { /* Response Time */ }
  <Text style={[tw.textBase, tw.mt8, tw.textGray400, tw.textCenter]}>
    Our goal is to respond to your inquiries within 24 business hours
  </Text>
</View>
</SafeAreaView>
);
}

```

In this code:

- We import `tw` from `react-native-tailwindcss` and use it to apply Tailwind CSS utility classes.
- We replace the inline styles with Tailwind CSS utility classes. For example, `tw.flex1` replaces `{ flex: 1 }`, `tw.px8` replaces `{ paddingHorizontal: 20 }`, etc.

This way, you can achieve a similar utility-first approach in React Native using `react-native-tailwindcss`. Make sure to adjust the styles as needed to match your design requirements.

What kind of `tailwindcss` is this code using?

```

import React, { useEffect, useRef } from 'react'
import {
  Keyboard,
  KeyboardAvoidingView,
  LayoutAnimation,
  Platform,

```



```
SafeAreaView,  
Text,  
View,  
} from 'react-native'  
import { ScrollView } from 'react-native-gesture-handler'  
import { router, useLocalSearchParams } from 'expo-router'  
  
import { Ionicons } from '@expo/vector-icons'  
import { ChatType } from '@prisma/client'  
  
import MessageInput from  
'~/components/message/messageInput'  
import RotatingBarbellIcon from  
'~/components/notif/RotatingBarbellIcon'  
import { useGlobalContext } from '~/context/global-context'  
import { api } from '~/utils/trpc/api'  
  
export default function MessageView() {  
  const scrollViewRef: React.RefObject<ScrollView> =  
    useRef(null)  
  const p = useLocalSearchParams()  
  const { userData: user } = useGlobalContext()  
  
  useEffect(() => {  
    const keyboardDidShowListener =  
      Keyboard.addListener('keyboardDidShow', () => {  
        if (scrollViewRef.current) {  
          scrollViewRef.current.scrollToEnd({ animated: true })  
        }  
      })  
  
    return () => {  
      keyboardDidShowListener.remove()  
    }  
  }, [])  
  
  const {  
    data: messages,
```

```

    isFetching,
    isFetched,
  } =
    api.notif.getMessagesFromChatIdAndChatType.useQuery
    ({
      id: Number(p['chatId']),
      type: p['type'] as ChatType,
    })
    const chattingWith = p['chatName']?.toString().trim()

    return (
      <SafeAreaView style={{ backgroundColor: '#1C1B1B',
flex: 1 }}>
        <KeyboardAvoidingView
          behavior={Platform.OS === 'ios' ? 'padding' : 'height'}
          keyboardVerticalOffset={Platform.OS === 'ios' ? 60 :
80}
          style={{ flex: 1 }}
        >
          <View style={{ flex: 1, margin: 10 }}>
            <View className='flex flex-row justify-between px-
5'>
              <Ionicons onPress={() => router.back()}
name='chevron-back' size={24} color='#CACACA' />
              <Text style={{ color: '#CACACA', fontSize: 20 }}>
{chattingWith}</Text>
              <View />
            </View>
            <View className='pt-3' style={{
borderBottomWidth: 1, borderBottomColor: '#737272' }}
/>
            {isFetching ? (
              <RotatingBarbellIcon />
            ) : isFetched ? (
              <ScrollView
                className='flex gap-y-3'
                ref={scrollViewRef}
                onContentSizeChange={() =>
                  scrollViewRef.current &&
                    scrollViewRef.current.scrollToEnd({ animated: true })
                }
            ) : null}
          </View>
        </SafeAreaView>
      )
    )
  }
}

```

```

    }
  >
  <View className='h-fit gap-y-3'>
    {messages?.map((message) =>
      message.senderId == user?.id ? (
        <View
          key={message.id}
          className='bg-dark-purple w-1/2 self-end
rounded-xl px-4 pt-3'
        >
          <Text className='text-left text-slate-200'>
{message.content + '\n'}</Text>
        </View>
      ) : (
        <View
          key={message.id}
          className='w-1/2 self-start rounded-xl bg-
zinc-800 px-4 pt-3'
        >
          <Text className='text-left text-slate-200'>
{message.content + '\n'}</Text>
        </View>
      ),
    )}
  </View>
</ScrollView>
): (
  <Text>Issue retrieving messages</Text>
)
</View>
<MessageInput />
</KeyboardAvoidingView>
</SafeAreaView>
)
}

```

The code you provided appears to use Tailwind CSS for styling. Tailwind CSS is a utility-first CSS framework, and the class names like `flex`, `justify-between`, `px-5`, `pt-3`, `bg-dark-purple`, `w-1/2`, etc., are typical of Tailwind CSS.

Here's a brief breakdown of some of the Tailwind CSS classes used in the code:

- `flex` : Establishes a flex container.
- `justify-between` : Justifies content evenly along the main axis with extra space placed between the items.
- `px-5` : Sets padding on the horizontal axis to a value determined by the Tailwind CSS spacing scale (in this case, 5).
- `pt-3` : Sets padding on the top to a value determined by the Tailwind CSS spacing scale (in this case, 3).
- `bg-dark-purple` : Sets the background color to a shade of dark purple.
- `w-1/2` : Sets the width to half of its parent container's width.
- `self-end` : Aligns the flex item to the end of the cross axis.
- `rounded-xl` : Applies rounded corners with a large border radius.
- `text-left` : Aligns text to the left.
- `text-slate-200` : Sets the text color to a shade of slate.

Overall, the code leverages Tailwind CSS utility classes to style various elements within a React Native application.

Okay so I want you to take the code that I sent you before this one and apply the same kind of tailwind to MY code block and not the most recent one. Do I make sense?

Absolutely, I understand now. Let's apply Tailwind CSS classes to your provided code block:

javascript

 Copy code

```
import React, { useEffect, useRef } from 'react'
import { Keyboard, KeyboardAvoidingView, SafeAreaView, Text, View, ScrollView:
import { router, useLocalSearchParams } from 'expo-router'

import { Ionicons } from '@expo/vector-icons'
import { ChatType } from '@prisma/client'

import MessageInput from '~/components/message/messageInput'
import RotatingBarbellIcon from '~/components/notif/RotatingBarbellIcon'
```

```

import { useGlobalContext } from '~/context/global-context'
import { api } from '~/utils/trpc/api'

export default function MessageView() {
  const scrollViewRef = useRef(null)
  const p = useLocalSearchParams()
  const { userData: user } = useGlobalContext()

  useEffect(() => {
    const keyboardDidShowListener = Keyboard.addListener('keyboardDidShow',
      if (scrollViewRef.current) {
        scrollViewRef.current.scrollToEnd({ animated: true })
      }
    })

    return () => {
      keyboardDidShowListener.remove()
    }
  }, [])

  const {
    data: messages,
    isFetching,
    isFetched,
  } = api.notif.getMessagesFromChatIdAndChatType.useQuery({
    id: Number(p['chatId']),
    type: p['type'] as ChatType,
  })

  const chattingWith = p['chatName']?.toString().trim()

  return (
    <SafeAreaView className='bg-gray-900 flex-1'>
      <KeyboardAvoidingView
        behavior={Platform.OS === 'ios' ? 'padding' : 'height'}
        keyboardVerticalOffset={Platform.OS === 'ios' ? 60 : 80}
        className='flex-1'
      >
        <View className='flex-1 m-10'>
          <View className='flex flex-row justify-between px-5'>
            <Icons onPress={() => router.back()} name='chevron-back' si

```

```

    <Text className='text-gray-400 text-base'>{chattingWith}</Text>
    <View />
  </View>
  <View className='pt-3' style={{ borderBottomWidth: 1, borderBottomColor: 'gray' }}>
    {isFetching ? (
      <RotatingBarbellIcon />
    ) : isFetched ? (
      <ScrollView className='flex gap-y-3' ref={scrollViewRef}
        onContentSizeChange={() =>
          scrollViewRef.current && scrollViewRef.current.scrollToEnd()
        }>
        <View className='h-fit gap-y-3'>
          {messages?.map((message) =>
            message.senderId == user?.id ? (
              <View
                key={message.id}
                className='bg-dark-purple w-1/2 self-end rounded-xl p-4'
              >
                <Text className='text-left text-slate-200'>{message.content}</Text>
              </View>
            ) : (
              <View
                key={message.id}
                className='w-1/2 self-start rounded-xl bg-zinc-800 p-4'
              >
                <Text className='text-left text-slate-200'>{message.content}</Text>
              </View>
            ),
          )}
        </View>
      </ScrollView>
    ) : (
      <Text>Issue retrieving messages</Text>
    )}
  </View>
  <MessageInput />
</KeyboardAvoidingView>
</SafeAreaView>

```

```
)
}
```

In this updated code block:

- I've replaced the inline styles with Tailwind CSS utility classes.
- Classes like `bg-gray-900`, `flex-1`, `m-10`, `justify-between`, `px-5`, `pt-3`, etc., are Tailwind CSS classes.
- The `className` prop is used to apply Tailwind CSS classes in React Native, similar to how it's done in web development.

Nooo I wanted you to apply TailwindCSS to THIS code block:

```
import React from 'react'
import { Linking, SafeAreaView, Text, View, ViewStyle }
from 'react-native'
```

```
import { Feather, Fontisto, SimpleLineIcons } from
 '@expo/vector-icons'
```

```
import NavBar from '~/components/ui/nav-bar/NavBar'
```

```
{
  /* these variables are used to simplify common styling */
}
```

```
const viewStyles: ViewStyle = { flexDirection: 'row',
alignItems: 'center', marginTop: 30 }
const textStyles = { fontSize: 18, color: '#CACACA' }
```

```
export default function ContactUsPage() {
  return (
    <SafeAreaView style={{ flex: 1, backgroundColor:
'#1C1B1B' }}>
      { /* Header */ }
      <NavBar center='Contact Us' />
```

```
      <View style={{ flex: 1, paddingHorizontal: 20,
paddingTop: 20 }}>
```

```
    {/ * Email */}  
    <View style={viewStyles}>  
      <Fontisto name='email' size={24} color='#CACACA'  
style={{ marginRight: 10 }} />  
      <Text style=  
{textStyles}>barbell_support@gmail.com</Text>  
    </View>
```

```
    {/ * Phone */}  
    <View style={viewStyles}>  
      <Feather name='phone' size={24} color='#CACACA'  
style={{ marginRight: 10 }} />  
      <Text style={textStyles}>+1 (702) 895-3011</Text>  
    </View>
```

```
    {/ * Location */}  
    <View style={viewStyles}>  
      <SimpleLineIcons  
        name='location-pin'  
        size={24}  
        color='#CACACA'  
        style={{ marginRight: 10 }}  
      />  
      <View>  
        <Text style={textStyles}>University of Nevada, Las  
Vegas</Text>  
        <Text style={textStyles}>4505 South Maryland  
Parkway</Text>  
        <Text style={textStyles}>Las Vegas, NV  
89154</Text>  
      </View>  
    </View>
```

```
    {/ * Response Time */}  
    <Text style={{ ...textStyles, fontSize: 16, marginTop:  
40, textAlign: 'center' }}>  
      Our goal is to respond to your inquiries within 24  
business hours.  
    </Text>  
  </View>
```



```

    </SafeAreaView>
  )
}

```

Ah, I see! Let's apply Tailwind CSS classes to the provided code block:

javascript

 Copy code

```

import React from 'react'
import { Linking, SafeAreaView, Text, View, ViewStyle } from 'react-native'

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons'

import NavBar from '~/components/ui/nav-bar/NavBar'

export default function ContactUsPage() {
  return (
    <SafeAreaView className="flex-1 bg-gray-900">
      { /* Header */ }
      <NavBar center='Contact Us' />

      <View className="flex-1 px-8 pt-8">
        { /* Email */ }
        <View className="flex-row items-center mt-8">
          <Fontisto name='email' size={24} color='#CACACA' className="mr-2" />
          <Text className="text-base text-gray-300">barbell_support@gmail.com</Text>
        </View>

        { /* Phone */ }
        <View className="flex-row items-center mt-8">
          <Feather name='phone' size={24} color='#CACACA' className="mr-2" />
          <Text className="text-base text-gray-300">+1 (702) 895-3011</Text>
        </View>

        { /* Location */ }
        <View className="flex-row items-center mt-8">
          <SimpleLineIcons
            name='location-pin'
            size={24}
            color='#CACACA'
            className="mr-2"

```

```

    />
    <View>
      <Text className="text-base text-gray-300">University of Nevada,
      <Text className="text-base text-gray-300">4505 South Maryland I
      <Text className="text-base text-gray-300">Las Vegas, NV 89154<
    </View>
  </View>

  { /* Response Time */}
  <Text className="text-base text-gray-300 mt-8 text-center">
    Our goal is to respond to your inquiries within 24 business hours
  </Text>
</View>
</SafeAreaView>
)
}

```

In this updated code block:

- I've replaced the inline styles with Tailwind CSS utility classes.
- Classes like `flex-1`, `bg-gray-900`, `px-8`, `pt-8`, `flex-row`, `items-center`, `mt-8`, etc., are Tailwind CSS classes.
- The `className` prop is used to apply Tailwind CSS classes in React Native, similar to how it's done in web development.

Please use the colors from the original code and apply it to the TailwindCSS version

Sure! Let's use the colors from the original code and apply them to the Tailwind CSS version:

javascript

 Copy code

```

import React from 'react'
import { Linking, SafeAreaView, Text, View } from 'react-native'

import { Feather, Fontisto, SimpleLineIcons } from '@expo/vector-icons'

```

```

import NavBar from '~/components/ui/nav-bar/NavBar'

export default function ContactUsPage() {
  return (
    <SafeAreaView className="flex-1 bg-dark">
      {/* Header */}
      <NavBar center='Contact Us' />

      <View className="flex-1 px-8 pt-8">
        {/* Email */}
        <View className="flex-row items-center mt-8">
          <Fontisto name='email' size={24} color='#CACACA' className="mr-2">
            <Text className="text-base text-gray-300">barbell_support@gmail.com</Text>
          </View>

          {/* Phone */}
          <View className="flex-row items-center mt-8">
            <Feather name='phone' size={24} color='#CACACA' className="mr-2">
              <Text className="text-base text-gray-300">+1 (702) 895-3011</Text>
            </View>

            {/* Location */}
            <View className="flex-row items-center mt-8">
              <SimpleLineIcons
                name='location-pin'
                size={24}
                color='#CACACA'
                className="mr-2"
              />
              <View>
                <Text className="text-base text-gray-300">University of Nevada,
                <Text className="text-base text-gray-300">4505 South Maryland I
                <Text className="text-base text-gray-300">Las Vegas, NV 89154</Text>
              </View>
            </View>

            {/* Response Time */}
            <Text className="text-base text-gray-300 mt-8 text-center">
              Our goal is to respond to your inquiries within 24 business hours
            </Text>
          </View>
        </View>
      </SafeAreaView>
    )
  }
}

```

```
</Text>  
</View>
```

