

Report conversation

How can I represent the following JSON response as a Python 3 dataclass model?

```
"data": [  
  {  
    "email": "user1@nylas.com",  
    "time_slots": [  
      {  
        "start_time": 1690898400,  
        "end_time": 1690902000,  
        "status": "busy",  
        "object": "time_slot"  
      },  
      {  
        "start_time": 1691064000,  
        "end_time": 1691067600,  
        "status": "busy",  
        "object": "time_slot"  
      }  
    ],  
    "object": "free_busy"  
  },  
  {  
    "email": "user2@nylas.com",  
    "error": "Unable to resolve e-mail address  
user2@nylas.com to an Active Directory object.",  
    "object": "error"  
  }  
]
```

To represent the given JSON response as a Python 3 dataclass model, you can create multiple dataclasses to represent different parts of the JSON structure. For this JSON structure, you would need at least three dataclasses: one for the top-level data, one for the `free_busy` object, and one for the `time_slot` object. Additionally, a fourth dataclass to handle the `error` object could be useful. Here's how you could structure these dataclasses:

python

```
from dataclasses import dataclass
from typing import List, Union, Optional

@dataclass
class TimeSlot:
    start_time: int
    end_time: int
    status: str
    object: str

@dataclass
class FreeBusy:
    email: str
    time_slots: List[TimeSlot]
    object: str

@dataclass
class Error:
    email: str
    error: str
    object: str

@dataclass
class ResponseData:
    data: List[Union[FreeBusy, Error]]
```

In this code:

1. The `TimeSlot` dataclass represents the individual time slot objects.
2. The `FreeBusy` dataclass represents the `free_busy` object, containing a list of `TimeSlot` objects.
3. The `Error` dataclass represents the `error` object.
4. The `ResponseData` dataclass represents the top-level data structure, containing a list of either `FreeBusy` or `Error` objects.

With these dataclasses, you can now easily parse the JSON response into a Python object using the `dataclasses_json` library or similar libraries.

