

IGNITE.

WEBSITE — MASTER HANDOVER DOCUMENT

How the site works, where everything lives, how to change it, and what still needs to be built. Written for the next web team. · August 2026

The living manual for the IGNITE React website: how it works, where everything lives, how to change it, and what still needs to be built. If you are inheriting this site, read this top to bottom once — it's written for you.

Status: proof-of-concept. The site is fully functional as a demo, but the storage layer (real database + logins) is not built yet. Sections marked  **TBD** are waiting to be filled in as those decisions get made.

QUICK FACTS

Live demo	https://dhirengithub.github.io/ignite-magazine/
Repository	https://github.com/DhirenGitHub/ignite-magazine (to be transferred — see below)
Stack	React 18 + Vite, React Router, TipTap editor, plain CSS
Hosting	GitHub Pages, auto-deployed by GitHub Actions on every push to <code>main</code>
Backend	None yet — content persists in each browser's localStorage (POC)
Maintainer (current)	Dhiren — Web Manager
Maintainer (next)	 TBD

1. ACCOUNTS & OWNERSHIP

1.1 GitHub account

The repository currently lives on a personal account and **must be moved to the official IGNITE GitHub account** so it survives committee handovers.

 **TBD — fill in when the account exists:**

IGNITE GitHub handle	
Account email	 (use the IGNITE email, not a personal one)
Password / 2FA recovery	 where is it stored? (committee password manager?)
Live URL after transfer	<a href="https://<ignite-handle>.github.io/ignite-magazine/">https://<ignite-handle>.github.io/ignite-magazine/

How to transfer the repo (one-time, ~10 minutes):

- On the repo: *Settings* → *General* → *Danger Zone* → *Transfer ownership* → enter the IGNITE account.
- On the IGNITE account after transfer: *Settings* → *Pages* → set **Source: GitHub Actions**.

3. Go to the *Actions* tab → run the **Deploy to GitHub Pages** workflow manually once.
4. The Pages URL changes to the new account's handle. The `/ignite-magazine/` part stays the same (it follows the **repo name**, not the account), so nothing in the code needs to change as long as the repo keeps its name. If you ever rename the repo, update `DEPLOY_BASE` in `.github/workflows/deploy.yml` to match.
5. Everyone with a local clone updates their remote: `git remote set-url origin https://github.com/<ignite-handle>/ignite-magazine.git`
6. Update the live-demo links in `README.md` and this document.

1.2 Domain (when we go live for real)

The real site should live at **unmignite.com**, which is currently attached to the Wix subscription. Before cancelling Wix, **transfer the domain out** to a registrar (Namecheap / Cloudflare / etc.) — do not let the subscription lapse first, or the domain can be lost. Renewal is roughly RM60–90/year and is the only unavoidable running cost.

 **TBD:** registrar account details, renewal date, who pays.

Custom domain setup on GitHub Pages (when ready): repo *Settings* → *Pages* → *Custom domain*, plus a CNAME record at the registrar pointing `www` to `<ignite-handle>.github.io`. Note: with a custom domain the site is served from the domain root, so `DEPLOY_BASE` in the workflow must change from `/ignite-magazine/` to `/`.

1.3 Editor accounts (demo)

Logins are currently hard-coded demo accounts in `src/data/users.js`:

EMAIL	ROLE	CAN
<code>chief@unmignite.com</code>	Editor-in-Chief (admin)	everything: edit, delete, feature on landing page
<code>editor@unmignite.com</code>	Section Editor	write, edit, publish — no delete, no feature

Password for both: `ignite2026`. These are placeholders — real authentication arrives with the storage layer (section 7).

2. RUNNING THE SITE LOCALLY

You need **Node.js** 18 or newer (LTS is fine). Then:

```
git clone https://github.com/<ignite-handle>/ignite-magazine.git
cd ignite-magazine
npm install          # once, ~1 minute
npm run dev          # dev server at http://localhost:5173
```

Changes to any file hot-reload instantly in the browser. Other commands:

```
npm run build        # production build into dist/
npm run preview       # serve the production build locally
```

You never deploy manually — see section 6.

3. MAP OF THE REPOSITORY

ignite-magazine/	
├ index.html	page shell: <title>, favicon, meta description
├ vite.config.js	build config (DEPLOY_BASE base-path logic lives here)
├ package.json	dependencies & the npm scripts above
├ .github/workflows/deploy.yml	auto-deploy pipeline (section 6)
├ HANDOVER.md	this document
└ src/	
├ main.jsx	entry point; loads fonts + global.css, mounts the app
├ App.jsx	routes, page shell (nav/footer), login-protected routes
├ styles/	
└ global.css	THE DESIGN LANGUAGE – every colour, font and component style on the site lives in this one file
├ data/	
├ seedArticles.js	the seeded articles + the list of sections/categories
└ users.js	demo accounts + role permission rules (can())
├ context/	
└ StoreContext.jsx	all state: articles + login session, saved to localStorage – THIS is the file the future backend replaces
├ components/	
├ Nav.jsx	top bar + mobile menu (which sections appear is set here)
├ Hero.jsx	A24-style landing carousel (timing: SLIDE_MS constant)
├ ArticleCard.jsx	the article card used in every grid/list
├ AdminBar.jsx	black bar shown across the site while logged in
└ Footer.jsx	footer + giant IGNITE wordmark
└ pages/	
├ Home.jsx	landing page: hero, The Latest, section rows, join banner
├ Section.jsx	one section's article grid (/section/music etc.)
├ Article.jsx	a single story (/article/<slug>)
├ Login.jsx	editor login page
├ Studio.jsx	CMS dashboard: search, filter, feature, edit, delete
├ Editor.jsx	the article editor (TipTap) + article settings panel
└ NotFound.jsx	404 page

Mental model of the data flow:

```
seedArticles.js → StoreContext (localStorage) → pages read via useStore()
                  ▲
                  |
Studio/Editor → (saveArticle / deleteArticle / toggleFeatured)
```

4. HOW TO CHANGE THINGS (COOKBOOK)

All visual identity lives in `src/styles/global.css`. It starts with design tokens:

```

:root {
  --black: #0a0a0a; --white: #ffffff; --grey: #737373;
  --yellow: #ffed00; --red: #f73630; --pink: #ff10a3;
  --green: #8acd01; --orange: #fc4c00;
  --font-display: 'League Spartan', ...; /* big loud headlines */
  --font-body: 'Montserrat', ...; /* body text */
  --font-serif: 'Times New Roman', ...; /* italic deks & pull quotes */
}

```

Change a colour everywhere → edit the token here once. **Change fonts** → fonts are bundled npm packages (@fontsource/...). To swap: `npm install @fontsource/<new-font>`, import its weights in `src/main.jsx`, update the token.

Common edits, where to make them:

I WANT TO...	GO TO
Change hero auto-advance speed	<code>SLIDE_MS</code> at the top of <code>src/components/Hero.jsx</code> (milliseconds)
Change which articles are in the hero	Studio → ★ toggle (or <code>featured: true</code> in seed data)
Add / rename / recolour a section	<code>SECTIONS</code> array at the top of <code>src/data/seedArticles.js</code> — pages, nav, footer and studio all read from it
Choose which sections show in the top nav	<code>NAV_SECTIONS</code> list in <code>src/components/Nav.jsx</code>
Edit seeded articles	<code>src/data/seedArticles.js</code> (each article is one object; <code>body</code> is HTML)
Change the ticker/join/footer text	<code>Home.jsx</code> (join banner) / <code>Footer.jsx</code>
Add a wholly new page	Create <code>src/pages/X.jsx</code> , add a <code><Route></code> in <code>src/App.jsx</code>
Change roles/permissions	<code>can()</code> in <code>src/data/users.js</code>
Change the site title / favicon	<code>index.html</code>

Adding an article as an editor (no code): log in → Studio → + *New article* → write in the editor (toolbar has headings, bold/colour, pull quotes, images by URL or upload with photo credits) → set cover, section, tags in the right panel → status *Published* → Save. ⚠️ POC caveat: this saves to **your browser only** (localStorage) — real shared publishing arrives with the storage layer. To permanently add content today, put it in `seedArticles.js` and push.

5. HOW THE SITE WORKS (THE PARTS WORTH UNDERSTANDING)

- **Routing** (`App.jsx`): `/home`, `/section/:slug`, `/article/:slug`, `/login`, and the protected `/studio`, `/studio/new`, `/studio/edit/:id`. "Protected" = redirects to `/login` unless someone is logged in.
- **State** (`StoreContext.jsx`): one React context provides `articles`, `user`, and the mutation functions. On every change it rewrites localStorage key `ignite.articles.v1`. The session lives in `ignite.session.v1`. *Reset demo content* in the Studio wipes back to the seed articles.
- **Hero carousel** (`Hero.jsx`): plain `setInterval` advancing an index every `SLIDE_MS`; the progress bars are buttons (clicking jumps and resets the timer); the fill animation duration is passed to CSS via the `--slide-ms` variable so they stay in sync.

- **The editor** (`Editor.jsx`): TipTap (ProseMirror) with extensions for images, links, colours, fonts and alignment. Output is HTML stored on the article's `body` field and rendered on the article page. Uploaded images become base64 data URLs inside that HTML — fine for a demo, replaced by real image hosting later (section 7).
- **Roles** (`users.js`): every privileged UI action asks `can(user, action)` . Adding a new role = add the account + extend `can()` .

6. DEPLOYMENT (ALREADY FULLY AUTOMATIC)

Push to `main` → GitHub Actions builds and publishes. That's the whole workflow.

What `.github/workflows/deploy.yml` actually does:

1. `npm ci && npm run build` with `DEPLOY_BASE=/ignite-magazine/` — GitHub Pages serves the site under that sub-path, and Vite needs to know it at build time. (`vite.config.js` reads it; locally it defaults to `/` so dev is unaffected.)
2. Copies `dist/index.html` to `dist/404.html` — the trick that makes shared deep links like `/article/<slug>` work on Pages (unknown paths serve 404.html, which boots the React app, which then shows the right page).
3. Uploads `dist/` to GitHub Pages.

Checking on a deploy: repo → *Actions* tab. Green tick ≈ 1–2 minutes after push. If a run fails, open it and read the first red step — the two historical causes are Pages not being enabled (Settings → Pages → Source: GitHub Actions) and a build error you'd also see locally with `npm run build` .

7. STORAGE LAYER — NOT BUILT YET

This is the main piece of engineering left. Today, articles written in the Studio persist only in the author's own browser. Production needs a shared backend for: the article database, real logins, and image hosting.

The good news: the app was shaped for this. Every read/write goes through one file — `src/context/StoreContext.jsx` — so the swap is contained: replace its `localStorage` calls with API calls and the rest of the site (Studio, editor, roles, pages) works unchanged.

Recommended path (free at our scale): **Supabase** — Postgres database + auth + file storage in one service.

PIECE	TODAY (POC)	PRODUCTION TARGET
Articles	<code>localStorage</code> array	<code>articles</code> table (columns ≈ the fields in <code>seedArticles.js</code>)
Login	hard-coded <code>users.js</code>	Supabase Auth; role stored per user
Role checks	<code>can()</code> client-side	keep <code>can()</code> for UI + enforce with row-level-security policies server-side
Cover/body images	hotlinked Wix CDN + base64	Supabase Storage bucket, upload from the editor

Migration checklist for whoever builds it:

- [] Create Supabase project **on an IGNITE-owned email**
- [] `articles` table + row-level security (public can read `status = 'published'` ; editors write)
- [] Swap `StoreContext.jsx` internals to `@supabase/supabase-js` calls
- [] Swap `Login.jsx` to Supabase Auth; map roles

- [] Editor image upload → Storage bucket (replace the base64 path in `Editor.jsx`)
- [] **Re-host the seed article images** — they currently hotlink Wix's CDN (`static.wixstatic.com`) and will break when the Wix site is cancelled
- [] Seed the database from `seedArticles.js` , then retire the `localStorage` code

■ **TBD once built:** Supabase project URL, dashboard login location, anon/service key storage, backup story.

8. COSTS

ITEM	COST
GitHub Pages hosting	RM0
Supabase free tier (future backend)	RM0 at our traffic
Domain renewal	~RM60–90 / year
Total	under RM100/year (vs ~RM500 on Wix)

If traffic ever outgrows free tiers, the first paid step is ~USD 25/month (Supabase Pro); cheaper escape hatches exist (Cloudinary free tier / Cloudflare R2 for images). Not a today-problem.

9. KNOWN QUIRKS & GOTCHAS

- **Seed images hotlink Wix.** Works today; dies when Wix is cancelled. Re-host first (see checklist above).
- **Uploaded images are base64 in localStorage** — a few large uploads can hit the ~5MB browser quota. The app warns when saving fails. Backend fixes this properly.
- **The repo must stay public** for free GitHub Pages.
- **Renaming the repo** changes the live URL and requires updating `DEPLOY_BASE` in the workflow.
- **Custom domain** requires `DEPLOY_BASE=/` (section 1.2) — don't forget or all assets 404.
- **Supabase free tier pauses** after ~a week of zero traffic (future concern; real visitor traffic prevents it).
- **node_modules inside OneDrive** (current dev machine) makes syncing sluggish — pause OneDrive sync for the folder or clone outside OneDrive.

10. HANDOVER CHECKLIST (DO THESE WHEN PASSING THE SITE ON)

- [] Transfer repo to the IGNITE GitHub account (section 1.1) and fill in the TBD table
- [] Confirm the new live URL works and update README + this doc
- [] Hand over: GitHub credentials, domain registrar login, (future) Supabase login — into the committee's shared credential store, never personal accounts
- [] Walk the new web manager through: local setup (section 2), one article publish in the Studio, one deploy (push something trivial and watch Actions)
- [] New maintainer updates the *Quick facts* table at the top of this doc

Last updated: August 2026 · Written at POC handoff by Dhiren (with Claude).