

# **pueo::Dataset::getEntry() behavior**

Oct-15-2024


- Example: `pueoBuilder/components/pueoEvent/examples/`
- 
- 
-


- Example: `pueoBuilder/components/pueoEvent/examples/`
- The python script and the ROOT macro behave the same in this case.
- 
-

- Example: `pueoBuilder/components/pueoEvent/examples/`
- The python script and the ROOT macro behave the same in this case.
- Toy simulation run; has 2 passed entries.
-


- Example: `pueoBuilder/components/pueoEvent/examples/`
- The python script and the ROOT macro behave the same in this case.
- Toy simulation run; has 2 passed entries.
- Behavior right now:
  - if request entry 0 or 1, works as expected.
  -


- Example: `pueoBuilder/components/pueoEvent/examples/`
- The python script and the ROOT macro behave the same in this case.
- Toy simulation run; has 2 passed entries.
- Behavior right now:
  - if request entry 0 or 1, works as expected.
  - Request non-existent entry: error message printed, but plot still made (entry 0 is used)











```

399 int pueo::Dataset::getEntry(int entryNumber)
400 {
401     //invalidate the indices
402     fIndex = -1;
403     fCutIndex=-1;
404
405
406
407     if (entryNumber < 0 || entryNumber >= (fDecimated ? fDecimatedHeadTree : fHeadTree)->GetEntries())
408     {
409         fprintf(stderr,"Requested entry %d too big or small!\n", entryNumber);
410     }
411     else
412     {
413         (fDecimated ? fDecimatedEntry : fWantedEntry) = entryNumber;
414         if (fDecimated)
415         {
416             fDecimatedHeadTree->GetEntry(fDecimatedEntry);
417             fWantedEntry = fHeadTree->GetEntryNumberWithIndex(fHeader->eventNumber);
418         }
419
420         if (!fHaveUsefulFile) fUsefulDirty = true;
421         if (!fHaveGpsEvent) fGpsDirty = true;
422     }

```