

## Contents

<b>1 Thu</b>	<b>4</b>
A Bash . . . . .	4
<b>2 Fri</b>	<b>5</b>
<b>3 Sat</b>	<b>6</b>
A Meeting with Julie . . . . .	6
B Regex . . . . .	6
<b>4 Sun</b>	<b>7</b>
A Meeting with Julie . . . . .	7
<b>5 Mon</b>	<b>8</b>
A Meeting with Julie . . . . .	8
B SLURM . . . . .	8
<b>6 Tue</b>	<b>9</b>
A Meeting with Julie . . . . .	9
<b>7 Wed</b>	<b>10</b>
A Meeting with Julie . . . . .	10
B Bash . . . . .	10
<b>8 Thu</b>	<b>11</b>
A Meeting with Julie . . . . .	11
<b>9 Fri</b>	<b>12</b>
A Meeting with Julie . . . . .	12
B Bash . . . . .	12
<b>10 Sat</b>	<b>13</b>
A Meeting with Amy . . . . .	13
B Python . . . . .	13
(a) XFintoARA.py . . . . .	13
<b>12 Mon</b>	<b>14</b>
A Python . . . . .	14
(a) XFintoARA.py . . . . .	14
(b) General . . . . .	14
<b>13 Tue</b>	<b>15</b>
A Meeting with Julie . . . . .	15
B Bash . . . . .	15

<b>14 Wed</b>	<b>16</b>
A Meeting with Julie . . . . .	16
B AraSim Job Submission Script . . . . .	16
(a) AraSimCall_Array.sh . . . . .	16
(b) AraSimCall_Array.sh: my attempt . . . . .	17
<b>15 Thu</b>	<b>18</b>
A AraSim Job Submission Script . . . . .	18
(a) AraSimCall_Array.sh: my attempt . . . . .	18
B Meeting with Julie . . . . .	18
<b>16 Fri</b>	<b>19</b>
A Birefringence Resources from Justin . . . . .	19
B Meeting with Julie . . . . .	19
(a) Notes from today's meeting . . . . .	19
(b) Second pass of the Loop continued . . . . .	19
C Bash . . . . .	20
<b>17 Sat</b>	<b>21</b>
A Meeting with Julie . . . . .	21
(a) Part_D2_Array.sh Second Pass . . . . .	21
<b>18 Sun</b>	<b>23</b>
A Meeting with Julie . . . . .	23
(a) Part_D2_Array.sh Second Pass Continued . . . . .	23
<b>19 Mon</b>	<b>24</b>
A Bash . . . . .	24
B Meeting with Julie . . . . .	24
(a) Part_D2_Array.sh Second Pass Continued . . . . .	24
<b>20 Tue</b>	<b>25</b>
A Meeting with Julie . . . . .	25
(a) Part_E_Asym.sh second pass . . . . .	25
<b>21 Wed</b>	<b>26</b>
A Meeting with Julie . . . . .	26
(a) Part_E_Asym.sh second pass continued . . . . .	26
<b>22 Thu</b>	<b>27</b>
A Meeting with Julie . . . . .	27
(a) Part_E_Asym.sh second pass continued . . . . .	27
<b>23 Fri</b>	<b>28</b>
A Meeting with Julie . . . . .	28
(a) notes from today's meeting . . . . .	28
(b) Part_A second pass . . . . .	28
(c) Latest_Asym_GA.cpp . . . . .	28

<b>25 Sun</b>	<b>29</b>
A Meeting with Julie . . . . .	29
(a) Latest_Asym_GA.cpp . . . . .	29
<b>26 Mon</b>	<b>30</b>
A Meeting with Julie . . . . .	30
(a) Latest_Asym_GA.cpp . . . . .	30

# 1 Thu

## A Bash

- a) A little bit of Bash each day keeps the doctor away. In the main loop, around line 140, we have

```
read -p "Starting generation ${gen} at location ${state}.\n      Press any key to continue... " -n1 -s
```

Option `-p <prompt>` outputs the **prompt** string before reading user input.

Option `-n <number>` returns after reading the specified **number** of chars.

Option `-s` does not echo the user's input.

## 2 Fri

*On a flight home. Didn't do much except started going over Part B1 again*

### 3 Sat

#### A Meeting with Julie

- a) The meeting this Wednesday was cancelled. In the meantime, Julie suggests reading the Appendix and her candidacy paper. I have largely finished reading the relevant part of the Appendix, so the rest of this week will most likely be spent reading the candidacy paper and checking out the **Loop Parts** in more detail.
- b) Part B1 second pass: will also check out the job submission script this time around (final line of **Part\_B\_GPU\_job\_1.sh**, but still not going to look into the xmacros).

#### B Regex

- a) Started reading about regular expression, although perhaps not directly relevant to anything.

## 4 Sun

### A Meeting with Julie

- a) Currently a bit confused by the job submission script `GPU_XF_job.sh`
- b) I think this is because I am not familiar enough with the file structure yet.
- c) Also, I am not entirely sure what the `individual number` is for in this script.

## 5 Mon

### A Meeting with Julie

- a) Still on the job submission script of **Part B1**. I am confused about when exactly are the `indiv_parent_dir` created (the ones in `$XFproj/Simulations`)

### B SLURM

**Filename replacement** are as follows:

- a) `%x` - Job name, which can be given as `--job-name=<name>`
- b) `%a` - Job array ID (index) number
- c) `%A` - Job Array's master job allocation number
- d) More options here: <https://slurm.schedmd.com/sbatch.html>

Note that the following are not the same:

- a) `$SLURM_ARRAY_JOB_ID`: this is the `%A` from above
- b) `$SLURM_ARRAY_TASK_ID`: this is the index (`%a` from above)



## **6 Tue**

### **A Meeting with Julie**

- a) Started reading Julie's candidacy paper.

## 7 Wed

### A Meeting with Julie

- a) Read everything aside from Chapter 5.
- b) **TODO:** Go over Chapter 3 again before reading chapter 5.
- c) Ask Julie about Figure 6,7 8 and 9 (a discussion on all of chapter 3.1.2 if possible)
- d) **Zenith Angle:** The angle at which the muon traveled into the IceCube detector, with respect to the vertical. Source: <https://user-web.icecube.wisc.edu/~krosenau/index.html>

### B Bash

- a) A backtick is not a quotation mark. Instance: `Part_B_GPU_job1.sh` line 37

```
for i in `seq 1 $NPOP`
```

Everything we type inside the backticks is executed before the main command (such as `chown`), and the output of the backticked-command is then read by the main command

## 8 Thu

### A Meeting with Julie

- a) Regarding Part [A](#) of the June 5th entry, from Alex:

those are created by XF. It's like a backend thing, we never make them ourselves but by virtue of simulating antennas they get made by XF as the location to store the antenna simulation data

In other words, we do not ourselves `mkdir` the `$indiv_dir_parent`.

- b) Meeting with Julie today moved to Monday next week.
- c) ~~It seems unlikely to be a bug given how long this script has been used, but I am getting an error from the for loop through all frequencies in freqlist. Will ask Alex about it.~~  
I'm an idiot. I need to initialize `$GeoFactor` first.
- d) Finished `Loop_Parts/Part_B1` second pass, moving on to `Part_B2`. Adding line breaks in the process; **Be careful with the trailing whitespace!** *Mayhap it's better to just leave them as single long lines?*
- e) **TODO:** sometime in the future I'll need to figure out what `simulation_PEC.xmacro` and `output.xmacro` do to really understand what `Part_B1` and `Part_B2` are about.

## 9 Fri

### A Meeting with Julie

- a) ~~Probably trivial, but it seems like the uan files are already being moved to the correct directory at the end of Part\_B2, so I am not sure why we do it again at the beginning of Part\_C.~~
- b) One of the `mv` command might be extra; will check with Alex.
- c) **Part\_C** second pass: digging into the python codes; should be able to finish by tomorrow.

### B Bash

- a) The dollar sign works inside the double quotes so there is no need for string concatenation in the example below:

```
$a=2;$b=2
echo "a * b = $(($a*$b))"
```

The above outputs `a * b = 4`. Note that the `$((...))` part is for arithmetics.

- b) At some point I should try to figure out exactly what double quotes are for in shell scripts; they seem to be more than just strings?

## 10 Sat

### A Meeting with Amy

- a) Get in touch with Nicholas to see what he's up to.
- b) Go to Monday's collaboration meeting this week if possible to see if there's a project for me.

### B Python

#### (a) XFintoARA.py

- a) instead of using the `%`'s for string interpolation, we could use `f-strings`.
- b) inside the curly braces we can call variables, for instance `{g.WorkingDir}` in line 66:

```
uanName = f'{g.WorkingDir}/.../{g.gen}_{indiv}_{freqNum}.uan'
```

- c) The `g` above is from line 102: `g = parser.parse_args()`
- d) Line 73: `mat = [[ "0" for x in range(n)] for y in range(m)]` is simply python's way to do `mat=zeros(m,n)` in Matlab. (List Comprehension)

## 12 Mon

### A Python

#### (a) XFintoARA.py

The following pertains `line 81` & `82`

- a) `line 81` first turns the third entry in the list `lineList` into a float.
- b) `line 82` contains the following: `"%.2f" % 10` which turns `10` into `10.00`. This is NOT modulo operation; this is probably more like string interpolation.
- c) Mostly finished reading this python script. Moving on to **Part D** tomorrow.

#### (b) General

- a) To access the `help` message of `argparse`'s `add_argument` function, one can run the command `python3 <filename>.py -h` at the terminal
- b) For more info on the `argparse` module one can look through the documentation of `argparse` on <https://docs.python.org/3/library/argparse.html> and the tutorial at <https://towardsdatascience.com/a-simple-guide-to-command-line-arguments-with-argparse-6824c30ab1c3>
- c) ~~Reviewed file opening (with open, etc)~~
- d) mode `w` and `w+`: `w` is write whereas `w+` is read and write
- e) apparently with `python3`, when using `os.chmod` one needs to add `0o` (zero-oh) in front of `777` to grant all read-write-execute, etc. For instance:  
`os.chmod("<filename>", 0o770)`  
This is because

In unix conventions, written numbers are assumed to be decimal unless they are prefixed with a `0x` (or `0X`) in which case they are hexadecimal

(<https://stackoverflow.com/questions/32729309/what-is-the-purpose-of-the-octal-digit-0-permission>) and according to the error message we “use an `0o` prefix for octal integers”.

## 13 Tue

### A Meeting with Julie

- a) Meeting with Julie today didn't happen.
- b) Around line 24 of **Part\_D1\_Array.sh** the comment says to “make a directory to hold the AraSim output and error files *for each generation*” but it seems like we are only making the directory for the zeroth gen?

### B Bash

- a) option **-e** of **sed** allows for multiple commands at once; for instance,  
`sed -e "s/world/universe/" -e "s/hello/goodbye/" ./temp > ./newtemp`  
first replaces the word “world” in **temp** with “universe” and then “hello” with “goodbye” and then pipe these changes to a new file **newtemp**.

## 14 Wed

### A Meeting with Julie

- a) Continuing **Part\_D1** second pass.
- b) Looking into the job submission script **Batch\_Jobs/AraSimCall\_Array.sh**
- c) Sort of annoying, but it seems like SLURM directives simply cannot be broken into multiple lines with backslash, so I'll just leave them.
- d) ~~what do num and seed in AraSimCall\_Array.sh refer to?~~ **Seed** is defined at the very beginning of the main loop and passed to the scripts along the way. See page 155 (Appendix A) of Julie's dissertation.
- e) Note: haven't looked into **setup.txt** yet

### B AraSim Job Submission Script

#### (a) AraSimCall\_Array.sh

```
#!/bin/bash
## This job is designed to be submitted by an array batch submission
## Here's the command:
## sbatch --array=1-NPOP*SEEDS%max --export=ALL,(variables) AraSimC...
#SBATCH -A PAS1960
#SBATCH -t 18:00:00
#SBATCH -N 1
#SBATCH -n 8
#SBATCH --output=/fs/ess/PAS1960/BiconeEvolutionOSC/BiconeEvolution/cur...
#SBATCH --error=/fs/ess/PAS1960/BiconeEvolutionOSC/BiconeEvolution/cur...

source /fs/ess/PAS1960/BiconeEvolutionOSC/new_root/new_root_setup.sh
cd $AraSimDir
num=$(( ((${SLURM_ARRAY_TASK_ID}-1) ) / ${Seeds} + 1 ))
seed=$(( ((${SLURM_ARRAY_TASK_ID}-1) ) % ${Seeds} + 1 ))
echo a_${num}_${seed}.txt

chmod -R 777 $AraSimDir/outputs/
./AraSim setup.txt ${SLURM_ARRAY_TASK_ID} $TMPDIR a_${num}.txt > \
  $TMPDIR/AraOut_${gen}_${num}_${seed}.txt
cd $TMPDIR
echo "Let's see what's in TMPDIR:"
ls -alrt

echo $gen > $TMPDIR/${num}_${seed}.txt
echo $num >> $TMPDIR/${num}_${seed}.txt
echo $seed >> $TMPDIR/${num}_${seed}.txt
```



```
mv AraOut.setup.txt.run${SLURM_ARRAY_TASK_ID}.root\  
  $WorkingDir/Antenna_Performance_Metric/AraOut_${gen}_${num}_${seed}.root  
mv AraOut_${gen}_${num}_${seed}.txt $WorkingDir/Antenna_Performance_Metric/  
mv ${num}_${seed}.txt $WorkingDir/Run_Outputs/$RunName/AraSimFlags  
  
## This part appears unnecessary now  
: << 'END'  
...  
...  
END
```

### (b) AraSimCall\_Array.sh: my attempt

This is an attempt to understand `AraSimCall_Array.sh`. My own edited version of the job submission script as attached at the end of this section. Run-on lines are mainly just SLURM directives which are unimportant here, so they are ignored here in the log.

- a) This is for `line 15`. There's really no need to start `$SLURM_ARRAY_TASK_ID` at 1, but if that's what we've been doing then I'll leave it for consistency. That is, we could have submitted the job array analogous to  
    `sbatch --array=0-8%4 foo.sh`  
in which case the first index would have been 0.

## 15 Thu

### A AraSim Job Submission Script

#### (a) AraSimCall\_Array.sh: my attempt

- a) **Seeds** is the number of AraSim jobs of an individual. So **num** on **line 15** is essentially just (ignoring the pesky index issue) **index** divided by **Seeds**.
- b) As an example, consider a task 33 in the array of tasks. Suppose **Seeds** is 8; that is, for each antenna, we do 8 AraSim runs. Since  $33 - 1 = 32$  divided by 8 is 4, and then we add one to get 5, **num** in this case is 5. In other words, task 33 is a task for antenna **number 5**.
- c) Similarly, right below **num**, **seed** refers to the “seed index” for that particular antenna. Continuing with the example above, task 33 will be seed number 1 of antenna 5 (start counting from 1, as usual).
- d) Pretty sure **line 16**: `echo a_${num}_${seed}.txt` is unnecessary, and the file name being **echoed** is probably a typo as well.
- e) Line 18 is also extra? Seems like we are not using this directory anymore?
- f) **Line 19** is likely the line that says “run AraSim” (with the appropriate setup and parameters) and then redirecting the output of the run to the (local) scratch space of the cluster, ie. `$TMPDIR`. (see osc documentation regarding parallel and local scratch space. Basically, `TMPDIR` is the fastest.)
- g) **Line 26** is like another “SaveState” file.
- h) **Line 30 to 33** move the AraSim output files from the scratch space back to the directories under **GE60**.

### B Meeting with Julie

- a) Meeting with Julie today rescheduled to same time tomorrow.
- b) Finished going through the job submission script; back to **Part\_D1**
- c) Skipping the **DEBUG\_MODE** of **Part\_D1** for now.
- d) Changed **line 98 and 99** of **Part\_D1** to use `$WorkingDir` to shorten the lines.

## 16 Fri

### A Birefringence Resources from Justin

Putting these here because apparently Slack hides messages older than 90 days. Boo.

- a) Amy's paper: <https://arxiv.org/abs/2110.09015>
- b) Paper by a collaboration member who studies the birefringence in ice: <https://arxiv.org/abs/1910.01471>
- c) "[A] decent paper on the theory, but it's a little math heavy":  
<https://link.springer.com/article/10.1007/s00371-011-0619-2>  
<https://arxiv.org/abs/2110.09015>  
<https://arxiv.org/abs/1910.01471>

### B Meeting with Julie

#### (a) Notes from today's meeting

- a) hpol – I will probably be using AraSim as is, without having to modify its code.
- b) Dylan built the PUEO software by modifying PAEA; Julie had a to-do list of instruction for him to do it which she will modify and send to me.
- c) Birefringence – Julie said that it sounds like what Amy wants is for hpol to be optimized for birefringence (?), but I don't need to worry about learning all about birefringence for now, since I will be mainly just working on scripts of the Loop.
- d) Charged current interaction

$$\bar{\nu}_l + N \rightarrow l^\pm + X$$

The lepton people see is usually muon because it is much more stable than tau (longer lifetime). We don't see electrons either because they just get reabsorbed immediately into the ice atoms. (Consequently, muons produce tracks whereas the other two create spheres)

- e) Julie recommends Dick, Chris Hirata, and Antonio Boveia for candidacy committee.

#### (b) Second pass of the Loop continued

- a) Continuing with `Part_D1_Array.sh`
- b) As reported a few weeks ago on Slack, `line 116` will never be executed. Alex set the impossible condition to keep the code, but I'll just comment it out.
- c) finished `Part_D1`, moving on to `Part_D2`.

## C Bash

- a) be sure not to include whitespace when assigning values to variables in bash. For instance, `a=2` is correct but not `a = 3`.
- b) Example usage of `expr`: `totPop=$( expr $NPOP \* $Seeds )` *Note the whitespace! It matters here whether or not there are spaces around the multiplication operator.*
- c) But what is the difference between `expr` and simply using double parentheses? For instance `totPop=$(( $NPOP * $Seeds ))` (in this case it seems like bash doesn't care as much about the whitespace around `*`)?

## 17 Sat

### A Meeting with Julie

#### (a) Part\_D2\_Array.sh Second Pass

- a) Might be able to shorten Line 22:

```
nFiles=$(ls -1 --file-type ../AraSimConfirmed | grep -v '/$' | wc -l)
```

using just `ls | wc -l`. Will test this tomorrow.

- b) Option 1(one) of `ls` “[forces] output to be one entry per line”
- c) `-file-type` makes it so that all the directories end with a `/`, and soft links end with a `@`, etc. <https://stackoverflow.com/questions/51952975/what-is-the-purpose-of-file-type-in-ls-command> Files don’t have anything attached.
- d) Thus, as an example, inside `$WorkingDir/Run_Outputs/2023_02_20_Symmetric_Run`, if we issue `ls` we get

2023_02_20_Symmetric_Run.xf	Fitness_Scores_RG.png	uan_files
Antenna_Images	FScorePlot2D.png	Veffectives_RG.png
AraOut	Gain_Plots	Veff_plot.png
AraSimConfirmed	Generation_Data	Violin_Plot.png
AraSim_Errors	GPUFlags	XF_Errors
AraSimFlags	Root_Files	XFGPUOutputs
AraSim_Outputs	runDate.txt	XF_Outputs
Evolution_Plots	run_details.txt	

and with `ls -1` we have

```
2023_02_20_Symmetric_Run.xf
Antenna_Images
AraOut
AraSimConfirmed
AraSim_Errors
AraSimFlags
AraSim_Outputs
Evolution_Plots
Fitness_Scores_RG.png
FScorePlot2D.png
Gain_Plots
Generation_Data
GPUFlags
Root_Files
runDate.txt
```

```
run_details.txt
uan_files
Veffectives_RG.png
Veff_plot.png
Violin_Plot.png
XF_Errors
XFGPUOutputs
XF_Outputs
```

Lastly, with `ls -l --file-type` (on OSC, not on Mac), we get

```
2023_02_20_Symmetric_Run.xf/
Antenna_Images/
AraOut/
AraSimConfirmed/
AraSim_Errors/
AraSimFlags/
AraSim_Outputs/
Evolution_Plots/
Fitness_Scores_RG.png
FScorePlot2D.png
Gain_Plots/
Generation_Data/
GPUFlags/
Root_Files/
runDate.txt
run_details.txt
uan_files/
Veffectives_RG.png
Veff_plot.png
Violin_Plot.png
XF_Errors/
XFGPUOutputs/
XF_Outputs/
```

- e) option `v` of `grep` is “invert-match”, which acts like a `not`-gate. It selects all entries that do not match. In this case we are trying to match all entries that has a forward slash `/` right before the end-of-line character `$`; that is, we are trying to match all the directories. And then, `v` makes sure that we select everything that is not a directory, ie. files. Finally, we pipe it to `wc -l` to count as usual.
- f) I’ll check with Alex to see if we really need to be this careful, because in `Part_B_GPU_job2_asym_array.sh` line 56 it seems like we decided to simply use `ls | wc -l`, which is much cleaner.

## 18 Sun

### A Meeting with Julie

#### (a) Part\_D2\_Array.sh Second Pass Continued

- a) Regarding the `for` loop around `line 28`, consider the following script:

```
#!/bin/bash
cd ~/Desktop/temp

for file in *
do
    echo $file
done
```

If there is *no* file inside `temp/`, then the output would be `*`. This is what the comment around `line 32` is talking about.

## 19 Mon

### A Bash

- a) We can break a line inside double quotes. For example, the following is legal

```
#!/bin/bash
pat="/users/PAS2137/unmovingcastle\
/temp"
out_name=$pat/%x.out
err_name=$pat/%x.error
sbatch --job-name=whatever --output=$out_name --error=$err_name a.sh
```

- b) Normally we don't even need the backslash if we are just **echoing** the stuff that is inside the double quotes. But if we are going to access the path later with **\$pat** then it appears that the backslash *is* necessary.
- c) **wait** waits for a process to finish; **sleep** sleeps for a certain amount of seconds.

### B Meeting with Julie

#### (a) Part\_D2\_Array.sh Second Pass Continued

- a) Used **\$WorkingDir** to shorten line 60 & 61
- b) The final **if** block is effectively a comment, so I'll comment it out.
- c) Finsihed **Part\_D2\_Array.sh**



20 Tue

A Meeting with Julie

(a) Part\_E\_Asym.sh second pass

a) The curly braces around \$10, \$11 and \$12 are *necessary*.

## 21 Wed

### A Meeting with Julie

#### (a) Part\_E\_Asym.sh second pass continued

- a) To understand the `for` block around line 37, consider the following example

```
for i in `seq 1 4`  
do  
    InputFiles="${InputFiles}out${i}.txt "  
done  
echo $InputFiles
```

- b) The output is  
`out1.txt out2.txt out3.txt out4.txt`
- c) **TODO:** haven't looked into `fitnessFunction_ARA.cpp` yet.
- d) *Why is `Veff_Plotting.py` still in this part and not moved to Part\_F? (line 95)*

## 22 Thu

### A Meeting with Julie

- a) Meeting with Julie today moved to tomorrow.

#### (a) Part\_E\_Asym.sh second pass continued

- a) Commented out line 109: `cd Antenna_Performance_Metric` because the next 25 lines have already been commented out, so there's no need.
- b) **TODO:** look into `Data_Generators/gensData_asym.py`
- c) Commented out line 144: `cd $WorkingDir/Antenna_Performance_Metric` because the subsequent command have already been commented out.
- d) **Be very careful with trailing whitespace when using backslash \ to break a line.** For example consider line 160

```
cp AraOut_${gen}_${i}_${j}.txt \  
  $WorkingDir/Run_Outputs/$RunName/AraOut/AraOut_${gen}/AraOut...
```

If we add a space after `\`, notice that the syntax highlighting color changes in **vscode**. This *will* be a bug, because what this line does is duplicating the source file and then naming the target **blank** (that is, the target file name is simply a whitespace, because the backslash in this case is used to escape the white space.)

- e) Went through **Part\_E**; looking into the python and **c++** scripts called by this part.

## 23 Fri

### A Meeting with Julie

#### (a) notes from today's meeting

- a) Contact Ryan and Alex to see what has been done on the hpol GA.
- b) Ask what genes to evolve for the initial check.
- c) Are we planning on making an entirely new software package for hpol or do we want it to be an `if-else` switch in the `vpol` software.
- d) Contact Alex and Nicholas to see what they have been doing related to XF.
- e) Check the instructions at [https://docs.google.com/document/d/1lViJQt9CQBYx5mOYceYGyqeWISUxZR00ziyPo5tp\\_gE/edit](https://docs.google.com/document/d/1lViJQt9CQBYx5mOYceYGyqeWISUxZR00ziyPo5tp_gE/edit). can ask Alex or Julie.
- f) Go to `step 1` of the instruction.

#### (b) Part\_A second pass

- a) ~~Actually I accidentally skipped Part\_A when I started the second pass, so I will finish going through this again before I look into the GA.~~
- b) `Line 25`: the condition can never be true because `NSECTIONS` is either 1 or 2 but never 0; **TODO**: check the above with Alex.
- c) Looking into `Latest_Asym_GA.cpp` now; the plan is eventually to convert the GA to python.

#### (c) Latest\_Asym\_GA.cpp

- a) `Line 72` function header for `new_tournament` contains a typo.

## 25 Sun

### A Meeting with Julie

#### (a) Latest\_Asym\_GA.cpp

- a) Created Latest\_Asym\_GA.py under \$WorkingDir/GA/. This is an attempt to translate the c++ program into python.
- b) Neat introduction on c++ <vector>:  
<https://shengyu7697.github.io/std-vector/> (in traditional Chinese.)
- c) Passing by value and passing by reference:  
<https://www.geeksforgeeks.org/passing-vector-function-cpp/>
- d) Pointer vs. Reference in c++:  
<https://www.geeksforgeeks.org/pointers-vs-references-cpp/>
- e) Appending f to a number makes it a float; otherwise, it is a double. So to properly declare a float variable, we write, for instance:  
`float a = 2.0f`
- f) Mostly went through the function declarations and global variables

## 26 Mon

### A Meeting with Julie

#### (a) Latest\_Asym\_GA.cpp

a) On `default_random_engine`:

<https://blog.gtwang.org/programming/cpp-random-number-generator-and-probability-distribution-tutorial/>

b) Not sure why we need to seed twice (around `line 300`). Actually, I am not sure why we use both the `default_random_engine` and `rand`.

c) Will look into parsing arguments in python tomorrow for `line 312`:  
`double GEOSCALE_FACTOR = stod(argv[3]);`