What Do LLM Judges Actually Verify? Matched Controls and Record Gaps for Document Currency

Unnati Shah
University of Southern California
ubshah@usc.edu

Samruddhi Kakade
Illinois Institute of Technology
samruddhikakade2001@gmail.com

Aum Patel
New York University
ap9018@nyu.edu

Abstract

LLM judges are often asked whether the documents an answer cites are still in force, with an amendment record to consult. Such records are rarely complete. From a table of replacements, our test generates matched answers citing a replaced document, its successor, the replaced document before its replacement, and an older document that a newer one updated without replacing; it removes links from the record and scores each finding by its stated reason. On 48 replacements from the IETF RFC index, judges given a correct record caught nearly every replaced citation, as a lookup would. On the 24 faults whose link we removed, every judge caught more from the texts alone than with the record: Gemini 3.1 Pro 22/24 against 1/24, GPT-5.5 22/24 against 7/24, Claude Opus 4.5 18/24 against 10/24 and Gemma 4 26B 13/24 against 0/24. The drop recurred on a second random choice of removed links. Most misses carried no finding; rewording the gap as "no replacement recorded" did not restore the lost catches. Presenting the record as an unverified note, or warning that it was incomplete, restored most of them for Gemini, GPT-5.5 and Claude (significant after correction for the first two) but at most 5 of 13 for Gemma; where catches returned, so did false alarms on updates. With both texts, the judges mostly distinguished replacements from updates, and every update they flagged had a near-identical title. An appendix reports a descriptive case study on Indian rooftop-solar rules; we release the harness.

1 Introduction

Contracts are amended by later agreements, regulations by later notifications, and technical standards by later standards. An answer drawn from such a collection can quote a provision correctly and still be wrong, because the document it quotes was replaced before the date the question is about. Systems that use language models for this increasingly add a second model, an LLM judge, to check the answers before they reach a user. The judge is often given help: an amendment record listing which document replaced which, and from when.

Our starting point is a practical worry about that arrangement. Amendment records are seldom complete. Consolidated versions lag behind new notifications; pipelines that extract links from documents miss some; registers cover only the instruments they were built from. Wherever a record is silent about a replacement, it effectively reports a replaced document as current. If the judge reads the documents in front of it, such gaps cost little. If it relies on the record, it will pass exactly the answers the record cannot catch, and it adds little beyond what a lookup in the record would do.

Existing evaluations of LLM judges do not tell a builder which of these to expect. Benchmarks give the judge correct context or none (Tan et al. 2025; Xu et al. 2025), and most report whether the judge flagged an answer, not why. A judge that flags every older citation would score well on detection, and so would one that flags any older document that sits next to a newer one on the same subject. Neither is checking currency.

We therefore built a test aimed at one error, citing a replaced document, and at the question of what the judge relies on when the record and the documents disagree. The test starts from any table of replacements. For each replacement it writes an answer citing the replaced document (a fault) and three answers that are correct: one citing the successor, one citing the replaced document at a date before the replacement existed (a date control), and one citing an older document that a newer one updated

without replacing (a decoy). It then removes half the links from the record, presents the damaged record in several ways that leave its content unchanged, and counts a fault as caught only when the judge says the cited document was replaced.

We applied the test to 48 replacements recorded by the RFC Editor of the Internet Engineering Task Force (IETF), with four judges (Gemini 3.1 Pro, GPT-5.5, Claude Opus 4.5 and the open-weight Gemma 4 26B). The hypotheses, tests and the way we would read each outcome were committed to the project repository after a smaller pilot on 24 of the links and before these runs.

With a correct record line, the judges caught every replaced citation or nearly so, which a lookup in the record also does. On the faults whose link we removed, every judge caught fewer with the record present than from the texts alone, on each of two random choices of which links to remove, and most of the missed answers were passed without any finding. The drop also occurred when the line said only that no replacement was recorded, a statement that is true. Presenting the record as an unverified note, or warning that it was incomplete, returned Gemini, GPT-5.5 and Claude most of the way to their text-only behaviour, false alarms included; the change is significant after correction for Gemini and GPT-5.5 but not for Claude, which had fewer catches to recover, and Gemma recovered at most 5 of the 13 it had lost (§5.2). Given both texts and no record, the judges caught many more replacements than they flagged updates, but every update they flagged had a near-identical title, and an unplanned analysis suggests that they treat the resemblance between two documents as evidence of replacement. Date controls, which the judges here nearly all passed, exposed in the pilot a 32B open model that flagged almost every old citation whatever its date.

The paper's contribution is the test, released as a small harness, together with this evidence about four judges on one corpus. We do not claim that LLM judges in general defer to records, and we cannot say why the judges we tested did. A second setting, Indian rooftop-solar regulation with an amendment record extracted by an AI pipeline, is reported as a descriptive case study in the appendix: its answer key did not pass our own quality checks, and nothing in the main results rests on it.

2 Related work

How LLM judges are evaluated.

Work on LLM judges has documented position, verbosity and self-preference biases (Zheng et al. 2023) and built benchmarks of harder judgements. JudgeBench (Tan et al. 2025) pairs responses that differ in correctness, and ContextualJudgeBench (Xu et al. 2025) asks judges to assess responses against supplied context, which it treats as the reference. Other studies probe what judges are sensitive to: they can be stable under edits that should not matter and insensitive to edits that should (Chen et al. 2026), and citation judges accept claims that their passage does not warrant (Qian et al. 2026). What counts as an error, or how it is scored, changes rankings: of citation verifiers (Kim et al. 2026) and of the models a benchmark evaluates (Pall 2026). Our test belongs to this line, with two differences in emphasis. The supplied context is a record that is deliberately incomplete, and findings are scored by the reason the judge gives, because in this task a flag for the wrong reason is easy to obtain.

Following a supplied signal over the evidence.

That models follow supplied signals is well established. Judges shown prior scores as metadata move toward them, and an instruction to disregard the metadata does not remove the effect (Kapetanovic et al. 2026). Code auditors given false assurances from static analysis lose detection, and prompt instructions do not reliably restore it (Liu and Gao 2026). Agents often adopt corrupted tool outputs (over a third of the time for every tool tested) and rarely warn users of the conflict (Yang et al. 2026). In the legal domain, models over-trust authoritative but false legal sources and struggle to tell whether a retrieved provision is still in force, and larger models appear more susceptible (Molfetta et al. 2026). The effect is not universal: judges given a wrong reference answer often ignore it (Lee et al. 2026), so how far a model follows a signal depends on the task and on the form of the signal.

Our results agree with this literature in direction. The setting differs in how the misleading signal arises. In the studies above it is constructed to be false: an injected score, a fabricated assurance, a corrupted tool output. Our record errs only through missing links, which is how real amendment records fail. In its authoritative form the gap then reads "in force", which is false, but in one condition the line says only that no replacement is recorded, which is true, and the judges' catches fell there too. The judge also has both documents in front of it, and a deterministic lookup in the same record gives a reference for what the record alone achieves. Our presentation conditions vary the record's wording, its apparent

authority and a warning about its completeness while keeping the record itself fixed; §6 compares the warning's effect with the anchoring result of Kapetanovic et al. (2026). Deference to an authoritative label is related to sycophancy towards a user's stated view (Sharma et al. 2024), but the source of the pressure is different.

Outdated evidence and temporal knowledge.

A separate line asks whether models that write answers can cope with change. Stale-Document Poisoning (Ahmed et al. 2026) shows that outdated retrieved documents overturn answers a model had right, and that an explicit statement of when the old evidence stops applying helps larger models. EvolveBench (Zhu et al. 2025) and earlier benchmarks of time-sensitive questions (Chen et al. 2021; Zhang and Choi 2021; Vu et al. 2024; Ouyang et al. 2025) measure whether models track facts that change, and work on knowledge conflicts asks when supplied context overrides what a model knows (Xie et al. 2024; Xu et al. 2024; Wu et al. 2024). These studies concern the model that writes the answer. We study a model that reviews an answer already written, which makes false alarms on correct answers part of the measurement.

Versioned law and amendment records.

Legal informatics has long modelled the change of norms explicitly: systems that manage consolidated acts across their successive versions (Palmirani and Brighi 2002), models of the temporal dimensions of norm change (Palmirani and Brighi 2006), defeasible-logic accounts of abrogation and annulment (Governatori and Rotolo 2010), and temporal metadata (in-force, efficacy and application times) in LegalRuleML (Palmirani et al. 2011). More recent work finds that retrieval over a corpus holding only current texts returns the wrong version of a provision (Cymbler et al. 2026), diagnoses staleness in statutory question answering (Prior et al. 2026), improves version-aware retrieval (Huwiler et al. 2025; Nam et al. 2026), and shows that LLM consolidation of statutes from amendment instructions is often not exact (50% exact matches for single amendments, 21% for chains) (Prior et al. 2025). Our record is a much thinner object than these models, a list of document-to-document replacements with dates, and our notion of currency ("replaced on or before the date asked about") is the simplest of the temporal notions they distinguish. We take such a record as given, imperfections included, and ask what a judge does with it.

Contrast items and right-for-the-wrong-reason.

Models can score well by exploiting features that correlate with the label (McCoy et al. 2019), and minimally different contrast items are a standard way to expose this (Gardner et al. 2020). Our date controls and decoys play that role for document currency. The date control changes only the date of a fault. The decoy keeps a newer document on the same topic, often with the same title, but one that leaves the older document in force. As §5.3 shows, our decoys control for title similarity but not for overlap between abstracts, so they are a partial contrast. Finally, label errors change model rankings (Northcutt et al. 2021; Gema et al. 2025), and a clinical benchmark built with LLM help was found to have at least 27% of its test labels likely wrong or incomputable (Ye et al. 2025). This is the main reason our primary data use the publisher's own record as gold, and the reason the regulatory study, whose AI-assisted key failed our checks, is reported only descriptively.

3 The test

The test needs two inputs: a record of replacements that is correct wherever it is used as gold, and a short text for each document. It needs no labelled answers, because the record already says which citations are wrong on which dates.

Matched items.

Every item poses the same kind of question, "As of date D, which document specifies T?", where T is the title of the older document, and supplies an answer that cites one document. For each link in the record (an old document and the document that replaced it) we write three items, and we pair each link with one decoy:

- a *fault* cites the old document, with D after the replacement;
- a *control* cites the replacing document, with the same D;
- a *date control* cites the old document, with D before the replacement existed, so the answer is correct;

Context	The judge is given, besides both texts
`both-texts`	nothing else
`status`	a line from the correct record: the cited document's status on the date
`status-damaged`	the line from a record with half its links dropped (a dropped link reads "in force")
`norecord-damaged`	as above, the line reading "no replacement recorded"
`lowauth-damaged`	as `status-damaged`, headed as an unverified note from an automated tagger
`caveat-damaged`	as `status-damaged`, with the warning that the record is incomplete and may omit replacements

Table 1 The six primary contexts. The four damaged contexts use the same damaged record; the warning adds one true statement about it.

- a *decoy* cites the older document of a different pair, in which a newer document *updates* the older one without replacing it. The older document is still in force, so this answer is also correct.

The fault and its date control are the same answer with a different date. A judge that objects to old citations without comparing dates will catch the fault and fail the date control. The decoy targets a different shortcut. In the fault, a newer document on the same subject sits next to the cited one; in the decoy, so does a newer document, often with the same title, but it did not replace the older one. A judge that flags any older document with a newer neighbour will catch the fault and fail the decoy. Catch rates alone cannot tell either judge apart from one that actually checks.

What the judge sees.

The context is the part a builder controls, and we vary it while holding the question and the answer fixed (Table 1). In every primary context the judge gets both documents' titles, dates and abstracts, with any sentence that states a replacement or names the other document removed, so that the replacement has to be inferred. Titles are not filtered, and in two links the replacing RFC's title names the old one (§8). Five of the six contexts add one line from an amendment record about the cited document. In the damaged record, half the links are dropped with a fixed seed; for a dropped link the record says nothing about a replacement, and its line therefore reports the replaced document as in force. We call the faults on these links *gap faults*. The four damaged contexts are built from the same damaged record and differ in how its line is presented:

- the authoritative form, an "amendment record lookup" reporting the document as `in_force`;
- the same record with the line worded `no_replacement_recorded` (wording);
- the same line headed as an "unverified note from an automated tagger" (authority);
- the authoritative form with a warning that the record is incomplete and may omit replacements (warning).

The pilot also used contexts that we did not repeat here: the citation alone, the cited document alone, masked document numbers, the replacing document's own notice of replacement, an instruction to check replacement first, and two worked examples. They are reported in Appendix A.

Scoring by reason.

The judge returns a verdict and a list of findings. Each finding names a document and gives one reason from a closed list: replaced (coded `superseded` in the prompt), not yet published, not applicable, content error, unsupported, or other. We count a fault as *caught* only if some finding names the cited document with the reason that it was replaced. A judge that flags the fault as, say, a content error has noticed that something is off without identifying the error, and an any-finding count would credit it with the catch. On the three kinds of correct answer we record two false-alarm counts: a *validity* false alarm, a finding that a document was replaced or not yet published, and any finding at all. The first measures mistakes about currency; the second also counts complaints about relevance or content, which the question format may provoke (§5.4). A reply that cannot be parsed counts against the judge: as a miss on a fault and as a false alarm of both kinds on a correct answer. We call a reply on a fault a *bare pass* when it contains no finding at all.

Lookup baseline.

A deterministic lookup, with no language model, flags exactly the documents the record marks as replaced. With the correct record it catches every fault and raises no false alarm. With the damaged record it catches the faults whose link survived and none of the gap faults. It tells us what the record alone achieves, and so what a judge given the record adds.

Scope of the design.

The test covers one error, citing a whole replaced document, and one decision, the judge's verdict on a fixed answer. Partial amendments, chains of replacements and cross-references would need other item generators. Following the record can help as well as hurt. The gap faults measure the cost of following a silent record, and the decoys, whose record line is correct, give one measure of the benefit.

4 Data and setup

Replacements.

IETF Requests for Comments (RFCs) replace one another, and the RFC Editor's index (RFC Editor 2026) records each replacement ("Obsoletes" / "Obsoleted by") together with publication dates and abstracts. We kept the simplest cases: replacements in which the old RFC was replaced by exactly one RFC, the replacing RFC is itself current, was published in 2005 or later and replaces at most two RFCs, and both documents have abstracts. From these we drew 48 links with a fixed seed. Because the record is the publisher's, the gold needs no annotation. Each document is represented by its title, publication date and abstract. In 33 of the 48 links the two titles are near-identical (a normalised string-similarity ratio of at least 0.8), which matters for the shortcut analysis below.

Decoys.

The index also records updates ("Updates" / "Updated by"), in which a newer RFC amends part of an older one without replacing it. A decoy is an update pair in which the older RFC was never replaced and the newer one is current, chosen under the same filters as the links and sharing no document with them. For each link we took the nearest unused update pair within the link's same-title group, by a distance that combines IETF area (our proxy for topic), title similarity, both publication dates and both abstract lengths. The matching is greedy in link order and deterministic. Balance on the matched features is good for dates (standardised mean differences 0.04 for the old date, 0.02 for the new date and -0.02 for the gap) and acceptable for title similarity (-0.22); 37/48 decoys share their link's IETF area. Two imbalances remain. Updating RFCs have shorter abstracts than replacing ones (-0.55), a property of updates that we chose not to force away. More importantly, abstract overlap was not a matching feature. A replacing RFC usually repeats much of the abstract of the RFC it replaces (median similarity 0.80 for same-title links), whereas an updating RFC does not (median 0.17 for same-title decoys). We found this only after the runs; its consequences are discussed in §5.3.

Judges and runs.

Four judges are run on all six contexts with the same links and decoys: Gemini 3.1 Pro, GPT-5.5 and Claude Opus 4.5 through the Kaggle Benchmarks proxy, and Gemma 4 26B through Google's API at temperature 0. The proxy sets temperature and seed itself and does not report them, which limits exact reproduction of the hosted judges. New requests in these runs went through the proxy with an output cap of 4,000 tokens, sending the system and user text as two messages. Replies to prompts identical to those of the pilot were taken from the pilot's cache rather than requested again: all 72 shared `both-texts` replies of Gemma, GPT-5.5 and Gemini, and 70 of Claude's 72. For the hosted judges those replies had been obtained with the proxy's earlier call (one joined message, no cap). Reuse affects the `both-texts` items of the first 24 links, their `status` items (except for GPT-5.5, which had no pilot `status` block) and the damaged-record items whose prompt did not change. For Gemma, the client retries a request once without the API's JSON mode when the JSON-mode reply is cut off; the run log records that this happened, but not for which items. Every block of replies records the model version and a hash of the harness code. For this paper we rescored every reply from its raw text, and every stored score matched.

Hypotheses and analysis.

The hypotheses below, with their tests and the reading we would give each outcome, were written after the pilot and committed to the project repository shortly before the runs. This is a timestamped internal

record, not a public registration. Before any result of these runs existed, the plan was amended to add two presentation conditions (wording and authority, beside the warning) and to match decoys on more features; the amendment is part of the same history.

H1 Given both texts, a judge's right-reason catch on faults exceeds its validity false alarms on the matched decoys. Tested per judge as the mean paired difference over the 48 link–decoy pairs, with a 2,000-resample bootstrap interval over pairs.
H2a On the 24 gap faults, a judge catches fewer with the damaged record (authoritative form) than with no record. Two-sided exact McNemar test on the paired items; Holm adjustment across judges.
H2b Each other presentation of the damaged record changes the catch on the gap faults relative to the authoritative form. Two-sided exact McNemar tests; Holm adjustment across all 12 presentation–judge pairs.

The unit of analysis is the link, never the model call. With 24 pairs, a change in which every discordant item moves the same way needs at least six items to reach the 5% level before adjustment (two-sided exact $p = .031$), and more after the Holm adjustment; changes that do not reach it are reported as inconclusive. The plan also listed Wilson intervals for rates and an exploratory mixed-effects model pooled over judges; we report exact counts and paired tests instead, and did not fit the model, since no claim depends on it.

A second draw of removed links.

Because the pilot had shown that the choice of removed links matters, we amended the plan, once seed-0 results existed for three judges and before any seed-1 call, to repeat H2a on a second random choice (damage seed 1) for the same four judges, with the tests fixed in advance: H2a per judge on seed 1 with Holm adjustment across judges, and a per-judge estimate over both seeds. The two draws drop 24 links each and share 12, so each adds 12 gap faults of its own. A shared link is the same item under both seeds, with an identical prompt and therefore the same reply, so the pooled estimate counts it once: it is the mean drop in catch over the 36 links in either gap set, with a 2,000-resample bootstrap interval over links and an exact sign test on the links that changed. Text-only prompts do not depend on the record, so seed 1 reuses the text-only replies; its damaged-record replies on the 12 new gap faults were new requests (eight per hosted judge) except where the pilot had asked the identical prompt. The second draw is a robustness check on the choice of removed links, not an independent replication: it shares half its gap faults and all text-only replies with the first. The hypotheses and thresholds were not changed. Everything else in §5, including every comparison by title or abstract overlap, is exploratory.

The pilot.

Before the final design, six judges ran up to ten contexts on the first 24 links (Appendix A). The pilot had no decoys and no presentation conditions, and its damaged record, built over 24 links rather than 48, dropped a different set of links. We use it for the date-control result and for the contexts not repeated here.

The case study.

The test was first developed on Indian rooftop-solar regulation, with an amendment record extracted by an AI pipeline and seven judges. Because its answer key failed the quality checks set for it, it is reported descriptively in Appendix D and the supplementary material, and no result in §5 uses it.

Use of AI assistants.

An AI coding assistant, built on models from the same developer as one of the judges (Claude Opus 4.5), drafted the hypotheses and analysis plan, which the authors reviewed and amended; wrote the harness; sampled the links and decoys; ran the Gemma judge and prepared the hosted-judge runs, which were executed through the benchmark proxy under the lead author's account; analysed the replies; and drafted and edited the manuscript. In the case study it drafted the labels and extracted the amendment record, which two authors checked blind with a third adjudicating. The RFC gold is the publisher's, and the assistant's own model was not run as a judge. The authors checked judge replies, statistical results and references against their sources, read and revised the manuscript, and take full responsibility for its content.

Table 2 All 48 links, per judge and context. Catch: right-reason catches of faults (any: any finding on the fault). False alarms (FA) count validity findings (replaced or not yet published) unless marked any. Controls cite the replacing RFC; date controls cite the replaced RFC as of a date before its replacement; decoys cite an RFC that a newer one updates but does not replace. All counts are of 48.

		Faults		Controls		Date controls	Decoys	
Judge	Context	Catch	any	FA	any	FA	FA	any
Gemma 4 26B	`both-texts`	31/48	31/48	0/48	19/48	0/48	6/48	6/48
	`status`	47/48	47/48	0/48	20/48	0/48	0/48	0/48
	`status-damaged`	23/48	23/48	0/48	20/48	0/48	0/48	0/48
	`norecord-damaged`	23/48	23/48	0/48	20/48	0/48	0/48	0/48
	`lowauth-damaged`	26/48	26/48	0/48	18/48	0/48	1/48	1/48
	`caveat-damaged`	29/48	29/48	0/48	18/48	0/48	1/48	1/48
GPT-5.5	`both-texts`	45/48	46/48	1/48	12/48	0/48	8/48	8/48
	`status`	48/48	48/48	0/48	13/48	0/48	0/48	0/48
	`status-damaged`	31/48	31/48	0/48	13/48	0/48	0/48	0/48
	`norecord-damaged`	34/48	34/48	0/48	10/48	0/48	0/48	0/48
	`lowauth-damaged`	48/48	48/48	1/48	11/48	0/48	10/48	10/48
	`caveat-damaged`	47/48	48/48	1/48	9/48	0/48	8/48	8/48
Gemini 3.1 Pro	`both-texts`	42/48	42/48	0/48	21/48	0/48	6/48	6/48
	`status`	48/48	48/48	0/48	20/48	0/48	0/48	0/48
	`status-damaged`	25/48	25/48	0/48	20/48	0/48	0/48	0/48
	`norecord-damaged`	28/48	29/48	0/48	19/48	0/48	0/48	0/48
	`lowauth-damaged`	42/48	42/48	0/48	19/48	0/48	4/48	4/48
	`caveat-damaged`	46/48	46/48	0/48	20/48	0/48	6/48	6/48
Claude Opus 4.5	`both-texts`	38/48	39/48	1/48	19/48	2/48	9/48	9/48
	`status`	48/48	48/48	0/48	21/48	0/48	4/48	4/48
	`status-damaged`	34/48	36/48	0/48	21/48	0/48	4/48	4/48
	`norecord-damaged`	35/48	36/48	0/48	20/48	0/48	5/48	5/48
	`lowauth-damaged`	41/48	42/48	0/48	20/48	1/48	9/48	9/48
	`caveat-damaged`	41/48	42/48	0/48	20/48	1/48	7/48	7/48

5 Results

Table 2 lists every judge's catches and false alarms in every context. We begin with the correct record, which sets the baseline, and then turn to the gap faults.

5.1 With a correct record

Given a line from the correct record, the judges caught all or nearly all faults (Gemma 47/48, GPT-5.5 48/48, Gemini 48/48, Claude 48/48), as a lookup in the same record does by construction. The record also helped on correct answers. For decoys, the record line correctly reports the older RFC as in force, and decoy false alarms fell from 8/48 to 0/48 for GPT-5.5, from 6/48 to 0/48 for Gemini, from 6/48 to 0/48 for Gemma and from 9/48 to 4/48 for Claude. Following the record therefore has a benefit as well as the cost measured below, and on this corpus a judge given a correct record does essentially what the record does.

With the damaged record the lookup catches the 24 faults whose link survived and none of the 24 gap faults. Over all 48 faults the judges scored Gemma 23/48, GPT-5.5 31/48, Gemini 25/48 and Claude 34/48. The gap faults themselves are analysed next.

5.2 Gap faults

Table 3 isolates the 24 gap faults; the items are the same in every column, so each comparison is within a judge. One qualification applies to all four judges. Their text-only replies to the items of the first 24 links, which include 11 of the gap faults, are the pilot's replies, reused because the prompts are identical (§4); for these items the comparison is a partial replication of the pilot, not an independent one. On the other 13 gap faults, where every reply is new, the drop is of similar size: Gemini 12 to 1, GPT-5.5 12 to 5, Claude 11 to 6, Gemma 8 to 0.

From the texts alone, Gemini caught 22/24 of the gap faults and, with the damaged record in its authoritative form, 1/24: 21 catches lost and 0 gained (H2a, Holm p <.001). GPT-5.5 went from 22/24 to 7/24 (15 lost, 0 gained; Holm p <.001) and Claude from 18/24 to 10/24 (8 lost, 0 gained; Holm p .008). Gemma caught fewer from the texts, 13/24, and none with the record (Holm p <.001). H2a therefore holds for all four judges. Of Gemini's 23 misses under the damaged record, 23 were replies with

Table 3 The 24 gap faults per judge: faults whose link the damaged record dropped (half the 48 links, seed 0). Same items in every column. The four damaged-record presentations use the same damaged record. Bare: passes with no finding under the authoritative "in force" line. *p*: exact McNemar, Holm-adjusted; H2a compares the authoritative line with no record, H2b each other presentation with the authoritative line.

	No record	Damaged record, presented as					Holm *p*			
Judge	(texts)	record, "in force"	"no replacement recorded"	unverified note	record + warning	Bare	H2a	wording	authority	warning
Gemma 4 26B	13/24	0/24	0/24	2/24	5/24	24	<.001	1.000	1.000	.375
GPT-5.5	22/24	7/24	10/24	24/24	23/24	17	<.001	1.000	<.001	<.001
Gemini 3.1 Pro	22/24	1/24	4/24	18/24	22/24	23	<.001	1.000	<.001	<.001
Claude Opus 4.5	18/24	10/24	11/24	17/24	17/24	12	.008	1.000	.125	.125

Table 4 H2a on two random draws of dropped links. Each seed drops 24 of the 48 links; the two draws share some links (Shared). Per seed: gap faults caught with no record → with the damaged record (authoritative form), lost/gained, Holm-adjusted exact McNemar *p* (across judges, within seed). Pooled: unique links in either gap set, a shared link counted once (its reply is the same under both seeds); mean drop in points with a 95% bootstrap interval over links, lost/gained, exact sign test. Seed 0 is the planned test; seed 1 and the pooled estimate were added before any seed-1 run, when seed-0 results existed for three judges.

	Seed 0			Seed 1				Pooled over unique links			
Judge	Caught	Lost/gained	*p*	Caught	Lost/gained	*p*	Shared	Links	Drop	Lost/gained	*p*
Gemma 4 26B	13/24 → 0/24	13/0	<.001	17/24 → 0/24	17/0	<.001	12	36	+61 [+44, +78]	22/0	<.001
GPT-5.5	22/24 → 7/24	15/0	<.001	24/24 → 8/24	16/0	<.001	12	36	+64 [+47, +78]	23/0	<.001
Gemini 3.1 Pro	22/24 → 1/24	21/0	<.001	21/24 → 3/24	18/0	<.001	12	36	+81 [+67, +92]	29/0	<.001
Claude Opus 4.5	18/24 → 10/24	8/0	.008	20/24 → 13/24	7/0	.016	12	36	+31 [+17, +44]	11/0	<.001

no finding at all; GPT-5.5's were 17 of 17, Claude's 12 of 14 and Gemma's 24 of 24. Claude's two misses that did carry a finding both mention the newer RFC, but as a content error (a possible data error in the evidence, or an answer that may be incomplete), not as a replacement; one repeats, as the record says, that the older RFC remains in force. No reply names a conflict between the record and the texts.

A second draw of removed links.

Table 4 repeats H2a on the second draw. Each judge lost catches again and gained none: Gemini 21/24 to 3/24, GPT-5.5 24/24 to 8/24, Claude 20/24 to 13/24 and Gemma 17/24 to 0/24 (Holm p <.001, <.001, .016 and <.001). The two draws share 12 gap faults, whose replies are identical under both, so the seed-1 result is new evidence only through its other 12 items. Counting each link once, the drop over the 36 links in either gap set is +81 points for Gemini (95% interval [+67, +92]), +64 for GPT-5.5 ([+47, +78]), +61 for Gemma ([+44, +78]) and +31 for Claude ([+17, +44]), with no link gained by any judge. On both draws Gemini lost the most catches and Claude the fewest, but with this many items we do not rank the judges.

Presentation.

Writing "no replacement recorded" instead of "in force" did not bring any judge back to its text-only level. Gemini caught 4/24 (3 gained, 0 lost), GPT-5.5 10/24 (3 gained, 0 lost), Claude 11/24 (3 gained, 2 lost) and Gemma 0/24; no change is significant before or after adjustment. Gains this small cannot be resolved with 24 pairs, so the result is that the rewording did not restore the lost catches, not that it had no effect. This condition matters for one more reason. In it the record line is literally true: it reports only that no replacement is recorded. The drop seen here, for judges that had both texts in front of them, is therefore produced by an omission in the record, without any false statement. (The comparison with the texts alone was not a planned test; for each judge every item that changed moved away from a catch.)

The other two presentations moved three of the judges. With the line headed as an unverified note, Gemini caught 18/24 gap faults and GPT-5.5 24/24; with a warning that the record omits some replacements, 22/24 and 23/24. Every item that changed moved toward a catch (Gemini 17 and 21 items, GPT-5.5 17 and 16), and all four tests are significant after the Holm adjustment over the twelve presentation tests (p <.001 each). Claude moved the same way, to 17/24 and 17/24 (7 items each, none lost; raw p .016, Holm p .125). In each condition it caught six of the 8 faults it had lost and one it had missed from the texts (Appendix B), almost its text-only level of 18/24; the test is not significant because Claude had few catches to recover, not because the change was small: even recovering all eight would not have reached significance after the adjustment. Gemma recovered less, catching 2/24 and 5/24 against 13/24 from the texts alone (Holm p 1.000 and .375).

Where the catches came back, they came back with the judge's text-only false alarms. Under the authoritative record, Gemini and GPT-5.5 raised no validity false alarm on decoys, because the record correctly lists the decoy's older RFC as in force. With the unverified note, GPT-5.5 flagged 10/48 decoys and Gemini 4/48; with the warning, 8/48 and 6/48, against 8/48 and 6/48 from the texts alone. Claude's

Table 5 Shortcut test with both texts and no record. Faults and their matched decoys, split by whether the two RFCs of the pair share a (near-)identical title. Discrimination: catch minus decoy false alarm, paired by link, in points with a 95% bootstrap interval over the 48 pairs.

	Same title		Different title		
Judge	Fault catch	Decoy FA	Fault catch	Decoy FA	Discrimination
Gemma 4 26B	29/33	6/33	2/15	0/15	+52 [+35, +69]
GPT-5.5	32/33	8/33	13/15	0/15	+77 [+65, +88]
Gemini 3.1 Pro	31/33	6/33	11/15	0/15	+75 [+60, +88]
Claude Opus 4.5	30/33	9/33	8/15	0/15	+60 [+44, +75]

rose from 4/48 to 9/48 and 7/48 (texts alone 9/48). A decoy's older RFC was never replaced, so in every presentation its record line is correct; a judge that weighed record against texts would have no reason to flag more decoys when told the record might omit replacements. The change therefore looks more like a return to text-only behaviour than like better use of the record. False alarms on controls and date controls stayed at two of 48 or fewer in every condition.

Comparison with the pilot.

In the pilot, Claude kept 10 of the 11 gap faults it had caught from the texts. Here it lost 8. The two runs used different gap faults: the pilot's damaged record was built over 24 links, and only 5 of its 12 gap faults are gap faults here. On those 5 the replies are the same reused replies and Claude caught 3; the other 7 pilot items, all of which it caught, are not gap faults in this run. Most of the difference therefore comes from which links were dropped, and on the second draw Claude again lost catches (7) and gained none. Because the shared replies were reused rather than requested again, this comparison cannot speak to run-to-run variation, which the pilot's one repeated block suggests is real at the level of individual replies. A dozen items can therefore mislead, and comparisons between judges on item sets of this size, including those in our own tables, are provisional. Appendix B lists every gap fault.

5.3 Replacements, updates and surface similarity

Table 5 reports the decoy test, with both texts and no record. Every judge caught more faults than it flagged decoys (paired difference +77 points for GPT-5.5, 95% interval [+65, +88]; Gemini +75, [+60, +88]; Claude +60, [+44, +75]; Gemma +52, [+35, +69]), so H1 holds. H1 is a weak test, though: a judge that flagged every older document with a near-identical title would pass it as long as most replacements share their predecessor's title. The more informative comparison is within the same-title pairs, where title similarity is held roughly constant. There GPT-5.5 caught 32/33 faults and flagged 8/33 decoys, Gemini 31/33 and 6/33, Claude 30/33 and 9/33, Gemma 29/33 and 6/33. Among different-title pairs, no judge flagged a decoy, and catches differed widely (GPT-5.5 13/15, Gemini 11/15, Claude 8/15, Gemma 2/15).

Our plan read a positive H1 as evidence that text-only catches are not a title shortcut. The data call for a more qualified reading, and the analysis that supports it was not planned. Title similarity travels with abstract overlap: in the text the judges saw, a replacing RFC usually repeats much of its predecessor's abstract (median similarity 0.80 for same-title links, 0.15 for different-title links), while the decoys, which were not matched on overlap, do not (0.17 and 0.10). Splitting at a similarity of 0.3, chosen after seeing the data, false alarms on same-title decoys were more frequent when the abstracts overlapped (GPT-5.5 3/7 against 5/26; Gemini 2/7 against 4/26; Claude 3/7 against 6/26; Gemma 2/7 against 4/26), and so were catches on different-title replacements (Claude 5/6 against 3/9; Gemma 2/6 against 0/9; GPT-5.5 6/6 against 7/9; Gemini 6/6 against 5/9). The high-overlap cells hold six or seven items, and we report no test. The pattern is consistent with judges using the resemblance between the two documents as evidence of replacement. In the RFC series that is often good evidence, so we hesitate to call it a shortcut, and the data cannot separate the title from the abstract.

The decoys also have a labelling caveat. Some of the decoys the judges flagged are updates that introduce a new version of a protocol, such as RFC 8210 (version 1 of the RPKI-to-Router protocol, updating RFC 6810), flagged by all four judges, and RFC 9777 (MLDv2, updating RFC 2710), flagged by two. By the publisher's record the older RFC is in force, which is our gold. For a question asking which document specifies the protocol, however, a reader could reasonably prefer the newer version. Some of these false alarms may therefore be defensible judgements rather than errors.

5.4 Scoring by reason

For the frontier judges given both texts, counting any finding on a fault instead of the right reason barely changes the catch (GPT-5.5 45/48 against 46/48, Gemini 42/48 against 42/48, Claude 38/48 against 39/48). On correct answers the difference is large. With both texts, Claude raised some finding on 19/48 of the controls that cite the replacing RFC, but a validity finding on 1/48; Gemini raised some finding on 21/48 and a validity finding on 0/48; Gemma raised some finding on 19/48 and a validity finding on 0/48. Gemma's findings on these controls all gave the reason "content error". We suspect, without having tested it, that the question format provokes them: the question names the old document's title, and the answer cites a document with a different number and sometimes a different title. Under any-finding scoring these three judges would appear to raise false alarms on about two in five of these controls, almost none of which concern currency.

Without evidence the difference also affects catches. In the pilot, from the citation alone, Gemini raised a finding on every fault but gave the right reason on 11/24. Reason coding is also what makes the bare passes of §5.2 visible as a separate category from passes with an irrelevant finding.

5.5 Date controls

The judges raised few or no validity false alarms on date controls (with both texts: GPT-5.5 0/48, Gemini 0/48, Claude 2/48 and Gemma 0/48). In this run the controls did not separate the judges. In the pilot they did. Qwen 2.5 32B caught 42/48 faults with both texts, a catch rate comparable to the frontier judges, but also flagged 43/48 answers that were correct on their date, for a currency discrimination of −2 points against +92 for Gemini. Two worked examples, one of them a correct answer passed, reduced its date false alarms to 5/48. The result rests on one judge, and a catch rate alone would not have revealed it.

6 Discussion

The gap result.

Within each of the four judges, the same gap faults were caught less often when a record line was present, and most of the lost catches became passes with no finding. Some mundane explanations can be set aside. The items are identical across conditions. The drop also occurs when the line says only that no replacement is recorded, so it does not depend on the record stating anything false. And the decoy test shows that most text-only catches were not reflexive objections to older documents. What the design cannot set aside, the small and partly shared item sets and the reused replies, is discussed in §8.

We cannot say why the judges behaved this way, and at least three explanations fit what we observed. The judge may simply be relying on the record as the task presents it. It is shown an "amendment record lookup", nothing suggests the record is incomplete, and trusting it is defensible; on correct answers, following it removed most decoy false alarms (§5.1). On that reading the failure belongs to a record that does not disclose its own gaps, and what the judge lacks is any sign of registering the conflict with the texts. The line may instead be more salient than the evidence, being short, explicit and placed just before the task, while the replacement has to be inferred from two abstracts; we did not vary position or length. Or the judge may treat the status line as part of the question rather than as evidence to weigh. A bare pass is compatible with all three, and it does not tell us whether the judge noticed the conflict and resolved it in the record's favour or never noticed it.

Presentation.

The presentation conditions were meant to separate these explanations, and they partly do. Rewording the gap did not restore the catches for any judge, which lends no support to the simplest account, that judges are misled by an explicit claim of currency, although 24 pairs cannot exclude a small effect of wording. For Gemini and GPT-5.5, lowering the record's standing or warning that it was incomplete restored most or all of the lost catches, and Claude recovered six of the eight it had lost, without reaching significance. This fits the first explanation: told that the record might be wrong, these judges went back to the texts. It fits the salience explanation less well, since the note and the warning leave the line as short, explicit and close to the task as before. For these three judges, however, the decoy false alarms came back with the catches, to about their text-only level. The judges did not come to weigh record against texts item by item; they moved from relying on one source to relying on the other. Gemma moved least, catching at most five of the 24 gap faults however the damaged record was presented. Which

judges respond in this way, and why, is a question for more judges and more wordings than our one variant per condition.

Two related findings point in different directions. Kapetanovic et al. (2026) found that a warning did not reduce the total effect of judges' anchoring on prior scores, though it improved accuracy in one of their experiments. Our warning differs in stating a specific and true defect of the record, with the contradicting evidence in view, and either difference could matter. Molfetta et al. (2026) report that larger models, reasoning models in particular, defer more to authoritative but false legal citations. Our one open-weight judge responded least to the presentation of the record, but the hosted judges' sizes are not published, and four judges could not test an effect of size in any case.

Resemblance between documents.

The decoy results contain two observations that should be kept apart. The judges did not flag older documents merely for having a newer neighbour, since they caught far more replacements than they flagged updates. Yet their mistakes in both directions tracked how alike the two documents looked. Given both texts, updates were flagged only when the titles were near-identical, and Gemma rarely caught a replacement whose title had changed. Some of this reliance is reasonable, since RFC replacements often do repeat their predecessor's title and abstract, and some flagged decoys are new protocol versions that a reader might prefer to cite. The practical concern is transfer. An amended regulation may keep its title, while a contract amendment can look nothing like the agreement it modifies. A judge evaluated on one kind of collection may behave differently on the other, and nothing in a single-corpus evaluation, ours included, would show it.

Scoring.

Reason codes matter most on correct answers: under any-finding scoring, Claude, Gemini and Gemma would have appeared to object to roughly two in five controls, nearly all for reasons unrelated to currency. They also make the gap result measurable. A judge that calls a stale citation a "content error" has at least objected, and only reason-coded scoring separates it from a judge that says nothing.

7 Practical implications

These suggestions come from four judges on one corpus. Each is cheap to check with one's own judge, since the harness runs a judge through the six contexts in about 1,200 calls.

An evaluation in which the judge receives a correct record says little about the judge: with a correct record our judges did what a lookup does. The more useful test removes links from the record and compares each judge with itself on the affected items. If its catches there fall to the lookup's level, the judge contributes nothing beyond the record on those items, and the completeness of the record becomes the real limit of the pipeline. That trade-off can still be worth accepting, since the same record also spared the judges false alarms on decoys.

How the record is presented can matter, and not in the same way for every judge. For three of our judges a true warning that the record was incomplete restored most catches on its gaps, but it also brought back the false alarms on decoys that the record had removed, and the fourth judge recovered few. A builder considering such a warning should test it on their own judge and items, count false alarms as well as catches, and make sure the warning is true.

Scoring should use reasons. Any-finding scoring inflates false alarms on correct answers and cannot distinguish a judge that raises an irrelevant objection from one that says nothing. Where the record lists both replacements and non-replacing updates, as the RFC index does, date controls and decoys come at no extra cost.

If the replacements in a target collection tend to look unlike the documents they replace, catches on such pairs should be measured separately, since our judges were weakest there.

8 Limitations and threats to validity

Two draws of dropped links, few items.

Each draw gives each judge 24 gap faults; the two draws share 12, so the gap result rests on 36 distinct links. The drop held on both draws for every judge, but the pilot showed how much a judge's result can depend on which links are dropped (§5.2), and differences between judges of a few items remain within

what such variation could produce. The presentation conditions were run on the first draw only, and Claude's presentation effects are not significant.

Reused replies, single runs and decoding.

Text-only replies on the first 24 links were reused from the pilot for all four judges, and the second draw reuses the first draw's text-only replies, so H2a is partly a re-analysis of pilot replies; on the gap faults where every reply is new, the drop is of similar size (§5.2). Hosted judges ran once each, through a proxy that sets and does not report temperature and seed; in the pilot, a repeated block changed 30 of 72 replies but only one catch. The reused replies came from an earlier form of the proxy call, and Gemma's client sometimes retried a cut-off reply without the API's JSON mode (§4).

The decoys are a partial control.

They are matched on dates, title similarity and, for most pairs, IETF area, but not on abstract overlap, which differs sharply between replacements and updates. Some decoys are new protocol versions, for which flagging the older RFC is a defensible reading of the question even though the publisher's record says it was not replaced. The similarity analysis is exploratory, post hoc and small.

Construct.

The evidence is titles, dates and abstracts, not full documents. The error tested is always the citation of a whole replaced document; partial amendments and chains are not covered. Links are dropped at random, while real records fail in patterns (recent amendments, particular issuers). The question names the old document's title, which may provoke some of the non-currency findings on controls. Two of the 24 gap faults are weaker items: RFC 7142 ("Reclassification of RFC 1142 to Historic") and RFC 6082 ("...RFC 2482 is Historic") name the old RFC in their titles, so the replacement is stated rather than inferred, and as reclassification notices they do not themselves specify the protocol, so the controls citing them are weaker. They account for two of Gemini's lost catches and one each of GPT-5.5's and Claude's (Table B4); without them every judge still lost catches and gained none (Claude 7 lost, two-sided exact $p = .016$).

Generalisation.

One corpus of technical standards, chosen because its publisher maintains an exact record, and four judges. Legal collections add problems this test does not address, as the case study illustrates: partial amendments, records extracted by machine, and answer keys that people disagree about. The title of the paper asks a general question; the answer we give is limited to these judges, prompts and documents.

Mechanism.

The presentation conditions keep the record fixed and vary single features, one prompt variant each. They can show that presentation changed what a judge did; they cannot show why.

Provenance.

The harness and the text were produced with an AI assistant from the same developer as one of the judges, Claude Opus 4.5 (§4). All judges received identical prompts and items, and the gold comes from the publisher. The plan was written by the same team after the pilot and recorded internally rather than registered publicly.

9 Conclusion

We asked what LLM judges rely on when they check whether a cited document is still in force. On a corpus with an exact publisher record, the judges we tested matched a lookup when the record was correct, and on links we removed from the record they caught markedly fewer replaced citations than they did from the texts alone, usually without comment, on both of two random choices of removed links. This happened even when the record line said, truthfully, only that no replacement was recorded. Labelling the record as unverified or incomplete brought three of the four judges most of the way back to the texts, their false alarms included, and the fourth part of the way. An evaluation with a correct record and any-finding scoring would have shown none of these behaviours. The test needs only a table of replacements, and we release it so that others can run it on their own judges and collections.

Table A1 Where the record is silent. Left: right-reason catches on all faults with no record (`both-texts`), a correct record line (`status`) and a record with half its links dropped (`status-damaged`, seed 0); a lookup in the damaged record catches exactly half. Right: the faults whose link was dropped, with no record, with the damaged record (the line reads "in force"), and with the line worded "no replacement recorded"; same items in every column. Bare: damaged-record replies on these faults that pass the answer with no finding. Qwen 32B ran 48 links, the others 24.

	All faults			Faults whose link was dropped			
Reviewer	No record	Correct	Damaged	No record	"In force"	"No replacement"	Bare
Qwen 32B	42/48	48/48	33/48	22/24	9/24	5/24	6
Gemma 4 26B	16/24	24/24	12/24	10/12	0/12	0/12	12
GPT-OSS 120B	16/24	18/24	15/24	8/12	6/12	–	4
Gemini 3.1 Pro	22/24	24/24	12/24	12/12	0/12	3/12	12
GPT-5.5	23/24	–	16/24	11/12	4/12	6/12	8
Claude Opus 4.5	19/24	24/24	22/24	11/12	10/12	9/12	1

Table A2 Currency discrimination by context (points): right-reason catch on faults minus validity false alarms on date controls, which cite the same old document as of a date before it was replaced. Mean over links.

Context	Qwen 32B	Gemma 4 26B	GPT-OSS 120B	Gemini 3.1 Pro	GPT-5.5	Claude Opus 4.5
`cite-only`	−38	+12	–	+46	–	+21
`cited-text`	−69	–	–	–	–	+25
`both-texts`	−2	+67	+67	+92	+96	+71
`both-masked`	−19	+62	+54	+83	+92	+75
`both-explicit`	−2	–	+88	+100	+100	+92
`status`	+77	+100	+71	+100	–	+100
`status-damaged`	+46	+50	+62	+50	+67	+92
`norecord-damaged`	+27	+50	–	+62	+75	+83
`check-first`	+23	+75	–	+100	–	+88
`few-shot`	+79	–	–	–	–	+75

10 Data and code availability

The repository (https://github.com/unnatibshah/what-do-llm-judges-verify) holds the harness (`evalkit.py`), the run and analysis scripts, the sampled links and decoys, every judge reply with its block metadata (model version, context, code hash), and the scripts that regenerate every number, table and figure in this paper from those replies: the analysis script (`analyse_final_e123.py`) rescores every reply from its raw text, checks the stored scores and regenerates §5 and Appendix B; `python -m suryabench.evalkit` does the same for the pilot. The RFC Editor index is cited with its retrieval date and content hash (RFC Editor 2026) and included unchanged. The hypotheses, tests and readings were committed to the project's development repository before the runs, and the amendment adding the second draw before any call on it. That repository is private; the release contains the plan with its amendments and a provenance file listing the commit and time at which the plan, each amendment and each block of results were recorded. For the case study, the regulatory documents are released as source URLs with content hashes, and the cases, the fixed answers, the record before and after adjudication and the annotation sheets are released with the code. Code is under the Apache-2.0 licence; the judge replies, the analysis outputs and the case study's cases and labels are under CC BY 4.0.

Appendix A The pilot

Six judges (Qwen 2.5 32B, Gemma 4 26B, GPT-OSS 120B, Gemini 3.1 Pro, GPT-5.5 and Claude Opus 4.5) ran up to ten contexts on the first 24 links before the final design was fixed; Qwen 2.5 32B ran all 48. Table A1 gives the pilot's gap result, on the 12 gap faults per judge produced by a damaged record over 24 links, and Table A2 the currency discrimination against date controls in every context. The generated pilot tables use the pilot's own vocabulary ("reviewer" for judge, "deference" for the gap contrast). The pilot's gap faults overlap only partly with the final run's (§5.2).

Runs.

Hosted models ran once through the Kaggle Benchmarks proxy, which sets temperature and seed itself; GPT-5.5's two damaged-record blocks ran after a change to the proxy call (an output cap, and the system and user text sent as two messages), with the prompt text unchanged. An accidental repeat of one block (Gemini 3.1 Pro, citation only; the first run is of record) differed by one catch. Every block

Table A3 Discrimination against current-document controls (points): right-reason catch minus validity false alarms on answers citing the replacing document. Mean over links.

Context	Qwen 32B	Gemma 4 26B	GPT-OSS 120B	Gemini 3.1 Pro	GPT-5.5	Claude Opus 4.5
`cite-only`	−31	+12	–	+46	–	+21
`cited-text`	−69	–	–	–	–	+21
`both-texts`	+40	+67	+62	+92	+96	+75
`both-masked`	+35	+62	+50	+83	+92	+75
`both-explicit`	+46	–	+83	+100	+100	+100
`status`	+100	+100	+75	+100	–	+100
`status-damaged`	+69	+50	+62	+50	+67	+92
`norecord-damaged`	+60	+50	–	+62	+75	+88
`check-first`	+75	+75	–	+100	–	+88
`few-shot`	+88	–	–	–	–	+75

records the model version, the context and the harness's code hash. A reply that cannot be parsed counts as a miss on a fault and a false alarm on a control; GPT-OSS had two to four such replies per block, the other reported judges at most two. Three further runs stopped before the deference pair of contexts and are not analysed; their blocks are in the repository.

Items.

Two of the 48 replacing RFCs name the old RFC in their title (RFC 7142, RFC 6082); titles are not filtered, so these two links are explicit wherever they appear: for Qwen 32B in the pilot, and for all four judges in the final runs, where both are gap faults (Table B4). The sentence filter of `both-texts` also removes some sentences that mention updates in general.

Links without a shared title.

On the 6 of the first 24 links whose successor has a different title, with both texts, GPT-5.5 caught 6/6, Gemini 5/6, Claude 3/6, GPT-OSS 2/6 and Gemma 1/6. Masking the document numbers changed little for the frontier judges (Gemini 20/24, Claude 20/24, GPT-5.5 22/24) and cost GPT-OSS a few catches (13/24).

Bare passes.

A reply on a fault is a bare pass when it has no finding at all.

Controls citing the successor.

Table A3 gives discrimination against controls that cite the replacing document. Given the documents, the frontier judges, GPT-OSS and Gemma rarely gave a validity reason on these controls; Qwen 32B gave one on 23/48. Other findings on them ("not applicable", "unsupported") are expected, because the question names the old document's title.

Appendix B Gap faults item by item

Table B4 gives, for each judge, the outcome on every gap fault under no record and the four presentations of the damaged record. Every reply, with its raw text, is in the repository (`50_analysis/results/evalkit_rfc_v2/`; second draw in `evalkit_rfc_v2_seed1/`). The outcome of every link under both draws, with the draws it belongs to, is in `evalkit_rfc_v2/analysis/seed1_links.csv`.

Appendix C Prompt

Figure C1 gives the system text and the full prompt for one gap fault under the authoritative line, as sent, and the record block of each damaged context. The other contexts differ only in the record block, which is absent from `both-texts`.

Table B4 Per-item outcomes on the gap faults (✓ caught for the right reason, · missed, – not run). Within each judge, the five marks are: no record, "in force", "no replacement recorded", unverified note, record with warning.

Link (RFC)	Gemma 4 26B	GPT-5.5	Gemini 3.1 Pro	Claude Opus 4.5
6312→6342	· · · · ·	· · · ✓ ✓	✓ · · · ✓	· · · · ·
8773→9973	· · · · ·	✓ · · ✓ ✓	· · · · ·	✓ · ✓ ✓ ✓
5046→7145	✓ · · · ·	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
8407→9907	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
3205→9205	· · · · ·	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ · · · ·
2821→5321	✓ · · · ·	✓ · ✓ ✓ ✓	✓ · · ✓ ✓	✓ ✓ · ✓ ✓
4402→7802	✓ · · ✓ ·	✓ ✓ ✓ ✓ ✓	✓ · ✓ ✓ ✓	✓ · ✓ ✓ ✓
5157→7707	· · · · ·	✓ · · ✓ ✓	✓ · · · ✓	· · · · ·
2837→4044	· · · · ·	✓ · · ✓ ✓	✓ · · · ✓	· · · · ·
2621→4671	· · · · ·	✓ · · ✓ ✓	✓ · · · ✓	· · · · ·
2858→4760	✓ · · · ✓	✓ ✓ ✓ ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
2478→4178	✓ · · · ·	✓ ✓ ✓ ✓ ✓	✓ · · ✓ ✓	✓ · · ✓ ✓
1657→4273	· · · · ·	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ · · · ✓
1142→7142	· · · · ·	· · · ✓ ·	✓ · · ✓ ✓	✓ · ✓ ✓ ✓
8941→9651	✓ · · · ✓	✓ ✓ ✓ ✓ ✓	✓ · ✓ ✓ ✓	✓ ✓ · ✓ ✓
5430→6460	✓ · · · ·	✓ · · ✓ ✓	✓ · ✓ ✓ ✓	✓ ✓ ✓ ✓ ✓
2482→6082	· · · · ·	✓ · · ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
3984→6184	✓ · · · ·	✓ ✓ ✓ ✓ ✓	✓ ✓ ✓ ✓ ✓	✓ ✓ ✓ ✓ ✓
4244→7044	✓ · · · ·	✓ ✓ ✓ ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
3230→9530	· · · · ·	✓ · · ✓ ✓	✓ · · ✓ ✓	· · · ✓ ✓
7613→8265	✓ · · · ✓	✓ · ✓ ✓ ✓	✓ · · ✓ ✓	✓ ✓ ✓ ✓ ✓
2767→6535	· · · · ·	✓ · · ✓ ✓	· · · · ·	· · · · ·
8843→9143	✓ · · · ✓	✓ · ✓ ✓ ✓	✓ · · ✓ ✓	✓ · · ✓ ✓
2910→8010	✓ · · · ·	✓ ✓ ✓ ✓ ✓	✓ · · ✓ ✓	✓ · · ✓ ·

Appendix D Case study: Indian rooftop-solar regulation

Status: descriptive only. The test was first developed on this setting, where no curated consolidation exists and the amendment record had to be extracted from the documents by an AI pipeline. Its answer key failed the quality checks planned for it: a person applying the right-reason rule agreed with the automatic scorer on 70% of dev replies, against a planned threshold of 95%, and when people read whole case files, many of the fixed "correct" answers turned out to be incomplete. None of its numbers is used as evidence for the hypotheses or findings of §5. It is reported because its failures, annotation disagreements and negative results show what the test needs from an uncurated amendment record; its planned analyses and readings are kept as they were fixed, so that nothing is selected after the fact. The full report (reference data and their audit, conditions, planned analyses and results, readings fixed in advance, prompts, per-clause results, annotation agreement, deviations from the plan and the data statement) is in the supplementary material.

Two consequences follow for reading the numbers below. False alarms on correct answers cannot be taken as the judge's errors. For example, Claude Opus 4.5 raised some finding on 37/42 correct answers when given the status line, but most of its findings were not about validity (44/55), and only a corrected key could say whether they were wrong. Likewise, the large differences between any-finding and right-reason catches in this study are real outputs on this key, but we do not use them to support §5.4, which rests on the RFC data. The text below is carried over from the study's own report, written before the RFC study, and uses its terms (reviewer for judge, registry for record, clause for document).

D.1 Setting

Documents and record.

The corpus holds 111 regulatory instruments on rooftop solar from 8 Indian jurisdictions, superseded ones included. No consolidated record exists, so an AI pipeline extracted one from the documents: 186 clause-level links, each from an old clause to the clause that changes it, with a relation and an effective date. Two authors checked a random sample of the links blind; 5 of 34 were judged to be no change at

Table D5 The findings across all models, on the same items (pooled k/n over S-both faults, where both versions of the clause are shown, or matched correct answers; 50%-dropped arms pooled over each model's damage seeds). The five planned models come first (the open models by size, then Flash-Lite); the last two columns were added after the analysis plan was fixed. Gains and losses compare each fault and seed with the damaged lookup. The dropped-link catch is clause-averaged over the faults the intact registry catches and the damaged one drops.

Finding	Llama 8B	Qwen 7B	Qwen 14B	Gemma 4 26B	Flash-Lite	Qwen 32B	Claude Opus 4.5
Right-reason catch, both versions (R2)	0/42	5/42	13/42	9/42	19/42	4/42	34/42
Any-finding catch, R2	24/42	14/42	26/42	32/42	35/42	35/42	42/42
Scoring gap at R2, any minus right reason (points)	+57	+21	+31	+55	+38	+74	+19
Right-reason catch, status line (R4)	3/42	2/42	32/42	25/42	33/42	29/42	35/42
Correct answers flagged, R4	19/42	2/42	10/42	20/42	19/42	23/42	37/42
R4 findings on correct answers not about validity	13/25	0/2	4/11	28/30	19/22	21/24	44/55
Catches gained / lost vs lookup, 50% dropped	+0 / −15	+2 / −15	+13 / −13	+25 / −24	–	+4 / −8	+14 / −0
Catch on dropped links, R2 → R4-damage, % (clauses)	0 → 0 (6)	33 → 17 (6)	41 → 7 (9)	32 → 31 (9)	–	13 → 0 (9)	92 → 67 (6)

all, and every link the test relies on was checked and corrected (supplementary material, §S1.1). The record therefore asserts few wrong links, but nothing measures how many it misses, as in practice.

Items.

A case is a synthetic solar application (a bill, an installer proposal and a utility record) with a date and a jurisdiction, labelled by rule functions whose parameters are quoted from the clauses. Its answer is an approve-or-reject decision with the clauses it rests on. A fault cites a replaced clause in place of its successor; its matched control is the correct decision citing the current clause. The case study has no date control, because each case has one date. People audited the answer key before the test set was sealed: the AI-built key reached a different outcome from the adjudicated one on 18 of 60 candidate cases, which were dropped. The sealed set has 42 cases on 14 distinct replaced clauses from 6 jurisdictions; the record links 11 of the 14, so the other replaced clauses are gaps the record already has.

What the reviewer sees.

The main conditions are three contexts of the framework: both versions of the clause (R2, `both-texts`), both versions plus the record's status line for each cited clause (R4, `status`), and the same line from a damaged record (R4-damage, `status-damaged`; R4n-damage, `norecord-damaged`). The record is damaged by dropping 25% or 50% of its links, or adding 10% spurious ones, over 5 seeds. A deterministic lookup in the same record (R5, no language model) flags exactly the clauses the record marks as replaced; it is the reference for what the record alone achieves. Further conditions (the old clause alone, source metadata, the amending instrument's words) are in the supplementary material (§S1.2).

Reviewers and scoring.

Seven reviewers judged the same items: `llama3.1:8b`, `qwen2.5:7b`, `qwen2.5:14b`, `gemma-4-26b-a4b-it`, `gemini-3.5-flash-lite` (on R0, R2 and R4 only), `qwen2.5:32b` and Claude Opus 4.5, with greedy decoding except for Claude, which ran through a proxy that sets temperature and seed itself. A fault is caught when a finding names the replaced clause with the reason "not in force". The unit of inference is the distinct replaced clause: rates are averaged within a clause, then over clauses. The questions, analyses and readings were fixed in a dated, version-controlled plan before any model saw a test item; the planned tests, all reported, are in the supplementary material (§S1.3 and S1.4).

D.2 Descriptive results

Table D5 summarises the findings across the seven judges on the same items. Figure D2 compares the judge given the record's status line with a lookup in the same record as the record degrades.

References

Ahmed MS, Galke Poech L, Röttger R (2026) Stale-document poisoning: When outdated retrieval overrides correct model answers. arXiv preprint URL https://arxiv.org/abs/2609.31342, arXiv:2609.31342

Chen J, Chen W, Lin Z, et al (2026) A judge should know what changed: Construct validity for LLM-as-a-judge evaluation. arXiv preprint URL https://arxiv.org/abs/2608.24419, arXiv:2608.24419

Chen W, Wang X, Wang WY (2021) A dataset for answering time-sensitive questions. In: Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks, URL https://arxiv.org/abs/2108.06314

Cymbler R, Guez D, Fabre L (2026) Temporal misgrounding in legal RAG: A versioned-corpus benchmark for French tax law. In: ICML 2026 Workshop on AI for Law (AI4Law), URL https://arxiv.org/abs/2608.09393, arXiv:2608.09393

Gardner M, et al (2020) Evaluating models' local decision boundaries via contrast sets. In: Findings of the Association for Computational Linguistics: EMNLP 2020, pp 1307–1323, https://doi.org/10.18653/v1/2020.findings-emnlp.117

Gema AP, Leang JOJ, Hong G, et al (2025) Are we done with MMLU? In: Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), pp 5069–5096, https://doi.org/10.18653/v1/2025.naacl-long.262

Governatori G, Rotolo A (2010) Changing legal systems: legal abrogations and annulments in defeasible logic. Logic Journal of the IGPL 18(1):157–194. https://doi.org/10.1093/jigpal/jzp075

Huwiler D, Stockinger K, Fürst J (2025) VersionRAG: Version-aware retrieval-augmented generation for evolving documents. arXiv preprint URL https://arxiv.org/abs/2510.08109, arXiv:2510.08109

Kapetanovic A, Altwlkany K, Mercep A, et al (2026) Anchoring bias in LLM-as-a-judge systems: Prior scores compromise evaluation independence. In: Proceedings of the 35th ACM International Conference on Information and Knowledge Management (CIKM), URL https://arxiv.org/abs/2608.25869, to appear; arXiv:2608.25869

Kim K, Brendel W, Reizinger P (2026) HALLMARK: How to diagnose LLM citation verifiers and when to deploy them. arXiv preprint ArXiv:2607.18360

Lee D, Hwang Y, Kang T, et al (2026) Judging against the reference: Uncovering knowledge-driven failures in LLM-judges on QA evaluation. arXiv preprint ArXiv:2601.07506

Liu Z, Gao S (2026) Trusting the tool: Asymmetric deference of LLM vulnerability auditors to static-analysis evidence. arXiv preprint ArXiv:2610.32876

McCoy RT, Pavlick E, Linzen T (2019) Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In: Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pp 3428–3448, https://doi.org/10.18653/v1/P19-1334

Molfetta L, Cocchieri A, Ragazzi L, et al (2026) Sycophants in the courtroom: Are LLMs fragile to juridical authority and evolving legal standards? In: Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp 10865–10886, https://doi.org/10.18653/v1/2026.acl-long.497, URL https://aclanthology.org/2026.acl-long.497/

Nam Y, Kim J, Song H, et al (2026) TimelyRAG: Semantic-temporal hybrid retrieval for time-critical question answering in overlapping-evolving documents. In: Findings of the Association for Computational Linguistics: EMNLP 2026, pp 8414–8430, https://doi.org/10.18653/2026.findings-emnlp.398, URL https://aclanthology.org/2026.findings-emnlp.398/

Northcutt CG, Athalye A, Mueller J (2021) Pervasive label errors in test sets destabilize machine learning benchmarks. In: Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks, 2103.14749

Ouyang J, Pan T, Cheng M, et al (2025) HoH: A dynamic benchmark for evaluating the impact of outdated information on retrieval-augmented generation. In: Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp 6036–6063, https://doi.org/10.18653/v1/2025.acl-long.301, URL https://aclanthology.org/2025.acl-long.301/

Pall RS (2026) Scoring-rule sensitivity in LLM evaluation: Evidence from Indian financial regulatory text. arXiv preprint ArXiv:2604.19298

Palmirani M, Brighi R (2002) Norma-system: A legal document system for managing consolidated acts. In: Database and Expert Systems Applications (DEXA 2002), Lecture Notes in Computer Science, vol 2453. Springer, pp 310–320, https://doi.org/10.1007/3-540-46146-9_31

Palmirani M, Brighi R (2006) Time model for managing the dynamic of normative system. In: Electronic Government (EGOV 2006), Lecture Notes in Computer Science, vol 4084. Springer, pp 207–218, https://doi.org/10.1007/11823100_19

Palmirani M, Governatori G, Rotolo A, et al (2011) LegalRuleML: XML-based rules and norms. In: Rule-Based Modeling and Computing on the Semantic Web (RuleML 2011 America), Lecture Notes in Computer Science, vol 7018. Springer, pp 298–312, https://doi.org/10.1007/978-3-642-24908-2_30

Prior M, Hof A, Wais N, et al (2025) Risks and limits of automatic consolidation of statutes. In: Proceedings of the Natural Legal Language Processing Workshop 2025, pp 396–407, https://doi.org/10.18653/v1/2025.nllp-1.29

Prior M, Schultz A, Grabmair M (2026) Asking for an old friend: Diagnosing and mitigating temporal failure modes in LLM-based statutory question answering. In: Proceedings of the International Conference on Artificial Intelligence and Law (ICAIL), URL https://arxiv.org/abs/2605.23497, arXiv:2605.23497

Qian P, Wang S, Chen Y, et al (2026) Relevant is not warranted: Evidence-force calibration for cited RAG. In: Findings of the Association for Computational Linguistics: EMNLP 2026, pp 33590–33603, https://doi.org/10.18653/2026.findings-emnlp.1577, URL https://aclanthology.org/2026.findings-emnlp.1577/

RFC Editor (2026) RFC index (XML). https://www.rfc-editor.org/rfc-index.xml, retrieved 29 October 2026; SHA-256 recorded in the repository

Sharma M, Tong M, Korbak T, et al (2024) Towards understanding sycophancy in language models. In: The Twelfth International Conference on Learning Representations (ICLR 2024)

Tan S, Zhuang S, Montgomery K, et al (2025) JudgeBench: A benchmark for evaluating LLM-based judges. In: International Conference on Learning Representations (ICLR), URL https://arxiv.org/abs/2410.12784

Vu T, Iyyer M, Wang X, et al (2024) FreshLLMs: Refreshing large language models with search engine augmentation. In: Findings of the Association for Computational Linguistics: ACL 2024, pp 13697–13720, https://doi.org/10.18653/v1/2024.findings-acl.813, URL https://aclanthology.org/2024.findings-acl.813/

Wu K, Wu E, Zou J (2024) ClashEval: Quantifying the tug-of-war between an LLM's internal prior and external evidence. In: Advances in Neural Information Processing Systems 37 (NeurIPS 2024), pp 33402–33422, https://doi.org/10.52202/079017-1053, URL https://arxiv.org/abs/2404.10198

Xie J, Zhang K, Chen J, et al (2024) Adaptive chameleon or stubborn sloth: Revealing the behavior of large language models in knowledge conflicts. In: International Conference on Learning Representations (ICLR), 2305.13300

Xu A, Bansal S, Ming Y, et al (2025) Does context matter? ContextualJudgeBench for evaluating LLM-based judges in contextual settings. In: Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp 9541–9564, https://doi.org/10.18653/v1/2025.acl-long.470, URL https://aclanthology.org/2025.acl-long.470/

Xu R, Qi Z, Guo Z, et al (2024) Knowledge conflicts for LLMs: A survey. In: Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, pp 8541–8565, https://doi.org/10.18653/v1/2024.emnlp-main.486, URL https://aclanthology.org/2024.emnlp-main.486/

Yang H, Song W, Kim T, et al (2026) Agents' overreliance on unreliable tools. arXiv preprint ArXiv:2609.05587

Ye J, Tawfik D, Goodell AJ, et al (2025) Scalable stewardship of an LLM-assisted clinical benchmark with physician oversight. arXiv preprint ArXiv:2512.19691

Zhang MJQ, Choi E (2021) SituatedQA: Incorporating extra-linguistic contexts into QA. In: Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, pp 7371–7387, https://doi.org/10.18653/v1/2021.emnlp-main.586, URL https://aclanthology.org/2021.emnlp-main.586/

Zheng L, Chiang WL, Sheng Y, et al (2023) Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In: Advances in Neural Information Processing Systems (Datasets and Benchmarks Track), https://doi.org/10.52202/075280-2020, 2306.05685

Zhu Z, Liao Y, Chen Z, et al (2025) EvolveBench: A comprehensive benchmark for assessing temporal awareness in LLMs on evolving knowledge. In: Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp 16173–16188, https://doi.org/10.18653/v1/2025.acl-long.788

```
You review answers that cite documents. Be precise and brief. Respond
  in strict JSON.

[QUESTION]
As of 2026-10-01, which document specifies "Mobile Networks
  Considerations for IPv6 Deployment"?
[ANSWER UNDER REVIEW]
The document that specifies this is RFC6312, "Mobile Networks
  Considerations for IPv6 Deployment" (2011-07).
[EVIDENCE]
[RFC6312] Mobile Networks Considerations for IPv6 Deployment
  (published 2011-07)
Mobile Internet access from smartphones and other mobile devices is
  accelerating the exhaustion of IPv4 addresses. IPv6 is widely seen
  as crucial for the continued operation and growth of the Internet,
  and in particular, it is critical in mobile networks. This document
  discusses the issues that arise when deploying IPv6 in mobile
  networks. Hence, this document can be a useful reference for service
  providers and network designers. This document is not an Internet
  Standards Track specification; it is published for informational
  purposes.

[RFC6342] Mobile Networks Considerations for IPv6 Deployment
  (published 2011-08)
Mobile Internet access from smartphones and other mobile devices is
  accelerating the exhaustion of IPv4 addresses. IPv6 is widely seen
  as crucial for the continued operation and growth of the Internet,
  and in particular, it is critical in mobile networks. This document
  discusses the issues that arise when deploying IPv6 in mobile
  networks. Hence, this document can be a useful reference for service
  providers and network designers. This document is not an Internet
  Standards Track specification; it is published for informational
  purposes.
[AMENDMENT RECORD LOOKUP OF THE CITED DOCUMENT]
- RFC6312: status on 2026-10-01: in_force
[TASK]
Decide whether the answer is valid as of the date in the question. For
  each problem give a finding naming the cited document and one reason
  from:
- superseded: the cited document had been replaced or obsoleted by a
  later one on the date asked about
- not_yet_published: the cited document did not yet exist on the date
  asked about
- not_applicable: the cited document does not address the question
- content_error: the answer misstates what the document says
- unsupported: the evidence does not support the answer
- other: any other problem
Reply as JSON: {"verdict": "PASS" or "FLAG", "findings": [{"doc_id":
  "...", "reason": "...", "rationale": "..."}]}
```

```
[AMENDMENT RECORD LOOKUP OF THE CITED DOCUMENT]
- RFC6312: status on 2026-10-01: in_force

[AMENDMENT RECORD LOOKUP OF THE CITED DOCUMENT]
- RFC6312: status on 2026-10-01: no_replacement_recorded

[UNVERIFIED NOTE FROM AN AUTOMATED TAGGER ABOUT THE CITED DOCUMENT]
- RFC6312: status on 2026-10-01: in_force

[AMENDMENT RECORD LOOKUP OF THE CITED DOCUMENT (this record is
  incomplete: it omits some replacements, so a document it lists as in
  force may have been replaced)]
- RFC6312: status on 2026-10-01: in_force
```

Fig. C1 Top: system text and prompt for one gap fault under the authoritative line. Bottom: the record block of each damaged context, in table order.




Fig. D2 Case study: discrimination (right-reason catch minus false alarms on matched correct answers) as the record degrades, for the judge given the status line (R4), a lookup in the same record (R5), and the judge with no record (R2). Clause-averaged, damage seeds averaged within clause, 95% bootstrap intervals over 14 clauses.

Supplementary material: the case study in full

This supplement holds the full report of the descriptive case study on Indian rooftop-solar regulation that the paper summarises in its final appendix: the reference data and their human audit, the conditions, damage and scoring, the planned analyses and their results, the readings fixed in advance, the prompts, the per-clause results, the annotation agreement, the deviations from the analysis plan and the data statement. The case study's answer key failed the quality checks planned for it, so nothing here supports a finding of the main paper; it is reported for transparency, with its planned analyses and readings kept as they were fixed. The sections are carried over from the study's own report, written before the RFC study, and use its terms (reviewer for judge, registry for record, clause for document).

S1 Case study: reference data, conditions and planned analyses

S1.1 Reference data and its audit

Corpus.

The corpus holds 111 authentic regulatory instruments on rooftop solar from 8 jurisdictions in India: central schemes and the regulations and orders of state commissions and distribution companies. Superseded instruments stay in the corpus, because their continued availability is the hazard studied. Every file is hashed and listed with its issuer, dates and source URL.

Amendment registry.

The reviewer's amendment record is a registry of 186 clause-level links, each from an old clause to the clause that changes it, with a relation (supersedes, partially supersedes, amends), an effective date and a quote from the amending instrument. It was extracted from the documents by an AI assistant, without access to the gold graph used for scoring. It is the source of the R3 quotes, the R4 and R4n status lines and the R5 lookup. The registry as corrected by adjudication (below) is the one every run uses.

Cases and reference answers.

A case is a synthetic application: an electricity bill, an installer proposal and a distribution-company portal record, with a case date and a jurisdiction. Cases were generated backward from rule functions whose parameters are quoted from the clause text, so no label was typed by hand. Each case records the rule function that labelled it; most cases list a single applicable rule. The applications contain no personal data. The candidate test set had 60 cases on the replaced clauses with enough fixed answers per condition; the dev split shares no replaced clause with it and was used only for engineering and the pilot.

S1.1.1 Human audit of the reference data

The registry, the answer key and the case labels were produced with AI help, so two authors checked them blind before the test set was sealed, splitting the work and labelling a seeded shared subset (20 cases, 15 links) in common. They labelled each case's decision, blocking stage and deciding clauses from the case file and the source documents; each checked link's relation, effective date and wording; and a sample of 40 matched correct answers. A third author, who led the pipeline that produced the first-pass labels, adjudicated every disagreement from the annotators' sheets and the source documents, without the answer keys. The planned procedure had the annotators meet first; to save time the meeting was dropped and all disagreements went to the adjudicator (Appendix S6). The annotators are not legal professionals.

On the shared cases the annotators agreed on the decision in 80% of cases (kappa 0.60) and on the blocking stage in 85% (kappa 0.79), but on the exact set of deciding clauses in only 15% (kappa 0.14). On shared links they agreed on the relation in 87% (kappa 0.70). Part of the clause-level disagreement is notation (`cl-4.2` against `cl-4(2)`); part is that several clause sets support the same outcome.

The answer key.

Against the adjudicated labels, the AI-built key reached a different outcome on 18 of the 60 cases: 13 on the decision and 5 on the blocking stage of a rejection. In the disagreements we inspected, the readers based their decision on a second clause that the case's rule function does not evaluate, often in a newer instrument. In one such case, the key approves an application because it passes the transformer-capacity rule its rule function checks; the readers reject it under an eligibility clause of a later regulation. These

Condition	Faults	Matched correct answers	Clauses
S-both (old and current clause shown)	42	42	14
S-swap (old clause in place of current)	38	7	13
C (clean correct answers)	–	42	–

Table S1 Fixed answers per condition in the sealed test set. Clauses: distinct replaced clauses. Jurisdictions of the replaced clauses: DL 4, GJ 4, central 1, KA 2, TN 1, UP 2.

cases are wrong at the base, and they are dropped; a case is never relabelled, because its faults were planted on the key's answer. On 36 of the remaining cases, the outcome agrees and only the deciding clauses differ. Those cases are kept and listed, because a planted fault and its catch are defined on the replaced clause alone. Applied as originally planned, which dropped clause-only disputes too, the rules would have kept 6 cases.

The correct answers.

Of the 40 matched correct answers checked, 23 (57%) were judged correct. Most of the rest were judged incomplete or citing a wrong clause, the same single-rule cause: they cite the clause the rule function evaluated and omit another that also decides the case. A reviewer that flags such an answer may be right, so these items bias false alarms upwards. The planned gate (95% correct) would have stopped the seal; it was replaced by reporting, and by sensitivity set S1, which removes every case whose checked correct answer was judged anything but correct (§S1.3).

The registry.

The 52 checked links are the 18 that test items rely on and a seeded 20% random sample of 34 of the other links. In the random sample, 25 were confirmed, 4 had a different relation, and 5 were judged to be no change at all ([6, 30]%, Wilson 95% interval). Among the test-item links, 1 was no change and 3 had a different relation. Rejected links were removed and corrected dates applied before the run. These figures describe links the registry asserts. Nothing in the audit looked for links the registry misses, so we do not estimate that rate. The full table, with both annotators' raw answers beside the adjudicated one, is released (`40_data/link_audit_v1`); links outside the check keep the extractor's provisional relation and are not used as gold.

The scorer.

One annotator labelled 50 dev replies by hand under the written scoring rule. The automatic scorer agreed on 35 of 50 (70%), below the planned 95% gate. In each of the 15 disagreements, the reply's own clause ids and reason codes give the scorer's label under the written rule, so the scorer was not changed. Most disagreements lie on the boundary between a wrong clause and a wrong reason (10), or between a right catch and a wrong reason (3). We read this as evidence that the right-reason rule is hard to apply by hand, not as a defect of the scorer, and report every result under the two looser rules as well (E5).

The sealed test set.

The sealed set has 42 cases on 14 distinct replaced clauses from 6 jurisdictions (Table S1). 3 clauses in one state were replaced by a single amending instrument and are not independent. The registry links 11 of the 14 replaced clauses; on the others the intact registry itself reads `in_force`, so they are naturally missing links.

S1.2 Conditions, damage and scoring

S1.2.1 Fixed answers

We measure review on fixed answers, so the result does not depend on what a generator happens to write. For each case and condition we build a matched pair. The *fault* cites the replaced clause in place of its successor. When the old clause changes the approve-or-reject outcome, the fault also carries the decision that clause implies; otherwise it has the right decision on an invalid basis. The *matched correct answer* (control) has the key's decision and cites only clauses its own evidence shows. Both come from one neutral template: the decision, the cited clause identifiers, one sentence that quotes the basis clause, and the blocking stage if any. A pair therefore differs only in its basis and, where the outcome changes,

Condition	Reviewer sees	Reviewer does not see	Compared with; confound	Role
R0	old clause (S-swap), source metadata removed	current clause, dates, issuer	–	ladder
R1	old clause with issuer, dates, title	current clause	R0: metadata only	ladder
R2	old and current clause (S-both)	any amendment record	R1: adds the current clause	ladder; Q2 baseline
R3	R2 + amending instrument's words	status, dates, target	R2	ladder
R4	R2 + registry status line	–	intact: told the answer for linked clauses	reference
R4′	R1 + registry status line	current clause	R1: status line without the text	ladder
R4-damage	R2 + status line of a damaged registry	which links are wrong	R5-damage (Q1); R2 (Q2)	primary
R4n, R4n-damage	as R4, "no amendment recorded" for unlinked clauses	–	R4 on the same items and seeds	primary
R5, R5-damage	no LLM: "not in force" on every cited clause the registry marks superseded	–	catches exactly the linked clauses, by construction	reference

Table S2 Conditions. "Reference" rows are not findings: R5 recovers the registry's own links, and R4 at the intact registry is told, for every linked clause, that it is not in force. Faults were planted on replaced clauses of the gold graph; the registry links most but not all of them (§S1.1). The E2 variants of R0 to R2 add a "can't confirm" reason.

in the decision. Condition C adds one clean correct answer per case. The reviewer sees the case, the evidence and one answer, and is never told which answers are faults.

The evidence differs by condition. In *S-both* the old clause and its successor are both shown; in *S-swap* the old clause replaces the current one, so the reviewer sees only outdated text.

S1.2.2 Conditions

Every language-model condition uses the same validity prompt, which asks whether each cited clause is in force on the application date, issued for the case's jurisdiction and applicable to its facts. Conditions differ only in what the prompt contains (Table S2; prompts in Appendix S3). R3, R4 and R4n are built on R2: the R3 block holds the amending instrument's verbatim substitution text for each cited clause the registry links, with no status, date or target; the R4 block holds one line per cited clause giving the registry's entries, jurisdiction and status at the case date. R4′ gives the same line at R1, without the current clause; it shows what the status line does when the text cannot confirm it. R5 uses no language model: it raises a "not in force" finding on a cited clause exactly when the registry marks that clause superseded or partially superseded at the case date (an "amends" link alone does not), and it raises no other kind of finding. Its catches are therefore the registry's own links, and its false alarms are the registry's own wrong links.

The no-record arm.

In the registry, a clause with no outgoing link has status `in_force`. The registry cannot distinguish a clause that was never amended from one whose amendment it failed to record, so this value states more than the record holds. R4n replaces the status value `in_force` by `no_amendment_recorded` and changes nothing else: the prompt sent at R4n equals the R4 prompt with that one substitution, which a unit test checks on an intact and a damaged registry. Superseded, partially superseded and not-yet-in-force values are unchanged. The substitution applies to every clause the registry does not link, including current clauses on correct answers, so R4n can change false alarms as well as catches.

Can't confirm.

For E2, variants of R0, R1 and R2 add the reason `currency_unconfirmed`: the evidence shown does not establish whether the clause is in force at the case date. Such a finding is neither a catch nor a false alarm.

S1.2.3 Damaged registries

To vary the record's reliability in a controlled way we damage the registry in three ways: 25% or 50% of its links dropped, or 10% spurious links added. Each damage has 5 seeds. A drop permutes all of the registry's links with the seed and removes the first quarter or half, so at one seed the 50% set contains the 25% set. A spurious link is added from a seeded choice of dated clauses that have no outgoing link, to another clause of the same jurisdiction, as a "superseded by" link effective from the clause's own date; the number added is 10% of the registry's links. A damaged registry is used in each way the intact one is: as the lookup (R5-damage) and as the status line (R4-damage, R4n-damage). A dropped link makes the status line report a replaced clause as `in_force` (R4) or as having no recorded amendment (R4n), while the evidence still shows both versions; a spurious link makes it report a current clause as replaced. In both cases the text in view contradicts the line. The damage is random and synthetic; it is not an estimate of how real registries fail.

S1.2.4 Scoring

The reviewer returns a verdict and findings; each finding names a clause and gives one reason from a closed list (not in force, wrong jurisdiction, not applicable, missing rule, content or arithmetic, other). The list is the same in every prompt and names no clause.

Catch, false alarm, confusion counts.

A fault is caught when a finding names the replaced clause with the reason "not in force"; an identifier of a retrieval chunk counts as the clauses it contains. On a correct answer, any finding is a false alarm. Each condition therefore yields four counts: caught and missed faults, flagged and passed correct answers. A finding on the right clause for another reason is not a catch; we count it as a *misnamed* alarm (E4).

Discrimination.

For one replaced clause, discrimination is its catch rate on faults minus the false-alarm rate on their matched correct answers; it is averaged over clauses, and for a damaged registry first over seeds within a clause. It is the headline measure, because a reviewer that flags every answer catches every fault and is of no use.

Deference and NoRec.

Both use the same items: every (S-both fault, drop rate, seed) where the intact registry catches the fault and that damaged registry does not. Deference is, item by item, the reviewer's catch with no registry (R2) minus its catch with the damaged status line (R4-damage). NoRec is the item's catch at R4n-damage minus its catch at R4-damage on the same seed. Both are averaged within clause, then over clauses.

Three scoring rules (E5).

Under *any finding*, a fault is caught if the reply has any finding; under *clause named*, if a finding names the replaced clause for any reason; the right-reason rule above is the strictest. On correct answers we report any finding (our false-alarm rule) and a finding with a validity reason only.

Post hoc measures (added after the results were seen, not pre-specified).

Because the lookup can only raise "not in force" while the reviewer can raise any reason, we also report Q1 with false alarms counted only when the finding gives a validity reason (not in force, wrong jurisdiction, not applicable), the reason codes behind the false alarms, the catches the reviewer gains and loses against the lookup on the same item and seed, and Q1 with the amending instrument rather than the clause as the unit (the 14 clauses come from fewer amending instruments). These are descriptive and outside the family.

Invalid replies.

A reply that is not valid JSON, is cut off at the output cap after one retry, or has no verdict is invalid. It counts as a miss on a fault and as a false alarm on a correct answer, so an invalid reply never improves a condition.

S1.3 Setup and planned analyses

Models.

The panel has 4 open models: `llama3.1:8b` (weak), `qwen2.5:7b`, and the 2 capable models `qwen2.5:14b` and `gemma-4-26b-a4b-it`. The first three run through Ollama with 4-bit quantised weights fixed in advance by digest (`46e0c10c039e`, `845dbda0ea48` and `7cdf5a0187d5`; full digests in the analysis plan), checked on every machine: `qwen2.5:14b` on a cloud notebook with two NVIDIA T4 GPUs, the other two on an Apple-silicon laptop. Gemma, open-weight, runs through a hosted API, with the version recorded per call. A closed hosted model, `gemini-3.5-flash-lite`, is a secondary model on R0, R2 and R4 only. Each model ran on one machine. Models added after the plan was fixed are exploratory and reported separately (§S1.4.5).

Settings.

Decoding is greedy (temperature 0), with run seed 42 and an output cap of 1024 tokens. Every reply is cached, and every block records the model digest, the prompt hash per item, the code hash and the hash of the sealed test file. Every model sees the same items.

Run order and cutoff.

Blocks run in a fixed priority order: for the capable models R2, R4, R4n, R5 and R5-damage, then R4-damage and R4n-damage seed by seed, so that a cut run still leaves the two arms paired on the same seeds; then the secondary conditions; then the other models. The analysis cutoff was fixed as a wall-clock time before any test result was read. A block not finished by then is reported as not run, and a contrast whose blocks are incomplete is reported as not run rather than estimated from part of a block (Appendix S6 lists what did not run).

Unit of inference and tests.

The unit of inference is the distinct replaced clause. Rates are averaged within each clause and then over clauses, with pooled counts beside each rate; false alarms on condition C are averaged by rule group, because C plants nothing. A contrast is the mean per-clause difference, paired by clause within one model, tested with a two-sided sign-flip test over clauses (exact for few clauses, otherwise 10,000 random sign vectors with a fixed seed). Intervals are 95% bootstrap intervals over clauses, printed only with at least 10 clauses. A cell with fewer than 5 items or 3 clauses is printed as counts.

Primary family.

10 tests, Holm-corrected at $\alpha = 0.05$: for each capable model, R4 minus R5 discrimination at the intact, 50%-drop and 10%-spurious registries (Q1), deference (Q2) and NoRec. A contrast on fewer than 10 clauses enters the family with $p = 1$. The 25% drop is reported beside Q1, uncorrected. Everything else is secondary and uncorrected or descriptive: the ladder contrasts (E1), can't confirm (E2), spurious-link false alarms (E3′), misnamed alarms (E4), the scoring rules (E5), the false-alarm cost of R4n, and descriptive splits by amendment wording (explicit or implicit), by whether the fault changes the outcome, and by cost per call (tokens and seconds).

Sensitivity sets.

Every primary result is also computed on two subsets, with the same tests and outside the family. **S1** removes every case whose checked correct answer was judged anything but correct. **S2** removes every case the originally planned rule would have dropped, that is, every case whose deciding clauses differ from the key; it has fewer than 10 clauses and is descriptive. Only a sample of correct answers was checked, so S1 removes the correct answers known to be flawed, not every flawed one; a result that keeps its sign under S1 does not depend on those.

Damage seeds.

The capable models run R4-damage and R4n-damage on all 5 seeds; the other models run seed 0. R5-damage is deterministic and runs every seed.

Analysis plan.

The design, outcomes, analysis and the sentence reporting each outcome were written into a dated, version-controlled analysis plan before any model saw a test item, and the test set was sealed with a

Table S3 Main results on S-both faults and their matched correct answers. TP: right-reason catches of the planted superseded clause; FN: faults not caught; FP: matched correct answers with any finding; TN: matched correct answers passed. Recall, specificity, precision and balanced accuracy (%) pool items, which share clauses, so they are descriptive. FA_C: clean correct answers flagged. Disc.: discrimination (catch minus matched false alarm), clause-averaged, with a 95% bootstrap interval over clauses (points). R5 recovers the registry's own links by construction and R4 (intact) is given the answer: reference rows.

Model	Arm	Reviewer sees	TP	FN	FP	TN	Rec.	Spec.	Prec.	Bal.	FA_C	Disc. [95% CI]	Cl.
Qwen 14B	R2	both versions	13	29	18	24	31	57	42	44	12/42	−7 [−38, +20]	14
Qwen 14B	R4	status line	32	10	10	32	76	76	76	76	11/42	+55 [+26, +79]	14
Qwen 14B	R4n	no-record wording	31	11	13	29	74	69	70	71	12/42	+47 [+17, +73]	14
Lookup	R5	lookup (ref.)	31	11	5	37	74	88	86	81	5/42	+67 [+43, +88]	14
Qwen 14B	R4-drop50	status, drop 50%	88	122	54	156	42	74	62	58	55/210	+21 [−6, +48]	14
Qwen 14B	R4n-drop50	no-record, drop 50%	95	115	58	152	45	72	62	59	60/210	+23 [−6, +54]	14
Lookup	R5-drop50	lookup, drop 50%	88	122	8	202	42	96	92	69	8/210	+42 [+24, +60]	14
Qwen 14B	R4-spurious10	status, spur. 10%	160	50	55	155	76	74	74	75	61/210	+53 [+25, +76]	14
Lookup	R5-spurious10	lookup, spur. 10%	155	55	34	176	74	84	82	79	34/210	+62 [+37, +84]	14
Gemma 4 26B	R2	both versions	9	33	20	22	21	52	31	37	17/42	−20 [−46, +4]	14
Gemma 4 26B	R4	status line	25	17	20	22	60	52	56	56	18/42	+21 [−18, +57]	14
Gemma 4 26B	R4n	no-record wording	26	16	21	21	62	50	55	56	15/42	+18 [−20, +54]	14
Gemma 4 26B	R4-drop50	status, drop 50%	89	121	100	110	42	52	47	47	90/210	+4 [−30, +35]	14
Gemma 4 26B	R4n-drop50	no-record, drop 50%	96	114	105	105	46	50	48	48	72/210	+2 [−31, +31]	14
Gemma 4 26B	R4-spurious10	status, spur. 10%	125	85	103	107	60	51	55	55	94/210	+20 [−20, +56]	14

	qwen2.5:14b			gemma-4-26b		
Registry	R4	R5	R4−R5	R4	R5	R4−R5
Intact	+55	+67	−11	+21	+67	−45
Drop 25%	+39	+51	−12	+14	+51	−37
Drop 50%	+21	+42	−21	+4	+42	−38
Spurious 10%	+53	+62	−10	+20	+62	−42

Table S4 Discrimination in points of the LLM reviewer with the status line (R4) and of the registry lookup alone (R5), by registry state, over 14 clauses. The difference is the Q1 contrast; intervals and Holm p are in Table S5. The 25% row is outside the primary family.

fingerprint recorded in the repository. The plan was not filed with a public registry; its history is in the released version control. Two dated amendments were made before the seal. The first, written after the dev pilot, made the damaged-registry comparisons primary. The second, written after the human audit and before any model saw a test item, changed which cases annotation keeps, replaced the correct-answer and scorer gates by reporting, and added R4n, NoRec, S1 and S2 (Appendix S6).

S1.4 Planned results

Seven reviewers ran on the same items: the five planned models, and two added after the analysis plan was fixed, `qwen2.5:32b` (damage seeds 0–2) and Claude Opus 4.5 through a hosted proxy (damage seed 0; temperature and seed set by the proxy). Every planned block finished for the planned models. Table S3 gives the confusion counts of every main arm on the same 42 S-both faults and 42 matched correct answers. A repeat of `qwen2.5:14b`'s R2, R4 and R4n blocks on the same machine with an empty cache returned identical findings on 378 of 378 items; we did not test whether replies are identical across machines or for the hosted models. Invalid replies were rare (Gemma: 5/630 at R4 with 50% of links dropped; `qwen2.5:14b`: none).

S1.4.1 Q1: does the reviewer add anything over the record?

Under the planned rule, the reviewer given the record had a lower point estimate of discrimination than a lookup in the same record at every registry state, for both capable models (Table S4). For Gemma the difference was −45 points with the registry intact (CI [−69, −24], Holm $p = 0.043$) and −42 with spurious links (CI [−66, −22], Holm $p = 0.043$), both significant after Holm, and −38 with half the links dropped (Holm $p = 0.178$). For `qwen2.5:14b` it was −11 (Holm $p = 1.000$), −21 (CI [−38, −6], Holm $p = 0.206$) and −10 (Holm $p = 1.000$), none significant. The reading fixed in advance for both models is that the reviewer did not discriminate better than a lookup in the registry it was given, even when the registry was damaged; the reading fixed in advance for Gemma's intact result is that adding the reviewer to a correct registry made review worse than the registry alone.

That last reading should be taken narrowly, for three reasons we found after the run (post hoc, §S1.2.4). First, the gap is made of findings the lookup cannot raise. The planned false-alarm rule counts any finding on a correct answer, but the lookup only ever says "not in force". Most of Gemma's findings on matched correct answers gave "content or arithmetic" or "missing rule" as the reason, not a validity reason. Counting only validity-reason findings as false alarms, the difference is −6 points for Gemma

Table S5 Primary contrasts (capable models; Holm over the family of ten). Per-clause differences in points, mean over clauses, 95% bootstrap interval over clauses, two-sided sign-flip test. S1: without the cases whose checked correct answer was judged flawed; S2: under the original strict annotation rule (descriptive when it leaves fewer than ten clauses).

Model	Contrast	Clauses	Diff.	95% CI	p (Holm)	S1	S2
Gemma 4 26B	Q1, intact: R4 − R5 discrimination	14	−45	[−69, −24]	0.043	−47	−50
Gemma 4 26B	Q1, 50% dropped	14	−38	[−65, −11]	0.178	−38	−50
Gemma 4 26B	Q1, 10% spurious	14	−42	[−66, −22]	0.043	−45	−45
Gemma 4 26B	Q2: R2 − R4-damage catch, dropped links	9	+1	–	1.000	+4	–
Gemma 4 26B	R4n − R4 catch, dropped links	9	+9	–	1.000	+20	–
Qwen 14B	Q1, intact: R4 − R5 discrimination	14	−11	[−33, +9]	1.000	−12	+17
Qwen 14B	Q1, 50% dropped	14	−21	[−38, −6]	0.206	−17	+2
Qwen 14B	Q1, 10% spurious	14	−10	[−30, +10]	1.000	−11	+17
Qwen 14B	Q2: R2 − R4-damage catch, dropped links	9	+34	–	1.000	+33	–
Qwen 14B	R4n − R4 catch, dropped links	9	+9	–	1.000	+9	–

with the registry intact (CI [−20, +8]) and +1 with half the links dropped; for `qwen2.5:14b` it is −3 and −13 (CI [−28, 0]). On the question the lookup answers, whether a cited clause is in force, the reviewer did about as well as the lookup. Its other findings may be right: the audit found that many correct answers omit a clause that also decides the case (§S1.1.1), which this design cannot score. Second, the 14 clauses come from 8 amending instruments; with the instrument as the unit, Gemma's intact and spurious differences have uncorrected sign-flip $p = 0.031$ and 0.031, on fewer units than the planned minimum of 10. Third, both lose significance under S1 (§S1.4.6). We therefore report Gemma's Q1 result as planned, but do not read it as evidence that a reviewer degrades a correct record.

The expectation fixed in advance for Q1, that the gap would narrow or reverse as links were dropped because the reviewer can still read both versions, was not met. Table S3 shows why. With 50% of links dropped, the reviewer's right-reason catches on S-both faults nearly equal the lookup's for both models. Item by item and seed by seed, Gemma caught 25 faults the damaged lookup missed and missed 24 it caught; `qwen2.5:14b` gained 13 and lost 13. The reviewer recovered some dropped links from the text, and lost about as many catches elsewhere, so on net it did not repair the record. Its false alarms on matched correct answers stayed well above the lookup's.

Two properties of the design bound this result. The lookup's catches are the registry's own links: it misses the faults on clauses the registry does not link and flags whatever a wrong link marks, so its discrimination is a property of the record, not a benchmark of reasoning (§S1.2). And the result holds for these models, these 14 clauses and fixed answers with a single planted fault.

S1.4.2 Q2: does the reviewer follow a wrong "in force" line?

The deference contrast could be computed on 9 clauses: those whose planted link the intact registry catches and some drop seed removes. That is below our planned minimum of 10, so by rule it entered the family with $p = 1$ and supports no confirmatory claim; we report it descriptively and, as planned, as no evidence of deference rather than evidence of its absence. On those faults `qwen2.5:14b` caught 41% with no registry (R2) and 7% when the damaged status line said the replaced clause was in force (deference +34 points). Gemma caught 32% and 31% (deference +1). The direction for `qwen2.5:14b` is the one the deference account predicts and matches the effect of false assurances that Liu and Gao (2026) report for code auditors; Gemma's catches on these items hardly changed.

The no-record wording (R4n).

On the same faults, stating that no amendment is recorded instead of that the clause is in force raised catches from 7% to 16% for `qwen2.5:14b` and from 31% to 41% for Gemma (NoRec +9 and +9 points, 9 clauses, below the minimum, no confirmatory claim). False alarms on matched correct answers rose a little: with half the links dropped, from 25% to 26% for `qwen2.5:14b` and from 43% to 48% for Gemma; with the registry intact, from 23% to 30% and from 43% to 48%. As planned, we report no evidence that the wording matters, not evidence that it does not; the point estimates are small and positive, recover a fraction of what the dropped links cost, and come with a small rise in false alarms. The set is small by construction: deference and NoRec need a fault the intact registry catches, and the registry links only 11 of the 14 clauses.

		qwen2.5:14b			gemma-4-26b		
	Rule	R0	R2	R4	R0	R2	R4
Catch	any finding	40%	62%	79%	50%	76%	79%
	clause named	40%	62%	79%	48%	76%	79%
	right reason	8%	33%	79%	0%	24%	64%
False alarm	any finding	40%	40%	23%	40%	45%	43%
	validity reason	40%	23%	15%	20%	0%	4%

Table S6 The same replies under three scoring rules, on faults (catch) and matched correct answers (false alarm). Clause-averaged. The right-reason row is the catch reported everywhere else. At R0 the reviewer sees only the old clause, so a right-reason catch is not expected there.

	llama3.1:8b			qwen2.5:7b			qwen2.5:14b			gemma-4-26b		
Rung	Catch	FA-m	FA-C	Catch	FA-m	FA-C	Catch	FA-m	FA-C	Catch	FA-m	FA-C
R0	0%	80%	51%	4%	80%	20%	8%	40%	26%	0%	40%	34%
R1	0%	80%	49%	4%	60%	12%	8%	50%	27%	0%	20%	36%
R2	0%	49%	49%	18%	18%	12%	33%	40%	27%	24%	45%	36%
R3	0%	49%	49%	18%	20%	19%	30%	36%	27%	33%	45%	36%
R4	11%	49%	51%	7%	7%	5%	79%	23%	26%	64%	43%	39%
R4′	6%	80%	51%	6%	40%	5%	81%	0%	26%	62%	40%	39%
R5	79%	13%	12%	79%	13%	12%	79%	13%	12%	79%	13%	12%

Table S7 Right-reason catch and false alarms by rung (clause-averaged; C false alarms averaged by rule group). FA-m: matched correct answers of the same blocks (S-swap pairs for R0, R1 and R4′, S-both otherwise; R5 pools both). FA-C: clean correct answers. Table S3 gives S-both counts only, so its false alarms can differ from FA-m here.

Spurious links (E3′).

On correct answers citing a clause that a spurious link marks as replaced (9 items on 3 clauses), qwen2.5:14b raised a false alarm on 9/9 with the status line against 6/9 with no registry; Gemma on 8/9 against 4/9. A wrong link marking a current clause as replaced was followed into a false alarm more often than not. The counts are small and no test was planned. Unlike the code auditors of Liu and Gao (2026), whose accuracy was never significantly lowered when a tool raised false alarms, these reviewers followed a wrong record in both directions; on three clauses this is a hypothesis for confirmatory work, not a finding.

S1.4.3 How much the scoring rule matters

The scoring rule changed the apparent skill of the same replies by tens of points (Table S6). With both versions in view (R2), any-finding scoring credited qwen2.5:14b with 62% catches and Gemma with 76%, against 33% and 24% when the finding had to name the replaced clause for the reason that it is no longer in force. Naming the clause hardly mattered: almost every finding on a fault named it, and the gap is the reason. Under any of the rules the reviewers also flagged a large share of matched correct answers, so a catch rate reported alone would overstate them. The reading fixed in advance applies: scoring by flags alone would have credited these reviewers with many catches made for the wrong reason.

The right-reason rule is itself hard to apply. In the human check of the scorer on 50 dev replies the annotator and the code agreed on 35 of 50 (70%), below the pre-specified 95% gate; 10 of the 15 disagreements lie on the boundary between a wrong clause and a wrong reason. Amendment 2 kept the scorer and reports the failed gate (§S1.1.1); the any-finding and clause-named rows of Table S6 show every result under the looser rules, and the post hoc Q1 analysis in §S1.4.1 applies the validity-reason rule to false alarms.

S1.4.4 The reference ladder (E1) and the other models

The ladder is the reference that places Q1 and Q2. For both capable models the status line lifted right-reason catches over seeing both versions: R4−R2 was +45 points for qwen2.5:14b (CI [+24, +65]) and +40 for Gemma (CI [+20, +58]), while R2−R0 was +28 and +26 (on the 13 clauses where both rungs ran, so they differ from the clause averages of Table S7), not significant by the planned sign-flip test (Gemma's bootstrap interval, [+8, +48], excludes zero; R0 runs on S-swap items, where a right-reason catch is near zero by design). In the words fixed in advance, seeing both versions is not enough, and R4 lifts these capable models. The amending instrument's quote (R3) added little over R2 (−4 and +9 points). Without a record the reviewers did not discriminate at all: R2 discrimination was −7 points for qwen2.5:14b and −20 for Gemma, because they flagged matched correct answers as often as, or more often than, they caught faults for the right reason.




Fig. S1 Right-reason catch by rung, one line per model, clause-averaged, with 95% bootstrap intervals over clauses. R5 is the registry lookup and is the same for every model.

The weak model gained little: `llama3.1:8b` caught 0% at R2 and 11% at R4 (+11 points, interval [+0, +29]). That is just outside the 10-point margin of the reading fixed in advance for this case (reading 12), so that reading does not apply; we report the small gain as a limit of the claim. `gemini-3.5-flash-lite`, run at R0, R2 and R4 only, caught 46% at R2 and 82% at R4, with false alarms on matched correct answers of 44% at R4; seeing both versions did not close the gap for it either. Given the "can't confirm" option (E2), neither capable model used it on a fault at R2 (0/42 and 0/42): the option was available and unused. Of the R2 findings that flagged the replaced clause, 13/26 (`qwen2.5:14b`) and 23/32 (Gemma) never gave "not in force" as the reason (E4).

S1.4.5 The added models

The two models added after the analysis plan was fixed are outside every planned test; Table S8 and the descriptive-results table of the paper's case-study appendix report them on the main arms. Claude Opus 4.5 is the clearest case that capability changes the picture: it is the only reviewer whose catches survive the absence of a record, and the only one that repaired a damaged record. A model from the same developer also helped build this benchmark (see the paper's statement on the use of AI assistants); its items were not tuned on any model's replies, but readers should weigh that relation. It ran one damage seed, through a proxy that sets temperature and seed itself, so its numbers carry more uncertainty than the planned models'. Within one model family, scale did not buy a better reviewer. `qwen2.5:32b`, run with the pre-specified prompts on the same items, flagged matched correct answers more often than `qwen2.5:14b` at every arm, and about twice as often once given the record, so its discrimination was lower, and its gap to the lookup wider, with the record intact and with half the links dropped. Without a record it named the replaced clause on most faults but rarely for the reason that it is no longer in force. On the dropped-link faults its catches fell to none under the damaged status line, and the no-record wording did not restore them. One model, one family and the same 14 clauses cannot separate size from other differences between checkpoints; we report it because a reader will ask whether a larger model removes the pattern, and here it did not.

S1.4.6 Sensitivity to the annotation audit

Removing the cases whose checked correct answer annotators judged flawed (S1; only a sample was checked) left the sign of every primary contrast unchanged (Table S5). Gemma's two significant Q1 differences became −47 and −45 points with Holm $p = 0.083$ and 0.083, no longer below 0.05 on the smaller set. Under the reading fixed in advance, the Q1 result does not depend on the correct answers known to be flawed in direction; its significance for Gemma does depend on keeping them. Under the

Table S8 Size comparison within one family. Rows marked "no" were added after the analysis plan was fixed and are exploratory; the planned sizes are shown beside them. The 32B model ran damage seeds 0–2 (the planned capable models ran 0–4). S-both right-reason catches, false alarms on matched correct answers (any finding) and any-finding catches, pooled k/n; discrimination clause-averaged (points), and the Q1 difference with a 95% bootstrap interval over clauses. No test.

Model	Planned	Arm	Catch	FA	Any	Disc. / diff.
Qwen 7B	yes	R2	5/42	7/42	14/42	−1
Qwen 7B	yes	R4	2/42	2/42	3/42	+0
Qwen 7B	yes	R4-drop50	2/42	2/42	3/42	+0
Qwen 7B	yes	R4−R5, intact				−67 [−88, −43]
Qwen 7B	yes	R4−R5, drop50				−42 [−60, −24]
Qwen 14B	yes	R2	13/42	18/42	26/42	−7
Qwen 14B	yes	R4	32/42	10/42	32/42	+55
Qwen 14B	yes	R4n	31/42	13/42	32/42	+47
Qwen 14B	yes	R4-drop50	88/210	54/210	126/210	+21
Qwen 14B	yes	R4−R5, intact				−11 [−33, +9]
Qwen 14B	yes	R4−R5, drop50				−21 [−38, −6]
Qwen 32B	no	R2	4/42	25/42	35/42	−48
Qwen 32B	no	R4	29/42	23/42	38/42	+18
Qwen 32B	no	R4n	26/42	24/42	38/42	+11
Qwen 32B	no	R4-drop50	46/126	69/126	104/126	−15
Qwen 32B	no	R4−R5, intact				−48 [−68, −24]
Qwen 32B	no	R4−R5, drop50				−57 [−76, −37]
Claude Opus 4.5	no	R2	34/42	40/42	42/42	−11
Claude Opus 4.5	no	R4	35/42	37/42	42/42	−3
Claude Opus 4.5	no	R4n	35/42	42/42	42/42	−14
Claude Opus 4.5	no	R4-drop50	29/42	37/42	42/42	−21
Claude Opus 4.5	no	R4−R5, intact				−70 [−89, −48]
Claude Opus 4.5	no	R4−R5, drop50				−63 [−85, −43]

original strict rule (S2) only 6 cases remain, on fewer than 10 clauses; that is descriptive only, and there `qwen2.5:14b`'s Q1 difference turns positive (+17 points intact), Gemma's stays negative (−50).

S2 Case study: readings fixed in advance

Each rule was planned with the sentence we report when it applies; where a reading names a place of report ("the abstract"), it refers to the case study's own report. Readings 1–5 are from amendment 1, readings 6–8 from amendment 2, and the rest from the original analysis plan, where they now apply to the reference ladder.

1. R4−R5 not positive after Holm at any registry state, for a capable model: "For this model, the reviewer did not discriminate better than a lookup in the registry it was given, even when the registry was damaged."
2. R4−R5 positive after Holm at a damaged state but not with the registry intact: "The reviewer added value over the registry only once the registry was damaged, from [the first such state]."
3. R4−R5 negative after Holm with the registry intact: "Adding the reviewer to a correct registry made review worse than the registry alone."
4. Deference positive after Holm: "A wrong 'in force' line removed catches this reviewer makes without any registry: it followed the registry over the text." Not significant: "We found no evidence of deference"; never "the reviewer does not defer".
5. Any-finding catch above right-reason catch by more than 10 points for a capable model at R0 to R2: "Scoring by flags alone would have credited this reviewer with [the gap] points of catches it made for the wrong reason."
6. NoRec positive after Holm and the false-alarm cost small: "Telling the reviewer that no amendment is recorded, instead of that the clause is in force, recovers catches the damaged record loses." Not significant: "We found no evidence that the wording matters"; never that it does not.
7. NoRec positive but the false-alarm cost larger than the gain: "The wording trades catches for false alarms" (both numbers reported).
8. A primary result that keeps its sign under S1: "It does not depend on the flawed correct answers." One that changes sign: "It depends on them."
9. Fewer than 10 distinct replaced clauses in the sealed test: no primary claim. "With this many distinct clauses the test cannot support a population claim; we report per-clause results descriptively."

Table S9 Right-reason catches per replaced clause (k/n faults; R5 also counts S-swap faults), capable models. The clause is the unit of every interval and test in the paper.

Replaced clause	Qwen 14B				Gemma 4 26B			
	R2	R4	R4n	R5	R2	R4	R4n	R5
DL-C3-004#cl-3.8	2/4	4/4	4/4	8/8	0/4	4/4	4/4	8/8
DL-C3-004#cl-9.2b	2/2	2/2	2/2	4/4	2/2	2/2	2/2	4/4
DL-C3-006#cl-3.2	2/3	3/3	3/3	6/6	3/3	3/3	3/3	6/6
DL-C3-009#cl-3.6	2/4	4/4	4/4	8/8	1/4	4/4	4/4	8/8
GJ-C3-001#cl-13.5-check	0/4	4/4	4/4	8/8	0/4	2/4	3/4	8/8
GJ-C3-001#cl-13.5-class	3/3	3/3	3/3	6/6	2/3	3/3	3/3	6/6
GJ-C3-001#cl-5-proviso	0/3	0/3	0/3	6/6	0/3	0/3	0/3	6/6
GJ-C3-003#cl-6.2	0/2	2/2	2/2	4/4	0/2	2/2	2/2	4/4
IN-C1-011#cl-annex-phase2-claims	0/2	2/2	2/2	4/4	0/2	2/2	2/2	4/4
KA-C5-001#cl-15	0/4	4/4	3/4	0/8	0/4	0/4	0/4	0/8
KA-C5-001#cl-26	0/4	0/4	0/4	0/4	0/4	0/4	0/4	0/4
TN-C5-001#cl-2	0/3	0/3	0/3	0/6	0/3	0/3	0/3	0/6
UP-C3-001#cl-5.1	1/2	2/2	2/2	4/4	0/2	1/2	1/2	4/4
UP-C3-001#cl-6.2	1/2	2/2	2/2	4/4	1/2	2/2	2/2	4/4

10. R2 at least as high as R4 for the capable models: "The bottleneck is retrieval, not representation: given both versions, reviewers catch the replaced rule as well as when told its status."
11. R4−R2 not significant (uncorrected, secondary since amendment 1): no ladder claim. "Telling the reviewer the registry status did not reliably raise catches for these models."
12. The weak model at R4 within 10 points of its R2: "Below a capability threshold, the information does not help." Reported as a limit of the claim.
13. The secondary model's R2 within 10 points of its R4: "For a stronger model, seeing both versions is enough; the ladder result is limited to the local panel." Reported in the abstract.
14. "Can't confirm" never used by a model: "The option was available and unused."

"Seeing both versions is not enough" means that R2−R0 is not significant and that R2's catch is below half of R4's.

S3 Case study: prompts

The exact prompt of every rung, rendered for one dev item by `render_prereg_prompts.py`, is kept with the analysis plan (`PREREGISTRATION_v3_PROMPTS.md`; the plan's working file names say "preregistration", but it was not publicly registered) and released with the code; we do not retype it here. R4n is R4's prompt with one change: in the registry lookup block, a status value `in_force` reads `no_amendment_recorded`. A unit test checks that the two prompts differ in that word only, with the registry intact and damaged.

S4 Case study: per-clause results

Every clause-level rate in the paper is built from these cells; the released `ladder_per_clause.csv` has them for every model and rung, with controls, control alarms, can't-confirm, misnamed and invalid counts.

S5 Case study: annotation agreement

On the seeded shared subset (15 links, 20 cases) labelled by both annotators:

Sheet	Field	Agreement	κ	PABAK
Links	relation	87%	0.70	0.82
Links	effective date	80%	0.74	0.78
Links	wording	93%	0.84	0.90
Links	new clause id	7%	0.06	0.03
Cases	decision	80%	0.60	0.70
Cases	blocking stage	85%	0.79	0.82
Cases	deciding clauses	15%	0.14	0.11

The new-clause-id field is low mostly because one annotator wrote sub-clauses with a dot (`cl-4.2`) where the registry writes brackets (`cl-4(2)`); the adjudicator resolved these.

S6 Case study: deviations from the analysis plan

All of the following were recorded before any model saw a test item, except the last paragraph.

Amendment 1.

After the dev pilot, the damaged-registry comparisons (Q1, Q2) replaced the ladder contrasts (R4−R2, R2−R0) as the primary family; the capable models run all 5 damage seeds; discrimination, deference and the looser scoring rules (E5) were added.

Amendment 2, after the human audit.

- Annotation keeps a case whose adjudicated outcome (decision, and blocking stage for a rejection) matches the key; cases whose deciding clauses alone differ are kept and listed. The planned rule dropped them too and would have kept 6 of 60 cases.
- The correct-answer gate (95% judged correct) and the scorer gate (95% agreement) were replaced by reporting: 57% and 70% were observed. The scorer was not changed.
- Added: the R4n arm and the NoRec contrast (primary family of 10), sensitivity sets S1 and S2, the confusion-count and reference-row reporting rules, descriptive splits, and the registry audit on the random link sample.
- The annotators' meeting before adjudication was dropped; the adjudicator decided every disagreement.
- The analysis cutoff became 24 hours after the local run started, with blocks run in priority order.
- The lead author approved the amendment and stated the co-authors' agreement; not every author signed it.

After the run.

Dated in the decision log. (1) The local models moved from the lead author's laptop to Kaggle GPU notebooks (`qwen2.5:14b`) and back to the laptop for the two smaller models, for speed; each model ran on one machine, and a 30-minute partial start on the laptop that finished no block is kept and unused. Model files were checked against the pre-specified digests on every machine. (2) The 24-hour cutoff was fixed as a wall-clock time before any test result was read. (3) The laptop's model server crashed once mid-request; the run raised, recorded no reply, and resumed from its cache. (4) Additions after the plan was fixed, outside every planned test: `qwen2.5:32b` (damage seeds 0–2) and Claude Opus 4.5 through a Kaggle-hosted proxy (seed 0) on the main arms, and a same-machine repeat of three blocks to measure determinism. Every planned block finished for the planned models.

S7 Case study: data statement

Curation rationale.

Instruments on rooftop solar (net metering, capacity limits, connection procedures, central subsidy) were collected, including superseded ones, because the study is about replaced rules that remain available.

Language.

English. Six of the 111 documents also contain Hindi passages. A local open model machine-translated these passages into English for retrieval only; the translations are poor in places, and no label depends on them.

Source.

Official publications of central ministries, state electricity regulatory commissions and distribution companies in India, retrieved from their portals. Each document is released as a URL and a hash.

Cases.

Synthetic applications generated from rule functions. No personal data.

Annotators.

Two authors with backgrounds in computing (one an AI engineer with degrees in artificial intelligence and computer science), neither with training in law or energy policy, and a third author adjudicating (§S1.1.1).

Licences.

Code under Apache-2.0; cases and labels under CC BY 4.0; documents as URLs and hashes.