

# NF-6M-F12

## 6 MP 360° fisheye camera

One ceiling camera covers a whole shop floor, with de-warped views and a heat map of where people go.

- 360° from one point
- On-camera de-warping
- Heat map
- People counting
- Built-in microphone



### Specifications

#### CAMERA

|                   |                                              |
|-------------------|----------------------------------------------|
| Image sensor      | 1/2.4" progressive-scan CMOS                 |
| Max. resolution   | 3200 × 1800                                  |
| Min. illumination | Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR |
| Shutter           | 1/3 s to 1/100,000 s                         |
| WDR               | 120 dB                                       |

#### LENS

|                |             |
|----------------|-------------|
| Lens type      | Fixed focal |
| Focal length   | 1.16 mm     |
| Horizontal FOV | 137°        |
| Aperture       | F1.6        |

#### PIXEL DENSITY (DORI)

|           |      |
|-----------|------|
| Detect    | 25 m |
| Observe   | 10 m |
| Recognise | 5 m  |
| Identify  | 3 m  |

#### ILLUMINATOR

|                     |                        |
|---------------------|------------------------|
| Supplemental light  | Infrared (850 nm)      |
| Range               | Up to 10 m             |
| Smart light control | Yes, anti-overexposure |

#### VIDEO

|             |                                          |
|-------------|------------------------------------------|
| Compression | H.265, H.265+, H.264, MJPEG (sub-stream) |
| Main stream | 25 fps @ 3200 × 1800                     |
| Bit rate    | 32 Kbps to 16 Mbps                       |

#### AUDIO

|       |              |
|-------|--------------|
| Audio | Built-in mic |
|-------|--------------|

#### NETWORK

|           |                                                            |
|-----------|------------------------------------------------------------|
| Protocols | TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3      |
| API       | Open video interface (Profiles S, G, T), Dhonaadhi SDK     |
| Security  | Signed firmware, secure boot, encrypted storage, audit log |

#### DEEP-LEARNING FUNCTION

|                 |     |
|-----------------|-----|
| Heat map        | Yes |
| People counting | Yes |

#### GENERAL

|                       |                        |
|-----------------------|------------------------|
| Power                 | PoE (802.3af), 12 V DC |
| Operating temperature | -30 °C to 60 °C        |
| Protection            | IP66                   |

#### APPROVAL

|                |                                                        |
|----------------|--------------------------------------------------------|
| Certifications | CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable) |
|----------------|--------------------------------------------------------|