

NP-2M-P15C

2 MP 15× compact PTZ

A graphite indoor PTZ for lobbies, atriums and retail floors.

- 15× zoom
- Quiet pan/tilt motors
- Graphite finish
- Built-in microphone



Specifications

CAMERA

Image sensor	1/2.8" progressive-scan CMOS
Max. resolution	1920 × 1080
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Motorised varifocal
Focal length	5-75 mm
Horizontal FOV	4°-58°
Aperture	F1.6
Optical zoom	15×

PIXEL DENSITY (DORI)

Detect	1029 m
Observe	408 m
Recognise	206 m
Identify	103 m

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 1920 × 1080
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic
-------	--------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

People counting	Yes
-----------------	-----

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP66

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--