

# NP-4M-P25C

## 4 MP 25× compact PTZ

Compact PTZ with LumaNight colour for building exteriors.

- 25× zoom
- Colour at night
- SentinelAI
- Compact housing



### Specifications

#### CAMERA

|                   |                              |
|-------------------|------------------------------|
| Image sensor      | 1/1.8" progressive-scan CMOS |
| Max. resolution   | 2560 × 1440                  |
| Min. illumination | Colour: 0.0005 lux @ F1.0    |
| Shutter           | 1/3 s to 1/100,000 s         |
| WDR               | 120 dB                       |

#### LENS

|                |                     |
|----------------|---------------------|
| Lens type      | Motorised varifocal |
| Focal length   | 4.8-120 mm          |
| Horizontal FOV | 3°-74°              |
| Aperture       | F1.0                |
| Optical zoom   | 25×                 |

#### PIXEL DENSITY (DORI)

|           |        |
|-----------|--------|
| Detect    | 1707 m |
| Observe   | 677 m  |
| Recognise | 341 m  |
| Identify  | 171 m  |

#### ILLUMINATOR

|                     |                        |
|---------------------|------------------------|
| Supplemental light  | Warm white LED         |
| Range               | Up to 30 m             |
| Smart light control | Yes, anti-overexposure |

#### VIDEO

|             |                                          |
|-------------|------------------------------------------|
| Compression | H.265, H.265+, H.264, MJPEG (sub-stream) |
| Main stream | 25 fps @ 2560 × 1440                     |
| Bit rate    | 32 Kbps to 16 Mbps                       |

#### NETWORK

|           |                                                            |
|-----------|------------------------------------------------------------|
| Protocols | TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3      |
| API       | Open video interface (Profiles S, G, T), Dhonaadhi SDK     |
| Security  | Signed firmware, secure boot, encrypted storage, audit log |

#### DEEP-LEARNING FUNCTION

|                      |     |
|----------------------|-----|
| Perimeter protection | Yes |
|----------------------|-----|

#### GENERAL

|                       |                        |
|-----------------------|------------------------|
| Power                 | PoE (802.3af), 12 V DC |
| Operating temperature | -30 °C to 60 °C        |
| Protection            | IP66                   |

#### APPROVAL

|                |                                                        |
|----------------|--------------------------------------------------------|
| Certifications | CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable) |
|----------------|--------------------------------------------------------|