

# NT-4M-T28

## 4 MP turret camera

A turret with no dome bubble, so infrared never reflects back into the image.

- No IR glare
- 30 m infrared
- Tool-free adjustment
- IP67



## Specifications

### CAMERA

|                   |                                              |
|-------------------|----------------------------------------------|
| Image sensor      | 1/3" progressive-scan CMOS                   |
| Max. resolution   | 2560 × 1440                                  |
| Min. illumination | Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR |
| Shutter           | 1/3 s to 1/100,000 s                         |
| WDR               | 120 dB                                       |

### LENS

|                |             |
|----------------|-------------|
| Lens type      | Fixed focal |
| Focal length   | 2.8 mm      |
| Horizontal FOV | 81°         |
| Aperture       | F1.6        |

### PIXEL DENSITY (DORI)

|           |      |
|-----------|------|
| Detect    | 60 m |
| Observe   | 24 m |
| Recognise | 12 m |
| Identify  | 6 m  |

### ILLUMINATOR

|                     |                        |
|---------------------|------------------------|
| Supplemental light  | Infrared (850 nm)      |
| Range               | Up to 30 m             |
| Smart light control | Yes, anti-overexposure |

### VIDEO

|             |                                          |
|-------------|------------------------------------------|
| Compression | H.265, H.265+, H.264, MJPEG (sub-stream) |
| Main stream | 25 fps @ 2560 × 1440                     |
| Bit rate    | 32 Kbps to 16 Mbps                       |

### NETWORK

|           |                                                            |
|-----------|------------------------------------------------------------|
| Protocols | TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3      |
| API       | Open video interface (Profiles S, G, T), Dhonaadhi SDK     |
| Security  | Signed firmware, secure boot, encrypted storage, audit log |

### DEEP-LEARNING FUNCTION

|                      |     |
|----------------------|-----|
| Perimeter protection | Yes |
|----------------------|-----|

### GENERAL

|                       |                        |
|-----------------------|------------------------|
| Power                 | PoE (802.3af), 12 V DC |
| Operating temperature | -30 °C to 60 °C        |
| Protection            | IP67                   |

### APPROVAL

|                |                                                        |
|----------------|--------------------------------------------------------|
| Certifications | CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable) |
|----------------|--------------------------------------------------------|