

NX-4K-D72

4K Ultra motorised dome

The flagship indoor/outdoor dome: 4K, motorised 2.8-7.2 mm lens and 140 dB WDR for glass-fronted lobbies.

- 4K motorised dome
- 140 dB WDR for glass lobbies
- IK10
- Face capture
- Remote zoom and focus



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	3840 × 2160
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Motorised varifocal
Focal length	2.8-7.2 mm
Horizontal FOV	53°-104°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	154 m
Observe	61 m
Recognise	31 m
Identify	15 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 40 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 3840 × 2160
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Face capture	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--