

# NB-4M-B28L

## 4 MP LumaNight fixed bullet camera

Full-colour night video at 0.0005 lux with a warm-white light that only switches on when a person or vehicle appears.

- Colour at 0.0005 lux with F1.0 lens
- Smart white light, 40 m
- SentinelAI human/vehicle detection
- Built-in microphone
- 130 dB WDR



### Specifications

#### CAMERA

|                   |                              |
|-------------------|------------------------------|
| Image sensor      | 1/1.8" progressive-scan CMOS |
| Max. resolution   | 2560 × 1440                  |
| Min. illumination | Colour: 0.0005 lux @ F1.0    |
| Shutter           | 1/3 s to 1/100,000 s         |
| WDR               | 120 dB                       |

#### LENS

|                |             |
|----------------|-------------|
| Lens type      | Fixed focal |
| Focal length   | 2.8 mm      |
| Horizontal FOV | 104°        |
| Aperture       | F1.0        |

#### PIXEL DENSITY (DORI)

|           |      |
|-----------|------|
| Detect    | 40 m |
| Observe   | 16 m |
| Recognise | 8 m  |
| Identify  | 4 m  |

#### ILLUMINATOR

|                     |                        |
|---------------------|------------------------|
| Supplemental light  | Warm white LED         |
| Range               | Up to 40 m             |
| Smart light control | Yes, anti-overexposure |

#### VIDEO

|             |                                          |
|-------------|------------------------------------------|
| Compression | H.265, H.265+, H.264, MJPEG (sub-stream) |
| Main stream | 25 fps @ 2560 × 1440                     |
| Bit rate    | 32 Kbps to 16 Mbps                       |

#### AUDIO

|       |              |
|-------|--------------|
| Audio | Built-in mic |
|-------|--------------|

#### NETWORK

|           |                                                            |
|-----------|------------------------------------------------------------|
| Protocols | TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3      |
| API       | Open video interface (Profiles S, G, T), Dhonaadhi SDK     |
| Security  | Signed firmware, secure boot, encrypted storage, audit log |

#### DEEP-LEARNING FUNCTION

|                      |     |
|----------------------|-----|
| Perimeter protection | Yes |
|----------------------|-----|

#### GENERAL

|                       |                        |
|-----------------------|------------------------|
| Power                 | PoE (802.3af), 12 V DC |
| Operating temperature | -30 °C to 60 °C        |
| Protection            | IP67                   |

#### APPROVAL

|                |                                                        |
|----------------|--------------------------------------------------------|
| Certifications | CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable) |
|----------------|--------------------------------------------------------|