

NF-6M-F12

6 MP 360° fisheye camera

One ceiling camera covers a whole shop floor, with de-warped views and a heat map of where people go.

- 360° from one point
- On-camera de-warping
- Heat map
- People counting
- Built-in microphone



Specifications

CAMERA

Image sensor	1/2.4" progressive-scan CMOS
Max. resolution	3200 × 1800
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	1.16 mm
Horizontal FOV	137°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	25 m
Observe	10 m
Recognise	5 m
Identify	3 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 10 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 3200 × 1800
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic
-------	--------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Heat map	Yes
People counting	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP66

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--