

NT-8M-T40A

8 MP Sentinel turret

Counts customers and measures queues at checkouts, with 4K evidence when something goes wrong.

- Queue length and waiting time
- People counting
- Face capture
- 4K in colour
- Dual-mic array



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	3840 × 2160
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Fixed focal
Focal length	4 mm
Horizontal FOV	84°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	85 m
Observe	34 m
Recognise	17 m
Identify	9 m

ILLUMINATOR

Supplemental light	Warm white LED
Range	Up to 40 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 3840 × 2160
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Dual-mic array
-------	----------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Face capture	Yes
People counting	Yes
Queue management	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--