

NX-4M-BX

4 MP box camera body

A C/CS-mount body for specialist lenses, from long-range plate reading to wide lobby views.

- C/CS lens mount
- Plate recognition
- 12 V DC, 24 V AC or PoE
- Alarm and audio I/O



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Manual varifocal
Focal length	3.8-16 mm
Horizontal FOV	25°-87°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	228 m
Observe	90 m
Recognise	46 m
Identify	23 m

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Number plate recognition	Yes
Face capture	Yes

GENERAL

Power	PoE (802.3af), 12 V DC, 24 V AC
Operating temperature	-10 °C to 50 °C

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--