

TH-B384-35

384 × 288 thermal bi-spectrum bullet

Detects a person at 400 m in fog or smoke with a 35 mm thermal lens.

- Detect people at 400 m
- 35 mm thermal lens
- Works in fog and smoke
- Temperature exception alarms



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Multi-lens
Focal length	8 mm
Horizontal FOV	48°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	114 m
Observe	45 m
Recognise	23 m
Identify	11 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 40 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Fire & smoke detection	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--