

NB-8M-B28L

8 MP LumaNight fixed bullet camera

4K colour around the clock from a large 1/1.2" sensor, with enough detail to identify a face at 13 m.

- 4K from a 1/1.2" sensor
- Colour at 0.0005 lux
- Face capture on the camera
- Dual-microphone array
- 140 dB WDR



Specifications

CAMERA

Image sensor	1/1.2" progressive-scan CMOS
Max. resolution	3840 × 2160
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Fixed focal
Focal length	2.8 mm
Horizontal FOV	125°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	40 m
Observe	16 m
Recognise	8 m
Identify	4 m

ILLUMINATOR

Supplemental light	Warm white LED
Range	Up to 40 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 3840 × 2160
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Dual-mic array
-------	----------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Face capture	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--