

ND-4M-D28L

4 MP LumaNight dome

Colour-at-night dome in graphite, designed to disappear into dark ceilings in retail and hospitality.

- Colour at 0.0005 lux
- Graphite finish
- Heat map on the camera
- Built-in microphone
- IK10



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	2.8 mm
Horizontal FOV	104°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	40 m
Observe	16 m
Recognise	8 m
Identify	4 m

ILLUMINATOR

Supplemental light	Warm white LED
Range	Up to 30 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic
-------	--------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Heat map	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--