

NB-8M-V2812A

8 MP Sentinel varifocal bullet

Four deep-learning models running at once, from plate reading at the gate to hard-hat checks on site.

- Four concurrent AI models
- Plate recognition up to 30 km/h
- Hard-hat detection
- 80 m hybrid light
- Metadata for fast search



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	3840 × 2160
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Motorised varifocal
Focal length	2.8-12 mm
Horizontal FOV	33°-104°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	256 m
Observe	102 m
Recognise	51 m
Identify	26 m

ILLUMINATOR

Supplemental light	Smart hybrid (IR + white)
Range	Up to 80 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 3840 × 2160
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic, Built-in speaker
-------	--------------------------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

EVENT

Active deterrence	Audio alarm, White strobe
-------------------	---------------------------

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Number plate recognition	Yes
Hard-hat detection	Yes
People counting	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--