


NP-4M-P32X

4 MP 32× auto-tracking speed dome

Detects a person at the fence and follows them automatically across the site.

- 32× zoom
- Auto-tracking
- 200 m infrared
- Wiper
- IK10



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Motorised varifocal
Focal length	4.8-153 mm
Horizontal FOV	3°-74°
Aperture	F1.6
Optical zoom	32×

PIXEL DENSITY (DORI)

Detect	2176 m
Observe	863 m
Recognise	435 m
Identify	218 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 200 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Face capture	Yes

GENERAL

Power	PoE (802.3af), 24 V AC
Operating temperature	-30 °C to 60 °C
Protection	IP66, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--