

NP-4M-P45X

4 MP 45× Sentinel speed dome

Ports, borders and highways: 45× zoom, 250 m infrared and plate reading at distance.

- 45× optical zoom
- 250 m infrared
- Plate reading at distance
- Colour at night
- IP67



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	140 dB

LENS

Lens type	Motorised varifocal
Focal length	6-270 mm
Horizontal FOV	2°-62°
Aperture	F1.0
Optical zoom	45×

PIXEL DENSITY (DORI)

Detect	3840 m
Observe	1524 m
Recognise	768 m
Identify	384 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 250 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
Number plate recognition	Yes
Face capture	Yes

GENERAL

Power	PoE (802.3af), 24 V AC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--