

NT-6M-T28L

6 MP LumaNight turret with two-way audio

Talk to visitors, or warn off loiterers, straight from the camera over the building entrance.

- Two-way audio
- Colour at night
- Custom voice warnings
- SentinelAI filtering
- 6 MP



Specifications

CAMERA

Image sensor	1/2.4" progressive-scan CMOS
Max. resolution	3200 × 1800
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	2.8 mm
Horizontal FOV	93°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	61 m
Observe	24 m
Recognise	12 m
Identify	6 m

ILLUMINATOR

Supplemental light	Smart hybrid (IR + white)
Range	Up to 30 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 3200 × 1800
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic, Built-in speaker, Two-way audio
-------	---

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

EVENT

Active deterrence	Audio alarm
-------------------	-------------

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
----------------------	-----

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--