

# NT-8M-T40A

## 8 MP Sentinel turret

Counts customers and measures queues at checkouts, with 4K evidence when something goes wrong.

- Queue length and waiting time
- People counting
- Face capture
- 4K in colour
- Dual-mic array



### Specifications

#### CAMERA

|                   |                              |
|-------------------|------------------------------|
| Image sensor      | 1/1.8" progressive-scan CMOS |
| Max. resolution   | 3840 × 2160                  |
| Min. illumination | Colour: 0.0005 lux @ F1.0    |
| Shutter           | 1/3 s to 1/100,000 s         |
| WDR               | 140 dB                       |

#### LENS

|                |             |
|----------------|-------------|
| Lens type      | Fixed focal |
| Focal length   | 4 mm        |
| Horizontal FOV | 84°         |
| Aperture       | F1.0        |

#### PIXEL DENSITY (DORI)

|           |      |
|-----------|------|
| Detect    | 85 m |
| Observe   | 34 m |
| Recognise | 17 m |
| Identify  | 9 m  |

#### ILLUMINATOR

|                     |                        |
|---------------------|------------------------|
| Supplemental light  | Warm white LED         |
| Range               | Up to 40 m             |
| Smart light control | Yes, anti-overexposure |

#### VIDEO

|             |                                          |
|-------------|------------------------------------------|
| Compression | H.265, H.265+, H.264, MJPEG (sub-stream) |
| Main stream | 20 fps @ 3840 × 2160                     |
| Bit rate    | 32 Kbps to 16 Mbps                       |

#### AUDIO

|       |                |
|-------|----------------|
| Audio | Dual-mic array |
|-------|----------------|

#### NETWORK

|           |                                                            |
|-----------|------------------------------------------------------------|
| Protocols | TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3      |
| API       | Open video interface (Profiles S, G, T), Dhonaadhi SDK     |
| Security  | Signed firmware, secure boot, encrypted storage, audit log |

#### DEEP-LEARNING FUNCTION

|                  |     |
|------------------|-----|
| Face capture     | Yes |
| People counting  | Yes |
| Queue management | Yes |

#### GENERAL

|                       |                        |
|-----------------------|------------------------|
| Power                 | PoE (802.3af), 12 V DC |
| Operating temperature | -30 °C to 60 °C        |
| Protection            | IP67                   |

#### APPROVAL

|                |                                                        |
|----------------|--------------------------------------------------------|
| Certifications | CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable) |
|----------------|--------------------------------------------------------|