

NX-8M-BX

8 MP box camera body

4K body with a 1/1.2" sensor for low-light specialist installs such as tunnels and ports.

- 1/1.2" sensor
- 4K
- Plate recognition
- Industrial temperature range



Specifications

CAMERA

Image sensor	1/1.2" progressive-scan CMOS
Max. resolution	3840 × 2160
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Manual varifocal
Focal length	8-32 mm
Horizontal FOV	19°-68°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	459 m
Observe	182 m
Recognise	92 m
Identify	46 m

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 3840 × 2160
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Number plate recognition	Yes
--------------------------	-----

GENERAL

Power	PoE (802.3af), 12 V DC, 24 V AC
Operating temperature	-40 °C to 65 °C

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--