

NB-16M-P4

16 MP PanoSight 180° multi-sensor

Four sensors stitched into one seamless 180° colour image for car parks, squares and junctions.

- 180° seamless stitching
- Four 4 MP sensors
- Colour at night
- SentinelAI filtering



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	5120 × 3200
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Multi-lens
Focal length	4 mm
Horizontal FOV	84°
Aperture	F1.0

PIXEL DENSITY (DORI)

Detect	114 m
Observe	45 m
Recognise	23 m
Identify	11 m

ILLUMINATOR

Supplemental light	Warm white LED
Range	Up to 30 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 5120 × 3200
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
People counting	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--