

NB-4M-B40H

4 MP hybrid-light bullet with deterrence

Warns intruders off with a strobe and a recorded voice message the moment they cross a virtual line.

- IR by default, white light on alarm
- Red/blue strobe and siren
- Two-way talk
- Line crossing and intrusion
- 50 m range



Specifications

CAMERA

Image sensor	1/2.7" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	4 mm
Horizontal FOV	68°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	76 m
Observe	30 m
Recognise	15 m
Identify	8 m

ILLUMINATOR

Supplemental light	Smart hybrid (IR + white)
Range	Up to 50 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic, Built-in speaker, Two-way audio
-------	---

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

EVENT

Active deterrence	Audio alarm, Red/blue strobe
-------------------	------------------------------

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
----------------------	-----

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--