

NB-6M-V2812

6 MP motorised varifocal bullet

Zoom and focus from the browser after installation, so one model covers a doorway or a car park.

- 2.8-12 mm motorised lens
- 60 m infrared
- Remote zoom and focus
- IK10 vandal-resistant
- Line counting on the camera



Specifications

CAMERA

Image sensor	1/2.4" progressive-scan CMOS
Max. resolution	3200 × 1800
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Motorised varifocal
Focal length	2.8-12 mm
Horizontal FOV	28°-93°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	260 m
Observe	103 m
Recognise	52 m
Identify	26 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 60 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 3200 × 1800
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
People counting	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP67, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--