

NF-12M-F16

12 MP 360° fisheye camera

Twice the pixels of the NF-6M for larger floors such as warehouses and atriums.

- 12 MP 360° image
- IK10
- Heat map and queues
- 15 m infrared



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	4000 × 3000
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	1.6 mm
Horizontal FOV	132°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	36 m
Observe	14 m
Recognise	7 m
Identify	4 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 15 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	20 fps @ 4000 × 3000
Bit rate	32 Kbps to 16 Mbps

AUDIO

Audio	Built-in mic
-------	--------------

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Heat map	Yes
People counting	Yes
Queue management	Yes

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP66, IK10

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--