


NP-2M-P25X

2 MP 25× IR speed dome

A 25× speed dome with 100 m infrared for car parks and campuses.

- 25× optical zoom
- 100 m infrared
- 300 presets and patrols
- High-PoE powered



Specifications

CAMERA

Image sensor	1/2.8" progressive-scan CMOS
Max. resolution	1920 × 1080
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Motorised varifocal
Focal length	4.8-120 mm
Horizontal FOV	3°-61°
Aperture	F1.6
Optical zoom	25×

PIXEL DENSITY (DORI)

Detect	1646 m
Observe	653 m
Recognise	329 m
Identify	165 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 100 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 1920 × 1080
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
----------------------	-----

GENERAL

Power	PoE (802.3af), 24 V AC
Operating temperature	-30 °C to 60 °C
Protection	IP66

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--