

NP-4M-P25C

4 MP 25× compact PTZ

Compact PTZ with LumaNight colour for building exteriors.

- 25× zoom
- Colour at night
- SentinelAI
- Compact housing



Specifications

CAMERA

Image sensor	1/1.8" progressive-scan CMOS
Max. resolution	2560 × 1440
Min. illumination	Colour: 0.0005 lux @ F1.0
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Motorised varifocal
Focal length	4.8-120 mm
Horizontal FOV	3°-74°
Aperture	F1.0
Optical zoom	25×

PIXEL DENSITY (DORI)

Detect	1707 m
Observe	677 m
Recognise	341 m
Identify	171 m

ILLUMINATOR

Supplemental light	Warm white LED
Range	Up to 30 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 2560 × 1440
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
----------------------	-----

GENERAL

Power	PoE (802.3af), 12 V DC
Operating temperature	-30 °C to 60 °C
Protection	IP66

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--