

NS-2M-S4G

2 MP SunLink solar 4G camera kit

An entry SunLink kit for construction sites and farms.

- Solar + 4G
- 5 days on battery
- Motion-triggered upload
- IP67



Specifications

CAMERA

Image sensor	1/2.8" progressive-scan CMOS
Max. resolution	1920 × 1080
Min. illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Shutter	1/3 s to 1/100,000 s
WDR	120 dB

LENS

Lens type	Fixed focal
Focal length	4 mm
Horizontal FOV	70°
Aperture	F1.6

PIXEL DENSITY (DORI)

Detect	55 m
Observe	22 m
Recognise	11 m
Identify	5 m

ILLUMINATOR

Supplemental light	Infrared (850 nm)
Range	Up to 30 m
Smart light control	Yes, anti-overexposure

VIDEO

Compression	H.265, H.265+, H.264, MJPEG (sub-stream)
Main stream	25 fps @ 1920 × 1080
Bit rate	32 Kbps to 16 Mbps

NETWORK

Protocols	TCP/IP, HTTPS, RTSP, NTP, 802.1X, IPv6, SNMP, TLS 1.3
API	Open video interface (Profiles S, G, T), Dhonaadhi SDK
Security	Signed firmware, secure boot, encrypted storage, audit log

INTERFACE

On-board storage	microSD up to 256 GB
------------------	----------------------

DEEP-LEARNING FUNCTION

Perimeter protection	Yes
----------------------	-----

GENERAL

Power	Solar + battery, 4G LTE
Operating temperature	-30 °C to 60 °C
Protection	IP67

APPROVAL

Certifications	CE, FCC, UL 62368-1, RoHS, EN 50131 (where applicable)
----------------	--