INFORMATION

MTOM . . . . . 540 KG
Useful Load (incl. Sprit) . . . . . 225 KG
Max. Ammount of Fuel . . . . . 60 ℓ / 43 KG
Useable Fuel 58 ℓ
SUPER unlead 95/98

Speeds:

Never Exceed - v_{NE} . . . . . 225 KM/H
Norm. Ops Speed - v_A . . . . . 166 KM/H
Max. Speed for Flaps. - v_{FE} . . . . . 140 KM/H
Best Glide - v_{BG} . . . . . 115 KM/H
Minimal Sink - v_{ms} . . . . . 95 KM/H

COCKPIT

Preflight Inspection . . . . . PERFORMED
Acc. to Handbook Capt. 4.1 (P. 34)
Fuel on Board . . . . . CHECKED
Documents and Dipstick . . . . . ON BOARD
Seat Belts . . . . . ON
Canopy . . . . . LOCKED

BEFORE ENGINGE START

Parking Brake . . . . . SET
Fuel Shutoff Valve . . . . . OPEN
Avionic Switches . . . . . ALL SWITCHES OFF
Life-Saving Equipment (Chute) . . . . . UNLOCKED
Put splint-pin in middle compartment,
and ignition key in the ignition-lock.
Master Switch . . . . . ON
Circuit breakers . . . . . ALL IN
Flaps . . . . . COMPLETELY RETRACTED (UP)

Do NOT start-up against extended flaps!

ENGINGE START

Strobes ("NAV LTS") . . . . . ON
Fuel Pump . . . . . 5 SEC. ON - THEN OFF
Throttle . . . . . IDLE
Choke . . . . . AS REQUIRED
Engine cold: PULL+HOLD
Engine warm: no Choke, Throttle ca. **2 mm**
Prop Area . . . . . CLEAR
Engine Start, via Key . . . . . PERFORMED
Enginge Rev, with Choke released MAX. 2000 RPM
Oil Pressure . . . . . GREEN ARC

AFTER START-UP

Avionic (Toggle Switches)

XPDR, Horizon, Master Radio: 3x ON
Transponder on device to STBY/GND

Altimeter . . . . . SET
Analogue Altimeter AND G5

TAXI

Headlights . . . . . ON
Engine Rev . . . . . IDLE
Release parking brake and brake manually.
Perform brake check on first movement!
Taxi always with walking pace and ONLY
according to required clearances!

BEFORE TAKE-OFF

Parking brake . . . . . SET
Throttle . . . . . IDLE
Headlights . . . . . OFF
Warm-up enging with max. 2000 RPM.
until oil temp. min. 50°C.
Run-up Check . . . . . PERFORMED
At 3200 RPM. Max. drop 250 RPM (L/R)
Flight Controls (Stick) . . . . . FREE
Trim . . . . . SET
Canopy . . . . . DOUBLE CHECKED

TAKE-OFF / DEPARTURE

For Line-Up:

Fuel Pump . . . . . ON
Headlights . . . . . ON
Transponder . . . . . ALT (MODE S, ADS-B)
Flaps . . . . . AS REQUIRED
Line-up only according to required clearances!

In Position / Take-Off

Throttle . . . . . FULL FWD
Rotation **earliest** at 65 km/h.
Best climb w/ FLAPS-1: 110 km/m. Clean: 115 km/h.
Trim . . . . . SET
At about 400 ft AGL, reduce Rev slightly.
Fuel Pumpe and lights OFF.
Retract Flaps. Climb w/ 115 to 120 km/h
Adjust trim accordingly.

CRUISE

Flaps . . . . . RETRACTED
Headlights . . . . . OFF
Fuel Pump . . . . . OFF

Powersetting:

| Normal Cruise: 4750 to 5000 RPM
| Fast Cruise: up to max. 5300 RPM

CAUTION: High fuel consumption from 5000 RPM on!

Check engine instruments regularly

APPROACH

Altimeter . . . . . SET
Analogue Altimeter AND G5
Speed . . . . . ACC. APPROACH
Altitude . . . . . ACC. APPROACH
Headlights . . . . . ON
Flaps . . . . . AS REQUIRED
CHECK IND. AIR SPEED!
Max. 140 km/h for Flaps.
Altitude . . . . . ACC. CIRCUIT OR CLEARANCE

FINAL APPROACH AND LANDING

Fuel Pump . . . . . ON
Flaps . . . . . AS REQUIRED
Final Approach w/o Flaps . . . . . 110 KM/H
Final Approach w/ Flaps 1/2 . . . . . 100 KM/H
Touch-down . . . . . 90 - 95 KM/H

AFTER LANDING / TURN-OFF

Fuel Pump . . . . . OFF
Flaps . . . . . FULLY RETRACTED
Transponder . . . . . STBY OR GND
Trhottle . . . . . IDLE
Taxi according to clearances, clean and with walkin pace. If necessary on hand on brake lever

Do NOT taxi with extended flaps!

SHUT-DOWN

At Parkingposition:

Throttle . . . . . IDLE
Parking Brake . . . . . SET
Headlights . . . . . OFF
XPDR, Horizon, Radio . . . . . OFF
Trim . . . . . NEUTRAL
Ignition (via key) . . . . . OFF

AFTER Engine has STOPPED:

Strobes ("NAV LTS") . . . . . OFF
Flaps . . . . . FULLY EXTENDED
Step-on protection! Check first, then:
MASTER . . . . . OFF
Life-saving Eq. (Chute) . . . . . SECURED
Ignition key . . . . . REMOVED

| Put key into middle compartment.

When getting out:

ALL Flip-Switches . . . . . OFF!
Parking Brake . . . . . AS REQUIRED

Will the A/C be moved?

| Parking Brake: released

Parking over night? Outside?

| Parking Brake: SET
| Controls: SECURED
| | (Arrest stick w/ Harness!)
| Wheel Chocks?
| A/C tied down?
| A/C covered? (Tarpaulin)