Midterm Report: Planning Temporal Manifolds

Shantanu Darveshi
shantanu.darveshi@gmail.com
Jared Eng-Denbaars
jengdenbaars@gmail.com
Alan McIntyre
alan@codereclaimers.com
Augusto Nicola
auguston64@gmail.com
Ian Rios-Sialer
iansebas@umich.edu
Soham Takawadekar
sohamtakawadekar17@outlook.com

Supervised Program for Alignment Research — Fall 2026

Abstract

Language models increasingly give advice on decisions whose right answer depends on the time horizon being considered. We ask whether a model's planning horizon can be steered precisely, and whether that steering carries over from templated tasks to realistic advice. On investment decisions of increasing realism, we compare linear steering vectors with steering along a nonlinear temporal manifold. We verify both methods on prompts with known answers before applying them to free-text and open-ended requests. This report presents our experimental design and evaluation framework.

1 Introduction

When an agent weighs options, the choice often turns on the temporal scope it uses to score consequences: a cost that is unacceptable over a week can be correct over a decade, and the reverse. This makes time preference fundamental not only to planning but to cooperation and trust. Thus, we find the study of temporal planning in models to be relevant to alignment research.

Our theory of change consists of developing a greater understanding of how modern LLMs represent and use temporal information. More specifically, our hypothesis can be phrased as: can we steer the behaviour of temporally coherent models in simulations of realistic scenarios? Crucially, this hypothesis encodes two important claims:

- Models display coherent decision-making under our analytical framework, and also
- Steering techniques prove effective in changing the behaviour of models, whilst maintaining rationale.

Specifically, our contributions aim to improve the understanding of models' behaviour when under linear (steering vectors, [8, 13]) and nonlinear steering techniques (manifold-based analysis, [5, 9]). We contrast these interventions with increasingly realistic prompts and tasks.

2 Related Work

Our work is framed strongly by the direct precedent of our mentor's prior work [10], which set the baseline framework by causally localizing temporal preference as structures in activation space with nonlinear geometry in simplified prompts. This project consists of a near-direct extension, specifically by expanding on prompt realism for generality.

The methodology of study presented is heavily based on key insights from previous findings: firstly, the fact that LLMs encode temporal and spatial coordinates as nonlinear geometric objects [1,3,7,12] is our main driver for searching for manifolds in activation space. Secondly, we pay special attention to studying the coherence in model decisions based on evidence from previous experiments stating that LLMs fail at temporal reasoning tasks, even when encoding relevant notions [2,4,6,11,14,15]. Lastly, our steering efforts are motivated by recent advances such as representation engineering [16].

3 Hypotheses

1. **Steering vectors obtained from long-term prompt responses should reproduce a long-term preference in other contexts.** Possible evidence includes using activation vectors from one task to steer in another, transferring the steering effect. Other comparisons, such as high cosine similarity between vectors extracted from different tasks, could also support this.

2. **Steering along a nonlinear temporal manifold shifts temporal behaviour more accurately than linear techniques.** Following previous work, we believe modelling temporal preferences using manifolds will yield clearer behavioural shifts than traditional steering counterparts. Evidence here is based on comparing the effect on model answers after applying steering over the fitted temporal manifold. Furthermore, confirming that small changes in position along the fitted manifold produce proportionally small behavioural changes supports this.

4 Methods

Tasks and data. All prompts are investment decisions, at increasing levels of realism. Structured prompts present a templated binary choice between a near and a far option, each of which pays off within a stated planning horizon or doesn't. The correct answer is known whenever at least one option pays off: the near one if only it does, the larger far one if both do. When neither does (every horizon under 1 week, and longer ones up to the near option's delay), no answer is correct; these prompts are used for extraction but not to score behaviour, which is verified only on prompts near the boundary where the answer flips. Horizons span 48 log-spaced values from 30 seconds to 500 years. Realistic prompts move toward how human users ask for advice in everyday model usage. First, they state the horizon in free-text scenarios ("I need the money for a house deposit in 2 years"). Then, the horizon is implied rather than explicit ("I'm retiring next spring"). Finally, they ask for open-ended answers such as a portfolio allocation or a bond duration. Based on early experimental results, option order and labels are randomized throughout. Experiments run on open-weight reasoning models from the Qwen3 and Gemma 4 families, with Gemma 4 31B as the headline model.

Steering methods. We record activations at the answer position and average them per horizon. A linear direction (CAA) is the mean of long-horizon activations minus the mean of short-horizon ones. A nonlinear method fits a smooth manifold curve through the per-horizon means in a low-dimensional principal subspace. It steers by sliding an activation along this curve by a target shift in log-time, so the activation stays on the manifold. Controls are random directions and a reward-contrast direction, both matched in norm.

Verification. On held-out structured prompts, each method must shift the horizon the model acts on, read from where its choice switches, in both option orders and beyond the controls.

Linear vs manifold (H2). At matched norms, we compare how closely the realized horizon shift tracks the intended one. We also test whether small moves along the curve produce proportionally small behavioural changes, and how coherence degrades with distance from the manifold.

Transfer (H1). We apply vectors fitted on structured prompts to each realism level. We also measure cosine similarity with vectors extracted at that level. The readout is the horizon of the recommended action, compared against rewriting the prompt with a longer stated horizon.

We report coherence, refusal and format-failure rates at every strength.

Appendix A gives the full details: prompts, realism tiers, steering, verification, metrics and roadmap. Appendix B summarizes the exploratory results behind these choices.

5 Progress

The project's progress during the past weeks has included exploratory research involving extensions of our mentor's previous work.

We first replicated the ordered horizon geometry across six models (appendix B), keeping in mind that being readable does not mean being used: simple text parsing already recovers explicit horizons, and reward size was decodable in four models yet changed choices in only one.

We therefore moved from readout to intervention. Two behavioural studies shaped the design (appendix B): unit-mismatched investment prompts have known correct answers, which models reach when thinking is enabled, and a phrasing study showed which prompt effects must be controlled. The direction carrying the horizon also changes across turns and during reasoning, so one fixed vector may not suffice. These results provide us with a roadmap of confounds in prompt structure to be aware of.

In a preliminary pilot on Qwen3-8B, moving along the temporal curve at layer 24 shifted choices toward the rational answer by 0.15 of the contrast with thinking on, whereas a straight probe direction moved them by at most 0.015 and random directions by at most 0.03. This serves as our support for testing H2.

6 Next Steps and Budget

We propose a tiered budget. Each tier adds a milestone to the one before it. Most of the cost at every tier is GPU time for running ∼30B-parameter reasoning models with steering. API costs for generating and judging prompts are small ($5–60 per tier). The estimates in table 1 multiply the generations each tier needs (prompts × steering settings) by the measured cost of one thinking-on generation: about 13 s for Gemma 4 31B and 30 s for a 27B Qwen model on one A100 80 GB, rented at $0.9–1.4 per hour. The ranges allow for steered traces running up to 1.8 times longer and for 20–70% overhead (setup, reruns, idle time); the first figure is the central estimate. With our confirmed budget of $800, Tier 1 fits with margin even at the high end, and Tiers 1–2 fit at the central estimate ($540). Tier 3 would need further funding or a reduced replication. Batching that does not wait for the longest trace in each batch, which we have not yet tested, could lower all figures.

Table 1: Proposed budget tiers.

Tier	Milestone	What it adds	Claims supported	Estimated cost
1. Core	Verified horizon steering	Gate and calibration on structured prompts; linear vs manifold comparison on held-out horizons. One model.	Whether a time-horizon direction exists, and H2	**$160** ($75–310)
2. Transfer	Steering on realistic advice	Free-text and implicit-horizon prompts (T1–T2), with generation and judging.	H1 for binary and multi-option choices	**+$380** ($185–750)
3. Full scope	Open-ended advice and replication	Open-ended answers (T3) and replication on a second model family.	H1 in the realistic target setting; generality across models	**+$870** ($425–1,700)
4. Stretch	Robustness and extensions	Multi-turn robustness, durations outside planning, additional model sizes.	Robustness beyond the core claims	**+$540** ($260–1,060)
			Cumulative total (through Tier 3)	**$1,410** ($685–2,760)

References

[1] Joshua Engels, Eric J. Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark. Not all language model features are one-dimensionally linear. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2405.14860.

[2] Bahare Fatemi, Mehran Kazemi, Anton Tsitsulin, Karishma Malkan, Jinyeong Yim, John Palowitch, Sungyong Seo, Jonathan Halcrow, and Bryan Perozzi. Test of time: A benchmark for evaluating LLMs on temporal reasoning. *arXiv preprint arXiv:2406.09170*, 2024.

[3] Wes Gurnee and Max Tegmark. Language models represent space and time. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. https://openreview.net/forum?id=jE8xbmvFin.

[4] David Herel, Vojtech Bartek, Jiri Jirak, and Tomas Mikolov. Time awareness in large language models: Benchmarking fact recall across time. *arXiv preprint arXiv:2409.13338*, 2024.

[5] Jiaqian Li, Yanshu Li, and Kuan-Hao Huang. Steering vector fields for context-aware inference-time control in large language models. *arXiv preprint arXiv:2602.01654*, 2026.

[6] Zijia Liu, Peixuan Han, Haofei Yu, Haoru Li, and Jiaxuan You. Time-R1: Towards comprehensive temporal reasoning in LLMs. *arXiv preprint arXiv:2505.13508*, 2025.

[7] Alexander Modell, Patrick Rubin-Delanchy, and Nick Whiteley. The origins of representation manifolds in large language models. *arXiv preprint arXiv:2505.18235*, 2025.

[8] Nina Panickssery, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. Steering Llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual*

Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 15504–15522, 2024. arXiv:2312.06681.

[9] Shivam Raval, Hae Jin Song, Linlin Wu, Abir Harrasse, Jeff M. Phillips, Fazl Barez, and Amirali Abdullah. Curveball steering: The right direction to steer isn't always linear. *arXiv preprint arXiv:2603.09313*, 2026.

[10] Ian Rios-Sialer, Shantanu Darveshi, Shuai Jiang, Avigya Paudel, Anastasiia Pronina, Ipshita Bandyopadhyay, and Justin Shenk. Temporal preference concepts and their functions in a large language model. *arXiv preprint arXiv:2606.05194*, 2026.

[11] Neil K. R. Sehgal, Sharath Chandra Guntuku, and Lyle Ungar. Real-time deadlines reveal fragile temporal adaptation in LLM strategic dialogues. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2026. arXiv:2601.13206.

[12] Federico Tiblias, Irina Bigoulaeva, Jingcheng Niu, Simone Balloccu, and Iryna Gurevych. Hypothesis-driven feature manifold analysis in LLMs via supervised multi-dimensional scaling. *Transactions on Machine Learning Research*, 2026. arXiv:2510.01025.

[13] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023.

[14] Jonas Wallat, Abdelrahman Abdallah, Adam Jatowt, and Avishek Anand. A study into investigating temporal robustness of LLMs. *arXiv preprint arXiv:2503.17073*, 2025.

[15] Yuqing Wang and Yun Zhao. TRAM: Benchmarking temporal reasoning for large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 6389–6415, 2024. arXiv:2310.00835.

[16] Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

A Experimental Details and Roadmap

A.1 Structured prompts

- Bank: 500 investment prompts (seed 0): 471 state a horizon, 29 don't (null control).
- Horizon grid (table 2): 48 values evenly spaced in log time from 30 seconds to 500 years, each 1.53 times the previous (about 5.4 per decade). Each value is written in the largest unit in which it is at least 2, rounded to a whole number (two significant figures above 100), so no value moves by more than 10% ("84 minutes", "15 months").
- Options: the near option pays \$1k–100k after 1 week to 1 year. The far option pays the near reward $\times \{2, 5, 10, 25, 50\}$ after 2–50 years. Option order is randomized.
- Regimes: neither option pays within the horizon, only the near one does, both do, or no horizon is given.

- Template variation: 4 phrasings of the constraint line (below), unit rewrites (the same duration in another unit, such as 23 months as 100 weeks), and two label styles (a)/b) and 1)/2)).
- Null control: the same prompt with the CONSTRAINT line removed.
- Verification grid: a separate set of prompts with matched units, around the boundary where the correct answer flips ($H/D \in [0.35, 2.8]$, where H is the stated horizon and D is the far option's delay). It does not overlap with the extraction prompts.

Sample prompt ($H/D = 0.8$, correct answer a):

```
SITUATION: Plan for the future of the household.
TASK: You, the head of the household, are tasked to choose the best investment:
 a) 10,000 dollars in 1 year.
 b) 50,000 dollars in 10 years.
OBJECTIVE: Think deeply about which option is preferable.
CONSTRAINT: You must select the option that provides the greatest benefit for
this time horizon:  8 years.
ACTION: Select one of the two options.  Provide reasoning.
FORMAT: I choose:  <a) or b)>.  My reasoning:  <1-3 sentences>
```

The four phrasings of the CONSTRAINT line, with `{H}` the rendered horizon:

1. `You must select the option that provides the greatest benefit for this time horizon: {H}.`
2. `Your planning horizon is {H}.  Choose the option that is best over that horizon.`
3. `Only outcomes within the next {H} matter for this decision.`
4. `Evaluate the two options over a time frame of {H} and pick the better one.`

Table 2: Horizon grid: the 48 stated horizons, grouped by the unit they are written in.

Unit	n	Values
seconds	4	30, 46, 71, 110
minutes	9	3, 4, 6, 10, 15, 23, 36, 55, 84
hours	8	2, 3, 5, 8, 12, 18, 28, 43
days	4	3, 4, 6, 10
weeks	4	2, 3, 5, 8
months	6	3, 4, 6, 10, 15, 23
years	13	3, 5, 7, 11, 16, 25, 39, 59, 91, 140, 210, 330, 500

A.2 Realism tiers (all investment)

- T1–T2: about 200 items each, generated with Haiku 5.5, checked by GPT-5.6 Luna, with a sample hand-audited.
- Investment risk is crossed with horizon, so that "long" does not always mean "safe".
- Every option in T1–T2 carries a duration h_i, which the expected-horizon readout uses (appendix A.5).

Table 3: Realism tiers.

Tier	Horizon cue	Answer	Readout	Example
T0 Structured	Explicit constraint line	a/b	Switch point	A.1
T1 Free-text	Explicit, in prose	a/b	Choice probability	"I need the money for a house deposit in 2 years. 2-year CD or 20-year index fund?"
T2 Implicit	Inferred	a/b, then 4/8 options	Expected horizon	"This is for my grandkids' education."
T3 Open-ended	Inferred	Free-form	Scalar from answer (equity share, bond duration)	"How should I allocate my savings? I'm retiring next spring."

Sample prompts for T1–T3 follow. They were written by us to show the format; the real items are generated as described above.

T1, free-text (stated horizon 2 years; expected answer a):

```
I'm saving for a house deposit and I'll need the money in 2 years.  I have
$30,000 to put away.  Which is the better choice for me?
 a) A 2-year certificate of deposit paying 4.5% a year.
 b) A global stock index fund, held for 20 years.
Start your answer with a) or b), then explain briefly.
```

T2, implicit, two options (horizon implied: about 18 years; expected answer b):

```
My daughter was born last week, and I want to set aside $10,000 for her
university education.  Which should I choose?
 a) A 1-year high-yield savings account, renewed each year.
 b) A global stock index fund, held until she starts university.
Start your answer with a) or b), then explain briefly.
```

T2, implicit, four options (horizon implied: under 1 year; $h_i = 1$ month, 1 year, 5 years, 20 years):

```
We're getting married next summer, and we want the $15,000 we've saved for the
wedding to grow a little until then.  Which option fits best?
 a) A high-yield savings account (withdraw at any time).
 b) A 1-year certificate of deposit.
 c) A 5-year bond fund.
 d) A stock index fund, held for 20 years.
Start your answer with a), b), c) or d), then explain briefly.
```

T3, open-ended (horizon implied; readout: equity share):

```
I'm 64 and I'm retiring next spring.  I have $400,000 in savings.  How should I
split it between stocks, bonds and cash?  Please give percentages.
```

A.3 Activations and steering

- Extraction site: residual stream at the answer-label token, at a layer fixed before evaluation. We will choose the layers based on results from prior work, locating the causal effect peaks at 0.61–0.69 of depth: layer 38 of 60 on Gemma 4 31B (the headline model, where the horizon geometry also peaks, fig. 1) and L24 on Qwen3-8B (the pilot).

- CAA: mean of long-horizon activations ($H/D \geq 4$) minus mean of short-horizon ones ($H/D \leq 1/4$), normalized. Strength is set as a fraction of the typical activation norm at that layer.
- Manifold curve: PCA on the per-horizon mean activations (top 3–8 components). We fit a smooth curve through them, indexed by log-time t. To steer, each token is projected onto the curve ($\hat{t}$) and moved to the curve point at $\hat{t} + \Delta$ (clamped to the observed range), leaving the rest of the activation unchanged. Δ is measured in decades.
- Positions: all tokens, as in prior work. Steering only generated tokens is run as a check.
- Statistics: repeated k-fold cross-validation grouped by prompt configuration, so paraphrases of one item never fall on both sides of a split.

A.4 Verification and calibration

- Switch point s: the stated H/D at which the model's choice flips from the near option to the far one. The acted-on horizon is $H^* = H/s$, so the steering effect is $\Delta \log H^* = -\Delta \log s$.
- Pass criteria:
  1. The shift in $\Delta \log H^*$ exceeds the 95th percentile of the random directions and also exceeds the reward-contrast direction.
  2. The shift has the same sign in both option orders.
  3. Steering does not move the model's reward-indifference point on prompts where both options pay off within the horizon.
- Calibration: α_k is the strength at which the model acts on a horizon k times longer (default $k = 2$). It is fixed here, separately for each steering direction, and never retuned on realistic prompts.

A.5 Metrics

- Expected horizon: $E[\log h] = \sum_i p_i \log h_i$ over the options. This is graded and works for 2, 4 and 8 options.
- Transfer efficiency: S/R, with a cluster-bootstrap 95% CI. S is the shift produced by steering at α_k. R is the shift produced by rewriting the prompt with a horizon k times longer.
- H2 precision: realized vs intended shift at matched norm. We also measure whether behavioural change is monotonic in Δ, and coherence as a function of distance to the curve.
- Health: coherence (LLM judge, validated on ∼50 hand labels), refusal, format failure and truncation at every strength. Broken outputs are counted as outcomes, not dropped.
- Baseline: prompting the model to "focus on the long term".

A.6 Roadmap

1. Pipeline: debug locally on a small Qwen3.
2. Extract and verify: gate and calibration on structured prompts. If the gate fails, stop before building realistic data.

3. H2: compare linear and manifold steering on held-out horizons.
4. H1: apply to T0 template variants (gate: ≥ 0.8 of the in-template effect), then T1 $\rightarrow$ T2 $\rightarrow$ T3.
5. Replicate: second model family, same rules, no new sweep.
6. Stretch: multi-turn robustness (steer only the reply to "are you sure?"); duration outside planning ("the movie lasted 3 hours").

Models: the headline model is Gemma 4 31B (instruction-tuned, `google/gemma-4-31B-it`; 60 layers, steered at layer 38). In a pilot with thinking on, it chose correctly in all 16 unit combinations tested, showed no option-order bias and never hit the 8,192-token cap (appendix B). Replication: Qwen3-8B, Qwen3-14B, Qwen3.5-27B and Qwen3-32B. Thinking is on, with a token cap.

B Exploratory Results

Table 4 lists the exploratory results behind the design choices in appendix A. They come from team members' studies during weeks 1–7, on the intertemporal-choice prompts of prior work.

Table 4: Exploratory results and the design choice each one supports.

Finding	Models	Result	Design choice
Ordered horizon geometry	Qwen3-8B, Qwen3-14B, Qwen3.5-9B, Qwen3.5-27B, Qwen3.8-27B, Gemma 4 31B	PC1 orders the stated horizons at the end of the user turn, with peak $\|\rho\|$ of 0.92–0.97 in all six models. Gemma 4 31B peaks at 0.63 of depth (fig. 1).	Steering layer: 38 of 60 on Gemma 4 31B.
Same direction with thinking on and off	Qwen3-8B	A horizon probe trained with thinking off reads thinking-on activations at $\rho = 0.98$–0.998.	Vectors can be extracted with thinking on.
Thinking fixes mismatched units	Qwen3-14B, Qwen3.8-27B, Gemma 4 31B	When the horizon and delay use different units and $H < D$, the far option is chosen 0.55–0.73 of the time without thinking and 0.00–0.01 with it. With thinking, Gemma switches at $H/D \approx 1.02$ in all 16 unit combinations.	Thinking on; the switch point is a usable verification gate.
Readable does not mean used	Qwen3-14B, Qwen3.5-27B, Qwen3.8-27B, Gemma 4 31B	Reward size is linearly decodable in all four, but changes choices only in Qwen3.5-27B: standardized coefficient +0.30 (90% CI $[+0.15, +0.45]$), against +0.05 and +0.08 (CIs include zero) in Qwen3.8-27B and Gemma.	Intervene rather than probe; reward-contrast control direction.
Option order shifts choices	Qwen3-14B, Qwen3-32B	Listing the near option first raises P(near) by 0.16 (95% CI $[0.06, 0.25]$) on Qwen3-14B and by 0.01 ($[-0.06, 0.09]$) on Qwen3-32B, averaged over prompt phrasings.	Randomize option order and labels; require the same sign in both orders.




Figure 1: Horizon ordinality by depth: $|\rho|$ between PC1 and log horizon at three token positions (end of user turn, role token, first response token) for six models, on canonical investment prompts. Depth is layer / number of layers.