

# COMS30035, Machine learning: Sequential Data 3: EM for HMMs

Edwin Simpson

`edwin.simpson@bristol.ac.uk`

Department of Computer Science, SCEEM  
University of Bristol


November 3, 2020

# Agenda

- ▶ Markov Models
- ▶ Hidden Markov Models
- ▶ EM for HMMs
- ▶ **Linear Dynamical Systems**
- ▶ Bayesian Timeseries Modelling with Gaussian Processes

# Generalising the Hidden Markov Models

- ▶ HMM assumes discrete latent states.
- ▶ Linear dynamical systems (LDS) assume states have continuous values.
- ▶ Both have the same graphical model:



- ▶ Inference has the same form as for an HMM, but when marginalising  $\mathbf{z}_{n-1}$  and  $\mathbf{z}_{n+1}$ , we take integrals instead of sums.

# Motivations for LDS

- ▶ Noisy sensors: inferring the true sequence of states from observations with Gaussian noise.
- ▶ Tracking: predicting the next movement and tracing the path from noisy observations.

# Transition and Emission Distributions for LDS

- ▶  $p(\mathbf{z}_1) = \mathcal{N}(\mathbf{z}_1 | \boldsymbol{\mu}_0, \mathbf{V}_0);$
- ▶  $p(\mathbf{z}_n | \mathbf{z}_{n-1}) = \mathcal{N}(\mathbf{z}_n | \mathbf{A}\mathbf{z}_{n-1}, \boldsymbol{\Gamma});$
- ▶  $p(\mathbf{x}_n | \mathbf{z}_n) = \mathcal{N}(\mathbf{x}_n | \mathbf{C}\mathbf{z}_n, \boldsymbol{\Sigma}).$
- ▶ Note that the means of both distributions are *linear* functions of the latent states.
- ▶ This choice of distributions ensures that the posteriors are also Gaussians with updated parameters
- ▶ This means that  $\mathcal{O}(N)$  inference can still be performed using the sum-product algorithm.

# Inference for an LDS

- ▶ *Kalman filter* = forward pass of sum-product for LDS.
- ▶ *Kalman smoother* = backward pass of sum-product for LDS.
- ▶ No need for an analogue of Viterbi: the most likely sequence is given by the individually most states, so we get this from the Kalman equations.

# Forward Inference (Kalman Filter) for an LDS



$$\alpha(\mathbf{z}_n) = \mathcal{N}(\mathbf{x}_n | \mathbf{C}\mathbf{z}_n, \Sigma) \int \mathcal{N}(\mathbf{z}_n | \mathbf{A}\mathbf{z}_{n-1}, \Gamma) \alpha(\mathbf{z}_{n-1}) d\mathbf{z}_{n-1} \quad (1)$$

- ▶ Normalising results in a Gaussian-distributed variable, whose parameters can be computed efficiently:

$\hat{\alpha}(\mathbf{z}_n) = p(\mathbf{z}_n | \mathbf{x}_1, \dots, \mathbf{x}_N) = \mathcal{N}(\mathbf{z}_n | \boldsymbol{\mu}_n, \mathbf{V}_n)$ , where

- ▶  $\boldsymbol{\mu}_n$  is a function of  $\boldsymbol{\mu}_{n-1}$ ,  $\mathbf{x}_n$ ,  $\mathbf{A}$  and  $\mathbf{C}$ .
- ▶  $\mathbf{V}_n$  is a function of  $\mathbf{V}_{n-1}$ ,  $\Sigma$ ,  $\mathbf{A}$ ,  $\Gamma$  and  $\mathbf{C}$ .
- ▶ We can view each forward step as predicting  $\mathbf{z}_n$  based on the distribution over  $\mathbf{z}_{n-1}$ , then correcting that prediction given the new observation  $\mathbf{x}_n$ .
- ▶ For details, see Bishop (2006), Section 13.3.1

# Backward Inference (Kalman Smoother) for an LDS

- ▶ Backward pass also follows that of the HMM: messages are passed from the final state to the start of the sequence.
- ▶ The backward messages contain information about future states that affects the posterior distribution at each step  $n$ .
- ▶ Since the transition and emission probabilities are all Gaussian, the posterior *responsibilities* are also Gaussian, as are the *state pair* expectations.
- ▶ For details, see Bishop (2006), Section 13.3.1



# Learning the Parameters of LDS

- ▶ Kalman filter/smoothing are analogous to the forward-backward algorithm for HMMs.
- ▶ Remember that this algorithm is used for the *E step* of EM.
- ▶ The parameters are optimised in the *M step* as before, by using the responsibilities  $\mathbb{E}[\mathbf{z}_n]$ ,  $\mathbb{E}[\mathbf{z}_n \mathbf{z}_n^T]$  and state pair expectations  $\mathbb{E}[\mathbf{z}_n \mathbf{z}_{n-1}^T]$ .
- ▶ For details, see Bishop (2006), Section 13.3.2

# Now do the quiz!

Please do the quiz for this lecture on Blackboard.