## PROGRAMMING LANGUAGES AND COMPUTATION

## Problem Sheet 11: The Halting Problem & Reductions

** 1.	Show that if <i>f</i>	$: U \lesssim V$	and $g: V \lesssim W$	then $g \circ f : U \lesssim W$ .
-------	-----------------------	------------------	-----------------------	-----------------------------------

## \*\* 2. Is the set

LUCKY<sub>127</sub> = {  $\gamma(S)$  | running S on input 1 runs for at least 127 computational steps }

decidable? (Hint: if it is, describe a program that decides it. Think simply, write informally, and do not let the expressive poverty of While confine you.)

\*\*\* 3. Suppose we have a way of encoding every DFA M as a natural number  $\delta(M) \in \mathbb{N}$ . Is the predicate

$$\mathsf{EMPTY} = \{ \delta(M) \mid L(M) = \emptyset \}$$

decidable? Why, or why not? (Hint: the advice from the previous question applies here too.)

- \*\* 4. (Trick question.) Is it decidable whether God exists?
- \*\* 5. Prove that if  $f: A \xrightarrow{\cong} B$  is a bijection, then so is its inverse  $f^{-1}: B \to A$ .
- \*\*\* 6. Prove that the set

$$\mathbb{N} \to \mathbb{N} = \{ f \mid f : \mathbb{N} \to \mathbb{N} \}$$

is uncountable.

\*\*\*\* 7. Prove that the set

$$ONE = \{ \gamma(S) \mid \llbracket S \rrbracket_{x}(0) \downarrow \}$$

is undecidable by reduction from HALT.