

[3.5](#)[3.4](#)[3.3](#)

Getting Started

This guide assumes that you know how to run a local server, work with git version control and run tools from the command line.

This section will describe how to install the application in a local development environment and stay up-to-date with the latest changes. It is intended for developers who want to work with the source code. Read the [Admin Guide](#) to learn how to install and host the application in a production environment.

System Requirements

If you are using Windows, you may need to install GNU Patch and add it to your system's **PATH** environment variable.

The Admin Guide describes the [system requirements](#). When running locally, many of the recommended dependencies are not required.

Install

Fork and clone the [OJS](#), [OMP](#), or [OPS](#) repository on GitHub. (Read more about [forking and cloning a repository](#) on GitHub).

```
git clone https://github.com/pkp/ojs --recurse-submodules -b stable-3_4_0
```

[3.5](#)[3.4](#)[3.3](#)

Next, copy the default config file:

```
cp config.TEMPLATE.inc.php config.inc.php
```

Open the `config.inc.php` file, find the database settings, and update them to match the credentials for your SQL server.

```
[database]
```

```
driver = <driver>    # mysql or postgres9
host = <host>        # usually `localhost`
username = <user>
password = <pass>
name = <db>
```

Find the `[email]` settings in the config file and route emails to the server `log` or a [local SMTP server](#).

```
[email]
```

```
; Default method to send emails
; Available options: sendmail, smtp, log
default = log
```

Install dependencies with [composer](#).

```
composer --working-dir=lib/pkp install
```

[3.5](#)[3.4](#)[3.3](#)

```
composer --working-dir=plugins/paymethod/paypal install
```

Install dependencies and build the JavaScript package with [NPM](#).

```
npm install  
npm run build
```

Run the following command to launch the application using PHP's built-in server.

```
php -S localhost:8000
```

Load your browser and navigate to <http://localhost:8000> to install the application.

Branches

Published versions of the software can be found in branches in the git repository. For example, run the following command to check out the latest 3.4.0-x version of the software.

```
git checkout stable-3_4_0
```

For any customization work, base your own branches on one of the stable branches. That should make it easier to maintain compatibility with plugins and future updates, and it locks down all dependencies to the versions used at the time of release. This is not true of the [main](#) branch,

[3.5](#)[3.4](#)[3.3](#)

Remotes

To get changes to the application that were made after you forked, add the `upstream` remote.

For OJS:

```
git remote add upstream git@github.com:pkp/ojs.git
cd lib/pkp
git remote add upstream git@github.com:pkp/pkp-lib.git
cd ../ui-library
git remote add upstream git@github.com:pkp/ui-library.git
cd ../..
```

For OMP:

```
git remote add upstream git@github.com:pkp/omp.git
cd lib/pkp
git remote add upstream git@github.com:pkp/pkp-lib.git
cd ../ui-library
git remote add upstream git@github.com:pkp/ui-library.git
cd ../..
```

For OPS:

```
git remote add upstream git@github.com:pkp/ops.git
cd lib/pkp
git remote add upstream git@github.com:pkp/pkp-lib.git
cd ../ui-library
```

[3.5](#)[3.4](#)[3.3](#)

```
# Update the app
git checkout main
git pull upstream main
git push

# Update the pkp-lib submodule
cd lib/pkp
git checkout main
git pull upstream main
git push

# Update the ui-library submodule
cd ../ui-library
git checkout main
git pull upstream main
git push

cd ../../
```

Updates

When you have pulled down changes from the `upstream` remote, run the following to sync the `lib/pkp` and `lib/ui-library` submodules.

```
git submodule update --init --recursive
```

You may need to update dependencies and rebuild the JavaScript package.

```
composer --working-dir=lib/pkp update
npm install
```

[3.5](#)[3.4](#)[3.3](#)

```
php tools/upgrade.php upgrade
```

Contributions

Read the [Contributor's Guide](#) to learn more about [how to prepare a pull request](#).

Now that you're up and running, learn more about the [application architecture](#).

[Edit this page](#) or [make a suggestion](#)

[3.5](#)[3.4](#)[3.3](#)

If your message is not about documentation, please use the general contact form.

COMMUNITY

[DOCUMENTATION INTEREST GROUP](#)[CONTRIBUTING DOCUMENTATION](#)[TRANSLATING GUIDE](#)[COMMUNITY FORUM](#)

ABOUT

[PUBLIC KNOWLEDGE PROJECT](#)[PKP|PUBLISHING SERVICES](#)[DOCS](#)

The Public Knowledge Project is a Core Facility of Simon Fraser University

888 University Drive, Burnaby, B.C., Canada V5A 1S6

We respectfully acknowledge that SFU occupies the unceded traditional territories of the Coast Salish peoples of the Musqueam, Squamish, and Tsleil-Waututh Nations.

3.5

3.4

3.3
