

Voting Guide

The May–June 2026 Zally shielded-voting deployment snapshot

m@rek.onl

Abstract

This volume of *The Zcash Arboretum* documents the commit-pinned May–June 2026 shielded-voting deployment snapshot. No specification of the protocol has merged anywhere; the commit-pinned implementation is the de facto specification, and this volume documents that implementation: ballot structure and eligibility proving against a snapshot of the note-commitment tree, the layered nullifier defences against double voting, threshold ElGamal tallying under a validator DKG, and — stated without euphemism — the trust assumptions, the quantisation gap between the published description and the circuit, and an unestablished delegation-signature binding.

Contents

1	The protocol and its provenance	3
1.1	What shipped	3
1.2	Lineage	4
1.3	The source situation: code as the de facto specification	4
2	Ballots and eligibility	6
2.1	The five-message round	6
2.2	Eligibility: the note-bundle relation (ZKP1)	7
2.3	Snapshot non-spentness: the Poseidon indexed Merkle tree	9
2.4	The snapshot roots: posted, never verified	10
2.5	Weight: ballot quantization	10
3	Vote encryption, nullifiers, and tally	12
3.1	The Vote Authority Note	12
3.2	Keystone authorisation: the synthetic signed note	13
3.3	Double-vote prevention: four layers	14
3.4	Vote encoding: sixteen lifted-ElGamal shares	15
3.5	The Election Authority: a per-round Joint-Feldman DKG	16
3.6	Tally: chain-verified threshold decryption	17
4	Trust model and verdict	18
4.1	The trust map	18
4.2	Claim inventory: the three bins	21
4.3	Verdict	21

1 The protocol and its provenance

This volume documents the *Shielded Voting Protocol* — internally “Zally”, shipped to wallet users as *Coinholder Polling*. The protocol lets a holder of Orchard notes vote with the weight of their unspent funds, privately: the funds never move, note and address openings remain hidden, and weights are encrypted. Individual share decisions do become public at reveal; the trust map below qualifies the privacy claim. The internal name appears in the client library’s own description of itself (“the Zally governance protocol”, `valargroup/zcash_voting @ 624cf198`, `README.md`); the draft ZIP carries the public name (`draft-valargroup-shielded-voting.md`, `zcash/zips PR #1200`); the wallet changelog carries the product name (`zashi-android @ b4edd6f6`, `CHANGELOG.md`). This section fixes what shipped, where the design came from, and — decisive for every citation in this volume — what the specification actually is.

1.1 What shipped

In outline: a voting round pins a snapshot of the Zcash chain — an Orchard note-commitment root and a nullifier-set root. A holder proves in zero knowledge that they control notes which existed and were unspent at the snapshot, and delegates their quantised weight — one ballot per 0.125 ZEC (12,500,000 zatoshi per ballot, `voting-circuits/src/params.rs`) — to a round-scoped governance hotkey. The hotkey casts each vote as ElGamal-encrypted split shares on a dedicated permissioned chain, `svoted`, whose ballot surface is five messages (`vote-sdk/proto/svote/v1/tx.proto`); relayers reveal shares with timing decorrelation; and a per-round threshold *Election Authority* — a distributed key generation among the chain’s validators — decrypts aggregates only (`vote-sdk/x/vote/keeper/keeper_tally.go`). The remainder of this volume constructs each of these objects in turn; here we record only their provenance.

Deployment. Coinholder Polling shipped in Zodl — the wallet formerly Zashi; the team left ECC in January 2026 and the application package identity is unchanged — version 3.5.0 on Android and iOS, released 2026-05-28, with signing support for the Keystone hardware wallet (`zashi-android @ b4edd6f6`, `CHANGELOG.md`, entry [3.5.0 (1736)]); a follow-up release, 3.5.2, followed on 2026-06-04 (*ibid.*, entry [3.5.2 (1742)]). The intended first production use — the NU7 sentiment coinholder poll, announced 2026-05-15 with a 2026-06-10 open, its close extended on 2026-05-29 from June 24 to June 29 to end with the parallel ZCAP poll of the same questions — never ran. On 2026-06-07 — three days before the open, the day after the NU7 scope collapsed to the Ironwood supply-soundness upgrade — the poll was paused “for both coin holders and the Zcash Foundation ZCAP”, and as of 2026-06-14 the next round “is delayed until after Ironwood activates”. No results exist for that unheld June round. A production round was provisioned in the signed round registry on 2026-06-05 (§4.1), but no public evidence shows a ballot cast (searched 2026-07-15).¹

¹Announcement: josh, “NU7 Sentiment Polling: Questions for Community Review & Coinholder Voting via Zodl”, forum topic 55713, 2026-05-15; extension: *ibid.* post 71, 2026-05-29; pause: *ibid.* post 73, 2026-06-07. Wayback snapshot of the topic carrying the pause notice, 2026-07-15: <https://web.archive.org/web/20260715193300/https://forum.zcashcommunity.com/t/nu7-sentiment-polling-questions-for-community-review-coinholder-voting-via-zodl/55713>; pre-pause schedule (RSS snapshot, 2026-06-05): <https://web.archive.org/web/20260605074855/https://forum.zcashcommunity.com/t/nu7-sentiment-polling-questions-for-community-review-coinholder-voting-via-zodl/55713.rss>. Scope change: “Ironwood: Verifying the Soundness of Zcash’s Circulating Supply”, topic 56044, 2026-06-06, Wayback 2026-07-15: <https://web.archive.org/web/20260715193458/https://forum.zcashcommunity.com/t/ironwood-verifying-the-soundness-of-zcash-s-circulating-supply/56044>. Deferrals: ZODL updates, topic 56072, 2026-06-07, Wayback 2026-07-15: <https://web.archive.org/web/20260715193328/https://forum.zcashcommunity.com/t/subduing-the-world-update-from-zodl/56072>; and topic 56211, 2026-06-14, Wayback 2026-07-15: <https://web.archive.org/web/20260715193352/https://forum.zcashcommunity.com/t/irrational-thinking-zodl-update/56211>.

This is not the end of the NU7 polling history. The August–September rounds have published results; ZIP 259, merged on 2026-09-22, records their role in the present NU7 scope (zips afa086bd, checked 2026-09-23). Those later rounds must not be confused with the unheld June round or used to attribute their deployed implementation to this volume’s May–June code snapshot.

Authorship. Valar Group designed and implemented the protocol, led by Dev Ojha (GitHub ValarDragon); the draft ZIP is authored by GitHub user p0mvn, also of Valar Group. The upstream orchard crate gained the protocol’s one in-tree dependency — the `unstable-voting-circuits` feature, which widens circuit internals (the `NoteCommit`, `nullifier-derivation`, and `Commitivk` chips) for out-of-tree reuse — in a commit by Adam Tucker (zcash/orchard @ c0b6b917, 2026-04-23). ZODL engineers str4d (Jack Grigg), Daira-Emma Hopwood, and Kris Nuttycombe reviewed — they did not design — the architecture in Q1 2026 (ZODL retroactive grant application, ZcashCoinholderGrantsProgram issue #33); ZODL also built the wallet integration.

1.2 Lineage

Coin-weighted shielded polling on Zcash has one prior implementation: hhanh00’s `zcash-vote`, a standalone application that ran the 2024 developer-fund poll and the April–May 2025 lockbox poll (hhanh00/zcash-vote @ f05f5f25, `src/election.rs`; it depends on a forked orchard at rev 75448e67 with a `vote` feature). Its ZIP — `zcash/zips` PR #853, “Coin Voting ZIP” — has been open since 2024-05-28 and remains unmerged as of 2026-07-08. Zally is independent of it: neither codebase references the other (verified by search over both trees, 2026-07-08), and Zally reuses the upstream orchard crate through a feature flag where `zcash-vote` patches in its fork. The two share the core idea — pin a snapshot, prove note eligibility against it, and prevent double voting with a per-election nullifier — but Zally adds hotkey delegation through a dedicated note type (the Vote Authority Note), split ElGamal shares, a threshold Election Authority, relayers, private eligibility queries by single-server PIR (private information retrieval: the server answers without learning which entry was queried), a dedicated chain, and hardware signing, and it lives inside the production wallet rather than beside it.

Two adjacent mechanisms are not ancestors. ZCAP, the Zcash Community Advisory Panel, polls an identified panel through Helios with no coin weighting; the June 2026 NU7 question was scheduled through both instruments in parallel and paused for both together (§1.1), which makes the distinction operational, not academic. Hopwood’s draft `draft-ecc-onchain-accountable-voting.md` (created 2025-02-21, in the merged zips tree at c6b70358) targets the complement — accountable on-chain voting by identified key-holders — and shares no design lineage with either.

1.3 The source situation: code as the de facto specification

No normative document exists. The would-be specification, `zcash/zips` PR #1200 (“[ZIP TBD] Shielded Voting Protocol”, opened 2026-03-05), is open and unmerged as of 2026-07-08, not updated since 2026-06-02, and carries a review comment flagging a section as “Underspecified”; the companion PIR draft, PR #1198, is likewise open. The design book the implementation itself cites — `valargroup/shielded-vote-book`, linked from the `zcash_voting` README — is private, as is its mirror `z-cale/shielded-vote-book` (both return 404 to anonymous access, verified 2026-07-08). The public documentation (`valargroup.gitbook.io/shielded-vote-docs`, fetched 2026-07-08) is prose: its circuit pages list public and private inputs and some Poseidon preimages (the arithmetisation-friendly hash constructed in the *Crypto Guide*, §“Arithmetisation-friendly hashing: Poseidon”), but omit the governance-nullifier, VAN-nullifier, and share-nullifier formulas, the nullifier-domain derivation, the proposal-bitmask width, and the indexed-Merkle-tree leaf

model — and it misstates the ballot-quantisation rule, the sole open problem this volume records (the closing paragraph of this section).

The consequence governs this volume: the commit-pinned implementation of Table 1 is the de facto specification, and what we document is that implementation. Every governance-specific formula in the chapters that follow is read from these sources at these commits, never from designer prose; where the prose and the code disagree, the code is the protocol, and we flag the disagreement.

Repository	Commit	Date	Role
valargroup/voting-circuits	4c39abd5	2026-06-03	circuits: prover <i>and</i> verifier
valargroup/vote-sdk	cb915f51	2026-06-05	vote chain: validation, DKG, tally
valargroup/zcash_voting	624cf198	2026-06-07	client: proofs, scheduling, persistence
valargroup/vote-nullifier-pir	603e4e3b	2026-06-03	PIR: nullifier non-membership
valargroup/spendability-pir	a924008d	2026-06-04	PIR: spendability and witness queries
zcash/orchard	c0b6b917	2026-04-23	unstable-voting-circuits feature

Table 1: The de facto specification: the sources this volume documents, pinned by commit. Wallet-side integration is pinned separately: `zcash-android-wallet-sdk @ f386369e` depends on `zcash_voting =0.11.0` and `orchard =0.14.0` with the `unstable-voting-circuits` feature (`backend-lib/Cargo.toml`); `zashi-android @ b4edd6f6`, `zashi-ios @ 8ab0e6ed`.

Current-head boundary (2026-08-30). The implementation has moved substantially since this snapshot. Current heads are `voting-circuits bd2531f` (release 0.11.2), `vote-sdk 7cf9b9c`, `zcash_voting 4535b0d`, and `vote-nullifier-pir 20e9c4a` (release 0.11.2). The current delegation builder requires Ironwood V3 notes, the circuit verifying keys and integration APIs have changed, and the client, chain, and PIR services have gone through several coordinated release lines. The one-ballot under-claim window proved in this volume remains explicitly documented in the current circuit. Unless a paragraph names one of these later heads, every formula and deployment-behaviour claim below is about the pinned snapshot in Table 1; this is historical protocol documentation, not a compatibility guide for the current stack.

The single-crate caveat. Crate `voting-circuits` exposes both the provers and the verifiers of all three circuits (`verify_delegation_proof`, `verify_vote_proof`, and `verify_share_reveal_proof`, each in its circuit directory’s `prove.rs`), and the chain consumes the same crate for validation: `vote-sdk/circuits/Cargo.toml` pins `voting-circuits` at version 0.8.0, and `vote-sdk/x/vote/ante/validate.go` invokes it. At matching circuit versions and configurations, wallet and chain share the same relation implementation. That reduces one source of drift but is not independent evidence of correctness. No independent second implementation is identified at these pins that could catch a mis-transcribed relation, and no merged specification exists against which either side could be audited. The reader should weigh every constraint we state in later sections with this in mind.

Classification. Design-stage material in this volume obeys a three-bin discipline. Every claim is exactly one of: *specified* — a merged normative artifact exists and we cite it; *designed but unspecified* — the design is concrete and open-source but no normative artifact pins it, so we cite the implementation and state what a specification would need to fix; or an *open problem* — the design itself leaves the question unresolved. The bin is always visible in the prose.

Specified. Only the inherited primitives: `NoteCommit`, nullifier derivation, `Commitivk`, the Sinemilla Merkle instance, `RedPallas`, the ZIP-244 sighash, and ZIP-32 key derivation —

each specified in the Zcash protocol specification and the ZIPs, constructed in the *Ironwood Guide* (§“Note commitments”, §“The nullifier”, §“Keys and addresses”, §“The Merkle hash and the tree”, §“The RedPallas signature scheme”), and reused unchanged through the `unstable-voting-circuits` feature (zcash/orchard @ c0b6b917). No governance-specific object has a specification of that rigor.

Designed but unspecified. Everything else this volume presents: the five-message ballot structure, the delegation relation with its indexed-Merkle-tree non-membership argument, the coordinator-posted snapshot roots, the Vote Authority Note and its synthetic-action authorisation, all four double-vote layers, the split-share ElGamal encoding and vote commitment, the relayer protocol and the trust it grants, the per-round DKG and chain-verified tally, and the PIR subsystem. For each we cite the pinned commit and file, and we note what PR #1200 would need to pin down for the object to change bins.

Open problems. The ballot-quantisation relation enforced by the delegation circuit is strictly weaker than the exact floor division the public documentation states — the relation admits a one-ballot *under*-claim for roughly a third of note-value totals, while an over-claim remains impossible (`voting-circuits/src/delegation/circuit.rs`, `src/delegation/README.md` §8). We state and analyse the gap where delegation weight is constructed. Separately, the chain verifies a client-supplied delegation sighash without establishing its binding to the proved delegation fields (§3.2). This is not a claim of a demonstrated live exploit, but it prevents treating the intended hardware-wallet authorisation as established by these checks.

2 Ballots and eligibility

A voting round is a conversation in five messages on the vote chain, and admission to it is a zero-knowledge proof against a pinned Zcash snapshot. This section constructs both sides of that admission: the wire surface of a round (§2.1); the eligibility relation the delegation circuit proves — ownership of Orchard notes that existed at the snapshot and were unspent at it (§2.2, §2.3); the provenance of the two snapshot roots those proofs are checked against (§2.4); and the quantization that turns note value into voting weight (§2.5). Except where marked otherwise, every claim below sits in the *designed but unspecified* bin of §1.3: we read it from the commit-pinned sources of Table 1, and each subsection closes by recording its bin. The quantisation mismatch is one of this volume’s open problems; we state and prove its exact extent where it arises.

2.1 The five-message round

The ballot surface of the vote chain is five protobuf messages (`vote-sdk/proto/svote/v1/tx.proto`). In lifecycle order: a coordinator opens the round, holders delegate weight, governance hotkeys cast votes, helper servers reveal shares, and the round closes with a tally. The vote chain is a Cosmos-SDK application, and an ordinary transaction there is a fee-paying envelope of messages signed by an on-chain account. The three voter-facing messages (2–4) are not ordinary Cosmos transactions: they bypass that envelope entirely, and the chain authenticates each by its zero-knowledge proof — messages 2 and 3 additionally by a RedPallas signature; message 4 carries none — rather than by an account signature (`tx.proto:10-13`; `vote-sdk/x/vote/ante/validate.go`).

Message 1: `MsgCreateVotingSession`. The round-opening message carries the snapshot pin and the agenda: `snapshot_height`, `snapshot_blockhash`, `proposals_hash`, `vote_end_time`, the two ledger anchors `nullifier_imt_root` and `nc_root`, the proposal list, and display metadata

(tx.proto:36-48). It is not a public RPC: it is absent from the Msg service and executes only as the payload of a threshold-approved coordinator action (vote-sdk/x/vote/keeper/msg_server_coordinator_actions.go:294-298). The handler derives the round identifier on-chain as one Poseidon hash over the creation height, the snapshot block hash and the proposals hash (each split into two field elements), the end time, and both anchors, so `vote_round_id` commits to the snapshot (tx.proto:32-35; msg_server.go:30-48).

Message 2: MsgDelegateVote (ZKP1). The delegation message carries `rk` (the randomized spend-validating key), `spend_auth_sig` (RedPallas), `signed_note_nullifier` (the nullifier of the synthetic keystone note), `cmx_new` (the output note commitment), `van_cmx` (the Vote Authority Note commitment), `gov_nullifiers` (up to five governance nullifiers), `proof`, `vote_round_id`, and `sighash` — a *client-provided* 32-byte value over which the chain verifies the RedPallas signature without recomputing it (tx.proto:55-65). This section proves the eligibility half of the message; the Vote Authority Note is constructed in §3.1, and the synthetic keystone note with its signature binding — the ρ -chain through which the RedPallas signature commits to the whole delegation — in §3.2.

Message 3: MsgCastVote (ZKP2). A cast vote carries `van_nullifier`, `vote_authority_note_new` (the successor Vote Authority Note), `vote_commitment`, `proposal_id`, `proof`, `vote_round_id`, the anchor height `vote_comm_tree_anchor_height`, `vote_auth_sig`, and `r_vpk`, a compressed Pallas point that the chain decompresses for the verifier; unlike message 2, the `sighash` here is recomputed on-chain (tx.proto:72-84, including the removed-field comments).

Message 4: MsgRevealShare (ZKP3). A share reveal carries `share_nullifier`, `enc_share` — 64 bytes, one lifted-ElGamal ciphertext $C_1 \parallel C_2$ (ElGamal with the plaintext in the exponent, Definition 3.2) as compressed Pallas points — `proposal_id`, `vote_decision`, `proof`, `vote_round_id`, and `vote_comm_tree_anchor_height` (tx.proto:89-97). Helper servers, not wallets, submit it: the share nullifier is constructed in §3.3, and the helper protocol and the trust it grants are treated in §4.1.

Message 5: MsgSubmitTally. The closing message carries `vote_round_id`, `creator` — which the chain checks against the *block proposer*: the proposer’s node injects the message during tallying, and the proto comment naming the session creator is unenforced (x/vote/keeper/msg_server_tally_decrypt.go:77-79; app/prepare_proposal.go:194-212) — and one `TallyEntry` {`proposal_id`, `vote_decision`, `total_value`, `decryption_proof`} per (proposal, decision) pair (tx.proto:104-116). The `total_value` field is denominated in ballots despite its proto comment saying *zatoshi*; we return to this in §3.6.

Classification. Designed but unspecified: the message set, field semantics, and transport exist only in `vote-sdk/proto/svote/v1/tx.proto` at commit `cb915f51` (Table 1). A specification would need to pin the byte-level encoding and length of every field, the validation order, the envelope-bypass transport, and the round-identifier derivation — the last currently fixed only by a proto comment and the FFI implementation it describes.

2.2 Eligibility: the note-bundle relation (ZKP1)

To delegate weight, a holder must prove three things about a set of Orchard notes without revealing any of them: the notes are theirs; each existed at the snapshot; each was unspent at the snapshot. The delegation circuit proves the conjunction — one Halo2/IPA circuit (the proof system and inner-product commitment of the *Halo 2 Guide*, §“The Halo 2 proof system”, §“The

inner-product polynomial commitment”) over Pallas at $K = 14$ (16,384 rows) with 14 public inputs (voting-circuits/src/delegation/circuit.rs:111 and the module README, both at commit 4c39abd5).

Bundle shape. The circuit carries exactly five note slots (`MAX_REAL_NOTES`); a wallet with fewer notes pads the remaining slots with zero-value notes, and one with more produces multiple delegation proofs. The fixed width is deliberate: every delegation publishes the same shape — five governance nullifiers at public-input offsets 8–12 — so the published proof does not reveal how many real notes it bundles (src/delegation/README.md, Inputs). The two ledger anchors enter as public inputs `nc_root` (offset 6) and `nf_imt_root` (offset 7); the nullifier domain `dom` (offset 13) is exposed for API compatibility but constrained in-circuit to `Poseidon(tag, vote_round_id)`, where `tag` is the ASCII string `governance authorization` zero-padded to a Pallas base-field element (src/domain_tags.rs; src/delegation/imt.rs:26–35). `Poseidon` throughout the protocol is the `P128Pow5T3` instance, width 3, rate 2 (src/protocol_hash.rs).

Per-slot conditions. Each slot proves six conditions, numbered 9–14 in the source² (src/delegation/circuit.rs:1497–1805):

- *Note commitment integrity* (condition 9). The prover witnesses the note plaintext $(g_d, pk_d, v, \rho, \psi)$, the trapdoor `rcm`, and the claimed commitment `cm`; the circuit recomputes `NoteCommitrcm` over the witnessed fields, constrains it equal to `cm`, and extracts `cmx = Extract(cm)` as an internal wire. The commitment scheme is the deployed Orchard `NoteCommit` — specified bin, reused unchanged through the unstable-voting-circuits feature (§1.3).
- *Address ownership* (condition 11). The circuit checks $pk_d = [ivk^*]g_d$, where ivk^* is selected by a witnessed boolean `is_internal` through the custom gate `q_scope_select`, $ivk^* = ivk + is_internal \cdot (ivk_{int} - ivk)$; both candidates are derived in-circuit by `Commitivk` from the witnessed r_{ivk} and its internal-scope counterpart (condition 5, global). Change notes therefore carry weight on equal terms with externally received ones. A wrong scope flag selects the wrong key and the ownership check rejects.
- *Snapshot membership* (condition 10). The circuit computes the Sinsemilla Merkle root from the leaf `cmx` over the witnessed 32-level authentication path, and the per-note gate `q_per_note` enforces

$$v \cdot (\text{root} - \text{anchor}) = 0,$$

with anchor the public `nc_root` (circuit.rs:1777–1798). A real note ($v \neq 0$) must resolve to the anchor; a zero-value padding note — which has no leaf in the Zcash tree — satisfies the gate vacuously.

- *Real nullifier* (condition 12). The circuit derives the note’s true Orchard nullifier $nf = \text{DeriveNullifier}_{nk}(\rho, \psi, cm)$ — the deployed Orchard rule, constructed in the *Ironwood Guide* (§“The nullifier”) — in-circuit and *never publishes it*: it exists only as a private wire feeding conditions 13 and 14 (circuit.rs:1682–1701).
- *Snapshot non-spentness* (condition 13). The circuit proves non-membership of `nf` in the snapshot’s nullifier set under the public `nf_imt_root` — the construction of §2.3. The root

²The headline counts disagree — `circuit.rs` line 3 says “all 14 conditions” but line 108 “all 15 conditions”; `README.md` lines 3 and 52 say “15” and “conditions 9–15” — yet the condition-by-condition definitions in both files stop at 14: the `README`’s numbered sections run 1 through 14, and the sole “condition 15” in the sources is a synthesis-stage comment (circuit.rs:1089–1098) labelling the padded slots’ zero value — a builder convention with no corresponding constraint. We state the total as fourteen — eight keystone-global conditions plus six per-slot conditions instantiated five times — and record the “15” headline counts and the `cond-15` comment as stale.

equality is unconditional: padding notes, too, must carry a valid non-membership proof (README.md §13).

- *Governance nullifier* (condition 14). The circuit computes and publishes $\text{nf}^{\text{gov}} = \text{Poseidon}(\text{nk}, \text{dom}, \text{nf})$ at the slot's public-input offset. Keyed by the private nk , the published value stays unlinkable to nf even after the note is later spent on the main chain (circuit.rs:1703–1729). Its role in double-vote prevention is treated in §3.3. Chain-side, the delegation handler applies the same atomic check-and-set to all five published slots, padding included (vote-sdk/x/vote/keeper/msg_server.go:148–154); a padding slot's nullifier enters the same round-scoped set, unique because the wallet samples fresh ρ and rseed per synthetic padding note (src/delegation/builder.rs, build_padding_slot), and a re-used padding witness is rejected as a duplicate delegation — a completeness cost, never a soundness one.

The conjunction across a slot reads: the prover's key material owns a note whose commitment lies in the Zcash note-commitment tree at the snapshot (membership under nc_root) and whose nullifier had not been revealed by the snapshot (non-membership under nf_imt_root) — existed, and unspent, at the pinned height.

Classification. The relation as a whole is designed but unspecified: it exists only as the circuit at voting-circuits @ 4c39abd5, which is simultaneously the prover and the verifier (§1.3). Its ingredients NoteCommit, nullifier derivation, $\text{Commit}^{\text{ivk}}$, and the Sinsemilla Merkle instance are the specified bin, inherited through zcash/orchard @ c0b6b917. A specification would need to pin the public-input layout, the custom-gate semantics, the fixed five-slot shape, and the padding-note rules.

2.3 Snapshot non-spentness: the Poseidon indexed Merkle tree

Membership alone would let a spent note vote: the note-commitment tree is append-only and a spent note's commitment remains in it forever. Snapshot eligibility therefore needs a second, negative statement — the note's nullifier is *not* in the set of nullifiers revealed up to the snapshot height. Proving non-membership in a Merkle set requires structure beyond a plain accumulator; the protocol uses an indexed Merkle tree over the sorted nullifier set.

Construction. The tree is Poseidon-based with depth 29 (IMT_DEPTH, voting-circuits/src/delegation/imt.rs:19). Each leaf is a *punctured range* — a triple of sorted boundaries, hashed and covering the punctured open interval

$$\text{leaf} = \text{Poseidon}(\text{nf}_{\text{lo}}, \text{nf}_{\text{mid}}, \text{nf}_{\text{hi}}), \quad (\text{nf}_{\text{lo}}, \text{nf}_{\text{hi}}) \setminus \{\text{nf}_{\text{mid}}\},$$

so the set members appear only as interval boundaries or interior punctures, and everything strictly between them is certified absent. In-circuit, non-membership of the private nf costs 31 Poseidon calls (2 for the leaf, 29 for the path) and proves (imt.rs:51–70; src/delegation/README.md §13):

1. the leaf authenticates: the 29-level path from the leaf hash resolves to the public nf_imt_root ;
2. the nullifier lies strictly inside the interval: the offsets $x_{\text{lo}} = \text{nf} - \text{nf}_{\text{lo}} - 1$ and $x_{\text{hi}} = \text{nf}_{\text{hi}} - \text{nf} - 1$ are each range-checked to $[0, 2^{250})$; and
3. the nullifier misses the puncture: $(\text{nf} - \text{nf}_{\text{mid}}) \cdot \delta = 1$ for a witnessed inverse δ .

What it excludes — and what it does not. The statement excludes, assuming the correct canonical snapshot tree, the nullifiers revealed on the Zcash chain up to the snapshot height: the note was unspent when the snapshot was taken. It excludes nothing after that height — a note spent the block after the snapshot still delegates its weight, because snapshot voting fixes the electorate at a single height by design. Two soundness assumptions live *outside* the circuit (imt.rs:56-70; README.md §13). First, the tree contract: the circuit checks only the one authenticated leaf, so the committed leaves must form the canonical punctured-range tree for the set — sorted, deduplicated, non-overlapping except for shared boundaries. A malformed tree in which some set member lies strictly inside another leaf’s interval would certify a spent note as unspent, and no per-leaf gate can detect the global overlap. Second, the span bound: to support the 250-bit offset checks throughout each interval, the builder guarantees $nf_{hi} - nf_{lo} \leq 2^{250}$ in canonical field order by pre-populating 33 sentinel nullifiers spaced at most 2^{249} apart, plus $p - 1$ to close the tail (the SpacedLeafImtProvider strategy). The tree is built by the PIR operator and its root posted by the coordinator — which is where the next subsection picks up.

Classification. Designed but unspecified (voting-circuits @ 4c39abd5). A specification would need to pin the leaf model, the sentinel schedule, and above all the canonical-tree contract — including which party is accountable for the tree’s well-formedness, since the circuit cannot check it.

2.4 The snapshot roots: posted, never verified

Both anchors originate off-chain, in coordinator tooling. The note-commitment root `nc_root` is recomputed by Rust FFI as the Sinsemilla hash of an Orchard frontier (the incremental-tree append state constructed in the *Crypto Guide*, §“Append-only and incrementally updatable trees”) fetched from a public lightwalletd server; the nullifier root `nullifier_imt_root` is fetched from the running PIR service (vote-sdk/api/snapshot.go:44-66). The coordinator posts both in message 1; the handler stores them verbatim in the round record and folds them into `vote_round_id` (x/vote/keeper/msg_server.go:36-138); and at validation the ante handler looks the stored roots up from the round and passes them to the FFI verifier as the public inputs of ZKP1 (x/vote/ante/validate.go:147-177).

Nothing on the vote chain verifies that the posted roots match real Zcash state: `svoted` runs no Zcash light client, and the circuit documentation is explicit that it “proves statements relative to the public inputs supplied by the verifier; it does not authenticate where those inputs came from” (voting-circuits/src/delegation/README.md, Public Input Provenance). The trust structure that results is asymmetric. Honest wallets are safe from a *wrong* snapshot in the sense that their proofs simply fail: their witnesses — Merkle paths and IMT leaves — come from the real chain and cannot resolve to fabricated roots. And the roots are public, so anyone with a Zcash node can audit them after the fact. But nothing prevents a coordinator quorum from pinning fabricated roots for which it alone holds matching witnesses, minting arbitrary voting weight that the chain would accept; detection is post hoc and protocol-external. The trust root for eligibility is therefore the coordinator threshold together with the PIR operator that builds the nullifier tree of §2.3.

Classification. Designed but unspecified, with an explicit trust assumption that must be flagged wherever eligibility is discussed. A specification would need either chain-side verification (a light client or a succinct proof that the roots match a Zcash block) or, failing that, a normative audit procedure with a defined challenge window.

2.5 Weight: ballot quantization

Delegated weight is denominated in ballots. The circuit sums the five slot values into $v_{\text{total}} = \sum_{i=1}^5 v_i$ (internal wires produced by condition 9, consumed by conditions 7 and 8; src/

delegation/README.md, Inputs), and one ballot represents $D = 12,500,000$ zatoshi (0.125 ZEC): the constant `BALLOT_DIVISOR` (voting-circuits/src/params.rs:14). The honest ballot count is $q = \lfloor v_{\text{total}}/D \rfloor$.

Condition 8 (src/delegation/circuit.rs:1290–1427) witnesses the count q (`num_ballots`) and a remainder r as *free advice*, and constrains

$$q \cdot D + r = v_{\text{total}}, \quad 0 \leq r < 2^{24}, \quad 1 \leq q \leq 2^{30}. \quad (1)$$

The range checks run through a 10-bit lookup table: the circuit multiplies r by 2^6 and checks the product to 30 bits (so $r < 2^{24}$), and checks $q - 1$ to 30 bits directly — which enforces both bounds at once, since $q = 0$ wraps $q - 1$ to $p - 1 \approx 2^{254}$ and fails. The lower bound $q \geq 1$ doubles as a minimum stake: a bundle worth less than 0.125 ZEC admits no valid witness. The upper bound is safe slack: 2^{30} ballots is about 134 million ZEC, far above the 21 million supply. The remainder bound 2^{24} is the tightest power-of-two-aligned bound that keeps completeness — every honest $r < D$ fits — but it is *looser* than D , and that slack admits a second witness.

Proposition 2.1 (One-ballot under-claim window). *Fix v_{total} and let $\hat{q} = \lfloor v_{\text{total}}/D \rfloor$ and $\hat{r} = v_{\text{total}} \bmod D$ form the honest witness, assumed valid ($\hat{q} \geq 1$). The pairs satisfying the constraints of Equation (1) are exactly $(\hat{q}, \hat{r})$ together with $(\hat{q} - 1, \hat{r} + D)$, the latter admissible if and only if*

$$\hat{r} < 2^{24} - D = 4,277,216 \quad \text{and} \quad \hat{q} \geq 2.$$

In particular, a prover can claim exactly one ballot fewer than floor division yields — for approximately 34.2% of totals under a uniform residue model, since $(2^{24} - D)/D \approx 0.3422$ — and can never claim more.

Proof. Suppose (q_1, r_1) and (q_2, r_2) both satisfy Equation (1) for the same v_{total} . Subtracting the two instances of the linear constraint gives $(q_1 - q_2)D \equiv r_2 - r_1 \pmod{p}$. The range checks bound the canonical representatives: $|q_1 - q_2| \cdot D \leq (2^{30} - 1)D < 2^{54}$ and $|r_2 - r_1| < 2^{24}$, both far below $p > 2^{254}$, so the congruence holds over the integers. Then $|q_1 - q_2| = |r_2 - r_1|/D < 2^{24}/D < 2$, forcing $|q_1 - q_2| \in \{0, 1\}$. The case 0 gives $r_1 = r_2$. The case $q_1 = q_2 + 1$ gives $r_2 = r_1 + D$, which is admissible precisely when $r_2 < 2^{24}$ (the remainder range check) and $q_2 \geq 1$ (the count range check) — for the honest pair, the stated window. The over-claim direction from the honest witness, $(\hat{q} + 1, \hat{r} - D)$, requires $\hat{r} - D < 0$; its canonical field representative is at least $p - D$, which fails the shifted 30-bit range check. No further pairs exist. $\square$

Impact and status. The deviation is self-harming: the only dishonest witness *under-claims*, discarding one ballot of the prover’s own weight, and aggregate totals consequently err low, never high. No downstream check repairs or re-derives the count: the Vote Authority Note commitment (condition 7) hashes whatever q the prover chose, and the vote-proof circuit later opens the same value. The gap is documented by the implementers themselves — src/delegation/README.md §8, “Soundness scope”, carries the analysis above together with two single-constraint tightenings (a 24-bit check on $(D - 1) - r$, or on $r + (2^{24} - D)$, either of which pins $r \in [0, D)$ at a cost of roughly 3–4 rows) — and it is unfixed at commit 4c39abd5. The public documentation states exact floor division (gitbook ZKP 1 page, fetched 2026-07-08), which the circuit does not enforce: this is the single spec-versus-code disagreement recorded in this volume (§1.3), conservative in direction — the code is the protocol, and the code is weaker.

Classification. The quantization relation as implemented — Equation (1) — is designed but unspecified. The gap between it and the stated floor-division rule is an *open problem*: the design intends exact division, the circuit proves less, and the tightening exists on paper only. A specification must either adopt the weaker relation and its under-claim window explicitly, or mandate one of the documented tightening constraints.

3 Vote encryption, nullifiers, and tally

Delegation leaves the governance hotkey holding a Vote Authority Note (VAN): a blinded commitment to the hotkey address, a ballot count, and a per-proposal authority mask. Three problems remain. The hotkey must cast a vote whose weight never appears in public; the protocol must stop every form of double-voting — the same coins delegated twice, the same VAN spent twice, the same proposal voted twice along a chain of successor VANs, the same encrypted share counted twice; and the aggregate totals must become public in a form every chain node verifies, without any single party ever holding the decryption key. This section develops the answers in order: the VAN itself, the synthetic keystone note whose signature authorises its minting, a four-layer double-vote discipline, a sixteen-share lifted-ElGamal encoding, a per-round threshold Election Authority, and a chain-verified tally.

Classification. Every governance-specific object in this section is *designed but unspecified*: the normative artifact is the implementation, cited commit-pinned — `valargroup/voting-circuits` at 4c39abd5 (2026-06-03) and `valargroup/vote-sdk` at cb915f51 (2026-06-05). File paths beginning `src/` refer to the former; paths beginning `x/vote/`, `crypto/`, or `proto/` to the latter. The would-be specification (zcash/zips PR #1200, opened 2026-03-05) remains unmerged as of 2026-07-08, and the single `voting-circuits` crate both proves and verifies, so no independent implementation cross-checks these formulas. The *specified* bin holds only the inherited Orchard primitives — `NoteCommit`, nullifier derivation, `Commitivk`, `RedPallas`, the `Sinsemilla` Merkle instance — reused through the orchard crate’s `unstable-voting-circuits` feature (zcash/orchard commit c0b6b917). One *open problem* reaches into this section from the delegation circuit; Remark 3.3 flags it where it lands.

Throughout this section, `Poseidon` denotes the `P128Pow5T3` instance over $\mathbb{F}_{p_{\text{Pallas}}}$ (width 3, rate 2), applied with the fixed-length padding of the stated arity. Domain separation uses two encodings, both pinned by unit tests (`src/domain_tags.rs`): small numeric tags (0 for VAN commitments, 1 for vote commitments), and short ASCII tags — “governance authorization”, “vote authority spend”, “share spend” — zero-padded to 32 bytes and read as little-endian integers, which are canonical in $\mathbb{F}_{p_{\text{Pallas}}}$ because the top byte stays zero. We abbreviate the ASCII tags T_{gov} , T_{spend} , T_{share} , and write `rid` for the voting round identifier and `pid` for the proposal identifier.

3.1 The Vote Authority Note

The VAN is the vote chain’s carrier of authority: one field element that commits to who may vote (the hotkey address), with how much weight (the ballot count), in which round, and on which proposals (the authority mask).

Definition 3.1 (VAN commitment). Let (g_d, pk_d) be the hotkey’s diversified address in the voting key hierarchy, n_b the ballot count, $auth \in [0, 2^{16})$ the proposal-authority mask, and r_{van} a uniformly random blind. The VAN commitment is the two-layer hash

$$\text{van} := \text{Poseidon}(\text{core}, r_{\text{van}}), \quad \text{core} := \text{Poseidon}(0, x(g_d), x(pk_d), n_b, \text{rid}, \text{auth}),$$

with $x(\cdot)$ the x -coordinate (`src/gadgets/van_integrity.rs`, lines 61–78; one gadget is shared by the delegation and vote-proof circuits).

The two layers divide labour. The inner layer is structural, and its preimage is low-entropy: the round id is public, the mask at mint is a fixed constant, and ballot counts are small integers — a bare inner hash would admit dictionary attacks on the weight and the address. The outer layer

closes them with the uniform blind (module documentation, `src/gadgets/van_integrity.rs`, lines 23–27).

The address enters by x -coordinates alone, which identifies (g_d, pk_d) without either point’s sign. Delegation additionally binds the full points through `NoteCommit` into the public $cm_{x_{new}}$; the module documentation warns that any future caller dropping that side constraint must widen the preimage to full points (`src/gadgets/van_integrity.rs`, lines 14–22).

The mask `auth` is a 16-bit bitmask minted at $2^{16} - 1 = 65535$ — all bits set, a constant baked into the verification key (`src/delegation/circuit.rs`, lines 162 and 1464–1467). Bit 0 is a permanent sentinel that no vote may consume, so usable bits are 1 through 15 and a round supports at most 15 proposals (`src/vote_proof/circuit.rs`, lines 123–143).

The vote chain keeps one per-round Poseidon Merkle tree of depth 24 (`src/params.rs`, line 25; per-round state in `x/vote/keeper/keeper_voting.go`, lines 72–80): delegation appends the freshly minted VAN commitment; each cast appends the successor VAN and then the vote commitment. The reduced depth is a sizing choice — governance produces one leaf per delegation plus two per vote, well within $2^{24} \approx 1.7 \times 10^7$ leaves (`src/params.rs`, lines 16–25).

3.2 Keystone authorisation: the synthetic signed note

The delegation message is authorised by a `RedPallas` spend-auth signature under the randomized key `rk` (§2.1, message 2), and the intended signer is a Keystone-class hardware wallet, which signs only Orchard Actions. The voting client therefore wraps the delegation in an Orchard-Action shape around a *synthetic* keystone note: a 1-zatoshi note that exists on no chain — the circuit witnesses no Merkle path for it and checks no anchor; the value is 1 rather than 0 only because the wallet UI does not render zero-value spends (`src/delegation/README.md`, “Integration: the Keystone (signed) note is synthetic”).

Conditions 1–6 of the delegation circuit govern this branch (`src/delegation/circuit.rs`, lines 16–29); the load-bearing pair is conditions 3 and 2. Condition 3 forces the keystone note’s ρ to a Poseidon hash of everything the delegation publishes,

$$\rho_{\text{signed}} = \text{Poseidon}(cm_{x_1}, \dots, cm_{x_5}, \text{van}, \text{rid}),$$

the arity-7 fixed-length instance (`rho_binding_hash`, `circuit.rs:176–190`). Condition 2 then derives the keystone nullifier by the deployed Orchard rule — constructed in the *Ironwood Guide* (§“The nullifier”) —

$$nf_{\text{signed}} = \text{DeriveNullifier}_{\text{nk}}(\rho_{\text{signed}}, \psi_{\text{signed}}, cm_{\text{signed}}),$$

and exposes it as a public input. An honest client includes this nullifier in the wrapping Action before obtaining a signature. The chain, however, verifies the `RedPallas` signature under `rk` over the *client-provided* sighash and separately verifies the delegation proof (`x/vote/ante/validate.go`, `verifyDelegation`, at `cb915f51`). It receives no wrapping transaction from which to recompute that sighash. The proof’s fourteen public inputs include the nullifier and `rk`, but not the sighash (`voting-circuits/src/delegation/circuit.rs`, at `4c39abd5`). Consequently the circuit’s ρ -binding alone does not prove that the signed digest commits to this delegation. Sharing `rk` between two verification checks is not a message-binding argument. The chain fixture generator confirms that the sighash may be arbitrary 32 bytes (`vote-sdk/circuits/tests/generate_fixtures.rs`). This is an unestablished authorisation binding at the cited pins, not a demonstration of an exploit against a live round. A protocol argument or additional verification would have to close this boundary before the intended hardware-wallet consent guarantee could be asserted.

The remaining circuit conditions are supporting: condition 4 proves $rk = [\alpha] \text{SpendAuthG} + ak$ for a witnessed randomizer α (the *Ironwood Guide*, §“Randomised validating keys”); condition 5 ties `ak`, `nk`, and `rivk` to the same `Commitivk` chain the real-note slots use (§2.2, condition 11); conditions 1 and 6 recompute the keystone and output note commitments from witnessed openings —

knowledge checks, not membership checks (`src/delegation/README.md`, the three-bucket audit note).

3.3 Double-vote prevention: four layers

A ballot can be replayed at four distinct joints: the Zcash note (delegate it twice), the VAN (spend it twice), the proposal bit (vote the same proposal again through a successor VAN), and the encrypted share (feed it to the accumulator twice). One defence guards each joint. The first, second, and fourth are nullifiers; chain-side, each kind lands in its own type- and round-scoped set under an atomic check-and-set (`x/vote/keeper/keeper_voting.go`, lines 19–48; type constants `x/vote/types/keys.go`, lines 96–101). The third is arithmetic, enforced in-circuit.

Layer 1: the governance nullifier (delegation). Each delegated note exposes

$$\text{nf}^{\text{gov}} := \text{Poseidon}(\text{nk}, \text{dom}, \text{nf}), \quad \text{dom} := \text{Poseidon}(T_{\text{gov}}, \text{rid}),$$

where `nk` and `nf` are the Zcash note’s nullifier key and real Orchard nullifier, both computed in-circuit — the real nullifier is never published (`src/delegation/circuit.rs`, lines 1703–1729). The domain `dom` is a public input, but the circuit re-derives it from the public round id and constrains equality (`src/delegation/circuit.rs`, lines 1041–1055), so a prover cannot substitute a foreign domain to escape the round scoping. The chain rejects duplicates in the governance-typed, round-scoped set. The attack closed: delegating the same unspent-at-snapshot note into two bundles in one round, which would double its weight. Keying by the secret `nk` serves privacy: when the note is later spent on mainnet and its real nullifier becomes public, no observer can link the pair — the governance trail does not deanonymise the payment trail.

Layer 2: the VAN nullifier (casting). Spending a VAN publishes

$$\text{nf}^{\text{van}} := \text{Poseidon}(\text{nk}_v, T_{\text{spend}}, \text{rid}, \text{van}_{\text{old}}),$$

where `nkv` is the voting hierarchy’s nullifier-deriving key, proved to belong to the witnessed address through the Commit^{ivk} chain (`src/vote_proof/circuit.rs`, lines 203–222). A cast proves membership of `vanold` in the round tree without identifying the leaf, and this nullifier is the only spend mark. The attack closed: re-spending the old VAN, whose mask still carries the bit the vote just consumed — without the nullifier, one delegation would vote the same proposal arbitrarily often from the same leaf.

Layer 3: the authority-mask decrement (casting). Layer 2 kills the parent, not the lineage: every cast mints a successor VAN, and a successor still carrying the consumed bit would re-enable the same vote. Condition 6 of the vote-proof circuit therefore forces

$$\text{auth}_{\text{new}} = \text{auth}_{\text{old}} - 2^{\text{pid}}.$$

Field arithmetic cannot express a variable exponent as a polynomial gate, so the prover witnesses 2^{pid} and a lookup over the table $\{(j, 2^j)\}_{j=0}^{15}$ proves it; a field-inverse gate excludes $\text{pid} = 0$ (the sentinel); a 16-bit decomposition of `authold` with a one-hot selector anchored at `pid` proves the consumed bit was actually set ($\sum_j \text{sel}_j b_j = 1$), and the recomposition returns `authnew` with exactly that bit cleared, implicitly range-checked to 16 bits (`src/vote_proof/gadgets/authority_decrement.rs`, lines 34–93). The successor VAN commits `authnew` and re-enters the tree. The invariant bought by layers 2 and 3 together: one delegation yields at most one vote per proposal, and at most 15 proposals per round.

Layer 4: the share nullifier (reveal). Revealing the i -th encrypted share of a vote publishes

$$\text{nf}_i^{\text{share}} := \text{Poseidon}(T_{\text{share}}, \text{vc}, i, \text{blind}_i),$$

where vc is the vote commitment (§3.4) and blind_i the share-commitment blind (`src/share_reveal/circuit.rs`, lines 161–187). The attack closed: the tally accumulator is a raw homomorphic sum (§3.6), so re-submitting one accepted ciphertext would double-count its weight; the share-typed set admits each (vc, i) once. The blind is load-bearing for privacy rather than soundness: the vote commitment is public in the cast message and i ranges over sixteen values, so an unblinded nullifier could be evaluated by any observer against every commitment in the tree, linking each reveal to its vote by dictionary test — collapsing exactly the anonymity that the reveal proof’s non-identifying membership provides. Blinds never appear on chain.

3.4 Vote encoding: sixteen lifted-ElGamal shares

Casting must convey weight to the tally without publishing it per vote. The instrument is additively homomorphic encryption to a key that no single party holds (§3.5).

Definition 3.2 (Vote share encryption). Fix the generator

$$G := \text{GroupHash}^{\text{Pallas}}(\text{z.cash} : \text{Orchard}, G),$$

Orchard’s spend-authorisation base. A vote on proposal pid splits its ballot count n_b into sixteen prover-chosen shares $v_0, \dots, v_{15}$ subject to

$$\sum_{i=0}^{15} v_i = n_b, \quad v_i \in [0, 2^{30}),$$

and encrypts each under the round’s Election Authority key $\text{ea}_{\text{pk}} \in \mathcal{E}(\mathbb{F}_{p_{\text{Pallas}}})$:

$$C_{1,i} := [r_i] G, \quad C_{2,i} := [v_i] G + [r_i] \text{ea}_{\text{pk}},$$

with fresh nonzero randomness r_i (`src/gadgets/elgamal.rs`; sum and range are conditions 8 and 9, `src/vote_proof/circuit.rs`, lines 416–457 and 1026–1036).

The scheme is *lifted*: the message enters the exponent, so componentwise addition of ciphertexts encrypts the sum of plaintexts and the accumulator needs no key. The price is paid at decryption, which yields $[v] G$ and recovers v only as a bounded discrete logarithm — the 2^{28} bound of §3.6. Reusing `SpendAuthG` avoids introducing a second fixed base; the in-circuit 22-window short-scalar tables share the same generator (`src/gadgets/elgamal.rs`, lines 57–66). The range check closes wraparound: shares are field elements, and without it a decomposition could encode negative shares as large residues while still satisfying the sum constraint. Sixteen shares serve weight privacy under staggered reveal: the prover-chosen random decomposition leaves no weight fingerprint on any single revealed ciphertext (`src/vote_proof/circuit.rs`, lines 418–423). Client-side, the randomness r_i and the blinds derive from a BLAKE2b-512 PRF (pseudorandom function; the keyed-BLAKE2 construction of the *Crypto Guide*, §“PRFs from hash functions: length extension and keyed BLAKE2”) with personalisation `ZcashVote_Expand` under distinct domain bytes (`src/domain_tags.rs`, lines 28–41).

The cast binds everything into one public field element:

$$\text{vc} := \text{Poseidon}(1, \text{rid}, h_{\text{sh}}, \text{pid}, d), \quad h_{\text{sh}} := \text{Poseidon}(\text{sc}_0, \dots, \text{sc}_{15}),$$

$$\text{sc}_i := \text{Poseidon}(\text{blind}_i, x(C_{1,i}), x(C_{2,i}), y(C_{1,i}), y(C_{2,i})),$$

where d is the vote decision (`src/gadgets/vote_commitment.rs`, lines 42–55; `src/shares_hash.rs`, lines 39–61). The y -coordinates are included deliberately: an x -coordinate identifies a point only up to sign, and hashing both coordinates blocks ciphertext sign-malleability. The leading tag 1 separates vote commitments from VANs (tag 0) in the shared tree and is baked into the verification key, so an honest verifier cannot be driven to confuse the two leaf kinds (`src/gadgets/vote_commitment.rs`, lines 11–13). A cast message reveals vc , the VAN nullifier, the successor VAN, and pid — neither the decision nor the weight. Note that the cast publicly links vc to nf^{van} , so per-vote weight privacy rests on the encryption, not on unlinkability.

Remark 3.3 (Quantization gap, propagated). The sum condition ties $\sum_i v_i$ to the ballot count n_b minted at delegation, so its soundness inherits the delegation circuit’s quantization relation: the constraint $n_b \cdot 12,500,000 + \text{rem} = v_{\text{total}}$ with $\text{rem} < 2^{24}$ is strictly weaker than floor division and admits a one-ballot *under*-claim for roughly 34% of note values; an over-claim is impossible (Proposition 2.1 in §2.5; `src/params.rs`, lines 9–13; `src/delegation/README.md`, §8). This is an open problem — the public design prose states exact floor division, the code does not enforce it.

3.5 The Election Authority: a per-round Joint–Feldman DKG

The tally requires a key that opens aggregates; any party holding that key alone could equally open each accumulated share the moment it lands on chain. The protocol therefore splits the round key across the bonded validator set by a Joint–Feldman distributed key generation, and re-runs the ceremony every round, so compromise of one round’s key reaches no other round and the validator set may change between rounds.

Each ceremony validator — registered through a whitelisted Pallas-key path — samples a secret polynomial of degree $t - 1$ over the Pallas scalar field, posts its t Feldman coefficient commitments (Pallas points) on chain, and delivers to every other validator its evaluation share, encrypted under ECIES: an ephemeral Pallas Diffie–Hellman, the symmetric key $\text{SHA-256}(E \parallel S_x)$ over the compressed ephemeral point and the shared-secret x -coordinate, and ChaCha20-Poly1305 with a zero nonce — safe because each envelope uses a fresh ephemeral key (`crypto/ecies/ecies.go`, lines 21–33). The chain validates point well-formedness and the commitment count (`x/vote/keeper/msg_server_ceremony.go`, lines 137–149). When the n -th contribution arrives, the chain sums the commitment vectors componentwise; the round key ea_{pk} is the combined constant term, and each validator’s verification key VK_i is the combined commitment polynomial evaluated at i in the exponent (`x/vote/keeper/msg_server_ceremony.go`, lines 224–269). No dealer ever holds the round secret: it exists only as the sum of shares.

The parameters are fixed in code: reconstruction threshold $t = \max(2, \lfloor (2n + 2)/3 \rfloor)$ for $n \geq 2$ validators (the degenerate $n = 1, t = 1$ case exists for local testing), ceremony finalization quorum $\lceil 4n/5 \rceil$ acknowledgements — stricter than t for most n — with non-ackers stripped from the ceremony and non-participants suspended from the active validator set (`x/vote/keeper/keeper_ceremony.go`, lines 46–79; `keeper_ceremony_jailing.go`).

The known key-bias attack on plain Joint–Feldman applies: contributions arrive sequentially through the block-proposer path, so the last contributor sees every prior commitment and can adapt its contribution. The repository’s design document argues that the resulting bias is harmless for threshold ElGamal, citing Gennaro et al. (2007) (`vote-sdk/docs/tss-ceremony.md`, “Why single-phase”). Two shortcuts in that explanation must not be read as proofs. Biasing a key distribution does not by itself let a party choose an arbitrary final public key while supplying valid shares with known openings. Nor does ElGamal confidentiality hold for every valid key regardless of its generation: an adversary that knows the corresponding secret can decrypt. The cited security argument’s assumptions must be matched to this ceremony, including its abort, acknowledgement, and validator-removal rules. That composition is not established by this volume.

Remark 3.4 (Threshold collusion). Any t colluding validators can reconstruct the round secret offline and decrypt every individual on-chain ciphertext. If they additionally learn which sixteen shares belong to a vote (for example through a helper), summing them yields that vote’s exact per-decision weight, which the cast message already links in public to a VAN nullifier. The linkage stops at the VAN layer — the governance nullifier’s keyed PRF keeps Zcash notes and addresses out of reach. No published source claims per-vote weight privacy against a threshold coalition; a specification would have to state this limit explicitly (inference from `crypto/elgamal/bsgs.go` and `proto/svote/v1/tx.proto`, lines 88–99; recorded 2026-07-08).

3.6 Tally: chain-verified threshold decryption

Accumulation. On each accepted reveal, the chain adds the 64-byte ciphertext componentwise into the accumulator keyed by the triple (round, proposal, decision), validating well-formedness and rejecting identity components (`x/vote/keeper/keeper_tally.go`, lines 33–74). By linearity, the accumulator encrypts the summed ballots of all revealed shares for that cell. Nothing decrypts until the round enters its tallying phase.

Partial decrypts. During tallying, each ceremony validator’s node injects — through the block-proposer path; the mempool route is rejected — one submission covering every non-empty accumulator: the partial decryption $D_i := [s_i] C_1$ under its DKG share s_i , with a Chaum–Pedersen DLEQ proof that $\log_G VK_i = \log_{C_1} D_i$. The proof is the pair (e, z) ; the verifier recomputes $R_1 = [z] G - [e] VK_i$ and $R_2 = [z] C_1 - [e] D_i$ and accepts iff

$$e = H(\text{svote-pd-dleq-v1} \parallel G \parallel VK_i \parallel C_1 \parallel D_i \parallel R_1 \parallel R_2),$$

with H a BLAKE2b-256 hash-to-scalar; the tag separates this proof family from the tally-level DLEQ family (`svote-dleq-v1`), barring cross-family replay (`crypto/elgamal/dleq.go`, lines 30–145). The verification key VK_i is re-derived on the fly from the round’s combined Feldman commitments rather than stored (`x/vote/keeper/msg_server_tally_decrypt.go`, lines 257–269). The DLEQ is what makes the tally trustless against its own operators: one forged D_i would silently shift every total. Duplicate submissions per validator are rejected, and each submission must cover every non-empty accumulator, so a proposer cannot inject a partial set that later wedges the tally (`msg_server_tally_decrypt.go`, lines 199–294).

Final verification. The block proposer alone may submit the claimed plaintext totals. For each entry the chain Lagrange-combines at least t stored partials at zero (the coefficients λ_i below are the Lagrange basis polynomials of the *Math Guide*, §“Lagrange interpolation”, evaluated at zero),

$$\sum_i \lambda_i D_i = \left[\sum_i \lambda_i s_i \right] C_1 = [s] C_1,$$

recovering the round secret only in the exponent (`crypto/shamir/partial_decrypt.go`, lines 37–71), and checks $C_2 - [s] C_1 = [v] G$ against the claimed total v ; an empty accumulator forces $v = 0$; any $v \geq 2^{28}$ is rejected outright (the constant `TallyBSGSBound`, an exclusive bound; `x/vote/types/keys.go`, lines 33–35). A completeness check requires the entries to cover every non-empty accumulator — without it a malicious proposer could finalize with results omitted (`msg_server_tally_decrypt.go`, lines 102–177). Only then does the round finalize.

Recovering the logarithm. The chain verifies by re-encoding $[v] G$, so only the proposer must solve discrete logarithms, by baby-step/giant-step under $N = 2^{28}$: a table of $m = \lceil \sqrt{N} \rceil = 2^{14} = 16,384$ baby steps $j \mapsto [j] G$, giant steps subtracting $[m] G$, a hit at (i, j) giving $v = im + j$ within at most $m + 1$ iterations (`crypto/elgamal/bsgs.go`, lines 11–110). The bound is ample: the full 21-million-ZEC supply quantizes to 1.68×10^8 ballots at 12,500,000 zatoshi per ballot (`src/params.rs`, line 14), below $2^{28} \approx 2.68 \times 10^8$, so no honest aggregate is ever truncated.

Two flags. Totals are denominated in *ballots*; the protobuf comment on the tally field says *zatoshi* and is wrong — the wallet multiplies by 12,500,000 for display (proto/svote/v1/tx.proto, lines 111–116, against zashi-android TallyResults.kt, lines 44–56, commit b4edd6f6). And the tallying phase carries a timeout of 21,600 seconds (six hours), after which the round finalizes *without* results (x/vote/types/keys.go, lines 28–31) — an availability caveat, not an integrity one, but a specification must decide whether a resultless finalization is acceptable.

What a specification must pin down. Until zips PR #1200 merges, the commit-pinned sources above are the only citable definition of: the Poseidon preimage layouts and the domain-tag registry (currently pinned by unit tests); the three nullifier formulas, their set scoping, and their key encodings; the decrement lookup table and the sentinel-bit convention; the share count, the per-share range bound, and their interaction with partial reveals; the DKG parameter formulas, ceremony state machine, and jailing policy; the DLEQ transcript formats and tags; and the BSGS bound and the unit denomination of totals as consensus parameters.

4 Trust model and verdict

The preceding sections constructed the protocol’s mechanisms from commit-pinned source (Table 1); this section assembles what those mechanisms do *not* guarantee. We first map every party the protocol trusts and state exactly what each is trusted with, then classify the volume’s claims into the three bins of §1.3, and close with the verdict: what a formal specification would have to pin down before the protocol’s guarantees become checkable, and what the protocol delivers today against the instruments scheduled for the same June 2026 question. File citations below are at the commits of Table 1; wallet files are at zashi-android @ b4edd6f6.

Every trust relation in this map is itself designed but unspecified: each is concrete, open-source behaviour at the pinned commits, and none is stated in a normative artifact. The inventory of §4.2 records the full classification.

4.1 The trust map

Helper servers hold the vote decision and the linkage. The payload a wallet sends to each chosen helper — struct SharePayload in zcash_voting/src/types.rs — carries the plaintext vote_decision, the vote commitment’s tree_position in the per-round tree, the shares_hash, all sixteen ciphertexts, the sixteen share commitments, and the revealed share’s blinding factor (primary_blind); the helper builds the Merkle path and the share-reveal proof server-side and submits MsgRevealShare itself (vote-sdk/internal/helper/processor.go). A helper therefore learns, before any reveal, how the voter voted, and holds precisely the share-to-commitment linkage that the on-chain data blinds; composed with the public pairing of vote_commitment and van_nullifier in MsgCastVote (proto/svote/v1/tx.proto), that linkage ties the decision to the vote’s delegated authority instance. This is a broader grant than a timing-relay framing suggests. What a helper never receives is weight: the plaintext share values and the El-Gamal randomness are marked SECRET in the client library and stripped from the wire type (types.rs, EncryptedShare versus WireEncryptedShare). The timing decorrelation itself is client policy, not a protocol guarantee: the wallet posts each share to half of the configured helpers rounded up, each with an independently random future submit_at scheduled no later than a last-moment buffer — two fifths of the round duration, capped at six hours — before the vote deadline (zcash_voting/src/share_policy.rs); a censoring helper causes partial weight loss, mitigated only by the multi-server fan-out and by a single-share fallback described below.

Any t colluding validators decrypt every posted ciphertext. Function `ThresholdForN` sets the reconstruction threshold $t = \max(2, \lfloor (2n + 2)/3 \rfloor)$ for n ceremony validators (`vote-sdk/x/vote/keeper/keeper_ceremony.go`). Any t of them can reconstruct the round’s ElGamal secret key offline from their dealt shares and decrypt every `enc_share` on the chain — not merely the aggregates the tally publishes. The decision attached to each ciphertext is public at reveal time in any case (`MsgRevealShare` carries `vote_decision`); what threshold collusion adds is the share values. In the single-share last-moment mode the exposure is immediate: the client builds a payload for share 0 only, “which carries all the voting weight”, and the remaining fifteen zero-value shares are never revealed (`zcash_voting/src/vote_commitment.rs`), so one decryption yields one vote’s exact weight. In the sixteen-share mode, recovering a per-vote weight additionally requires grouping shares by vote — a linkage the chain withholds (share nullifiers are blinded), the helpers of the previous paragraph possess outright, and the client-side timing policy merely obfuscates. The linkage stops at the Vote Authority Note layer in every case: the governance nullifier is keyed by the holder’s nullifier-deriving key `nk`, so mainnet notes and addresses stay unlinkable even after a later spend (`voting-circuits/src/delegation/circuit.rs`, condition 14). We flag the analytical gap explicitly: neither the public documentation nor the source claims — or denies — per-vote weight privacy against a colluding Election Authority threshold. The limit stated here is our adversarial inference from `crypto/elgamal/bsgs.go`, the message surface, and the share-range condition of the vote-proof circuit; the property is absent from every published analysis.

The chain is closed and its lifecycle is coordinator-gated. The vote chain enforces a positive-security message whitelist at the ante handler: only enumerated message types pass, standard bank transfers are disabled — explicitly “because unrestricted transfers would let anyone accumulate enough stake to create a validator, bypassing the controlled validator set” (`vote-sdk/proto/svote/v1/tx.proto`, comment on `MsgAuthorizedSend`) — and post-genesis validator creation is disallowed outside the registered-Pallas-key path (`vote-sdk/app/ante_whitelist.go`). Round lifecycle, privileged funding, and software upgrades are threshold-gated *coordinator actions* proposed and approved by a vote-manager set (`MsgProposeCoordinatorAction`, `MsgApproveCoordinatorAction`); the default genesis ships a single vote manager, and the coordinator threshold defaults to one (`vote-sdk/x/vote/module.go`, `DefaultVoteManagerAddresses`; `tx.proto`, `MsgUpdateVoteManagers`). In production the vote-manager custodians are named — by the configuration repository, not by the chain. At the volume’s pinned commit of `valargroup/token-holder-voting-config` (2785311d, 2026-05-27; the authentication root discussed below), the `trusted_keys` notes of `prod/static-voting-config.json` label three Keplr-derived keys as vote-manager keys for stated `sv1` addresses — key ids `valargroup`, `tachyon`, and `zodl`; a fourth, shielded-labs, arrived on 2026-05-29 (commit 82711181), and all four are present at head `e7d11990` (2026-06-25). These annotations are the custodians’ claims about themselves; the deployed chain’s on-chain `VoteManagerAddresses` set is published nowhere we could find. The production coordinator threshold is not publicly established: the repository carries no genesis file, no announcement states the value, and the registry’s only production round entry — `3fda6c83b054...`, added 2026-06-05 by pull request #330 — carries a single signature (key id `valargroup`), consistent with a threshold of one at the configuration layer but an inference, not a source. No validator identity is published either: the closest public artifact is the ten-operator `vote_servers` list of `prod/dynamic-voting-config.json` (at `e7d11990`), and a vote server is an RPC endpoint, not evidence that its operator runs a validator. We searched public artifacts on 2026-07-15; the deployed chain’s public REST endpoint would settle threshold and validator set directly and remains unqueried.³ The same coordinators post the snapshot: the eligibility anchors

³Static configuration at the pinned commit, Wayback snapshot 2026-07-15: <https://web.archive.org/web/20260715193658/https://raw.githubusercontent.com/valargroup/token-holder-voting-config/2785311d/>

`nc_root` and `nullifier_int_root` arrive in `MsgCreateVotingSession` as client-fetched values — the note-commitment root recomputed from a `lightwalletd` frontier, the nullifier root taken from the operator’s PIR service (`vote-sdk/api/snapshot.go`) — and the chain stores them without verifying that they describe any real Zcash state; it runs no light client (`x/vote/keeper/msg_server.go`). Honest wallets’ proofs fail against fabricated roots, and anyone can audit the posted roots after the fact, but nothing in the protocol prevents a coordinator quorum from pinning a snapshot of its own invention.

The wallet vendor’s configuration is the authentication root. A voter’s assurance that they are voting in a genuine round reduces to a static configuration file bundled with the wallet: fetched from a commit-pinned URL (`valargroup/token-holder-voting-config@2785311d`) and verified against a hard-coded SHA-256 digest, it names the ed25519 keys that must sign the dynamic per-round configuration — helper endpoints, PIR endpoints, and each round’s Election Authority key (`StaticVotingConfig.kt`, `BUNDLED_PINNED_SOURCE`). The round authenticator rejects a round whose on-chain `ea_pk` disagrees with the signed entry (`RoundAuthenticator.kt`, `status EA_PK_MISMATCH`) — the wallet’s only defence against an attacker-substituted encryption key, under which every cast share would be attacker-decryptable. An on-chain endorsement registry (`MsgEndorseRound`) is secondary. The trust root of the whole client-side protocol is therefore the custodians of the config-signing keys together with the application distribution channel; the custodians are named only by the configuration’s own `trusted_keys` annotations (above), the distribution channel in no published artifact.

Tally liveness admits finalization without results. The tally verification itself is real: validators’ nodes auto-inject partial decryptions whose Chaum–Pedersen DLEQ proofs are checked on-chain against Feldman-derived verification keys, and the proposer-only `MsgSubmitTally` is accepted only if every claimed total matches the Lagrange combination of stored partials, covers every non-empty accumulator, and lies below the discrete-log recovery bound 2^{28} (`vote-sdk/x/vote/keeper/msg_server_tally_decrypt.go`; `crypto/shamir/feldman.go`; the `TallyEntry` field `decryption_proof` is dead — “reserved for future use” — the binding check is the recomputation). But the threshold t is a liveness parameter as well as a secrecy parameter: if fewer than t validators decrypt, the round sits in `TALLYING` until the timeout — 21,600 seconds by default (`x/vote/types/keys.go`, `DefaultTallyTimeout`) — and end-of-block processing then finalizes it with `tally_timed_out = true` and *empty results* (`x/vote/module.go`). A finalized round in which every cast vote remains permanently undisclosed is a protocol outcome, not an excluded failure mode; the design accepts it as the price of not blocking the chain on an unreachable threshold.

The tally wire format mislabels its units. The comment on `TallyEntry.total_value` reads “Decrypted aggregate (zatoshi)” (`vote-sdk/proto/svote/v1/tx.proto:114`). It is wrong: the accumulated plaintexts are *ballot counts* — the vote-proof circuit constrains each vote’s shares to sum to the Vote Authority Note’s ballot count, and the wallet converts totals to zatoshi by multiplying by the ballot divisor 12,500,000 (`TallyResults.kt`, `toTallyResults`; constant `BALLOT_DIVISOR_ZATOSHI` in `VotingCryptoClient.kt`). The recovery bound corroborates the correct reading: 2^{28} ballots is roughly 33.6 million ZEC — comfortably above the monetary

`prod/static-voting-config.json`; at head, via the served URL: <https://web.archive.org/web/20260715193616/https://voting.valargroup.org/prod/static-voting-config.json>; dynamic configuration at `e7d11990`: <https://web.archive.org/web/20260715193707/https://raw.githubusercontent.com/valargroup/token-holder-voting-config/e7d11990/prod/dynamic-voting-config.json>. Operators named in `vote_servers`: `valargroup`, `ruzcash`, `zend`, `ShieldedLabs-JM`, `Legends`, `stardust-staking`, `zodl`, `ZecHub`, `katz`, `Keplr` — a list not maintained as a roster: the 2026-06-14 ZODL update reports the “decommissioned Stardust servers” removed from the app while `stardust-staking` remains in the configuration of 2026-06-25. Both files follow the schema of draft ZIP 1244, “Shielded Voting Wallet API” (`zcash/zips` PR #1244).

supply — whereas 2^{28} zatoshi is under 2.7 ZEC. A consumer that trusts the comment under-reports every result by a factor of 12.5 million. In a protocol whose only specification is its implementation, a wrong comment in the wire definition is not a cosmetic defect; it is an error in the closest thing the protocol has to a spec.

4.2 Claim inventory: the three bins

Specified. Only the inherited primitives: NoteCommit, nullifier derivation, $\text{Commit}^{\text{ivk}}$, the Sinsemilla Merkle instance, RedPallas, the ZIP-244 sighash, and ZIP-32 derivation, each specified in the protocol specification and the ZIPs, constructed in the *Ironwood Guide* (§“Note commitments”, §“The nullifier”, §“Keys and addresses”, §“The Merkle hash and the tree”, §“The RedPallas signature scheme”), and reused unchanged through the unstable-voting-circuits feature (zcash/orchard @ c0b6b917). No governance-specific object reaches this bin.

Designed but unspecified. Everything this volume constructed: the five-message ballot surface; the delegation relation with its note-bundle eligibility and indexed-Merkle-tree non-membership argument; the coordinator-posted, chain-unverified snapshot roots; the Vote Authority Note and its synthetic-action authorization — including the asymmetry that the chain verifies the delegation signature over a *client-provided* sighash, whose binding to the delegation is unestablished here, while the cast-vote sighash is recomputed on-chain (x/vote/ante/validate.go); all four double-vote layers; the sixteen-share lifted-ElGamal encoding, vote commitment, and bitmask decrement; the helper protocol and the trust it grants; the per-round Joint-Feldman DKG with threshold $t = \max(2, \lfloor (2n + 2)/3 \rfloor)$ and finalization quorum $\lceil 4n/5 \rceil$; the chain-verified tally, its 2^{28} recovery bound, and the timeout path; the PIR eligibility subsystem; and every trust relation of §4.1. Each is concrete and open-source at the pinned commits; none is normative. The would-be specifications — zcash/zips PRs #1200 and #1198, and the prior-art PR #853 — were all open and unmerged as of 2026-07-08.

Open problems. First, the ballot-quantization relation. The delegation circuit constrains $\text{num_ballots} \cdot 12,500,000 + \text{remainder} = v_{\text{total}}$ with $\text{remainder} < 2^{24}$, which is strictly weaker than the floor division the public documentation states: the pair $(q - 1, r + 12,500,000)$ also satisfies every constraint whenever the honest remainder obeys $r < 2^{24} - 12,500,000 = 4,277,216$ — about 34.2% of residues — and the honest ballot count is at least two, while the opposite deviation fails the range check, so a prover can under-claim exactly one ballot and can never over-claim (voting-circuits/src/delegation/circuit.rs;src/delegation/README.md §8, which states the window, proves over-claim impossible, and lists unimplemented tightening constraints). The deviation is self-harming, but it is a concrete disagreement between the code and the code’s own public description, and the exact relation a specification must choose — floor division or the shipped weaker relation — is unresolved. Second, the delegation authorisation checks do not establish that the signed client-supplied digest commits to the proved fields (§3.2). This volume no longer treats the ρ -chain as a proof of that missing link.

4.3 Verdict

What a specification must pin down. For the protocol’s guarantees to become checkable — by an auditor, by a second implementation, or by this volume — a normative artifact would need to fix, at minimum:

1. the three circuit relations in full: public-input layouts, every condition, and the exact quantization rule — either closing the under-claim window or normatively accepting the shipped relation;

2. every governance-object formula: the four nullifiers and the nullifier-domain derivation, the Vote Authority Note commitment (with the argument that its x -only encoding is bound elsewhere), the vote commitment, and the shares hash;
3. the snapshot: how `nc_root` and the nullifier root are derived, and *who verifies them* — at present, on-chain, nobody;
4. the authorization model: which sighashes the chain recomputes, which it accepts from the client, and how the signed delegation digest is bound to the fields accepted on-chain;
5. the Election Authority: the threshold and quorum formulas, key registration and rotation, and an explicit confidentiality claim stating against whom per-vote weight privacy holds;
6. the helper interface: the exact payload, the trust granted by it, and the status of the timing policy as guarantee or convention;
7. tally semantics: the verification equation, the unit of `total_value` (ballots), and the meaning of a timed-out round;
8. independent verification: a second implementation of at least the verifiers, breaking the single-crate tautology of §1.3.

What the protocol delivers today. Measured against the instruments beside it (§1.2), the deliverable is real but conditional. Against ZCAP, the protocol opens participation to every Orchard coinholder in proportion to holdings, with no identified panel and no registrar, and it hides identity and weight from public observers — where ZCAP offers the converse trade: an identified panel on mature, independently analysed voting software. Against the prior coin-weighted instrument, hhanh00's `zcash-vote`, it adds threshold decryption in place of a single tallying authority, blinded delegation through the Vote Authority Note, hardware signing, PIR-private eligibility queries, and wallet-native deployment — at the price of the trust map of §4.1: a permissioned chain, a coordinator quorum, helper servers, and a vendor-held configuration root. Aggregate decryption is publicly checkable: the tally check executes on-chain, so observers can replay it. That does not by itself establish the authorisation of every accepted delegation, and a fabricated snapshot is only auditable after the fact. Individual privacy is the weakest: it holds against outside observers, degrades to helper honesty for the linkage of decisions to votes, and degrades to the honesty of all but $t - 1$ validators for individual weights — a limit no published analysis states. The provisioned June 2026 use was a non-binding sentiment poll, but it had not occurred in this snapshot (§1.1). This review does not certify suitability for that use or for binding governance: the delegation-signature binding, the specification above, independent verification, and the Election Authority's confidentiality analysis remain to be established.