When Do Physics-Informed Neural Networks Resolve Dielectric Interfaces? A Pre-registered, Seed-Level Evaluation Against Interface-Conforming Finite Elements

Oct 17, 2026 ·

Devesh Patwari[1], Daksh Mehta[1], Tolga Uras Kurtay[1], Yasir Balat[1]

[1] Independent researchers

Corresponding author: Devesh Patwari, devesh.patwari.1@gmail.com

Keywords: physics-informed neural networks; dielectric interfaces; electrostatics; high-contrast coefficients; finite element method; pre-registration; reproducibility

Abstract

Background. Physics-informed neural networks (PINNs) are increasingly applied to electrostatic problems with piecewise-constant permittivity, but their accuracy is usually reported as a global solution error from the best of several runs, which says little about the electric field at material interfaces where breakdown occurs.

Methods. We report a pre-registered evaluation of six PINN formulation families on five problems: a one-dimensional layered capacitor (P1), a dielectric cylinder in a uniform field (P2), a line charge above a planar interface (P3), a two-material corner (P4) and a thin high-permittivity film (P5). The permittivity contrast κ spans 1 to 2000, with inverse contrasts in two dimensions; every configuration uses five matched seeds and a fixed budget of 3,000 gradient evaluations. The primary metric is the relative L^2 error of the electric field and displacement in an interface band, with failure defined as an error above 5%. Matched-seed interventions, eight robustness variations and a time-to-accuracy comparison against interface-conforming finite elements (FEM) complete the design; 3,856 completed runs are recorded.

Results. In one dimension a single network with a strong-form loss fails at every $\kappa \geq 5$ because the flux condition is invisible to its loss, while two-network soft coupling survives to $\kappa = 400$–2000. In two dimensions every formulation fails every seed at $\kappa \geq 80$ on all four geometries. Global potential error understates interface-band field error by a median factor of 2.4 (P1) to 8.2 (P5), and on P5 37% of failures have a potential error below 5%. Gradient-norm rebalancing helps one formulation at high contrast and harms another at low contrast; residual normalisation does not help; float64 has no effect under Adam once initial weights are held identical; L-BFGS at equal budget removes many one-dimensional

failures but none on the curved interface. The formulation ranking survives all robustness variations (Kendall $\tau \geqslant 0.65$). Interface-conforming quadratic FEM reaches 1% band field error in 0.10–4.75 s on P2 and P5, whereas no PINN configuration reaches 1% at any $\kappa \neq 1$.

Conclusions. Under a stated budget, PINN accuracy at dielectric interfaces is governed more by geometry than by contrast alone, and global error metrics conceal a substantial fraction of failures. We do not claim that PINNs cannot solve interface problems or that FEM is universally superior; the contribution is a reproducible, seed-level map of where these formulations fail, why, and at what cost relative to FEM.

1. Introduction

Electrostatic fields in layered and composite dielectrics are governed by the variable-coefficient Poisson equation

$$-\nabla\cdot\big(\varepsilon(\mathbf{x})\,\nabla\varphi(\mathbf{x})\big)=\rho(\mathbf{x}),\qquad \mathbf{x}\in\Omega=\Omega_1\cup\Omega_2, \tag{1}$$

where the permittivity ε takes the constant values ε_1 and ε_2 in two materials separated by an interface Γ. Across Γ, in the absence of free surface charge, the potential and the normal component of the electric displacement $D = -\varepsilon\nabla\varphi$ are continuous:

$$[\![\varphi]\!]_{\Gamma}=0,\qquad [\![\varepsilon\,\partial_n\varphi]\!]_{\Gamma}=0 . \tag{2}$$

The normal electric field therefore jumps by the permittivity ratio $\kappa = \varepsilon_2/\varepsilon_1$, and the potential has a kink at Γ. Engineering quantities such as breakdown margin, capacitance and field enhancement at corners and in thin films depend precisely on this interface-local field.

Physics-informed neural networks (PINNs) [18] represent φ by a neural network and minimise the residuals of (1), (2) and the boundary conditions at sampled points. Two obstacles are known. Smooth networks represent a kink poorly and learn low-frequency components first [17]; and a single network trained on the strong-form residual of (1) cannot see the flux condition in (2), because inside each material the residual reduces to $\Delta\varphi = 0$ [15]. These observations have motivated many interface-aware variants: domain decomposition [11, 12, 19, 20], cusp- and discontinuity-capturing networks [4, 9, 24], hard constraints [2, 21] and variational formulations [3, 6]. Most of this work reports a global solution error at a few contrasts, often from the best of several initialisations [2].

This study asks a narrower and testable question: under a fixed and stated computational budget, for which formulations, contrasts and geometries does a PINN resolve the electric field at a dielectric interface; where it does not, what fails; and does any single change

rescue it? We pre-registered eleven hypotheses (H1–H11), the metrics, the failure threshold, the seed counts and the analyses before running the primary experiments, and recorded every later decision in a dated change log. The aim is evidence that another group can rerun, not a new architecture.

The contributions, each measured on the stated problems and budget, are:

1. seed-level failure maps for six PINN formulation families over three orders of magnitude of contrast on five geometries (Sections 7 and 8);
2. a quantification of how much global potential error masks interface-band field error (Section 8.3);
3. matched-seed interventions that change one factor at a time, namely gradient weighting, residual scaling, floating-point precision, hard constraints and optimiser (Section 10);
4. an assessment of the robustness of these conclusions to eight training and architecture settings (Section 11);
5. time-to-accuracy and error-at-equal-cost comparisons against interface-conforming finite elements (Section 12); and
6. a reusable evaluator and run database, with code, raw data and a pipeline that regenerates every reported number (Appendix G).

2. Related work

2.1 Interface-aware neural solvers

Domain-decomposition PINNs couple subdomain networks through interface penalties [11, 12, 14, 30]. Interface PINNs and their adaptive variant assign each material its own activation function or network [19, 20]. Cusp- and discontinuity-capturing networks add an interface-distance feature to the input [9, 24], discontinuity-removing PINNs transform the problem so that the unknown is smooth [4], interfaced neural networks build the jump into the architecture [26], and Dirichlet–Neumann learning schemes alternate subdomain solves [22]. Several of these methods report accurate solutions at contrasts of 10^3–10^5 on elliptic test problems [6, 8, 9, 24], so high contrast as such is not untested territory. Convergence theory is available for domain-decomposed PINNs on linear elliptic interface problems [27].

2.2 Hard constraints

Distance-function constructions impose boundary conditions exactly [21]. Chung et al. [2] extend the idea to interface conditions and compare six methods at $\kappa = 10$ using solution L^2 error and the best of four initialisations; this is the study closest to ours, and

our formulations F4 and F4full follow its construction in one dimension.

2.3 Failure analysis

Imbalance between the gradients of loss terms [25], ill-conditioned loss landscapes [13] and loss-scale imbalance between coupled networks [10] have each been proposed as failure mechanisms. Nohra and Dufour [15] show that a piecewise-constant coefficient renders the flux condition invisible to a single-network strong-form residual; we quantify this effect across contrast but do not claim to have discovered it. Recent work argues that many PINN failures are artefacts of single precision [28] and that optimiser and precision interact [23]; our Intervention C tests this claim on interface problems.

2.4 Electromagnetic applications, benchmarks and finite elements

PINN studies of electric-field distributions and dielectric scattering typically smooth the permittivity or report global errors [1, 29], and the PINNacle benchmark evaluates PINNs across many PDE families [7]. Classical numerical analysis shows that gradients at interfaces are typically one order less accurate than the solution, even for finite elements [16]. The systematic comparison of Grossmann et al. [5] finds FEM faster and more accurate than PINNs on problems without material interfaces. A cost-to-target comparison on interface-band field accuracy against interface-conforming FEM was not found in our review.

2.5 Positioning of this work

Relative to the closest studies, this work (i) reports interface-band E and D error against a fixed failure threshold alongside global potential error; (ii) sweeps contrast over three orders of magnitude, including inverse contrast, with five seeds per configuration and no best-seed selection; (iii) attributes failure through matched-seed interventions rather than single remedies; (iv) compares cost-to-accuracy against interface-conforming FEM; and (v) releases the evaluator, run database and change log. It proposes no new architecture as its main contribution.

3. Research questions and hypotheses

The research questions concern failure onset and its dependence on formulation (RQ1), the masking of interface error by global metrics (RQ2), failure mechanisms (RQ3–RQ5), robustness (RQ6), cost relative to FEM (RQ7), transfer across geometry (RQ8), evaluator reusability (RQ9), corner fields (RQ10) and early-training predictors (RQ11). Each was turned into a falsifiable hypothesis with explicit support and refutation criteria, frozen before the primary sweep (Appendix B). Gaps found later, for example which

configurations count for H5, were filled by dated change-log entries written before the affected runs (Appendix F). Of the eleven hypotheses, four were supported, four refuted, two were inconclusive and one (H5) was judged per intervention (Table 1).

Table 1. Pre-registered hypotheses and verdicts.

H	Statement (abridged)	Verdict
H1	Single-network strong form fails at κ > 1; error grows with κ for soft coupling	Supported (P1)
H2	Global potential error understates band field error (median R > 3)	Inconclusive on P1 (R = 2.39); R > 3 on P2–P5
H3	Soft-coupled failures are flux-dominated	Refuted: they are continuity failures
H4	High-κ F2 failures are optimisation, not representation, failures	Refuted by its criteria
H5	Each intervention moves failure in its predicted direction	A mixed, B refuted, D refuted, E mixed; C's no-effect prediction holds
H6	Rankings and masking are robust to settings	Inconclusive: ranking robust (8/8), R > 3 in 1/8
H7	Conforming FEM reaches 1% ⩾ 10× faster and is more accurate at equal cost	Supported (excluding degenerate κ = 1)
H8	P1 conclusions transfer to P2	Refuted (τ = 0.30 on failure counts)
H9	The evaluator is reusable	Supported, with a 1D → 2D qualification
H10	Smooth networks underestimate the corner field	Refuted: the sign depends on formulation and material
H11	Early gradient ratios predict failure	Supported (AUC 0.85), confounded with κ

4. Problems and formulations

Five problems of increasing geometric difficulty (Table 2) were solved with six formulation families (Table 3), all using identical networks, optimiser and budget. Throughout, $\varepsilon_1 = 1$ and $\varepsilon_2 = \kappa$.

4.1 Problems $(\varepsilon_1 = 1, \varepsilon_2 = \kappa)$

Table 2. Test problems.

ID	Geometry	Reference	Note
P1	1D layered capacitor on [0, 1], interface at a = 0.5, φ(0) = 1, φ(1) = 0	Exact (piecewise linear)	Conforming FEM is exact: degenerate for cost comparison
P2	Dielectric cylinder, radius 0.25, uniform field $E_0\hat{x}$, box of side 2	Exact isolated-cylinder solution as Dirichlet data	Curved interface
P3	Line charge λ = 2π at height 0.25 above a planar interface	Exact image solution	Networks learn w = φ + ln r_1; disc r_1 < 0.05 excluded
P4	Two-material corner; material 2 fills one quadrant	Exact singular eigen-solution φ = r^λ Φ(θ)	Field singular at the corner for κ > 1; disc r < 0.02 excluded
P5	Thin film, thickness t = 0.02, width 1, uniform field	Converged body-fitted quadratic FEM (< 0.1% band change; 1D three-slab check ~10^{-13})	Small corner squares excluded

Interface band and error metrics. The interface band B is the set of points within distance 0.05 of Γ (for P5 it also contains the film). For a quantity υ with reference υ* the relative L^2 error over a region S is

$$e_S(u)=\frac{\lVert u-u^{*}\rVert_{L^2(S)}}{\lVert u^{*}\rVert_{L^2(S)}} . \tag{3}$$

The primary metric is the larger of the band field and displacement errors, and a run fails when it exceeds 5%:

$$e_{\mathrm{prim}}=\max\big(e_B(\mathbf{E}),\,e_B(\mathbf{D})\big),\qquad \text{failure}\iff e_{\mathrm{prim}}>0.05 . \tag{4}$$

The masking ratio compares this with the global potential error:

$$R=\frac{e_{\mathrm{prim}}}{e_{\Omega}(\varphi)} . \tag{5}$$

Secondary metrics are the global, material-wise and band errors of φ, E and D; the relative potential and displacement jumps across Γ; capacitance and field-energy errors; and an effective-contrast diagnostic. Integrals are evaluated on fixed refined quadrature, independent of the training points.

4.2 Formulations

All formulations use fully connected tanh networks with three hidden layers of width 32 (2,209 parameters per network in 1D), trained with Adam and a cosine learning-rate decay from 10^{-3} to 10^{-4} over 3,000 steps in float32, on stratified jittered collocation points (Appendix C). Writing $r_i = \nabla\cdot(\varepsilon_i\nabla\varphi_i)$ for the PDE residual in material i, and N_i, N_Γ, N_∂ for the numbers of interior, interface and boundary points, the soft-coupled loss of F2 is

$$\mathcal{L}_{F2}=\sum_{i=1}^{2}\frac{1}{N_i}\sum_{\mathbf{x}\in\Omega_i} r_i(\mathbf{x})^2+\frac{1}{N_\partial}\sum_{\partial\Omega}(\varphi-g)^2+\frac{1}{N_\Gamma}\sum_{\Gamma}[\![\varphi]\!]^2+\frac{1}{N_\Gamma}\sum_{\Gamma}[\![\varepsilon\,\partial_n\varphi]\!]^2 . \tag{6}$$

F1 drops the two interface terms and uses a single network. F6 divides each residual by a frozen physical scale, the displacement scale being

$$D_s=\frac{\varepsilon_h V}{L},\qquad \varepsilon_h=\frac{2\varepsilon_1\varepsilon_2}{\varepsilon_1+\varepsilon_2} . \tag{7}$$

F5 minimises the Ritz energy estimated by Monte Carlo on fixed points,

$$J[\varphi]=\sum_{i=1}^{2}\frac{|\Omega_i|}{N_i}\sum_{\mathbf{x}\in\Omega_i}\tfrac12\,\varepsilon_i\,|\nabla\varphi(\mathbf{x})|^2 , \tag{8}$$

with the boundary conditions imposed exactly. The six formulations are summarised in Table 3.

Table 3. PINN formulations.

ID	Representation	Loss
F1	One network $\varphi(x)$	Strong-form residual $\varepsilon\varphi''$ per material + BCs; no interface term
F2	One network per material	Residuals, BCs, soft continuity $[\varphi] = 0$ and soft flux $[\varepsilon\varphi'] = 0$, unit weights
F3	One network $N(x, \lvert x - a\rvert)$ with a cusp input [24]	Residuals, BCs, soft flux
F4	Hard BCs and continuity: $\varphi = V(1 - x) + x(1 - x)[N_A + \max(x - a, 0)\, N_B]$	Residuals and soft flux
F5	As F3, with hard BCs	Ritz energy $\int \tfrac{1}{2}\varepsilon\lvert\nabla\varphi\rvert^2$ on fixed points [3]

ID	Representation	Loss
F6	As F2	As F2, each residual divided by its physical scale (frozen contrast-derived weights)

In 2D, F3 and F5 use a level-set feature ψ in place of |x − a|. F1, F2 and F6 were run at 11 contrasts {0.0005, 0.0025, 0.0125, 0.05, 0.2, 1, 5, 20, 80, 400, 2000}; F3–F5 at κ ∈ {1, 80, 2000}, a pre-registered reduction.

5. Experimental protocol

Seeds and summary statistics. Every configuration was trained with seeds 0–4 (0–9 in the intervention set); the seed fixes both the network initialisation and the collocation points. We report medians and interquartile ranges of the primary error and failure counts with Clopper–Pearson 95% intervals, and never select a best seed. Five seeds give coarse rates: 0/5 failures is compatible with a true failure rate of up to 52%.

Paired comparisons. Each intervention is compared with the unchanged baseline seed by seed. With k the number of seeds (out of n) in which the intervention lowers the primary error, the one-sided exact sign test gives

```
p=\sum_{j=k}^{n}\binom{n}{j}2^{-n} , \tag{9}
```

and the median paired difference is reported with a bootstrap 95% interval (10,000 resamples, seed 12345). A configuration supports a predicted direction when at least 9 of 10 seeds move that way; Holm-adjusted p-values are reported as secondary.

Budget and timing. Each run has a budget of 3,000 value-and-gradient evaluations. Wall-clock time is the sum of blocked update times after ahead-of-time compilation, measured with time.perf_counter on a single CPU core; compile time is recorded separately. L-BFGS runs count every function-and-gradient evaluation, verified against an independent host-side counter, and used 2,981–3,000.

Change control and reproducibility. The protocol was frozen at version 1.0.0. Every later decision is recorded with date, reason, affected experiments and reruns, including six code defects found during the study (Appendix F). A single pipeline regenerates every table and figure from the raw databases, and regression tests retrain stored configurations and require agreement to 10^{-13} (Appendix G).

6. Evaluator and reference validation

Before any PINN run, the evaluator passed a battery of self-tests (Gate 1): exact solutions must give zero error, controlled perturbations must give their known error, imposed interface jumps must be reported exactly, mutated metric code must be caught, and refined quadrature must agree. It passed 98 of 98 checks in one dimension and 17 of 17 for each of P2–P5. Each formulation's loss was then checked (Gate 3): it vanishes to round-off at the exact solution and is positive at constructed wrong solutions, except where invisibility is the point, F1 having exactly zero loss at the uniform-permittivity solution; all gradients are finite.

The finite-element references were validated by convergence (Figure 1). For P1, conforming FEM is exact to round-off for any mesh. For P2–P4, interface-conforming quadratic FEM converges in the band; at $\kappa = 80$, P2 reaches 1.0% band error at 30,337 degrees of freedom. Non-conforming FEM does not converge in the band at $\kappa \neq 1$ (P2: 0.21–580 on the meshes tested). For P3 at $\kappa = 2000$ even conforming FEM reaches only 12% at 1.2×10^5 degrees of freedom, so that configuration is hard for FEM as well.

The evaluator proved reusable within a dimension (H9). The one-dimensional evaluator was not modified after the P1 freeze, and the two-dimensional evaluator, written for P2, received a single additive hook for the P4 corner metrics; no metric definition was rewritten. The step from one to two dimensions required a new 69-line module.




Figure 1. Conforming quadratic FEM: primary band field error versus degrees of freedom for P2–P5. $\kappa = 1$ is omitted (exact to round-off); P5 errors are relative to the finest level; dotted line = 1%.

7. Results in 1D (P1)

Figure 2 shows the P1 failure map. Single-network F1 fails at every $\kappa \geq 5$, the interface-aware formulations F3–F5 fail from $\kappa = 20$, and the soft-coupled formulations F2 and F6 survive to $\kappa = 400$ and $\kappa = 2000$ respectively.




Figure 2. P1 failure map: failed seeds (of 5) by formulation and contrast; 10^4 is the pre-registered extension.

Over the 25 runs per formulation with $\kappa \in \{5, 20, 80, 400, 2000\}$, the failure counts are F1 25, F2 8, F3 19, F4 20, F5 20 and F6 3. The critical contrast, the smallest κ at which at least three of five seeds fail, is 5 for F1, 20 for F3–F5 and 2000 for F2 and F6. At the pre-registered extension $\kappa = 10^4$, F2 and F6 fail in all five seeds.

H1 is supported. F1 fails in all seeds at every $\kappa \geqslant 5$ because it converges to the uniform-permittivity solution, for which its loss is exactly zero, and F2's error grows monotonically with $\log \kappa$ (Spearman $\rho = 0.96$, 95% CI 0.90–0.98). H3 is refuted: failing F2 and F6 runs violate potential continuity (median jump 5.3% of the applied voltage) while the flux jump is small (median 2.6×10^{-4}), and none of the eleven failing runs is flux-dominated. H4 is refuted by its pre-registered criterion: supervised fitting of φ with the F2 architecture is not more accurate in the field than PINN training where F2 fails.

The interface-aware designs fail earlier than the plain soft-coupled ones. Pilot runs showed F3 and F5 succeeding with 20,000 steps, and L-BFGS rescues F3 (Section 10), so at this budget building the interface into the representation made optimisation harder rather than easier. Seed variability is large: F2 at $\kappa = 400$ gives band errors of 0.212, 0.082, 0.005, 0.011 and 0.048 for seeds 0–4, and reporting only the best seed would suggest 0.5% error where two of five runs fail.

8. Results in 2D (P2–P5)

In two dimensions the picture changes sharply. At $\kappa \in \{80, 2000\}$ every formulation fails all ten runs on P2, P3, P4 and P5, whereas on P1 the same cells give 6/10 failures for F2 and 3/10 for F6 (Figure 3).




Figure 3. Left: failed runs at $\kappa \in \{80, 2000\}$ per problem and formulation (5 seeds each). Right: median masking ratio R over $\kappa \neq 1$ runs; dashed line = H2 threshold R = 3.

8.1 Failure maps

Median band field errors at $\kappa = 80$ are listed in Table 4. Even the best entries, F2 and F6 on the thin film at about 7%, exceed the failure threshold.

Table 4. Median primary band field error at $\kappa = 80$ (5 seeds; 1 = 100%).

Problem	F1	F2	F3	F4	F5	F6
P2 cylinder	30	0.63	1.0	0.84	1.2	0.63
P3 line charge	31	6.1	3.5	8.5	1.3×10^4	10.5
P4 corner	14	0.69	1.0	17	1.7	0.70
P5 thin film	30	0.070	1.6	2.4	2.8	0.069

Away from $\kappa = 1$, the only passing two-dimensional configurations are F2 and F6 on P5 at $\kappa = 5$ (0/5 failed) and $\kappa = 20$ (2/5 and 1/5 failed), and F2 on P3 at mild inverse contrasts (0/5 failed at $\kappa = 0.2$ and 0.05). The critical contrast of F2 and F6 thus drops from 2000 on P1 to 5 on P2–P4 and 80 on P5. H8 is refuted: Kendall's τ between the P1 and P2 formulation rankings by failure count is 0.30, below the pre-registered 0.6. On median error τ is 0.73, so the ordering of errors partly transfers while the pass/fail picture does not.

8.2 Problem-specific findings

Cylinder (P2). F2 and F6 plateau at a band error of about 0.63. A float64 run of 20,000 steps at $\kappa = 5$ stays at 0.486 from step 4,000 to step 20,000, with per-term gradients of order 0.1 that cancel. Minimising the F2 loss over a three-parameter family that contains the exact solution recovers it to six digits (loss $\approx 10^{-31}$), so the loss is correct and the plateau is a property of network training.

Fixed-point quadrature overfitting (F5). F5 fails even at $\kappa = 1$ on P2 and P4. On P2 its Monte Carlo energy (8) on the fixed points (0.59–1.59) falls below the true minimum energy (2.0), while the true energy of its prediction is 4.2–75: the network fits the quadrature points rather than the field.

Line charge (P3). Subtracting the singular part separately in each material, a pre-registered sensitivity analysis, lowers F2′s error at $\kappa = 80$ from 6.1 to 0.61, but all five seeds still fail.

Corner (P4). H10 is refuted. F2 underestimates the near-corner field on both bisectors (median signed $|E|$ error −0.58 to −0.88), but F1 overestimates it in the high-permittivity wedge (+5.7 at $\kappa = 80$, +18.6 at $\kappa = 2000$). The sign of the error depends on formulation and material.

Thin film (P5). The band error of F2 at $\kappa = 80$ falls for thinner films (13% at $t = 0.1$, 7.0% at $t = 0.02$, 3.4% at $t = 0.005$), but the error inside the film stays at 13–16% for every thickness; the pooled band metric is dominated by the easier exterior field. Increasing the number of film collocation points (128, 512, 2,048) has no measurable effect (0.069, 0.070, 0.069). F3 and F5 fail even at $\kappa = 1$, plausibly because the frozen level-set feature reaches magnitudes of about 150 away from the film and saturates their tanh inputs; this was not tested further.

8.3 Masking: global potential error versus band field error (H2)

The ratio R = band field error / global potential error ($\kappa \neq 1$ runs) has medians 2.39 (P1), 7.5 (P2), 3.95 (P3), 4.0 (P4) and 8.2 (P5); $R > 1$ in 97–100% of runs. Failures with global potential error below 5% ("concealed") are 23%, 1.7%, 2.4%, 11.7% and 37% of failures respectively. H2′s threshold $R > 3$ is not met on P1 (CI 1.73–3.18), so H2 is inconclusive as stated; it is met on every 2D problem.

9. Failure mechanisms

Four failure mechanisms are directly measured.

Loss invisibility. F1′s loss is exactly zero at a wrong solution [15]. Rescaling its residuals cannot help: under Intervention B, F1 converges to the uniform-permittivity solution at every κ with the identical loss value 2.147×10^{-6} (Section 10).

Continuity rather than flux. Soft-coupled F2 and F6 fail with an unsatisfied potential-continuity condition, both on P1 and on P2 (Sections 7 and 8.2).

Early gradient imbalance, confounded with contrast (H11). The median over steps 0–300 of the $\log_{10}$ ratio of the largest to the smallest weighted per-term gradient norm predicts failure with AUC 0.85 (95% CI 0.77–0.92). It is, however, strongly correlated with log κ ($\rho = 0.81$), and within a single κ the AUC ranges from 0.42 to 0.88, so its predictive value is largely that of contrast itself (Appendix E).

Fixed-point quadrature overfitting. The Ritz formulation minimises a Monte Carlo estimate (8) that can be driven below the true minimum energy on a fixed point set (Sections 8.2, 10 and Appendix F).

We offer the following interpretation, which these experiments do not demonstrate. At high contrast the unit-weight flux penalty in (6), whose scale grows as D^2, dominates the continuity penalty; the optimiser satisfies flux balance first and is left at a stationary point with a potential jump. F6′s physical rescaling (7) is consistent with its lower one-dimensional failure count. On curved, singular and thin geometries the same stationary point is reached at much lower contrast, and on P2 neither a stronger optimiser nor a longer budget escapes it (Section 12).

10. Controlled interventions (P1; H4, H5)

Five interventions were applied on P1, each changing one factor relative to the baseline, using seeds 0–9 paired with the unchanged baseline seed by seed, and judged by criteria logged before its runs (1,155 rows, of which 270 were superseded after a defect fix; see C below). Only the optimiser change (E) substantially reduced one-dimensional failures; rebalancing (A) was mixed, residual normalisation (B) and hard continuity (D) did not help, and the apparent precision effect (C) proved to be an initialisation artefact (Table 5, Figure 4).

Table 5. Interventions on P1: predictions and pre-registered verdicts.

Intervention	Prediction	Verdict	Key numbers
A: gradient-norm rebalancing [25] (L2-norm variant, every 10 steps)	Lowers error for F2 and F3	Mixed: 3/12 supported	Helps F3 at $\kappa \geq 80$ (κ = 400 median 1.06 → 0.033); harms F2 at every κ (10/10 fail at κ = 1 and 5). F3 at κ = 80 does not survive Holm correction (p = 0.107)
B: residual normalisation r_i/ε_i	Helps F2 at $\kappa \geq 80$	Refuted (3/3)	1–2 of 10 seeds improve; F1 "no change" holds (identical flags 10/10)
C: float64	No material effect under Adam; larger under L-BFGS	Holds	Adam: median fold change 1.0001 (max 1.07), no flag changes; L-BFGS: float64 better in 6/6 cells (median fold 3.4)
D: hard interface conditions	F4 fails less than F2 at $\kappa \geq 400$; F4full < 1%	F4 refuted; F4full holds	F4 fails 10/10 from κ = 20; F4full median 1.2×10^{-6} to 9.9×10^{-4} (trivial on P1: the exact solution lies in its buffer space)
E: L-BFGS; Adam 2k → L-BFGS 1k (equal evaluations)	Lower error for F3 and F5	Mixed: 9/12 supported	F3 κ = 80: 0.55 → 3.5×10^{-5}; F5 refuted at κ = 1 (quadrature overfitting); F2 (descriptive) κ = 2000 failures 9/10 → 4/10

H4′s intervention clause is not met: A and B leave F2 at 9/10 failures at κ = 2000.




Figure 4. Pre-specified paired comparisons, one point per seed (10 matched seeds); colour = κ; points below the diagonal follow the predicted sign; dotted lines = 5% threshold.

Rebalancing inverts its intent near convergence. The pre-registered L²-norm variant of gradient rebalancing [25] updates the weight of each non-PDE term every ten steps as

```
\lambda_i\leftarrow
0.9\,\lambda_i+0.1\,\frac{\lVert\nabla_\theta\mathcal{L}_{\mathrm{pde}}\rVert
_2}{\lVert\nabla_\theta\mathcal{L}_i\rVert_2} . \tag{10}
```

Terms that are already satisfied have small gradients and therefore receive large weights (up to 5×10^4), while the still-violated continuity term, which has the largest gradient, is pushed down to 0.05. The behaviour was confirmed with an independent implementation (agreement to 6×10^{-8}). It applies to the variant tested, not to every rebalancing scheme.

Initialisation variability exceeds the precision effect. We first measured precision effects up to 20.7× in median error; investigation showed the float64 runs had drawn *different initial weights* from the float32 runs with the same seed. With identical initialisation the effect vanishes (fold change ⩽ 1.07). On this problem, initialisation alone exceeds the genuine precision effect under Adam by more than an order of magnitude, which supports seed-level reporting and cautions precision studies that do not control initial weights [28].

11. Robustness (P1; H6)

To test whether the conclusions depend on particular settings, the P1 study was repeated with one setting changed at a time: width 16 and 64, depth 2 and 5, 32 and 512 collocation points per material, an initial learning rate of 3×10^{-3}, and 12,000 training steps. Each variation covers all six formulations at $\kappa \in \{1, 80, 2000\}$ with five seeds (720 runs). Two descriptive extras were added: a parameter-matched two-network variant of width 22, and 16 additional collocation points per side inside the interface band. The formulation ranking is robust in all eight variations (Kendall τ-b ≥ 0.65), but the masking threshold $R > 3$ is met in only one of eight, so H6 is inconclusive by its criteria (Figure 5).




Figure 5. Robustness on P1: failed runs (of 15: $\kappa \in \{1, 80, 2000\} \times 5$ seeds) per formulation and setting, with Kendall τ-b against the baseline ranking and median R. Rows below the line are descriptive extras.

The ranking correlation is $\tau = 1$ in five of the eight variations and lowest (0.65) for 12,000 steps. The masking ratio is stable at 1.84–2.49 in seven variations, against 2.24 for the baseline on the same subset: the effect persists and it is the absolute threshold that fails. R also decreases with contrast, from 3.4 at $\kappa = 5$–20 to 2.1 at $\kappa = 2000$.

Longer training (12,000 steps) reduces F2 failures from 6 to 1 out of 15 but doubles the number of concealed failures (7 → 16) and raises R to 5.6; with more training the global potential error becomes a worse indicator of band field accuracy. Network capacity affects only F2 and F6. Parameter matching does not remove their advantage: at width 22, with fewer parameters than F1, they record 6 and 4 failures against 10 for every single-network formulation.

12. Comparison with finite elements (P2, P5; H7)

We compared the baseline PINNs, and the two remedies that changed outcomes on P1, with interface-conforming quadratic FEM on P2 and P5. The remedies were L-BFGS at equal budget for F2, F3 and F6 at $\kappa \in \{1, 80, 2000\}$ (90 runs) and Adam for 20,000 steps for F2 and F6 at $\kappa = 80$ (20 runs). FEM cost is mesh generation, assembly and a sparse direct solve. PINN time-to-target is the time of the first logged evaluation (every 250 steps) that meets the target, scaled from the run's wall-clock assuming constant cost per step; compile time is excluded. Two comparisons are reported (Figure 6): the time needed to reach 5% and 1% band field error, and the error of the FEM mesh whose cost is closest to the PINN's median wall-clock.




Figure 6. Error versus wall-clock on P2 and P5: PINN medians (bars = IQR over 5 seeds; colour = formulation, marker = optimiser/budget) against conforming and non-conforming FEM refinement; dotted lines = 5% and 1%.

No PINN configuration reaches 1% band field error at any $\kappa \neq 1$, in any of 64 configurations or any seed, including both remedies. Conforming FEM reaches 1% in 0.65–4.75 s on P2 and 0.10–0.58 s on P5. The 5% target is reached only by F2 and F6 on P5 at $\kappa = 80$, in about 5 s with L-BFGS and about 47 s with 20,000-step Adam, against 0.042 s for FEM, factors of roughly 115 and 1,100. At equal cost, the FEM error is 86 to 1.7×10^5 times lower than the PINN median error ($\kappa \neq 1$).

The remedies behave differently on the two problems. On P2 neither L-BFGS nor 20,000 steps moves F2 or F6 from their plateau (0.634, 0.635 and 0.635 at $\kappa = 80$), in contrast with P1, where L-BFGS rescued F3 and halved F2′s failures at $\kappa = 2000$. On P5, L-BFGS brings F2 and F6 just below 5% at $\kappa = 80$ and lowers their $\kappa = 2000$ errors (F2: 1.21 → 0.072), which nevertheless still fail.

H7: supported, excluding $\kappa = 1$. At $\kappa = 1$ FEM is exact at every mesh; there, 10 PINN configurations reach 1% within the first 250-step logging interval, so the 10× margin cannot be resolved at this logging resolution (logged ratios 21–139×).

Caveats. Timings are single-threaded CPU; P2 and P5 FEM ran on different CPU models; GPU training would change absolute PINN times but not which configurations reach 1%. $\kappa = 5$ and 20, where PINNs pass on P5, have no FEM refinement records, so the PINN′s most favourable regime is absent from the time-to-target comparison.

13. Limitations

All conclusions are conditional on the stated budget, small tanh networks, five seeds per configuration and the five problems tested.

Budget and architecture. The main budget is 3,000 gradient evaluations (12,000 and 20,000 in specific checks), the networks are small tanh MLPs, and training is in float32 except where stated. Larger networks, adaptive sampling, curricula over contrast and other interface architectures [2, 4, 19] were not tested at scale.

Statistical resolution. Five seeds per configuration give coarse failure rates; 0/5 failures has a 95% upper bound of 52%.

Reduced grid. F3–F5 were run at $\kappa \in \{1, 80, 2000\}$ only in two dimensions, so their two-dimensional critical contrasts are resolved only to that grid.

Pre-registration gaps. Several gaps were filled during the study, including the configuration sets for H5, the ten-seed failure threshold and the L-BFGS budget rule; all were logged before the affected runs. One analysis addition, the logging-resolution check for H7, was made after a trial analysis but before the verdict, and is stricter than the original rule.

Defects. Six code defects were found and fixed during the study, each with a regression test and with the original rows kept and labelled as superseded (Appendix F). Two of them changed reported results before correction: float64 runs initialised differently from float32 runs (270 runs rerun) and a biased F5 energy quadrature with non-uniform points (15 runs rerun).

Benchmark design. The P5 level-set scaling probably disadvantages F3 and F5; the success of F4full on P1 is trivial because the exact solution lies in its representation; interventions were run on P1 only and remedies on P2 and P5 only.

Bibliography. The author lists of references [1] and [29] could not be verified.

14. Discussion

Within the tested budget, PINN accuracy at dielectric interfaces is governed less by contrast alone than by geometry.

A planar 1D interface tolerates κ up to 400–2000 for soft-coupled two-network formulations; curved, singular and corner geometries fail from $\kappa = 5$, and the thin film from $\kappa = 80$. The dominant failure is a stationary point with unsatisfied potential continuity. More training, a better optimiser or higher precision escapes it in 1D but not on the curved interface.

Global potential error hides much of this: up to 37% of failures look accurate by that measure. Studies of PINNs for dielectric problems should therefore report interface-band field error with a stated threshold, and seed-level failure rates rather than best runs.

Several plausible remedies failed under matched seeds (rebalancing, residual normalisation, hard continuity), and the one apparent precision effect was an initialisation artefact. This argues for controlled, one-factor-at-a-time evaluation before attributing improvements to a method.

The study does not show that PINNs cannot solve these problems: interface-specialised architectures and larger budgets may succeed, and published work reports such successes, usually as best-of-several runs. Nor does it show that FEM is always preferable: P3 near a singular source is hard for conforming FEM too, and PINNs offer mesh-free inverse and parametric uses we did not evaluate. It shows that for these forward problems, on this hardware, with these formulations and budget, interface-conforming FEM reached 1% band field accuracy in seconds where no PINN configuration reached it at all.

15. Conclusion

Across six PINN formulations and five dielectric-interface problems, 1D success transfers poorly to 2D, global potential error systematically understates interface field error, no single tested intervention removes high-contrast failure on curved interfaces, and interface-conforming FEM dominates on accuracy per unit cost for the forward problems tested.

These conclusions rest on pre-registered hypotheses, seed-level statistics, interface-band field metrics, matched-seed interventions, robustness variations and an FEM cost comparison, all regenerable from the released raw data.

Data and code availability

The project repository, https://github.com/upcomingresearcher-cloud/PINNs-dielectric-, contains the source code, the raw databases (3,856 completed runs plus 60 technical-failure rows, superseded rows retained and labelled), processed outputs and figures, the frozen protocol and change log, and a single analysis pipeline (`scripts/make_all.py`) that regenerates every table and figure in about 70 s. Installation, testing (169 automated tests) and reruns are described in `docs/REPRODUCTION_GUIDE.md`.

Acknowledgments

The authors thank John DeMason (University of Michigan, Ann Arbor) for his support. This work received no specific funding; all computations were run on a single CPU core.

Author contributions

Devesh Patwari, Daksh Mehta, Tolga Uras Kurtay and Yasir Balat conceived and directed the study, reviewed the results and approved the final manuscript. The AI system Claude (Anthropic) was used extensively under the authors' direction: it wrote the code, ran the experiments, performed the analyses and drafted the manuscript. The authors take full responsibility for the content of this article.

Competing interests

The authors declare no competing interests.

References

1. arXiv:2607.27349 (2026). Physics-informed neural networks for 2D plane wave scattering in arbitrary dielectric structures. *arXiv preprint*. Author list not verified.

2. Chung, S. W., Castonguay, S. T., Roy, S., Penwarden, M. S., Fu, Y., Roy, P. (2026). Hard-constrained physics-informed neural networks for interface problems. *arXiv:2604.08453*.
3. E, W., Yu, B. (2018). The Deep Ritz method: a deep learning-based numerical algorithm for solving variational problems. *Communications in Mathematics and Statistics*, 6, 1–12.
4. Fan, H., Tan, Z. (2025). Novel and general discontinuity-removing PINNs for elliptic interface problems. *Journal of Computational Physics*, 529, 113861.
5. Grossmann, T. G., Komorowska, U. J., Latz, J., Schönlieb, C.-B. (2024). Can physics-informed neural networks beat the finite element method? *IMA Journal of Applied Mathematics*. doi:10.1093/imamat/hxae011
6. Guo, H., Yang, X. (2021). Deep unfitted Nitsche method for elliptic interface problems. *arXiv:2107.05325*.
7. Hao, Z., Yao, J., Su, C., Su, H., Wang, Z., Lu, F., Xia, Z., Zhang, Y., Liu, S., Lu, L., Zhu, J. (2023). PINNacle: a comprehensive benchmark of physics-informed neural networks for solving PDEs. *arXiv:2306.08827*.
8. He, C., Hu, X., Mu, L. (2020). A mesh-free method using piecewise deep neural network for elliptic interface problems. *arXiv:2005.04847*.
9. Hu, W.-F., Lin, T.-S., Lai, M.-C. (2022). A discontinuity capturing shallow neural network for elliptic interface problems. *Journal of Computational Physics*, 469, 111576.
10. Huang, Y. (2021). Parallel physics-informed neural networks with bidirectional balance. *arXiv:2111.05641*.
11. Jagtap, A. D., Karniadakis, G. E. (2020). Extended physics-informed neural networks (XPINNs): a generalized space-time domain decomposition based deep learning framework for nonlinear partial differential equations. *Communications in Computational Physics*, 28(5).
12. Jagtap, A. D., Kharazmi, E., Karniadakis, G. E. (2020). Conservative physics-informed neural networks on discrete domains for conservation laws. *Computer Methods in Applied Mechanics and Engineering*, 365, 113028.
13. Krishnapriyan, A. S., Gholami, A., Zhe, S., Kirby, R. M., Mahoney, M. W. (2021). Characterizing possible failure modes in physics-informed neural networks. *Advances in Neural Information Processing Systems*, 34.
14. Moseley, B., Markham, A., Nissen-Meyer, T. (2023). Finite basis physics-informed neural networks (FBPINNs). *Advances in Computational Mathematics*, 49(4), 62.
15. Nohra, M., Dufour, S. (2024). Physics-informed neural networks for the numerical modeling of steady-state and transient electromagnetic problems with discontinuous media. *arXiv:2406.04380*.

16. Qin, F., Wang, Z., Ma, Z., Li, Z. (2017). Accurate gradient computations at interfaces using finite element methods. *International Journal of Applied Mathematics and Computer Science*, 27(3), 527–537. doi:10.1515/amcs-2017-0037
17. Rahaman, N., Baratin, A., Arpit, D., Draxler, F., Lin, M., Hamprecht, F., Bengio, Y., Courville, A. (2019). On the spectral bias of neural networks. *International Conference on Machine Learning*, 5301–5310.
18. Raissi, M., Perdikaris, P., Karniadakis, G. E. (2019). Physics-informed neural networks. *Journal of Computational Physics*, 378, 686–707.
19. Roy, S., Annavarapu, C., Roy, P., Sarma, A. K. (2024). Adaptive interface-PINNs (AdaI-PINNs). *arXiv:2406.04626*.
20. Sarma, A. K., Roy, S., Annavarapu, C., Roy, P., Jagannathan, S. (2024). Interface PINNs (I-PINNs). *Computer Methods in Applied Mechanics and Engineering*, 429, 117135.
21. Sukumar, N., Srivastava, A. (2022). Exact imposition of boundary conditions with distance functions in physics-informed deep neural networks. *Computer Methods in Applied Mechanics and Engineering*, 389, 114333.
22. Sun, Q., Xu, X., Yi, H. (2025). Dirichlet–Neumann learning algorithm for solving elliptic interface problems. *Communications in Computational Physics*, 38(1), 248–284. doi:10.4208/cicp.OA-2024-0046
23. Tarekegn, M., Wu, C., Sharma, T., Garg, S. (2026). Optimizer or precision? Understanding optimizer-precision interactions in PINNs. *NeurIPS (poster)*.
24. Tseng, Y.-H., Lin, T.-S., Hu, W.-F., Lai, M.-C. (2023). A cusp-capturing PINN for elliptic interface problems. *Journal of Computational Physics*, 491, 112359.
25. Wang, S., Teng, Y., Perdikaris, P. (2021). Understanding and mitigating gradient flow pathologies in physics-informed neural networks. *SIAM Journal on Scientific Computing*, 43(5), A3055–A3081.
26. Wu, S., Lu, B. (2022). INN: interfaced neural networks as an accessible meshless approach for solving interface PDE problems. *Journal of Computational Physics*, 470, 111588.
27. Wu, S., Zhu, A., Tang, Y., Lu, B. (2023). Convergence of physics-informed neural networks applied to linear second-order elliptic interface problems. *Communications in Computational Physics*, 33(2), 596–627. doi:10.4208/cicp.OA-2022-0218
28. Xu, C., Liu, D., Nassereldine, A., Xiong, J. (2025). FP64 is all you need: rethinking failure modes in physics-informed neural networks. *NeurIPS (poster)*; arXiv:2505.10949.
29. Zhang et al. (2023). Physics informed neural networks for electric field distribution characteristics analysis. *Journal of Physics D: Applied Physics*, 56, 165202. Author list not verified.

30. Zhang, B., Wu, G., Gu, Y., Wang, X., Wang, F. (2022). Multi-domain physics-informed neural network for steady-state heat conduction in multilayer media. *Physics of Fluids*, 34(11).

Appendix A. Nomenclature

Table A1. Symbols and abbreviations.

Symbol	Meaning
φ	Electric potential
$E = -\nabla\varphi$	Electric field
$D = \varepsilon E$	Electric displacement
$\varepsilon_1, \varepsilon_2$	Permittivities of materials 1 and 2 ($\varepsilon_1 = 1$)
$\kappa = \varepsilon_2/\varepsilon_1$	Permittivity contrast; $\kappa < 1$ is an inverse contrast
Γ, B	Material interface; interface band (points within 0.05 of Γ)
[[·]]	Jump across Γ
e_S(u)	Relative L^2 error of u over region S, eq. (3)
e_prim	Primary metric: max of band E and D errors, eq. (4)
R	Masking ratio e_prim / e_Ω(φ), eq. (5)
D_s, ε_h	Displacement scale and harmonic-mean permittivity used by F6, eq. (7)
J[φ]	Monte Carlo Ritz energy used by F5, eq. (8)
λ_i	Loss weight of term i under rebalancing, eq. (10)
τ, τ-b	Kendall rank correlation (tie-corrected)
AUC	Area under the ROC curve
DOF	Degrees of freedom of an FEM discretisation
FEM	Finite element method
L-BFGS	Limited-memory Broyden–Fletcher–Goldfarb–Shanno optimiser
PINN	Physics-informed neural network

Appendix B. Pre-registered hypotheses and criteria

The criteria below are reproduced from the frozen experimental protocol (version 1.0.0). Operational details added before the relevant runs, such as H5′s configuration sets, are listed in Appendix F.

Table B1. Hypotheses, experiments and decision criteria.

H	Relationship	Experiment	Supported if	Refuted if
H1	Contrast drives failure for F1 and unit-weight soft coupling (F2); interface-aware designs fail less	P1 primary sweep	F1 fails ⩾ 4/5 at every $\kappa \geqslant 5$; Spearman ρ(log κ, error) for F2 > 0 with CI excluding 0; each of F3–F6 has fewer failed seeds than F1 over $\kappa > 1$	F1 passes ⩾ 2/5 at any $\kappa \geqslant 20$; or F2 ρ CI includes 0 or is negative; or any of F3–F6 fails as often as F1
H2	Global potential error understates band field error	All P1 runs with $\kappa > 1$	Median $R > 3$; $R > 1$ in ⩾ 80% of runs; ⩾ 20% of failures concealed ($e_\Omega(\varphi) < 5\%$)	Median $R \leqslant 1$
H3	Soft-coupled failures violate flux, not potential, continuity	F2, F6 runs	⩾ 80% of failing runs have relative D jump > 5% and relative φ jump < 1%	< 50% show the flux-dominant pattern
H4	F1 failures are loss-visibility failures; high-κ F2 failures are optimisation failures	Regression baseline; loss visibility; Interventions A/B	Regression < 1% for every architecture and κ; $L_{F1}(\text{wrong}) \leqslant L_{F1}(\text{exact})$; $L(\text{wrong})/L(\text{exact}) > 10$ for F2–F6; A or B removes ⩾ 3 F2 failures where the baseline fails ⩾ 4/5	Regression > 5% where F2 fails; or interventions change no F2 outcome
H5	Each intervention moves failure in a stated direction	Interventions A–E, matched seeds	Predicted sign in ⩾ 9/10 seeds	Predicted sign in ⩽ 5/10 seeds, or opposite sign in ⩾ 9/10

H	Relationship	Experiment	Supported if	Refuted if
H6	Rankings and masking are not artefacts of one setting	Eight robustness variations	$\tau \geqslant 0.6$ in $\geqslant 6/8$ variations and median $R > 3$ in $\geqslant 6/8$	$\tau < 0.6$ in $\geqslant 3/8$
H7	Conforming FEM reaches accuracy at much lower cost and is more accurate at equal time	Remedy comparison on P2, P5	For every formulation, FEM time-to-1% $\geqslant 10\times$ smaller than PINN median, or PINN never reaches 1%; FEM error at PINN median time lower	Any PINN median time-to-target within $10\times$ of FEM
H8	P1 conclusions transfer to curved and singular geometries	P2–P5	$\tau \geqslant 0.6$ between P1 and P2 rankings; median $R > 3$ on each of P2–P5	$\tau < 0.6$, or $R \leqslant 1$ on any of P2–P5
H9	Evaluator reusable: new problems need only a problem module	P2–P5 implementation	No edits to evaluator core after the P1 freeze except additive metrics	A core metric function must be rewritten
H10	Smooth networks underestimate the near-corner field	P4	Median signed field error at $r = 0.02$ and 0.05 (fixed rays, each material) below −10% for F1 and F2	Within ±10%, or positive
H11	Early gradient ratios predict failure	P1 runs of F2, F3, F4, F6	AUC $\geqslant 0.75$ with CI lower bound > 0.5 (median log ratio, steps 0–300)	AUC CI includes 0.5

Appendix C. Training, sampling and evaluation settings

Table C1. Frozen settings (identical across formulations unless stated).

Setting	1D (P1)	2D (P2–P5)
Network	Fully connected, tanh, 3 hidden layers × 32	Same
Parameters per network	2,209	Same architecture; inputs per formulation
Initialisation	Glorot normal weights, zero biases; drawn in float32 and cast	Same
Optimiser	Adam ($\beta_1 = 0.9$, $\beta_2 = 0.999$, $\varepsilon = 10^{-8}$)	Same
Learning rate	Cosine decay $10^{-3} \to 10^{-4}$ over the budget	Same
Budget	3,000 value-and-gradient evaluations	Same
Precision	float32	float32
Collocation	Stratified jitter, 128 points per material	512 interior per material, 128 interface, 64 per box edge
Seeds	0–4 (0–9 for interventions)	0–4
Gradient logging	Per-term loss and gradient norms every 25 steps	Same
Metric logging	All evaluator metrics every 250 steps	Same
Interface band	Distance ⩽ 0.05 from Γ	Same (P5: includes film)
Failure threshold	e_prim > 0.05	Same
Contrasts	{1, 5, 20, 80, 400, 2000} + extension 10^4	F1, F2, F6: {0.0005, 0.0025, 0.0125, 0.05, 0.2, 1, 5, 20, 80, 400, 2000}; F3–F5: {1, 80, 2000}
Hardware	Single CPU core, Intel Xeon (2.10 and 2.80 GHz)	Same
Software	Python 3.12, JAX 0.11.2, Optax 0.2.8	Plus scikit-fem 12.0.2, gmsh 4.15.2

Intervention and remedy settings. L-BFGS uses memory 50 and a zoom line search with at most 20 steps; an iteration starts only if its worst case fits in the remaining budget. The hybrid variant runs Adam for 2,000 steps with its own full cosine schedule, then L-BFGS for at most 1,000 evaluations. Rebalancing (A) updates λ every 10 steps by (10). Residual normalisation (B) divides the PDE residual of material i by ε_i; interface residuals are unchanged.

Appendix D. Complete two-dimensional failure maps

Figures D1–D4 give the failed-seed counts (of 5) for every formulation and contrast on each two-dimensional problem. Cells marked "not run" follow the pre-registered reduced grid for F3–F5; κ < 1 denotes inverse contrast.




Figure D1. P2, dielectric cylinder: failed seeds of 5 (primary criterion).




Figure D2. P3, line charge above a planar interface: failed seeds of 5.




Figure D3. P4, two-material corner: failed seeds of 5.




Figure D4. P5, thin high-permittivity film: failed seeds of 5.

Appendix E. Intervention, robustness and training-dynamics details

Table E1. Intervention and remedy run sets.

Set	Formulations	Contrasts	Seeds	Runs
Baseline extension (seeds 5–9)	F1–F4 (all κ), F5 (3 κ)	P1 primary grid	5–9	135
A: rebalancing	F2, F3	6 primary κ	0–9	120
B: residual normalisation	F1, F2	6 primary κ	0–9	120
C: float64 replica (Adam)	F1–F6	6 primary κ	0–4	180
C: float64 2 × 2 cells	F2, F3	1, 80, 2000	0–9	30 Adam + 60 L-BFGS

Set	Formulations	Contrasts	Seeds	Runs
D: F4full	F4full	6 primary κ	0–9	60
E: L-BFGS; Adam 2k → L-BFGS 1k	F2, F3, F5	1, 80, 2000	0–9	90 + 90
Remedies (P2, P5): L-BFGS	F2, F3, F6	1, 80, 2000	0–4	90
Remedies (P2, P5): Adam 20,000 steps	F2, F6	80	0–4	20

The 270 float64 runs originally recorded under C were superseded after the initialisation defect was fixed (Appendix F); with matched initialisation the median fold change of the primary error under Adam is 1.0001 (maximum 1.07, no failure-flag changes), against 1.38 (maximum 20.7) for the superseded runs.

Table E2. Robustness on P1: failed runs of 15 ($\kappa \in \{1, 80, 2000\} \times 5$ seeds), Kendall τ-b against the baseline ranking, and median masking ratio R ($\kappa > 1$).

Setting	F1	F2	F3	F4	F5	F6	τ-b	R
Baseline	10	6	10	10	10	3	1	2.24
Width 16	10	9	10	10	10	5	1.00	1.84
Width 64	10	5	10	10	10	0	1.00	2.37
Depth 2	10	7	10	10	10	5	1.00	2.18
Depth 5	10	5	10	10	10	2	1.00	2.25
32 points/material	10	6	10	10	11	3	0.87	2.28
512 points/material	10	6	10	10	10	3	1.00	2.24
Learning rate 3×10^{-3}	10	5	9	10	10	1	0.87	2.49
12,000 steps	10	1	7	10	7	2	0.65	5.62
Width 22 (extra)	10	6	10	10	10	4	1.00	2.28
16 band points/side (extra)	10	6	10	10	10	3	1.00	2.02

Figure E1 shows training convergence of the primary error for representative formulations and problems, and Figure E2 the relation between early gradient imbalance and final error underlying H11.




Figure E1. Primary band field error every 250 Adam steps (median, shaded = IQR over 5 seeds) for P1 F2, F3, F6 and P2, P5 F2, F6 at κ = 1, 80 and 2000; dashed line = 5%.




Figure E2. Median early (steps 0–300) $\log_{10}$ ratio of largest to smallest weighted per-term gradient norm versus final primary error, P1, coloured by κ; dashed line = 5%.

Appendix F. Protocol change log and defect record

The protocol was frozen at version 1.0.0 and reached version 1.6.0 by the end of the study. Every change records its date, reason, affected experiments and required reruns. The principal operational decisions, each logged before the runs it governs, are summarised in Table F1 and the defects in Table F2.

Table F1. Principal post-freeze decisions.

Item	Decision	Logged
Robustness budget variation	12,000-step variation added after the pilot	Before the primary sweep (v1.1.0)

Item	Decision	Logged
H5 configuration sets	A: F2, F3 × 6 κ; B: F2 at κ ⩾ 80; D: F4 vs F2 at κ ⩾ 400; E: F3, F5 × {1, 80, 2000} × 2 variants	Before intervention runs
10-seed failure threshold	A configuration fails if ⩾ 6/10 seeds fail (sensitivity ⩾ 5/10)	Before intervention runs
L-BFGS budget rule	Count every function-and-gradient evaluation; start an iteration only if its worst case fits	Before intervention runs
Residual normalisation (B)	Applied to material PDE residuals only	Before intervention runs
Robustness reference and τ	Baseline on the same subset; τ-b on failure counts; undefined τ counts as < 0.6	Before robustness runs
Remedy selection (Phase 13)	L-BFGS and 20,000-step Adam; A and B not carried over (refuted on P1)	Before remedy runs
H7 resolution check	Clause 1 also tested at the lower bound of each 250-step logging interval (stricter)	After a trial analysis, before the verdict

Table F2. Defects found, effect and remedy (each with a regression test; superseded rows retained).

Defect	Effect on results	Remedy
Gradient formula error in 2D FEM post-processing	None (caught by a reproduction test before use)	Fixed
Shape error in ahead-of-time compiled 2D training (P3)	60 runs failed for a technical reason	Fixed; runs repeated; failed rows kept
Derivative error in P4 verification code	None (verification code only)	Fixed
float64 runs initialised with different weights from float32 runs	Precision effect overstated (up to 20.7×)	Initialisation drawn in float32 and cast; 270 runs rerun

Defect	Effect on results	Remedy
F5 energy estimate unweighted with non-uniform extra band points	F5 failed at $\kappa = 1$ in a robustness extra	Importance weights $1/\rho$; 15 runs rerun
Missing problem filter in a P2 summary script	Regenerated P2 tables would mix other problems' FEM rows	Filter added; outputs regenerated

Unexpected results that were investigated and found not to be defects include the low-contrast degradation under rebalancing (Section 10), F5 quadrature overfitting under L-BFGS at $\kappa = 1$, and the F1norm magnitudes under Intervention B.

Appendix G. Reproducibility and software

The project repository (https://github.com/upcomingresearcher-cloud/PINNs-dielectric-) contains the source code, raw run databases, processed tables, figures, the frozen protocol, the change log and a reproduction guide. Every completed run is one row of the database with its full configuration, all metrics, cost, software environment, hardware and git commit; per-run training trajectories (every 250 steps) and per-term gradient logs (every 25 steps) are stored separately.

Table G1. Reproduction steps.

Step	Command	Time on one CPU core
Install pinned environment	sh scripts/setup_environment.sh	Minutes
Rebuild P5 FEM references	python scripts/rebuild_p5_references.py	About 3 min
Run all tests (169)	python -m pytest tests	About 9 min
Evaluator self-tests	python scripts/run_evaluator_selftests.py; scripts/run_selftests_2d.py P2 … P5	About 1 min
Regenerate every table and figure	python scripts/make_all.py	About 70 s

Regression tests retrain stored primary configurations in one and two dimensions and require agreement with the database to 10^{-13}. Results are deterministic on the same software stack and CPU type; different hardware or library versions can change individual

runs at round-off level, which training dynamics can amplify, so medians and failure counts are the quantities to compare. Software: Python 3.12, NumPy 2.4.4, SciPy 1.17.1, pandas 3.0.2, JAX 0.11.2, Optax 0.2.8, scikit-fem 12.0.2, gmsh 4.15.2, Matplotlib 3.10.8.