



NANJING UNIVERSITY

ACM-ICPC Codebook 2

Number Theory
Linear Algebra
Combinatorics

August 1, 2017

Contents

1	Number Theory	4
1.1	Modulo operations	4
1.1.1	Modular exponentiation (fast power-mod)	4
1.1.2	Mathematical modulo operation	4
1.2	Extended Euclidian algorithm	4
1.2.1	Modular multiplicative inverse	5
1.3	Primality test (Miller-Rabin)	5
1.4	Sieve of Eratosthenes	6
1.5	Number theoretic transform	6
2	Linear Algebra	8
2.1	Modular exponentiation of matrices	8
3	Combinatorics	9
3.1	Möbius inversion	9
3.2	Pólya enumeration theorem	9

1 Number Theory

1.1 Modulo operations

1.1.1 Modular exponentiation (fast power-mod)

Calculate $b^e \bmod m$.

Time complexity: $O(\log e)$

```

1 LL powmod(LL b, LL e, LL m){
2     LL r = 1;
3     while (e){
4         if (e & 1) r = r * b % m;
5         b = b * b % m;
6         e >>= 1;
7     }
8     return r;
9 }
```

1.1.2 Mathematical modulo operation

The result has the same sign as divisor.

```

1 inline LL mathmod(LL a, LL b){
2     return (a % b + b) % b;
3 }
```

1.2 Extended Euclidian algorithm

Solve $ax + by = g = \gcd(a, b)$ w.r.t. x, y .

If (x_0, y_0) is an integer solution of $ax + by = g = \gcd(x, y)$, then every integer solution of it can be written as $(x_0 + kb', y_0 - ka')$, where $a' = a/g$, $b' = b/g$, and k is arbitrary integer.

\triangle x and y must be positive.

Usage:

`exgcd(a, b, g, x, y)` Find a special solution to $ax+by = g = \gcd(a, b)$.

Time complexity: $O(\log \min\{a, b\})$

```

1 void exgcd(LL a, LL b, LL &g, LL &x, LL &y){
2     if (!b) g = a, x = 1, y = 0;
3     else exgcd(b, a % b, g, y, x), y -= x * (a / b);
4 }

```

1.2.1 Modular multiplicative inverse

An integer a has modular multiplicative inverse w.r.t. the modulus m , iff $\gcd(a, m) = 1$. Assume the inverse is x , then

$$ax \equiv 1 \pmod{m}.$$

Call `exgcd(a, m, g, x, y)`, if $g = 1$, $x + km$ is the modular multiplicative inverse of a w.r.t. the modulus m .

```

1 inline LL minv(LL a, LL m){
2     LL g, x, y;
3     exgcd(a, m, g, x, y);
4     return (x % m + m) % m;
5 }

```

Or, by Fermat's little theorem ($a^{p-1} \equiv 1 \pmod{p}$), when $m = p$ is a prime, the multiplicative inverse can also be written as $a^{-1} = (a^{p-2} \pmod{p})$.

1.3 Primality test (Miller-Rabin)

Test whether n is a prime.

The array `a[]` (excluding sentinel, e.g. `LLONG_MAX`) should be

<code>{2}</code>	when $n < 2,047$.
<code>{2, 7, 61}</code>	when $n < 4,759,123,141$ (2^{32}).
<code>{2, 3, 5, 7, 11}</code>	when $n < 2.1 \times 10^{12}$.
<code>{2, 325, 9375, 28178, 450775, 9780504, 1795265022}</code>	when $n < 2^{64}$.

△ When n exceeds the range of `int`, the `mul-mod` and `pow-mod` operations should be rewritten.

Requirement:

1.1.1 Modular exponentiation (fast power-mod)

Time complexity: $O(\log n)$

```

1 bool test(LL n){
2     if (n < 3) return n==2;

```

```

3 // ! The array a[] should be modified if the range of x changes.
4 const LL a[] = {2LL, 7LL, 61LL, LLONG_MAX};
5 LL r = 0, d = n-1, x;
6 while (~d & 1) d >>= 1, r++;
7 for (int i=0; a[i] < n; i++){
8     x = powmod(a[i], d, n);
9     if (x == 1 || x == n-1) goto next;
10    rep (i, r) {
11        x = (x * x) % n;
12        if (x == n-1) goto next;
13    }
14    return false;
15 next:;
16 }
17 return true;
18 }

```

1.4 Sieve of Eratosthenes

Usage:

sieve()	Generate the table.
p[i]	True if i is not a prime; otherwise false.

Time complexity: Approximately linear.

```

1 const int MAXX = 1e7+5;
2 bool p[MAXX];
3
4 void sieve(){
5     p[0] = p[1] = 1;
6     for (int i = 2; i*i < MAXX; i++) if (!p[i])
7         for (int j = i*i; j < MAXX; j+=i) p[j] = true;
8 }

```

1.5 Number theoretic transform

△ The size of the sequence must be some power of 2.

△ When performing convolution, the size of the sequence should be doubled. To compute k , one may call `32-__builtin_clz(a+b-1)`, where a and b are the lengths of two sequences.

Usage:

NTT(k)	Initialize the structure with maximum sequence length 2^k .
ntt(a)	Perform number theoretic transform on sequence a .
intt(a)	Perform inverse number theoretic transform on sequence a .
conv(a, b)	Convolve sequence a with b .

Time complexity: $O(n \log n)$.

```

1  const int NMAX = 1<<21;
2  // 998244353 = 7*17*2^23+1, G = 3
3  const int P = 1004535809, G = 3; // = 479*2^21+1
4
5  LL rev[NMAX];
6  LL omega[NMAX], oinv[NMAX];
7  struct NTT{
8      int g, g_inv; // g: g_n = G^((P-1)/n)
9      int K, N;
10
11      LL powmod(LL b, LL e){
12          LL r = 1;
13          while (e){
14              if (e&1) r = r * b % P;
15              b = b * b % P;
16              e >>= 1;
17          }
18          return r;
19      }
20
21      NTT(int k){
22          K = k; N = 1 << k;
23          g = powmod(G, (P-1)/N);
24          g_inv = powmod(g, N-1);
25          omega[0] = oinv[0] = 1;
26          rep (i, N){
27              rev[i] = (rev[i>>1]>>1) | ((i&1)<<(K-1));
28              if (i){
29                  omega[i] = omega[i-1] * g % P;
30                  oinv[i] = oinv[i-1] * g_inv % P;
31              }
32          }
33      }
34
35      void _ntt(LL* a, LL* w){
36          rep (i, N) if (i < rev[i]) swap(a[i], a[rev[i]]);
37          for (int l = 2; l <= N; l *= 2){
38              int m = l/2;
39              for (LL* p = a; p != a + N; p += l)
40                  rep (k, m){
41                      LL t = w[N/l*k] * p[k+m] % P;

```

```

42         p[k+m] = (p[k] - t + P) % P;
43         p[k] = (p[k] + t) % P;
44     }
45 }
46 }
47
48 void ntt(LL* a){_ntt(a, omega);}
49 void intt(LL* a){
50     LL inv = powmod(N, P-2);
51     _ntt(a, oinv);
52     rep (i, N) a[i] = a[i] * inv % P;
53 }
54
55 void conv(LL* a, LL* b){
56     ntt(a); ntt(b);
57     rep (i, N) a[i] = a[i] * b[i] % P;
58     intt(a);
59 }
60 };

```

2 Linear Algebra

2.1 Modular exponentiation of matrices

Calculate $b^e \bmod \text{modular}$, where b is a matrix. The modulus is element-wise.

Usage:

<code>n</code>	Order of matrices.
<code>modular</code>	The divisor in modulo operations.
<code>m_powmod(b, e)</code>	Calculate $b^e \bmod \text{modular}$. The result is stored in <code>r</code> .

Time complexity: $O(n^3 \log e)$

```

1  const int MAXN = 105;
2  const LL modular = 1000000007;
3  int n; // order of matrices
4
5  struct matrix{
6      LL m[MAXN][MAXN];
7
8      void operator *=(matrix& a){
9          static LL t[MAXN][MAXN];
10         Rep (i, n){
11             Rep (j, n){

```



```

12         t[i][j] = 0;
13     Rep (k, n){
14         t[i][j] += (m[i][k] * a.m[k][j]) % modular;
15         t[i][j] %= modular;
16     }
17 }
18 }
19 memcpy(m, t, sizeof(t));
20 }
21 };
22
23 matrix r;
24 void m_powmod(matrix& b, LL e){
25     memset(r.m, sizeof(r.m), 0);
26     Rep(i, n)
27         r.m[i][i] = 1;
28     while (e){
29         if (e & 1) r *= b;
30         b *= b;
31         e >>= 1;
32     }
33 }

```

3 Combinatorics

3.1 Möbius inversion

Möbius function:

$$\mu(n) = \begin{cases} 1 & \text{if } n = 1 \\ 0 & \text{if } p_i^{a_i} \mid n \text{ where } a_i > 0 \\ (-1)^r & \text{if } n \text{ is the product of } r \text{ distinct primes} \end{cases}$$

If $S_f(n) = \sum_{d|n} f(d)$, then $f(n) = \sum_{d|n} \mu(d) S_f(n/d)$.

3.2 Pólya enumeration theorem