

NAME:- U.Praneeth

ROLL NO:-2520030188

EXP 1:-

```
GNU nano 8.7.1
#include<stdio.h>
int main()
{
printf("Welcome to OS\n");
return 0;
}
```

```
praneeth@PRANEETH:~/os$ nano hello.c
praneeth@PRANEETH:~/os$ gcc hello.c -o hello
praneeth@PRANEETH:~/os$ ./hello
Welcome to OS
```

EXP - 2 :-

```
GNU nano 8.7.1
#include<stdio.h>
int main()
{
    char name[30];
    printf("Enter your name\n");
    scanf("%s",name);
    printf("Welcome %s\n", name);
    return 0;
}
```

```
praneeth@PRANEETH:~/os$ gcc P2.c -o P2
praneeth@PRANEETH:~/os$ ./P2
Enter your name
Praneeth
Welcome Praneeth
```

EXP - 3 : -

```
#include<stdio.h>
#include<unistd.h>
int main()
{
printf("Process ID = %d\n",getpid());
return 0;
}
```

```
praneeth@PRANEETH:~$ gcc p4.c -o p4
praneeth@PRANEETH:~$ ./p4
Process ID = 819
praneeth@PRANEETH:~$ |
```

EXP - 4 (a) :-

```
#include<stdio.h>
#include<unistd.h>
int main()
{
fork();
printf("Hello\n");
return 0;
}
```

```
praneeth@PRANEETH:~$ gcc p5.c -o p5
praneeth@PRANEETH:~$ ./p5
Hello
Hello
praneeth@PRANEETH:~$ nano p5.c
praneeth@PRANEETH:~$ |
```

Exp: -4 (B) :

```
#include<stdio.h>
#include<unistd.h>
int main()
{
fork();
fork();
printf("Hello\n");
return 0;
}
```

```
praneeth@PRANEETH:~$ nano p6
praneeth@PRANEETH:~$ gcc p6a.c -o p6a
praneeth@PRANEETH:~$ ./p6a
Hello
Hello
Hello
Hello
praneeth@PRANEETH:~$ |
```

EXP-5 :-

```
#include<stdio.h>
#include<unistd.h>
int main()
{
    pid_t pid;
    pid=fork();
    if(pid==0)
    {
        printf("I am Child Process\n");
    }
    else
    {
        printf("I am Parent Process\n");
    }
    return 0;
}
```

```
praneeth@PRANEETH:~$ gcc p6.c -o p6
praneeth@PRANEETH:~$ ./p6
I am Parent Process
I am Child Process
praneeth@PRANEETH:~$ |
```

EXP-6:-

```
GNU nano 0.7.1
#include<stdio.h>
#include<unistd.h>
int main()
{
    pid_t pid;
    pid*fork();
    if(pid==0)
    {
        printf("Child PID = %d\n",getpid());
        printf("ParentPID = %d\n",getpid());
        return 0;
    }
}
```

```
praneeth@PRANEETH:~$ nano p7.c
praneeth@PRANEETH:~$ gcc p7.c -o p7
praneeth@PRANEETH:~$ ./p7
Child PID = 916
ParentPID = 916
Child PID = 917
ParentPID = 917
praneeth@PRANEETH:~$ nano p7.c
praneeth@PRANEETH:~$ |
```

EXP-7 :-

```
#include<stdio.h>
#include<unistd.h>
#include<sys/wait.h>

int main()
{
    pid_t pid;
    pid=fork();
    if(pid==0)
    {
        printf("Child Running\n");
    }
    else
    {
        wait(NULL);
        printf("Parent Running After Child\n");
    }
    return 0;
}
```

```
praneeth@PRANEETH:~$ gcc p8.c -o p8
praneeth@PRANEETH:~$ ./p8
Child Running
Parent Running After Child
praneeth@PRANEETH:~$ nano p8.c
praneeth@PRANEETH:~$ |
```