

NAME :- U.PRANEETH

ROLL NO:- 2520030188

SEC :-02

1.



praneeth@PRANEETH: ~



GNU nano 8.7.1

```
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];

    // Create socket
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    // Set socket address
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    // Remove old socket
    unlink(SOCKET_PATH);

    // Bind socket to path
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));

    // Wait for client
    listen(server_fd, 5);

    printf("Server waiting...\n");

    // Accept client
    client_fd = accept(server_fd, NULL, NULL);

    // Receive message
    read(client_fd, buffer, sizeof(buffer));

    printf("Message from client: %s\n", buffer);
```

```

printf("Server waiting...\n");

// Accept client
client_fd = accept(server_fd, NULL, NULL);

// Receive message
read(client_fd, buffer, sizeof(buffer));

printf("Message from client: %s\n", buffer);

close(client_fd);
close(server_fd);

unlink(SOCKET_PATH);

return 0;
}

```

^{^G} Help
^{^X} Exit

^{^O} Write Out
^{^R} Read File

^{^F} Where Is
^{^_\} Replace

^{^K} Cut
^{^U} Paste

^{^T} E
^{^J} J

OUTPUT:-

```

praneeth@PRANEETH:~$ nano socketserver.c
praneeth@PRANEETH:~$ gcc socketserver.c -o socketserver
praneeth@PRANEETH:~$ ./socketserver
Server waiting...
Message from client: Hello Server
praneeth@PRANEETH:~$ |

```

2.

```
praneeth@PRANEETH: ~  
GNU nano 8.7.1  
#include <stdio.h>  
#include <unistd.h>  
#include <sys/socket.h>  
#include <sys/un.h>  
#include <string.h>  
  
#define SOCKET_PATH "/tmp/my_socket"  
  
int main()  
{  
    int client_fd;  
    struct sockaddr_un address;  
  
    // Create socket  
    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);  
  
    // Set socket address  
    address.sun_family = AF_UNIX;  
    strcpy(address.sun_path, SOCKET_PATH);  
  
    // Connect to server  
    connect(client_fd,  
            (struct sockaddr *)&address,  
            sizeof(address));  
  
    // Send message  
    write(client_fd, "Hello Server", 12);  
    printf("Message sent to server.\n");  
  
    close(client_fd);  
  
    return 0;  
}
```

OUTPUT:-

```
praneeth@PRANEETH: ~  
praneeth@PRANEETH:~$ nano serverclient.c  
praneeth@PRANEETH:~$ gcc serverclient.c -o serverclient  
praneeth@PRANEETH:~$ ./serverclient  
Message sent to server.  
praneeth@PRANEETH:~$ |
```