




ROHS



### FPC INTERFACE

1	X(L)
2	Y(U)
3	X(R)
4	Y(D)
5	GND
6	IOVCC(1.8V/2.8V)
7	VCI(2.8)
8	FMARK
9	CS/SPI CS
10	RS/A0(4 WIRE)
11	WR/SPI SCL/SCK
12	RD
13	SPI SDI/SDA
14	SPI SDO
15	RESET
16	GND
17	D0
18	D1
19	D2
20	D3
21	D4
22	D5
23	D6
24	D7
25	D8
26	D9
27	D10
28	D11
29	D12
30	D13
31	D14
32	D15
33	A
34	K
35	K
36	K
37	GND
38	IMO
39	IM1
40	IM2

展开出货

LCD SIZE/TYPE	3.5"CTC/IPS/320*480	OPERATING TEMP.	-20°C TO +70°C	3rd Angle UNMARKED TOLERANCE.:±0.3	UNIT: mm	SCALE: FIT	PART NAME	TFT MODULE
VIEWING DIRECTION	ALL	STORAGE TEMP.	-30°C TO +80°C		REV.: 1.0	PAGE: 1/1		
DRIVER IC	ST7365P	BACKLIGHT	6 LED / VF=2.8~3.3V / IF=120mA	NAME	DATE		MODEL NO.	CH035B-P-GT
POLARIZE TYPE	上砂0.15MM/下光0.15MM	LUMINANCE	TBD					
OPERATING VOLTAGE	VCC:2.8~3.3V	Environmental Protection	RoHS Compliant	APPROVED BY			CUSTOMER NO.	/
MARK " * " ARE IMPORTANT DIMENSION, MARK " ( ) " ARE REFERENCE DIMENSION, MARK "★" ARE SPECIAL CHARACTERISTICS RELATED TO SAFETY, MARK "☆" ARE SPECIAL CHARACTERISTICS IRRELEVANT TO SAFETY, MARK "●" ARE IMPORTANT CHARACTERISTICS EXCEPT FOR THE SPECIAL CHARACTERISTICS.								



深圳川航